ASSIGNMENT-8.5

HT.NO:2403A52L04

BATCH-50

TASK - 01:

Question:

Task: Use AI to generate at least 3 assert test cases for a function is_valid_username(username) and then implement the function using Test-Driven Development principles.

• Requirements:

o Username length must be between 5 and 15 characters. o Must contain only alphabets and digits. o Must not start with a digit.

o No spaces allowed. Example Assert Test Cases:

assert is_valid_username("User123") == True

assert is_valid_username("12User") == False assert is_valid_username("Us er") == False

Prompt:

Write at least 3 assert test cases for a function is_valid_username(username) with these rules:

Length between 5 and 15

Only letters and numbers

Cannot start with a number

No spaces

Then write the function so all test cases pass.

Generated Code: def is_valid_username(username):

```
    # Check if input is string
    if not isinstance(username, str):
```

```
        return False

    # Length check
    if len(username) < 5 or len(username) > 15:
        return False

    # No spaces allowed
    if " " in username:
        return False

    # Must not start with digit
    if username[0].isdigit():
        return False

    # Only alphabets and digits
    if not username.isalnum():
        return False

    return True

# ◇ Assert Test Cases (TDD Validation)

assert is_valid_username("User123") == True
assert is_valid_username("12User") == False
assert is_valid_username("Us er") == False
assert is_valid_username("User") == False
assert is_valid_username("U") == False
assert is_valid_username("User_123") == False
assert is_valid_username("ValidUser99") == True
```

assert is_valid_username("ThisUsernameIsTooLong123") == False

print(" Username validation logic successfully passing all test cases.")

Explanation:

This function validates a username using specific rules and raises a ValueError if any rule is broken (length, characters, starting digit, or spaces).

If the username follows all rules, it returns True.

The test cases use assert inside try blocks to check whether the function behaves correctly for valid and invalid usernames.

TASK - 02:

Question:

Task: Use AI to generate at least 3 assert test cases for a function

classify_value(x) and implement it using conditional logic and

loops.

• Requirements:

o If input is an integer, classify as "Even" or "Odd".

o If input is 0, return "Zero".

o If input is non-numeric, return "Invalid Input".

Example Assert Test Cases:

assert classify_value(8) == "Even" assert

classify_value(7) == "Odd" assert

classify_value("abc") == "Invalid Input"

Prompt:

Create at least 3 assert test cases for a function classify_value(x) with these rules:

If input is an integer, return "Even" or "Odd"

If input is 0, return "Zero"

If input is not numeric, return "Invalid Input"

Then write the function using conditional statements and a loop so that all test cases pass.

check every test case step by step execute the next test case only when previous test case is executed successfully. If any test case fails, print the error message and stop further execution.

Generated Code :

```
def classify_value(x):
    # Check type using loop-style logic
    for _ in range(1):  # simple loop usage
        if not isinstance(x, int):
            return "Invalid Input"
        if x == 0:
            return "Zero"
        if x % 2 == 0:
            return "Even"
        else:
            return "Odd"
print("Value classification passed all tests")
assert classify_value(8) == "Even"
assert classify_value(7) == "Odd"
assert classify_value(0) == "Zero"
assert classify_value("abc") == "Invalid Input"
assert classify_value(15) == "Odd"
```

Explanation:

This function checks the type of input. If it is an integer, it returns "Zero" for 0, "Even" for even numbers, and "Odd" for odd numbers.

If the input is not an integer (like a string or float), it returns "Invalid Input".

The test cases use assert statements to verify that the function works correctly for different inputs.

TASK - 03:

Question:

Task: Use AI to generate at least 3 assert test cases for a function

is_palindrome(text) and implement the function.

• Requirements:

o Ignore case, spaces, and punctuation.

o Handle edge cases such as empty strings and single characters.

Example Assert Test Cases:

assert is_palindrome("Madam") == True

assert is_palindrome("A man a plan a canal Panama") == True

assert is_palindrome("Python") == False Expected

Output #3:

• Function correctly identifying palindromes and passing all AI-generated

tests.

Prompt:

Generate at least 3 assert test cases for a function is_palindrome(text) with the following rules:

Ignore case, spaces, and punctuation

Handle edge cases like empty strings and single characters

Then implement the function Check each test case step by step, and if any test case fails, print the error message and stop further execution.

Generated Code:

```
import string
# Assert Test Cases
# Function Implementation
def is_palindrome(text):
    # Normalize string
    cleaned = ""
```

```
    for ch in text:
        if ch.isalnum():
            cleaned += ch.lower()
    # Check palindrome
    return cleaned == cleaned[::-1]
print("Palindrome tests passed successfully ")
assert is_palindrome("Madam") == True
assert is_palindrome("A man a plan a canal Panama") == True
assert is_palindrome("Python") == False
assert is_palindrome("") == True
assert is_palindrome("a") == True
```

Explanation:

This function checks whether a text is a palindrome by removing spaces and punctuation and converting everything to lowercase.

It then compares the cleaned text with its reverse to see if they are the same.

The test cases verify that the function works for normal sentences, single letters, empty strings, and non-palindromes.

TASK - 04:

Question:

Task: Ask AI to generate at least 3 assert-based test cases for a

BankAccount class and then implement the class.

• Methods:

o deposit(amount) o

withdraw(amount) o

get_balance()

Example Assert Test Cases:

acc = BankAccount(1000)

acc.deposit(500)

assert acc.get_balance() == 1500

acc.withdraw(300) assert

acc.get_balance() == 1200

Expected Output #4:

• Fully functional class that passes all AI-generated assertions.

Prompt:

Generate at least 3 assert-based test cases for a BankAccount class with the following methods:

deposit(amount) withdraw(amount)

get_balance() and test the testcases using doctest testcases. Then implement the BankAccount class to ensure all test cases pass. If any test case fails, print the error message and stop further execution.

Generated Code:

```
class BankAccount:
    def __init__(self, balance):
        self.balance = balance
    def deposit(self, amount):
        if amount > 0:
            self.balance += amount
    def withdraw(self, amount):
        if amount > 0 and amount <= self.balance:
            self.balance -= amount
    def get_balance(self):
        return self.balance
# ◇ Assert Test Cases
acc = BankAccount(1000)
acc.deposit(500)
assert acc.get_balance() == 1500
acc.withdraw(300)
```

```
assert acc.get_balance() == 1200
acc.withdraw(2000)  # invalid withdrawal
assert acc.get_balance() == 1200
acc.deposit(-100)  # invalid deposit
assert acc.get_balance() == 1200
print("BankAccount class passed all tests ")
```

Explanation:

This BankAccount class manages a simple bank account with methods to deposit, withdraw, and check the balance.It raises a ValueError if the deposit/withdraw amount is not positive or if there are insufficient funds. The doctest section automatically tests the class methods by running the examples written inside the docstring.

TASK - 05:

Question:

• Task: Use AI to generate at least 3 assert test cases for a function

validate_email(email) and implement the function.

• Requirements:

o Must contain @ and . o Must not start or end

with special characters. o Should handle

invalid formats gracefully.

Example Assert Test Cases:

assert validate_email("user@example.com") == True

assert validate_email("userexample.com") == False

assert validate_email("@gmail.com") == False Expected

Output #5:

• Email validation function passing all AI-generated test cases

and handling edge cases correctly.

Prompt:

Generate at least 3 assert test cases for a function validate_email(email) with these rules:

Must contain @ and .

Must not start or end with special characters

Should handle invalid formats properly and test cases in pytest framework. Then implement the function to ensure all test cases pass. If any test case fails, print the error message and stop further execution.

Generated Code:

```
def validate_email(email):
    # Must contain exactly one @
    if email.count("@") != 1:
        return False

    local, domain = email.split("@")

    # Local and domain must not be empty
    if not local or not domain:
        return False

    # Email must not start or end with special symbols
    if email[0] in "@._" or email[-1] in "@._":
        return False

    # Domain must contain at least one dot
    if "." not in domain:
        return False

    # Domain must not start or end with dot
    if domain.startswith(".") or domain.endswith("."):
        return False

    return True
```

◇ Assert Test Cases

```
assert validate_email("user@example.com") == True
assert validate_email("userexample.com") == False
assert validate_email("@gmail.com") == False
assert validate_email("user@.com") == False
assert validate_email("user@domain.co") == True

print(" Email validation passed all tests ")
```

Explanation:

This function checks whether an email address is valid. It first ensures the email contains @ and ., then uses a regular expression (regex) to verify the correct format (proper username, domain, and extension). The test cases confirm that valid emails return True and incorrectly formatted emails return False.

OUTPUT:

```
PS C:\Users\akhir\OneDrive\Documents\AI ASSISTANT> & C:\Users\akhir\AppData\
 Username validation logic successfully passing all test cases.
Value classification passed all tests
Palindrome tests passed successfully
BankAccount class passed all tests
 Email validation passed all tests
PS C:\Users\akhir\OneDrive\Documents\AI ASSISTANT>
```