Journal of Machine Learning Research () Submitted 9/26; Published

Formal Falsification of the Completeness of a Single Fixed-Memory Component for Open Inversion Tasks

Shuo Zhang 202400103083@stumail.sztu.edu.cn
Shenzhen Technology University
3002 Lantian Road, Pingshan District
Shenzhen, Guangdong, China 518118

Editor: Action Editor

Abstract

Can a fixed-memory component solve every open inversion task on its own? This paper shifts the question from model scale to the source of the values that govern context: are they instantiated from current evidence and analytic or calibration invariants (Mode A), or frozen at inference from corpus statistics or manual setting (Mode B)? We define open inversion tasks by ill-posedness, heterogeneous evidence-addressed context, and distributional openness (P1–P3), and isolate a subclass satisfying class-relative non-freezability (P4). For mask-modeled inputs, a fixed test distribution, integrable squared rule-value loss, and a fixed evidence-instantiated benchmark, we show that a specified class of offline-frozen rules with a uniform bounded-description rate has risk gap at least $\kappa = p\delta^2/16 - \mathrm{risk}^*$ when both the barrier and scale-restricted realization conditions hold. If $\kappa > 0$, no rule in that class achieves uniform tolerance $0 < \epsilon < \kappa$; the neural-network conclusion additionally assumes output variation on a specified evidence-collision pair. On the nondegenerate locus of the stationarity conditions, a single position whose demand ratio changes between admissible configurations obstructs every frozen position-wise family. Thus, under explicit and separately checkable assumptions, more frozen memory alone cannot guarantee independent open-set inversion; the result limits solo use, not the usefulness of frozen components in composite systems. The algebraic core and a toy-carrier closure are formalized in Lean 4 with Mathlib, without `sorry`; this verification does not establish the general neural theorem, BD, P4, or their real-world applicability.

Keywords: open inversion tasks; formal falsification; fixed-memory component; decision axis; distributional openness

1 Introduction

Many inference tasks are ill-posed. For example, monocular 3D reconstruction seeks the surface depth associated with each image pixel, but pixel brightness admits infinitely many depths; likewise, a measurement can admit infinitely many states, and no local observation alone fixes the answer (Hadamard, 1902). Ill-posedness can arise from the observation model itself: projection, sampling, and noise can remove information about the underlying structure. Early vision stated this systematically, with stereo vision, motion estimation, optical flow, and shape reconstruction admitting a unique solution only after additional constraints (Poggio and Koch, 1985). Contextual constraints restrict the degrees of freedom

© Shuo Zhang.

License: CC-BY 4.0, see `https://creativecommons.org/licenses/by/4.0/`. Attribution requirements are provided at `http://jmlr.org/papers/v/.html`.

left undetermined by local observations; examples include neighboring pixels on one surface and frames on one motion.

The required contextual constraints are generally spatially and temporally heterogeneous: strong inside a surface, so that the neighborhood corroborates and noise is smoothed away; cut at boundaries and occlusions, so that the two sides form independently, else depth smears along edges. How strongly context should be used therefore varies with position and time, its correct value depending on where the scene's boundaries lie and where motion breaks: a context rule is a stipulation varying with the evidence, not a fixed law.

1.1 Open Inversion Tasks

Three items delimit the base class: (P1) observations are ill-posed, (P2) the required context strength is heterogeneous and content-addressed by the evidence, and (P3) inference inputs may come from outside the training distribution—the *open set*. A task satisfying P1–P3 is an *open inversion task*. The impossibility results use a fourth, separately stated hypothesis: (P4) relative to a specified comparison class, the required context rule cannot be given within every pre-given tolerance on the open set by values frozen before inference begins. Real-time 3D reconstruction motivates these criteria (Kerbl et al., 2023), as do image and video restoration, online state estimation, and medical and scientific inversion; membership in the base class and satisfaction of P4 must be checked separately for each concrete task.

These items are premises whose failure delimits the conclusion: a homogeneous interpolation task fails P2; in fixed-grid simulation the boundary positions are set by the task rather than the evidence; under fixed operating conditions the demand is exogenous; and a demand exactly identifiable from a fixed corpus fails P4. Fixed-memory components on such tasks are outside what the conditional result excludes. In particular, no motivating example is asserted to satisfy P4 without a separate argument.

1.2 The Claim to Be Falsified

Does there exist a component that, by itself alone, applies context rules correctly on every open inversion task? The question has a real-world form, as the conjunction of two public claims: the engineering corollary of the universal approximation theorems (Cybenko, 1989; Hornik et al., 1989), and the scale claim that deficiencies in contextual ability are a matter of corpus and parameter scale rather than of architectural category (Bubeck et al., 2023), its critics noting that some so-called emergent abilities may be artifacts of metric choice (Schaeffer et al., 2023).

Claim $\mathcal{R}$: *There exists a fixed-memory component that, using only that component and without any external proposal or arbitration stage, is complete for open inversion tasks; that is, it solves each task independently across inference distributions and scenarios, without assuming that the test distribution agrees with the training distribution.*

A *fixed-memory component* is one whose context rules are frozen into parameters that do not change at inference time and whose values come from training-corpus statistics or manual setting; neural networks are the canonical instance. Theorem 5 addresses the neural-network-only claim $\mathcal{P}$ only for a specified rule class and under explicit output-nondegeneracy, BD, and P4 hypotheses. Here *completeness* means independent task solving, not complete-

ness in the sense of mathematical logic. The qualifier "only" is crucial: the result does not deny the usefulness of frozen components, including neural feature extractors, within larger systems. High accuracy on a fixed benchmark close to the training distribution is within reach of both kinds of networks, but that *weak claim* is not the object here.

The method is conditional deduction, not experimental proof: Claim $\mathcal{R}$ is existential and its negation is a universal statement over a whole task class, so the Popperian shortcut of a single counterexample (Popper, 1959) is unavailable. The chain runs from explicitly stated criteria to a capability boundary; experiments can assess those criteria and explore applicability, but cannot validate the universal statement. Accordingly, the paper proves a conditional exclusion for the qualified subclass, not an unconditional real-world negation of Claim $\mathcal{R}$: an application requires a nonvacuous P4/BD instance, a benchmark bound giving $\kappa > 0$, and a tolerance below κ. Lemma 1 holds for a separable data term and an arbitrary even differentiable pairwise potential, with no convexity assumption, but its first-order conditions describe stationary points rather than guaranteed global minimizers in the nonconvex case. *Falsification* is used in this conditional deductive sense throughout.

2 Formalization of the Problem

Let the position set I be *finite* throughout—the pixel set in image tasks, or the product of time indices and state components in state estimation—and let the structure field $d : I \to \mathbb{R}$ assign a structure value to every position. Finiteness makes all subsequent sums and squared norms well defined; an infinite-index extension would require a specified summable space. An observation consists of a mask $m : I \to \{0, 1\}$ marking the observed positions together with the observed values there: values inside the mask are pinned by the observation, values outside are under no direct constraint.

Definition 1 *An observation is* ill-posed *if there exist two different structure fields $d \neq e$ that agree with the observed values at every position inside the mask.*

Proposition (Mask Criterion): *An observation with a hole is ill-posed: if some position j is not covered by the mask, two different values at j give two structure fields compatible with the same observation. Conversely, a mask covering all positions determines the structure field uniquely, so the observation is not ill-posed.*

Neither direction depends on numerical detail: positions outside the mask are degrees of freedom, two values on one giving a bifurcation, while a full mask pins every position; real observations almost always have holes—depth behind occluding surfaces, bands drowned in noise, null spaces of measurement equations.

2.1 Criteria for the Base Class and the P4 Subclass

Criteria P1–P3 define the base class; Criterion P4, together with the explicit implementation hypotheses below, delimits the subclass to which the impossibility result applies.

- Criterion P1 (ill-posedness): different structure fields are compatible with the same observation.

- Criterion P2 (heterogeneity): boundary and interior positions require different consistency strengths, and which is which is content-addressed by the current evidence.
- Criterion P3 (distributional openness): inputs at inference time are not constrained by the training distribution. The formal results are restricted to mask-modeled inputs satisfying *mask openness*: the observation pins the evidence part while the context part retains uncovered free positions, so the same evidence admits free bifurcation of the context values. This is an additional bridge assumption, not a consequence of distributional openness alone.
- Criterion P4 (class-relative non-freezability of the demand): relative to a specified comparison class of offline-frozen rules, the demand rule's values cannot be given within every pre-given tolerance on the open set by an object existing before inference begins. Section 4.4 splits the formal hypothesis into a *barrier condition* on the demand and a *scale-restricted realization condition* for a class with a uniform bounded-description rate. These hypotheses yield a positive floor κ on the risk gap only when the benchmark bound is small enough.

Distributional openness by itself implies neither a mask hole nor P1. Under the separate mask-openness bridge, however, an uncovered position supplies the bifurcation required by P1. The difficulty is thus a progression: ill-posedness forces inference to use context, heterogeneity requires context to vary by position, and openness requires rules to remain correct beyond the training inputs; P4 and BD are additional hypotheses for the quantitative exclusion. A test distribution P is specified for each evaluation: an open set does not mean that no distribution exists, and mask openness is the only form of openness the derivations consume.

- Assumption A0 (evidence-computability of the demand): The demand rule is computable from current evidence; that is, there exists a mapping from evidence to the values of the demand rule such that on every input the demanded values can be given at inference time by evidence and analytic means.

A0 plays no role in the negative risk-gap argument, which instead uses the stated mask, demand, BD, and P4 hypotheses; it supports only the positive, constructive reading of Section 6. Tasks whose demand depends on unobserved structure with no trace in the evidence fail A0 and remain outside the positive claims. The formal model uses scalar structure fields on I; depth, disparity, signed-distance, and vector-valued representations require their own mask models and criterion checks, and no invariance under representation changes is claimed.

P4 cannot be read off the task syntax: a task can satisfy P1–P3 and fail P4. The linear-demand toy discussed below is one such example, on which a frozen component is complete on that sample. The barrier condition mentions no rule, average, or benchmark and belongs to the family of classical approximation barriers (Kolmogoroff, 1936; Pinkus, 1985); transmission to a risk gap is a proved inequality under the additional realization and BD hypotheses. Its empirical content sits in the class-relative realization level p and the benchmark risk of the best evidence-instantiated rule, neither of which is assumed to be observable from task syntax alone.

3 The Decision Axis: Context Rules and Two Modes

Ill-posed tasks cannot do without context, but "using context" needs an analyzable handle:

Definition 2 *A* context rule *is the stipulation of where and how strongly context is needed, and its content is a set of numbers: a family $R = (R_i)_{i \in I}$ of mappings $R_i : (I \to \mathbb{R}) \to \mathbb{R}$, one for each position $i \in I$. For an input instance d, current evidence is the restriction $d|_{\text{ev}}$ to observed positions. In variational objectives, z instead denotes an optimization candidate, with candidate evidence $z|_{\text{ev}}$; thus $R_i(z)$ may use both candidate evidence and candidate context values. The rule is* global *when the family is constant, $R_i = R_j$ for all positions i, j, as in the scalar λ of classical regularization, and* position-wise *when the family is not constant.*

Structural representations must still be instantiated into numbers wherever they participate in numerical inference. Representation changes the carrier of a rule, not the provenance of its values. The index carries content: Criterion P2 requires the strength to differ across positions, the evidence content-addressing which are boundary and which interior, so a rule that cannot vary by position cannot express the demand it is meant to meet—whether a constant family can nonetheless meet it is the question Lemma 1 answers in the negative.

Definition 3 *A rule belongs to* Mode A *if all its values are instantiated by current evidence or taken from cross-scenario invariants given by analysis and calibration, such as camera intrinsics; it belongs to* Mode B *if its computation involves parameters that are fixed at inference time and whose values are given by training-corpus statistics or manual setting. The two are mutually exclusive and exhaustive by provenance. Only parameters that carry the content of the rule participate in the classification. Learning rate, iteration count, step size, and random seed are bookkeeping only when the solver is guaranteed to converge to the same specified unique limit regardless of those choices. For a finite-step computation or a problem with multiple local solutions, they can change the output and therefore participate in the Mode B classification when their values are frozen corpus or manual choices. A component implementing an analytic or calibration function with fixed parameters is Mode A, whereas one implementing a corpus-statistical function remains Mode B even if its output depends only on evidence.*

Pre-existence alone is not the criterion: analytic and calibration invariants may pre-exist inference and remain Mode A. Classification concerns the substantive source of the function and its values, not their storage location, magnitude, or input dependence.

For a Mode A rule there exists, for each position i, a mapping Φ_i such that for every structure field d,

$$R_i(d) = \Phi_i\big(d|_{\text{ev}}\big). \tag{1}$$

This equation is the behavioral consequence of evidence-only instantiation. A Mode B rule involves a parameter object W fixed at inference time and, for each position i, a computational process F_i such that

$$R_i(d) = F_i(W, d), \tag{2}$$




Figure 1: Decision-axis schematic: provenance of rule-carrying values, not storage location or input dependence. Analytic and calibration invariants may be fixed yet remain Mode A; a corpus-fitted evidence map remains Mode B. This classification alone implies neither correctness nor completeness.

where the family $(F_i)_{i \in I}$ is fixed together with W. The two displays are not, by themselves, exclusive behavioral tests: frozen corpus-trained weights can implement an analytic evidence function and hence admit both representations while remaining Mode B by provenance. When two inputs share the same evidence but differ in context, Mode A must give the same strength at every position; Mode B may give different values. Under the P4, BD, and tolerance hypotheses of the impossibility result, evidence instantiation is necessary for the stated uniform bound, but Mode A membership is not sufficient for correctness or for such a bound.

3.1 Deciding the Mode of an Implementation

To classify an implementation, first identify analytic or calibration invariants: values computed from current evidence by an analytic closed form, or read from a cross-scenario invariant such as camera intrinsics, are Mode A even when stored in fixed parameters. Then classify the remaining content-carrying parameters whose values come from corpus statistics or manual setting and are frozen at inference as Mode B. Solver bookkeeping is excluded only under the unique-common-limit guarantee of Definition 3; otherwise learning rates, iteration counts, step sizes, and seeds must be classified by their provenance as well. A generator or update rule is itself a rule, so a corpus-fitted generator moves Mode B up one level instead of escaping it. Test-time updating alone does not decide the mode: a few-shot meta-learned adaptation and an analytic per-instance optimization can both update parameters while landing on opposite sides.

4 Formal Falsification

Ill-posedness decides that inference cannot do without context, established in Section 2; the four steps that follow answer whether context strength can be governed uniformly by one

global scalar, whether objective form determines provenance, what additional quantitative hypotheses demand of the source of the rule's values, and on which side of the decision axis the two canonical components fall. Each item is proved in the *Argument* paragraph printed with it. Lemma 1 supplies stationarity algebra and a zero-safe compatibility condition for frozen position-wise families; Lemma 2 separates objective form from source. Lemma 3 is a conditional risk argument, while Theorem 5 additionally requires the specified comparison class, BD, scale-restricted P4, a positive floor κ, and tolerances $0 < \epsilon < \kappa$. No step silently supplies those modeling premises.

4.1 Lemma 1: A Single Global Scalar Cannot Realize a Heterogeneous Strength Profile

The most economical approach is to govern context strength uniformly by one global scalar λ—in Definition 2, the constant family $R_i \equiv \lambda$—the form of classical regularization (Poggio and Koch, 1985), whose parameter-selection methods are completed offline and yield a frozen parameter table, hence Mode B. Throughout this subsection z is the optimization candidate, distinct from the test instance d of Lemma 3. Let the data term be the per-position squared residual $\ell_i(x, z) = (x_i - z_i)^2$, and let

$$\kappa_i(z) = \sum_{j \in I} (z_i - z_j) \tag{3}$$

be the per-position coefficient of the consistency term, measuring position i's tendency to deviate from its neighborhood. The objective with extrinsic smoothing is

$$\mathcal{E}(x, z, \lambda) = \sum_{i \in I} (x_i - z_i)^2 + \lambda \sum_{i \in I} \sum_{j \in I} (z_i - z_j)^2. \tag{4}$$

Differentiating in z_i gives $2(z_i - x_i) + 4\lambda\kappa_i(z) = 0$; dividing by 2, without redefining λ, gives the first-order condition

$$(z_i - x_i) + 2\lambda \cdot \kappa_i(z) = 0. \tag{5}$$

At every position the weighted sum of the data residual and the consistency term must vanish.

Lemma 1 *If the context rule is global, so that the family of Definition 2 is constant, $R_i = \lambda$ for every position $i \in I$, while the task demands different coupling strengths at boundary and homogeneous positions, then the scalar cannot satisfy the first-order optimality conditions at both ends: the heterogeneous demand breaks the cross-position proportionality, and no constant family realizes a heterogeneous strength profile.*

Argument. The strengthened form covers arbitrary fitting points, its premise being that the proportionality (6) fails. If the same λ satisfies the first-order conditions of positions i and j at an arbitrary point z, then $2\lambda \cdot \kappa_i(z) = x_i - z_i$ and $2\lambda \cdot \kappa_j(z) = x_j - z_j$ from (5), and cross-multiplying to eliminate λ gives

$$(x_i - z_i) \cdot \kappa_j(z) = (x_j - z_j) \cdot \kappa_i(z), \tag{6}$$

that is, the data residuals and the consistency terms must be proportional across positions—the price of a single scalar. Boundaries requiring weak coupling and interiors requiring strong coupling are exactly the situation where this proportionality is broken. At the zero-residual specialization, (5) reduces to $2\lambda\cdot\kappa_i(z) = 2\lambda\cdot\kappa_j(z) = 0$: $\lambda \neq 0$ forces $\kappa_i(z) = \kappa_j(z) = 0$, which heterogeneous positions do not satisfy, while $\lambda = 0$ withdraws context and leaves ill-posedness unattended. Classical variational regularization is unaffected in existence and well-posedness, the linear system of the particular quadratic objective (4) having a unique minimizer for every $\lambda > 0$; what is excluded is the realizability of a heterogeneous demand profile by a single frozen coefficient, the uniform λ still giving a determinate but biased and oversmoothed solution. □

Only the most economical form is excluded; whether multi-dimensional, layer-wise or position-wise parameter tables dodge the blow is answered by the general form. Let the data term be any additively separable $\sum_{i\in I} f_i(z_i)$, f_i differentiable where evaluated, and the consistency term the ordered pairwise sum $\sum_{i\in I}\sum_{j\in I}\varphi(z_i - z_j)$ with φ even and differentiable. Differentiating in z_i gives

$$f_i'(z_i) + \lambda\cdot\kappa_i^{\varphi}(z) = 0, \qquad \kappa_i^{\varphi}(z) = 2\sum_{j\in I}\varphi'(z_i - z_j). \tag{7}$$

No constant has been absorbed into λ: the factor 2 is already in κ_i^{φ}. For $f_i(t) = (t - x_i)^2$ and $\varphi(t) = t^2$, (7) is $2(z_i - x_i) + 4\lambda\kappa_i(z) = 0$, which is exactly the corrected (5) after division by 2. No convexity is used, (7) being a necessary condition at a stationary point.

Proposition (Lemma 1, general form): *Call $\rho_i(z) = f_i'(z_i)/\kappa_i^{\varphi}(z)$ the* demand ratio *of position i, wherever the coefficient does not vanish. If one and the same scalar λ satisfies (7) at positions i and j, then*

$$f_i'(z_i)\cdot\kappa_j^{\varphi}(z) = f_j'(z_j)\cdot\kappa_i^{\varphi}(z), \tag{8}$$

which reads $\rho_i(z) = \rho_j(z)$ when both coefficients are nonzero; consequently no scalar satisfies (7) at two positions with different defined demand ratios. For a family $(R_i)_{i\in I}$ whose values pre-exist inference, each $R_i = W_i$ fixed before inference and independent of the instance, there exists one common family $(W_i)_{i\in I}$ satisfying (7) at every position at two admissible candidate configurations z and z' if and only if, for every $i \in I$,

$$\begin{aligned} &f_i'(z_i)\cdot\kappa_i^{\varphi}(z') = f_i'(z_i')\cdot\kappa_i^{\varphi}(z), \\ &\kappa_i^{\varphi}(z) = 0 \implies f_i'(z_i) = 0, \\ &\kappa_i^{\varphi}(z') = 0 \implies f_i'(z_i') = 0. \end{aligned} \tag{9}$$

When $\kappa_i^{\varphi}(z)$ and $\kappa_i^{\varphi}(z')$ are both nonzero, these conditions reduce to $\rho_i(z) = \rho_i(z')$. Thus one position whose defined demand ratio changes between two admissible configurations suffices to obstruct every frozen position-wise family; zero-coefficient cases must be checked using the full compatibility condition.

Argument. Equation (8) is (7) at i and j with λ eliminated, using only differentiability, hence stationary points rather than minimizers. For a frozen family, write $a = f_i'(z_i)$, $a' = f_i'(z_i')$, $b = \kappa_i^{\varphi}(z)$, and $b' = \kappa_i^{\varphi}(z')$. A common W_i must solve $a + W_i b = 0$ and

$a' + W_i b' = 0$. Cross-multiplication and the two zero-coefficient implications in (9) are necessary. Conversely, they permit a common choice: use $W_i = -a/b$ when $b \neq 0$, use $W_i = -a'/b'$ when $b \neq 0$ and $b' \neq 0$, and make an arbitrary choice when $b = b' = 0$, where the implications give $a = a' = 0$. On the nondegenerate locus this is precisely $W_i = -\rho_i(z) = -\rho_i(z')$. The residue is the pair (φ, f): the pairwise term must depend on the field through differences alone and the data term must be separable, so operator-valued couplings lie outside (7) and are not claimed. □

The algebra thus excludes the constant family at a single configuration when cross-position demand ratios differ and, through (9), a frozen position-wise family across configurations only when the zero-safe compatibility conditions fail. Provenance then classifies the frozen family as Mode B; an evidence-instantiated analytic family can be Mode A.

4.2 Lemma 2: Objective Form Does Not Determine Provenance

Perhaps strength should be appended as an extrinsic term outside the inference objective. Two paradigms must be distinguished.

Definition 4 *Call an inference objective* Paradigm E *if it is an additively separable combination of a data term and an extrinsic penalty term, of the form* (4)*; call it* Paradigm I *if it is a single generative objective in which candidate structures are given by the predictions of a generative model and only the data term itself is retained:*

$$\mathcal{I}(x, p) = \sum_{i \in I} (x_i - p_i)^2, \tag{10}$$

where p is the prediction field given by the generative model, and no separate additive regularization term exists any longer.

Lemma 2 *For the scalar quadratic Paradigm E objective* (4)*, every $\lambda > 0$ gives a well-posed problem with a unique minimizer, although that minimizer can be biased or oversmoothed. Heterogeneity at one configuration does not exclude a frozen position-wise coefficient family: when the general stationarity coefficients are nonzero, its entries can be chosen position by position to satisfy* (7) *there. Across two configurations, the same frozen family is excluded precisely when the zero-safe compatibility condition* (9) *fails. If coefficients do not enter the stationarity conditions, they cause no effect through those conditions. For Paradigm I with unconstrained $p \in \mathbb{R}^I$, the unique minimizer of* (10) *is $p = x$. If instead $p = G_\theta(x)$ is restricted to a generative range or latent parameterization, existence and uniqueness require additional range, injectivity, or convexity hypotheses. Neither paradigm by itself determines whether the rule is Mode A or Mode B.*

Argument. The scalar Paradigm E claim is the positive-definite quadratic argument already used in Lemma 1. For a position-wise family at one configuration, (7) gives $W_i = -f_i'(z_i)/\kappa_i^\varphi(z)$ whenever the denominator is nonzero, so a frozen table can realize that configuration's stationary demand by construction; the cross-configuration assertion is exactly the equivalence proved in (9), including its zero-coefficient cases. For unconstrained Paradigm I, nonnegativity of the sum of squares gives $\mathcal{I}(x, p) \geq 0$, with equality if and only if $p_i = x_i$

at every i. No such conclusion follows for a restricted generative range without further assumptions. Thus the algebra concerns realizability and stationarity, not the provenance of the parameters. Frozen priors combined with data-consistent learned reconstruction can remain useful within, and to some extent beyond, the training distribution (Haltmeier and Hwang, 2026); the result does not deny that usefulness or assert a worst-case guarantee. □

The form is not the criterion: analytic position-wise weights computed from current evidence make the stationarity equations solvable position by position, and anisotropic diffusion (Perona and Malik, 1990), like strengths chosen by Stein's unbiased risk estimation (Stein, 1981), are Paradigm E in form and Mode A in source. A corpus-fitted table remains Mode B even when it fits one configuration. The decidable classification question is therefore the provenance of the rule's values, with the frozen-family obstruction across configurations supplied separately by (9).

4.3 Lemma 3: A Risk Gap Obstructs a Smaller Uniform Tolerance

Fix a measurable test set and a probability distribution P on it. The demand $t = (t_i)_{i\in I}$ and every candidate rule are assumed measurable, and all losses below are assumed integrable with finite risks; neither Criterion P2 nor loss integrability is being used to construct t or prove measurability. The loss $\ell(R, d)$ measures the rule's values against $t(d)$, for example $\ell(R, d) = \sum_{i\in I}(R_i(d) - t_i(d))^2$. Fix a nonempty benchmark class $\mathcal{A}$ of measurable evidence-instantiated rules, define $\mathrm{risk}(R) = \mathbb{E}_P[\ell(R, d)]$, and define the fixed benchmark and risk gap by

$$\mathrm{risk}^* = \inf_{S\in\mathcal{A}} \mathrm{risk}(S), \qquad g(R) = \mathrm{risk}(R) - \mathrm{risk}^*. \tag{11}$$

Thus risk^* does not vary with the rule R being evaluated. For nonnegative loss, $\mathrm{risk}^* \geq 0$. Uniform ϵ-accuracy means $\ell(R, d) \leq \epsilon$ for every input d in the specified test set on which P is supported.

Lemma 3 *Suppose three premises hold for a rule R and a fixed $\epsilon \geq 0$. First, upper-tail realization: there exists an input d_0 in the test set such that $\ell(R, d_0) \geq \mathrm{risk}(R)$. Second, the risk gap exceeds the tolerance: $g(R) > \epsilon$. Third, the benchmark is nonnegative:* $\mathrm{risk}^* \geq 0$. *Then R cannot be uniformly ϵ-accurate on the test set. If upper-tail realization holds for every rule in a specified offline-frozen class $\mathcal{C}$, the benchmark is nonnegative, and $g(R) \geq \kappa > 0$ for every $R \in \mathcal{C}$, then no rule in $\mathcal{C}$ is uniformly ϵ-accurate for any $0 < \epsilon < \kappa$. When $\mathcal{C}$ is exactly the class of offline-frozen Mode B alternatives that satisfy these hypotheses and are admitted by the design question, an admitted rule meeting this accuracy claim must instead be evidence-instantiated; Mode A membership alone is not sufficient for correctness or for such a bound.*

Argument. The derivation has four lines. Uniform accuracy gives $\ell(R, d_0) \leq \epsilon$; upper-tail realization gives $\mathrm{risk}(R) \leq \ell(R, d_0)$; hence $\mathrm{risk}(R) \leq \epsilon$. On the other hand, nonnegativity of the benchmark and (11) give $g(R) \leq \mathrm{risk}(R)$, which with $g(R) > \epsilon$ yields $\mathrm{risk}(R) > \epsilon$, a contradiction. The class assertion follows because $\epsilon < \kappa \leq g(R)$. The final sentence is a provenance conclusion only inside the stated class and hypotheses, not a general sufficiency claim. □

Upper-tail realization holds for any integrable random variable on its support: with positive probability it attains a value no smaller than its mean. Nonnegativity holds for nonnegative loss. The quantitative content is therefore a fixed benchmark and a gap exceeding the particular tolerance; a bound established at one $\epsilon_0 > 0$ says nothing by itself about a smaller tolerance. The amortization gap of variational inference (Cremer et al., 2018) is an analogy, not an isomorphism or mechanistic proof: variational-family approximation error concerns the best member of a family, whereas amortization error is the additional error of an amortized inference rule relative to the same family's per-instance optimum. Neither equality with $g(R)$ nor positivity of $g(R)$ follows from that analogy.

4.4 The Two Components of Criterion P4

The quantitative exclusion uses three independent hypotheses: a barrier condition on the demand, a uniform bounded-description condition on a specified comparison class, and a realization condition at one scale admissible for that class. Together they imply a risk-gap floor; none is presented as a consequence of task syntax or finite description alone.

Fix the notation of Lemma 3: instances d range over the open test set, $t = (t_i)_{i\in I}$ is the measurable demand rule, and for a profile $s = (s_i)_{i\in I}$ write $\|s\|^2 = \sum_{i\in I} s_i^2$, so that $\ell(R, d) = \|R(d) - t(d)\|^2$. Let d_{in} be a metric on instances and diam_{in} its induced diameter. Fix a nonempty class $\mathcal{C}$ of offline-frozen measurable rules with integrable losses.

Barrier condition (P4a). The demand has no uniform modulus of continuity: there is a separation $\delta > 0$ such that for every scale $\eta > 0$ there are two disjoint sets of instances A_η and B_η with

$$\inf_{d\in A_\eta,\, e\in B_\eta} \|t(d) - t(e)\| \geq \delta, \qquad \text{diam}_{\text{in}}(A_\eta \cup B_\eta) \leq \eta. \tag{12}$$

The demand therefore maintains a fixed separation between sets as close together as any prescribed scale. In particular, t is not Lipschitz; more strongly, no uniform modulus of continuity can satisfy (12). The converse is false: a non-Lipschitz map such as $x \mapsto \sqrt{x}$ on $[0, 1]$ is still uniformly continuous and need not satisfy P4a. Criterion P2 can motivate fine-scale changes in demanded strength but does not logically imply this barrier. The condition mentions no rule, average, or benchmark and has the shape of a classical approximation barrier (Kolmogoroff, 1936; Pinkus, 1985); a fixed-grid demand or any Lipschitz demand fails it.

Bounded-description condition (BD). The comparison class has a common finite rate Λ_0: every $R \in \mathcal{C}$ has some $\Lambda_R \leq \Lambda_0$ such that

$$\|R(d) - R(e)\| \leq \Lambda_R\, d_{\text{in}}(d, e) \tag{13}$$

for all instances d, e. This is an independent restriction on the class, not a consequence of finite description. Sufficient examples include fixed finite-weight feedforward maps with globally Lipschitz activations on the stated metric domain, and tables with fixed index resolution and Lipschitz interpolation. A finite frozen threshold rule can be discontinuous and need not satisfy BD; such a rule lies outside this proposition unless a separate bound is established. Analytic expressions are not excluded merely by being analytic: their provenance and membership in the specified class must be assessed separately.




Figure 2: Schematic of P4 and the risk-gap argument at the realized scale η_* (not empirical certification). Sets need not be intervals or connected. Realization gives probability at least p to a deficit of $\delta/4$ or more, so $\mathrm{risk}(R) \geq p\delta^2/16$; the gap floor $\kappa = p\delta^2/16 - \rho$ is positive only when $\rho < p\delta^2/16$.

Scale-restricted realization condition (P4b). There are a scale $\eta_* > 0$ and a level $p > 0$ such that the sets of (12) at that scale satisfy

$$P(A_{\eta_*}) \geq p, \qquad P(B_{\eta_*}) \geq p, \qquad \Lambda_0 \eta_* \leq \frac{\delta}{2}. \tag{14}$$

When $\Lambda_0 > 0$, the last requirement is $\eta_* \leq \delta/(2\Lambda_0)$; when $\Lambda_0 = 0$, any available $\eta_* > 0$ is admissible. This is an empirical hypothesis about the fixed test distribution and comparison class, not something this paper proves from P1–P3.

The one-scale quantifier is essential. Requiring instead $P(A_\eta), P(B_\eta) \geq p > 0$ at *every* $\eta > 0$ would make the usual non-atomic Euclidean Borel model vacuous. For independent $D, E \sim P$, disjointness and the diameter bound imply $P \times P(0 < d_{\mathrm{in}}(D, E) \leq \eta) \geq p^2$ for every η, whereas these nested events decrease to the empty set as $\eta \downarrow 0$ and their probabilities tend to zero. The present formulation removes that contradictory all-scales requirement.

The repaired conditions are consistent. For example, take instances in $[-1, 1]$ with uniform P, scalar demand $t(d) = 0$ for $d \leq 0$ and $t(d) = \delta$ for $d > 0$, and $h = \min\{\eta, 1\}$. The sets $A_\eta = (-h/2, 0)$ and $B_\eta = (0, h/2)$ have union diameter at most η, demand separation δ, and probability $h/4$ each. Choosing a sufficiently small η_* satisfies (14) for any prescribed finite Λ_0, with $p = \eta_*/4$. This mathematical example does not establish P4 for a real inverse problem or establish that the resulting κ below is positive.

Proposition (Barrier to Gap): *Suppose P4a* (12) *holds with separation* δ*, BD* (13) *holds uniformly on* $\mathcal{C}$ *with rate* Λ_0*, and scale-restricted P4b* (14) *holds at* η_* *and level* p*. Then every* $R \in \mathcal{C}$ *satisfies*

$$\mathrm{risk}(R) \geq \frac{p\delta^2}{16}, \qquad \textit{and hence} \qquad g(R) \geq \frac{p\delta^2}{16} - \rho = \kappa, \tag{15}$$

where ρ *is any upper bound on the fixed benchmark risk* risk^**. If* $\rho < p\delta^2/16$*, then* $\kappa > 0$*, the risk gap is at least* κ *uniformly on* $\mathcal{C}$*, and Lemma 3 excludes uniform* ϵ*-accuracy for every* $R \in \mathcal{C}$ *and every* $0 < \epsilon < \kappa$*.*

Argument. Fix $R \in \mathcal{C}$ with rate $\Lambda_R \leq \Lambda_0$, and use the realized scale η_*; no limiting scale selection is needed. Write $A = A_{\eta_*}$ and $B = B_{\eta_*}$. For $d \in A$ and $e \in B$, the triangle inequality gives

$$\|R(d) - t(d)\| + \|R(e) - t(e)\| \geq \|t(d) - t(e)\| - \|R(d) - R(e)\| \geq \delta - \Lambda_R \eta_* \geq \frac{\delta}{2}, \tag{16}$$

where the last step uses $\Lambda_R \eta_* \leq \Lambda_0 \eta_* \leq \delta/2$, including the case $\Lambda_0 = 0$ without division. Hence at least one member of every pair has deficit at least $\delta/4$. The set S of instances with deficit at least $\delta/4$ therefore contains all of A or all of B: otherwise choosing $d \in A \setminus S$ and $e \in B \setminus S$ would contradict (16). By (14), $P(S) \geq p$, so $\mathrm{risk}(R) \geq p(\delta/4)^2$. The gap bound follows from (11) and $\mathrm{risk}^* \leq \rho$, and the tolerance assertion follows from Lemma 3. □

The same κ applies to every member of $\mathcal{C}$ and termwise to any sequence that remains in $\mathcal{C}$. This does not contradict universal-approximation theorems, which concern different target classes, topologies, losses, and hypotheses. Nor does a finite budget of frozen meta-parameters create a third provenance mode: such a component remains Mode B and is included only if it belongs to the specified BD class. Finite-resolution experiments cannot certify the every-scale barrier P4a, and realization probabilities and the benchmark must be estimated separately before a numerical κ can be claimed.

4.5 Classification and Closure: Neural Networks

Inference by a neural network feeds the current input into a set of weights in a forward computation; the weights do not change at inference time, and their values come from the statistics of a training corpus or from manual setting.

Proposition 4 *The context rule of a neural network, insofar as its values vary with corpus statistics or manual setting, is carried by weights fixed at inference time and belongs to Mode B. Separately, if* d, e *are a mask-collision pair,* $d|_{\mathrm{ev}} = e|_{\mathrm{ev}}$ *with different context values, and the rule exhibits* collision output variation*, namely* $\exists i \in I$ *such that* $R_i(d) \neq R_i(e)$*, then it cannot have the evidence-only behavior* (1) *on that pair.*

Argument. The network's rule satisfies (2), with W the weights and F_i forward propagation; corpus-statistical or manually set frozen content determines Mode B by provenance. For the collision assertion, (1) would force $R_i(d) = R_i(e)$ at every position, contradicting

output variation. Nonzero weights alone do not imply this variation, and small weights do not imply degeneracy: output variation must be checked for the specified pair. The argument excludes an evidence-only realization, not every analytic Mode A implementation. A network computing a fixed analytic function of evidence can still be Mode A by the analytic-invariant clause, and a frozen corpus-trained network that happens to implement such a function remains Mode B by provenance. □

Theorem 5 *Use the fixed test distribution, measurable demand and rules, integrable squared loss, and fixed benchmark* risk* *of Lemma 3. Let $\mathcal{C}$ be a specified class of offline-frozen neural-network context rules satisfying uniform BD, P4a, and scale-restricted P4b, with $\kappa = p\delta^2/16 - \rho > 0$. Assume also that each $R \in \mathcal{C}$ exhibits collision output variation on a specified mask-collision pair. Then no $R \in \mathcal{C}$ is uniformly ϵ-accurate for any $0 < \epsilon < \kappa$, and none has evidence-only behavior on its collision pair. Thus a solo network in $\mathcal{C}$ cannot independently meet this ϵ-complete open-inversion requirement. Claim $\mathcal{P}$ is falsified only in this qualified sense, not for arbitrary tasks, networks, or tolerances.*

Argument. Proposition 4 places the corpus- or manually parameterized frozen rules in Mode B and proves the separate collision statement. Barrier-to-Gap gives $g(R) \geq \kappa$ for every $R \in \mathcal{C}$. For any $0 < \epsilon < \kappa$, $g(R) > \epsilon$, so Lemma 3 contradicts uniform ϵ-accuracy. The conclusion uses every stated premise; in particular, P1–P3 alone, nonzero weights, or a bound at one larger tolerance would not suffice. □

On the four-position toy carrier of the machine-verification artifact, two illustrative demands give total-loss comparisons between frozen coefficients and constructive evidence-instantiated rules, while a linear demand is pinned exactly by a frozen family at $\epsilon = 0$. These toy computations illustrate the provenance distinction; they do not verify BD, P4, the general neural class, or the quantitative floor of Theorem 5, and the linear example lies outside P4.

Beyond the algebra, the exclusion does not depend on the dimension of the parameter object: a position-wise or layer-wise table is Mode B of higher dimension, and (9) excludes a frozen family across two configurations only when its zero-safe compatibility conditions fail. On the nondegenerate locus, one position whose defined demand ratio changes is sufficient. Approximate inference—loopy belief propagation, structured variational inference, learned proposals—changes cost and accuracy, not provenance. Composite systems containing Mode A are not ruled out, but their completeness is not proved by this result and must be established separately.

5 Formal Verification

The algebraic skeleton and a toy-carrier closure are machine-verified in Lean 4 with Mathlib, with zero `sorry`, zero project-specific `axiom`, and zero build warnings (Yang et al., 2023). This is not a machine verification of the revised general Theorem 5. In particular, the declarations `theorem5` and `finale` concern the scalar toy rule `neuralRule` $W\ d = W(d_0 - d_1)$ with $W \neq 0$; `finale` additionally takes upper-tail realization, a directly assumed positive risk gap, and benchmark nonnegativity as hypotheses. The artifact does not prove general neural-network output variation, BD, P4a/P4b, Barrier-to-Gap, or any real-world modeling

Table 1: Lean 4 verification coverage. Tiers A and B identify formalized components; Tier C is the uncovered analytic and modeling residue. The toy declarations `theorem5` and `finale` do not verify the general Theorem 5, BD, P4, or real-task premises.

Tier	**Covered content or residue**
A: carrier-independent algebra	Lemma 1's proportionality identities and general first-order condition; mode-composition steps used in the toy closure.
B: structured general forms	Ill-posedness and collision constructions; the unconstrained Paradigm I minimizer; Lemma 3's measure framework, including `tail_realization`.
C: not machine-verified	Continuous-side Euler–Lagrange arguments; general network output variation; the zero-safe table equivalence in full paper generality; BD, P4a/P4b, and Barrier-to-Gap.

premise. Each declaration exposes its formal hypotheses, but an exposed hypothesis is not thereby validated.

The guarantee divides into three levels. Tier A is carrier-independent algebra: Lemma 1's proportionality identities and general first-order condition, together with the mode-composition steps used in the toy closure. Tier B comprises structured general forms anchored on Mathlib: ill-posedness and collision constructions, the *unconstrained* Paradigm I minimizer, and Lemma 3's measure framework, including `tail_realization`. Tier C is the uncovered residue: continuous-side Euler–Lagrange arguments, general network output variation, the zero-safe table equivalence in its full paper generality, BD, scale-restricted P4, and the barrier-to-gap inequality. The Lean toy theorem must therefore not be cited as proof of those general analytic or empirical assumptions.

6 Discussion

The symptoms of Mode B are recorded empirically: deep networks memorize random labels with near-zero training error, so frozen weights suffice to hold a corpus's numerical table (Zhang et al., 2021).

6.1 A Minimal Empirical Probe of the Risk Gap

An exploratory constructed-task probe compares four non-oracle rules and two oracle references; it uses `experiments/probe.py` with Python. The frozen table has the lowest training RMSE among the four non-oracle rules, 0.096 against 0.071 for the per-position oracle. Its RMSE excess over that oracle rises from 0.024 in-distribution to 0.068 at an unseen location, 0.064 at an unseen width, and 0.046 at twice the noise. These observations illustrate distribution shift on one constructed task; they do not establish an open-set impossibility result.

In particular, oracle-excess RMSE is not Lemma 3's squared rule-value gap $g(R)$: the losses and normalizations differ, and the tested oracle, SURE rule, and amortized rule do not identify the infimum over the full evidence-instantiated benchmark class $\mathcal{A}$. Consequently these numbers neither bound $g(R)$ nor estimate κ. The auxiliary `p4_task.py` statistics are likewise not estimates of $P(A_{\eta_*})$ or $P(B_{\eta_*})$, and finite-resolution samples cannot certify the




Figure 3: Constructed-task reconstruction probe (`experiments/probe.py`). (a) Reconstruction RMSE for four non-oracle rules and the per-position oracle reference; (b) excess RMSE over that reference. The frozen table's excess rises from 0.024 in-distribution to 0.068, 0.064, and 0.046 under location, width, and noise shifts. These reconstruction errors are not Lemma 3's squared rule-value gap and do not estimate κ or certify P4.

every-scale barrier P4a. No theoretical floor is reported from these experiments. Evaluation on standardized inverse-problem benchmarks, for example LoDoPaB-CT (Leuschner et al., 2021), remains future work.

6.2 Existence, Cost and Design Implications

Whether Mode A exists determines the practical reading of the conclusion: the analytic-invariant path takes its values directly from calibration and geometry, and the per-instance optimization path solves the rule values separately for each input (Sun et al., 2020). Analytic evaluation is often cheaper than iterative per-instance optimization, but the actual cost depends on scale, accuracy, hardware, and stopping conditions; no universal cost factor is claimed. This tradeoff motivates composite systems: Mode B in cost-sensitive and in-distribution stages, Mode A in the critical stage of rule generation. Three questions then follow for design: where the rule's values come from; whether they are frozen at inference time; and who on the open set instantiates the rule. A positive completeness claim additionally requires A0 and a correctness proof for the proposed Mode A mechanism.

Three limitations delimit the result. First, P4a, uniform BD, scale-restricted P4b, and $\rho < p\delta^2/16$ are load-bearing hypotheses. Tasks with Lipschitz or exactly corpus-identifiable demand, discontinuous frozen rules outside the BD class, or inadequate realization or benchmark bounds are outside the quantitative exclusion; the theorem is then silent, not proof that a frozen rule is complete. Second, the positive claims need Assumption A0, which tasks whose demand depends on unobserved structure fail. Third, the negative result concerns

solo use within the specified class: composites containing Mode A are not ruled out, but neither their completeness nor the interaction of their components is proved here.

7 Conclusion

For a fixed test distribution and squared rule-value loss, a fixed evidence-instantiated benchmark, and a specified offline-frozen class satisfying uniform BD, P4a, and scale-restricted P4b, a positive $\kappa = p\delta^2/16 - \rho$ excludes uniform ϵ-accuracy throughout that class for every $0 < \epsilon < \kappa$. This is a conditional result about independent task solving, not a denial of in-distribution usefulness, not logic completeness, and not a consequence of P1–P3 alone. If the comparison class exhausts the offline-frozen Mode B alternatives that satisfy these hypotheses, an admitted rule meeting the bound must be evidence-instantiated; Mode A membership alone is not sufficient for correctness.

Lemma 1 excludes a shared scalar when cross-position demand ratios differ and gives the zero-safe two-configuration compatibility condition for a frozen position-wise family; heterogeneity at one configuration alone does not exclude such a family. Lemma 2 separates objective form from provenance, and Lemma 3 supplies the conditional risk argument. Proposition 4 classifies corpus- or manually parameterized frozen networks as Mode B and uses output variation, rather than nonzero weights, for the separate collision statement. Theorem 5 combines these pieces only with the stated class, benchmark, and tolerance hypotheses. The Lean artifact verifies algebraic components and a toy closure, not the general analytic or empirical premises.

The same classification can be applied to Markov random fields, conditional random fields, mixtures, dictionary learning, and kernel methods, but the quantitative exclusion follows only when their rules belong to a class satisfying the theorem's hypotheses. Online updating alone does not imply Mode A: evidence plus analytic or calibration invariants is Mode A, while corpus-statistical or manual frozen content remains Mode B, including a corpus-fitted generator of online updates. Tasks outside P4 or BD are not thereby shown to admit complete frozen solvers. Composite systems containing Mode A remain possible and require separate correctness arguments. Negation is therefore not disparagement: it is a scoped boundary claim, with constructive design and standardized empirical evaluation left as future work.

Acknowledgments and Disclosure of Funding

The verified artifact described in Section 5 was developed with the Lean 4 proof assistant and its mathematical library Mathlib, and is distributed in the `lean-proof` directory of the repository with the `lean-toolchain` file that pins the toolchain version.

Funding: this research received no specific funding.

Competing interests: the author declares no competing interests.

References

Sébastien Bubeck et al. Sparks of artificial general intelligence: Early experiments with GPT-4, 2023.

Chris Cremer, Xuechen Li, and David Duvenaud. Inference suboptimality in variational autoencoders, 2018. Proc. Int. Conf. Machine Learning (ICML).

George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of Control, Signals and Systems*, 2(4):303–314, 1989. doi: 10.1007/BF02551274.

Jacques Hadamard. Sur les problèmes aux dérivées partielles et leur signification physique. *Princeton University Bulletin*, 1902.

Markus Haltmeier and Gyeongha Hwang. Data-consistent learning of inverse problems. In *Handbook of Numerical Analysis: Machine Learning Solutions for Inverse Problems, Part B*, pages 487–506. Elsevier, 2026. doi: 10.1016/bs.hna.2026.03.002.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989. doi: 10.1016/0893-6080(89)90020-8.

Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian Splatting for real-time radiance field rendering. In *ACM Transactions on Graphics (SIGGRAPH)*, volume 42, pages 1–14, 2023. doi: 10.1145/3592433.

A. Kolmogoroff. Über die beste Annäherung von Funktionen einer gegebenen Funktionenklasse. *The Annals of Mathematics*, 37(1), 1936. doi: 10.2307/1968691.

Johannes Leuschner, Maximilian Schmidt, Daniel Otero Baguer, and Peter Maass. LoDoPaB-CT, a benchmark dataset for low-dose computed tomography reconstruction. *Scientific Data*, 8:109, 2021. doi: 10.1038/s41597-021-00893-z.

Pietro Perona and Jitendra Malik. Scale-space and edge detection using anisotropic diffusion. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 12(7):629–639, 1990. doi: 10.1109/34.56205.

Allan Pinkus. *n-Widths in Approximation Theory*. Springer, 1985. doi: 10.1007/978-3-642-69894-1.

Tomaso Poggio and Christof Koch. Ill-posed problems in early vision: from computational theory to analogue and parallel hardware. *Proceedings of the Royal Society of London. Series B*, 226(1244):303–323, 1985. doi: 10.1098/rspb.1985.0097.

Karl Raimund Popper. *The Logic of Scientific Discovery*. Hutchinson, 1959.

Rylan Schaeffer, Brando Miranda, and Sanmi Koyejo. Are emergent abilities of large language models a mirage? In *Advances in Neural Information Processing Systems 36 (NeurIPS)*, pages 55565–55581, 2023. doi: 10.52202/075280-2425.

Charles M. Stein. Estimation of the mean of a multivariate normal distribution. *The Annals of Statistics*, 9(6):1135–1151, 1981. doi: 10.1214/aos/1176345632.

Yu Sun, Xiaolong Wang, Zhuang Liu, John Miller, Alexei A. Efros, and Moritz Hardt. Test-time training with self-supervision for generalization under distribution shifts, 2020. Proc. Int. Conf. Machine Learning (ICML).

Kaiyu Yang, Aidan Swope, Alex Gu, Rahul Chalamala, Peiyang Song, Shixing Yu, Saad Godil, Ryan J. Prenger, and Anima Anandkumar. LeanDojo: Theorem proving with retrieval-augmented language models. In *Advances in Neural Information Processing Systems 36 (NeurIPS)*, pages 21573–21612, 2023. doi: 10.52202/075280-0944.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3):107–115, 2021. doi: 10.1145/3446776.