TELECOM Paris

IP PARIS

université PARIS-SACLAY



ICS904/CD2IC : Cell Design For Digital Integrated Circuits

L5 : Design Automation (2)

Yves MATHIEU
yves.mathieu@telecom-paris.fr

Outline

Standard Cell characterization

"Liberty" files

- Give all necessary informations to the synthesis and P&R tools
- A de-facto standard : "Liberty" files from "Synopsys" company.
- For each cell :
  - Logic behavior
  - Area
  - Power Consumption
  - Timing
- But also, for a whole library :
  - Characterization conditions (Process, Supply Voltage , Temperature)
  - Characterization conditions (Max rising time, Max capacitances,...)
  - Statistical capacitance model for wiring...

Standard Cell characterization

"Liberty" files

- Give all necessary informations to the synthesis and P&R tools
- A de-facto standard : "Liberty" files from "Synopsys" company.
- For each cell :
  - Logic behavior
  - Area
  - Power Consumption
  - Timing
- But also, for a whole library :
  - Characterization conditions (Process, Supply Voltage , Temperature)
  - Characterization conditions (Max rising time, Max capacitances,...)
  - Statistical capacitance model for wiring...

Standard Cell characterization

"Liberty" files

- Give all necessary informations to the synthesis and P&R tools
- A de-facto standard : "Liberty" files from "Synopsys" company.
- For each cell :
  - Logic behavior
  - Area
  - Power Consumption
  - Timing
- But also, for a whole library :
  - Characterization conditions (Process, Supply Voltage , Temperature)
  - Characterization conditions (Max rising time, Max capacitances,...)
  - Statistical capacitance model for wiring...

Standard Cell characterization

"Liberty" files

- Give all necessary informations to the synthesis and P&R tools
- A de-facto standard : "Liberty" files from "Synopsys" company.
- For each cell :
  - Logic behavior
  - Area
  - Power Consumption
  - Timing
- But also, for a whole library :
  - Characterization conditions (Process, Supply Voltage , Temperature)
  - Characterization conditions (Max rising time, Max capacitances,...)
  - Statistical capacitance model for wiring...

An example library

Nangate 45nm Open Cell Library

- Nangate is company creating characterization tools for standard cell libraries.
- Library distributed by Si2 (Silicon Integration Initiative) an association of electronic design automation companies.
- No way to process any true circuit, but usable for research and teaching purposes.
- Based on the NCSU (North Carolina State University) FreePDK45 process kit.
- FreePDK45 : An open source fictitious, non manufacturable process.

An example library

Nangate 45nm Open Cell Library

- Nangate is company creating characterization tools for standard cell libraries.
- Library distributed by Si2 (Silicon Integration Initiative) an association of electronic design automation companies.
- No way to process any true circuit, but usable for research and teaching purposes.
- Based on the NCSU (North Carolina State University) FreePDK45 process kit.
- FreePDK45 : An open source fictitious, non manufacturable process.

An example library

Nangate 45nm Open Cell Library

- Nangate is company creating characterization tools for standard cell libraries.
- Library distributed by Si2 (Silicon Integration Initiative) an association of electronic design automation companies.
- No way to process any true circuit, but usable for research and teaching purposes.
- Based on the NCSU (North Carolina State University) FreePDK45 process kit.
- FreePDK45 : An open source fictitious, non manufacturable process.

An example library

Nangate 45nm Open Cell Library

- Nangate is company creating characterization tools for standard cell libraries.
- Library distributed by Si2 (Silicon Integration Initiative) an association of electronic design automation companies.
- No way to process any true circuit, but usable for research and teaching purposes.
- Based on the NCSU (North Carolina State University) FreePDK45 process kit.
- FreePDK45 : An open source fictitious, non manufacturable process.

An example library

Nangate 45nm Open Cell Library

- Nangate is company creating characterization tools for standard cell libraries.
- Library distributed by Si2 (Silicon Integration Initiative) an association of electronic design automation companies.
- No way to process any true circuit, but usable for research and teaching purposes.
- Based on the NCSU (North Carolina State University) FreePDK45 process kit.
- FreePDK45 : An open source fictitious, non manufacturable process.

Outline

Nangate 45nm Open Cell Library

Units for measurements

```
/* Units Attributes */
voltage_unit              : "1V";
current_unit              : "1mA";
pulling_resistance_unit   : "1kohm";
capacitive_load_unit        (1,ff);
```

- All measurements use defined units.

Nangate 45nm Open Cell Library

Characterization conditions

```
   /* Operation Conditions */
nom_process                 : 1.00;
nom_temperature             : 25.00;
nom_voltage                 : 1.10;

voltage_map (VDD,1.10);
voltage_map (VSS,0.00);
```

- Supply and ground nodes have a name...

Nangate 45nm Open Cell Library

"Corners" : Process, Voltage, Temperature

```
define(process_corner, operating_conditions, string);
operating_conditions (typical) {
  process_corner : "TypTyp";
  process        : 1.00;
  voltage        : 1.10;
  temperature    : 25.00;
  tree_type      : balanced_tree;
}
default_operating_conditions : typical;
```

- Several liberty files may be loaded at the same time by the tools (synthesis, P&R)
- For each kind of analysis, the appropriate "PVT" corner is choosen by the tool.
- For example a "worst case" corner is used for Tsetup analysis.
- For example a "best case" corner is used for Thold analysis.

Nangate 45nm Open Cell Library

"Corners" : Process, Voltage, Temperature

```
define(process_corner, operating_conditions, string);
operating_conditions (typical) {
  process_corner : "TypTyp";
  process        : 1.00;
  voltage        : 1.10;
  temperature    : 25.00;
  tree_type      : balanced_tree;
}
default_operating_conditions : typical;
```

- Several liberty files may be loaded at the same time by the tools (synthesis, P&R)
- For each kind of analysis, the appropriate "PVT" corner is choosen by the tool.
- For example a "worst case" corner is used for Tsetup analysis.
- For example a "best case" corner is used for Thold analysis.

Nangate 45nm Open Cell Library

"Corners" : Process, Voltage, Temperature

```
define(process_corner, operating_conditions, string);
operating_conditions (typical) {
  process_corner : "TypTyp";
  process        : 1.00;
  voltage        : 1.10;
  temperature    : 25.00;
  tree_type      : balanced_tree;
}
default_operating_conditions : typical;
```

- Several liberty files may be loaded at the same time by the tools (synthesis, P&R)
- For each kind of analysis, the appropriate "PVT" corner is choosen by the tool.
- For example a "worst case" corner is used for Tsetup analysis.
- For example a "best case" corner is used for Thold analysis.

Nangate 45nm Open Cell Library

"Corners" : Process, Voltage, Temperature

```
define(process_corner, operating_conditions, string);
operating_conditions (typical) {
  process_corner : "TypTyp";
  process        : 1.00;
  voltage        : 1.10;
  temperature    : 25.00;
  tree_type      : balanced_tree;
}
default_operating_conditions : typical;
```

- Several liberty files may be loaded at the same time by the tools (synthesis, P&R)
- For each kind of analysis, the appropriate "PVT" corner is choosen by the tool.
- For example a "worst case" corner is used for Tsetup analysis.
- For example a "best case" corner is used for Thold analysis.

Nangate 45nm Open Cell Library

Voltage thresholds for timing analysis

```
/* Threshold Definitions */
  slew_lower_threshold_pct_fall  : 30.00 ;
  slew_lower_threshold_pct_rise  : 30.00 ;
  slew_upper_threshold_pct_fall  : 70.00 ;
  slew_upper_threshold_pct_rise  : 70.00 ;
  input_threshold_pct_fall       : 50.00 ;
  input_threshold_pct_rise       : 50.00 ;
  output_threshold_pct_fall      : 50.00 ;
  output_threshold_pct_rise      : 50.00 ;
```

- Thresholds (fraction of the full range power supply) for logic level detection.
- Rising or Falling time of signal transition.
- Propagation time.

Nangate 45nm Open Cell Library

Voltage thresholds for timing analysis

```
/* Threshold Definitions */
  slew_lower_threshold_pct_fall  : 30.00 ;
  slew_lower_threshold_pct_rise  : 30.00 ;
  slew_upper_threshold_pct_fall  : 70.00 ;
  slew_upper_threshold_pct_rise  : 70.00 ;
  input_threshold_pct_fall       : 50.00 ;
  input_threshold_pct_rise       : 50.00 ;
  output_threshold_pct_fall      : 50.00 ;
  output_threshold_pct_rise      : 50.00 ;
```

- Thresholds (fraction of the full range power supply) for logic level detection.
- Rising or Falling time of signal transition.
- Propagation time.

Nangate 45nm Open Cell Library

Voltage thresholds for timing analysis

```
/* Threshold Definitions */
  slew_lower_threshold_pct_fall  : 30.00 ;
  slew_lower_threshold_pct_rise  : 30.00 ;
  slew_upper_threshold_pct_fall  : 70.00 ;
  slew_upper_threshold_pct_rise  : 70.00 ;
  input_threshold_pct_fall       : 50.00 ;
  input_threshold_pct_rise       : 50.00 ;
  output_threshold_pct_fall      : 50.00 ;
  output_threshold_pct_rise      : 50.00 ;
```

- Thresholds (fraction of the full range power supply) for logic level detection.
- Rising or Falling time of signal transition.
- Propagation time.

Nangate 45nm Open Cell Library

Default maximum values for capacitors and transition

```
default_inout_pin_cap        : 1.000000;
default_input_pin_cap        : 1.000000;
default_output_pin_cap       : 0.000000;
default_fanout_load          : 1.000000;
default_max_transition       : 0.198535;
```

- Default input capacitor, load capacitor or fanout values of gates.
- Warning : The default maximum transition time is a constraint.
  - An arbitrary value chosen by the library designers.
  - Followed by the synthesis tool (or not ...)
  - Guarantees the validity domain of the timing characterization of library's gates.
  - QUESTION : what compromises are made when choosing this constraint ?

Nangate 45nm Open Cell Library

Default maximum values for capacitors and transition

```
default_inout_pin_cap        : 1.000000;
default_input_pin_cap        : 1.000000;
default_output_pin_cap       : 0.000000;
default_fanout_load          : 1.000000;
default_max_transition       : 0.198535;
```

- Default input capacitor, load capacitor or fanout values of gates.
- Warning : The default maximum transition time is a constraint.
  - An arbitrary value chosen by the library designers.
  - Followed by the synthesis tool (or not ...)
  - Guarantees the validity domain of the timing characterization of library's gates.
  - QUESTION : what compromises are made when choosing this constraint ?

Nangate 45nm Open Cell Library

Default maximum values for capacitors and transition

```
default_inout_pin_cap        : 1.000000;
default_input_pin_cap        : 1.000000;
default_output_pin_cap       : 0.000000;
default_fanout_load          : 1.000000;
default_max_transition       : 0.198535;
```

- Default input capacitor, load capacitor or fanout values of gates.
- Warning : The default maximum transition time is a constraint.
  - An arbitrary value chosen by the library designers.
  - Followed by the synthesis tool (or not ...)
  - Guarantees the validity domain of the timing characterization of library's gates.
  - QUESTION : what compromises are made when choosing this constraint ?

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Wires model

```
wire_load("1K_hvratio_1_4") {
 capacitance : 1.774000e-01;
 resistance : 3.571429e-03;
 slope : 5.000000;
 fanout_length( 1, 1.3207 );
 fanout_length( 2, 2.9813 );
 fanout_length( 3, 5.1135 );
 fanout_length( 4, 7.6639 );
 fanout_length( 5, 10.0334 );
 fanout_length( 6, 12.2296 );
 fanout_length( 8, 19.3185 );
}
wire_load(....){...}
...
default_wire_load : "5K_hvratio_1_1" ;
```

- Allowing the synthesizer to estimate wire loads.
- A statistical model based on real circuits.
- $R = resistance * fanout\_length(fanout)$
- $C = capacitance * fanout\_length(fanout)$
- Several models based on circuit toplogy.
- Default model : 5K gates / form factor 1

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

Table templates for measurements

- Timings and power values are tabulated (no analytical model)
- Table interpolation for arbitrary input variables.

```
power_lut_template (Hidden_power_7) {
  variable_1 : input_transition_time;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Example table template for power consumption measurement
- Named Hidden_power_7
- Input variable is a transition time
- 7 measurement points for 7 transition time values

Nangate 45nm Open Cell Library

A table template for propagation time

```
lu_table_template (Timing_7_7) {
  variable_1 : input_net_transition;
  variable_2 : total_output_net_capacitance;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
  index_2 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Propagation time is a function of :
  - The transition time of the input signal causing the output transition.
  - The out load capacitance.
  - $7x7 = 49$ measurement points.

Nangate 45nm Open Cell Library

A table template for propagation time

```
lu_table_template (Timing_7_7) {
  variable_1 : input_net_transition;
  variable_2 : total_output_net_capacitance;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
  index_2 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Propagation time is a function of :
  - The transition time of the input signal causing the output transition.
  - The out load capacitance.
  - $7x7 = 49$ measurement points.

Nangate 45nm Open Cell Library

A table template for propagation time

```
lu_table_template (Timing_7_7) {
  variable_1 : input_net_transition;
  variable_2 : total_output_net_capacitance;
  index_1 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
  index_2 ("0.0010,0.0020,0.0030,0.0040,0.0050,0.0060,0.0070");
}
```

- Propagation time is a function of :
  - The transition time of the input signal causing the output transition.
  - The out load capacitance.
  - $7x7 = 49$ measurement points.

Outline

Nangate 45nm Open Cell Library

NAND2_X4 : global data

```
cell (NAND2_X4) {
  drive_strength : 4;
  area           : 2.394000;
  pg_pin(VDD) {
    voltage_name : VDD;
    pg_type      : primary_power;
  }...
```

- Global info on the cell
- General info on output buffers .(integer 1,2,4,8...)
- The synthesizer uses area info in order to optimize global synthesized area.
- All signals should be known, even supplies and grounds.

Nangate 45nm Open Cell Library

NAND2_X4 : global data

```
cell (NAND2_X4) {
  drive_strength : 4;
  area           : 2.394000;
  pg_pin(VDD) {
    voltage_name : VDD;
    pg_type      : primary_power;
  }...
```

- Global info on the cell
- General info on output buffers .(integer 1,2,4,8...)
- The synthesizer uses area info in order to optimize global synthesized area.
- All signals should be known, even supplies and grounds.

Nangate 45nm Open Cell Library

NAND2_X4 : global data

```
cell (NAND2_X4) {
  drive_strength : 4;
  area           : 2.394000;
  pg_pin(VDD) {
    voltage_name : VDD;
    pg_type      : primary_power;
  }...
```

- Global info on the cell
- General info on output buffers .(integer 1,2,4,8...)
- The synthesizer uses area info in order to optimize global synthesized area.
- All signals should be known, even supplies and grounds.

Nangate 45nm Open Cell Library

NAND2_X4 : global data

```
cell (NAND2_X4) {
  drive_strength : 4;
  area           : 2.394000;
  pg_pin(VDD) {
    voltage_name : VDD;
    pg_type      : primary_power;
  }...
```

- Global info on the cell
- General info on output buffers .(integer 1,2,4,8...)
- The synthesizer uses area info in order to optimize global synthesized area.
- All signals should be known, even supplies and grounds.

Nangate 45nm Open Cell Library

NAND2_X4 : Leakage power

```
cell_leakage_power  : 69.573240;
leakage_power () {
  when              : "!A1 & !A2";
  value             : 13.930180;
}
leakage_power () {
  when              : "!A1 & A2";
  value             : 99.197450;
}
leakage_power () {
  when...
```

- The leakage power (Watts...) of the cell is a function of the internal state of the cell
- One mean value
- 4 values for the 4 entries in the truth table of the gate

Nangate 45nm Open Cell Library

NAND2_X4 : Leakage power

```
cell_leakage_power  : 69.573240;
leakage_power () {
  when              : "!A1 & !A2";
  value             : 13.930180;
}
leakage_power () {
  when              : "!A1 & A2";
  value             : 99.197450;
}
leakage_power () {
  when...
```

- The leakage power (Watts...) of the cell is a function of the internal state of the cell
- One mean value
- 4 values for the 4 entries in the truth table of the gate

Nangate 45nm Open Cell Library

NAND2_X4 : Leakage power

```
cell_leakage_power  : 69.573240;
leakage_power () {
  when              : "!A1 & !A2";
  value             : 13.930180;
}
leakage_power () {
  when              : "!A1 & A2";
  value             : 99.197450;
}
leakage_power () {
  when...
```

- The leakage power (Watts...) of the cell is a function of the internal state of the cell
- One mean value
- 4 values for the 4 entries in the truth table of the gate

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An input signal : A1

```
pin (A1) {
  direction          : input;
  related_power_pin  : "VDD";
  related_ground_pin : "VSS";
  capacitance        : 5.954965;
  fall_capacitance   : 5.698021;
  rise_capacitance   : 5.954965;
}
```

- A1 is an input
- A1 has an input capacitance.
- A mean value of the input capacitance is given
- An input capacitance when A1 is falling.
- An different input capacitance when A1 is rising.

- QUESTION : Why two different input capacitances ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567*fF*
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567*fF*
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567fF
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567*fF*
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567*fF*
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : An output signal : ZN

```
pin (ZN) {
  direction  : output;
  related_power_pin : "VDD";
  related_ground_pin : "VSS";
  max_capacitance  : 237.427000;
  function  : "!(A1 & A2)";
```

- ZN is an output
- The boolean equation is given (for synthesis...)
- Remember that the NAND2_X4 gate has a max fanout of 4.
- The max capacitance for a X1 gate is 59.3567*fF*
- The max load capacitance a X4 gate is four times this value.

- QUESTION : Is it coherent with the max transition time ?

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- related_pin : which is the input pin causing the output transition ?
- timing_sense : The output transition has not the same direction as the input transition.
- cell_fall : Propagation time for a falling output.
- Reference to the Timing_7_7 (transition,load) template.
- First index related to line. Second Index related to column.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- related_pin : which is the input pin causing the output transition ?
- timing_sense : The output transition has not the same direction as the input transition.
- cell_fall : Propagation time for a falling output.
- Reference to the Timing_7_7 (transition,load) template.
- First index related to line. Second Index related to column.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- related_pin : which is the input pin causing the output transition ?
- timing_sense : The output transition has not the same direction as the input transition.
- cell_fall : Propagation time for a falling output.
- Reference to the Timing_7_7 (transition,load) template.
- First index related to line. Second Index related to column.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- related_pin : which is the input pin causing the output transition ?
- timing_sense : The output transition has not the same direction as the input transition.
- cell_fall : Propagation time for a falling output.
- Reference to the Timing_7_7 (transition,load) template.
- First index related to line. Second Index related to column.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- related_pin : which is the input pin causing the output transition ?
- timing_sense : The output transition has not the same direction as the input transition.
- cell_fall : Propagation time for a falling output.
- Reference to the Timing_7_7 (transition,load) template.
- First index related to line. Second Index related to column.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- Index values are redefined.
- Note : max transition < default_max_transition.
- Note : max capa < max_capacitance.
- Same kind of table for a rising transition of the output.
- Same kind of table for each path from any input to any output.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- Index values are redefined.
- Note : max transition < default_max_transition.
- Note : max capa < max_capacitance.
- Same kind of table for a rising transition of the output.
- Same kind of table for each path from any input to any output.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- Index values are redefined.
- Note : max transition < default_max_transition.
- Note : max capa < max_capacitance.
- Same kind of table for a rising transition of the output.
- Same kind of table for each path from any input to any output.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- Index values are redefined.
- Note : max transition < default_max_transition.
- Note : max capa < max_capacitance.
- Same kind of table for a rising transition of the output.
- Same kind of table for each path from any input to any output.

Nangate 45nm Open Cell Library

NAND2_X4 : propagation time between A1 and ZN

```
timing () {
   related_pin     : "A1";
   timing_sense     : negative_unate;
   cell_fall(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00616709,0.00999692,0.0139268,0.0217239,0.0372647,0.0683098,0.130380", \
            "0.00734947,0.0112111,0.0151774,0.0230153,0.0385880,0.0696532,0.131734", \
            "0.00995234,0.0155306,0.0201539,0.0279856,0.0435159,0.0745711,0.136650", \
            "0.0111666,0.0189948,0.0256394,0.0365212,0.0535191,0.0842981,0.146225", \
            "0.0108485,0.0208434,0.0293531,0.0434564,0.0658692,0.100138,0.161536", \
            "0.00880319,0.0209282,0.0312687,0.0484222,0.0759517,0.118635,0.183723", \
            "0.00494015,0.0190727,0.0312259,0.0514041,0.0838078,0.134588,0.211792");
   }
   cell_rise(Timing_7_7) {
```

- Index values are redefined.
- Note : max transition < default_max_transition.
- Note : max capa < max_capacitance.
- Same kind of table for a rising transition of the output.
- Same kind of table for each path from any input to any output.

Nangate 45nm Open Cell Library

NAND2_X4 : Falling Transition time of ZN signal

```
fall_transition(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00313418,0.00633765,0.00970606,0.0164353,0.0298921,0.0567985,0.110610", \
            "0.00315002,0.00633771,0.00970602,0.0164361,0.0298928,0.0567975,0.110614", \
            "0.00594783,0.00855601,0.0108711,0.0165314,0.0298930,0.0567989,0.110613", \
            "0.0100557,0.0135596,0.0166079,0.0217381,0.0314545,0.0568000,0.110613", \
            "0.0155905,0.0199433,0.0237401,0.0301861,0.0406656,0.0599695,0.110612", \
            "0.0227162,0.0279150,0.0324341,0.0400918,0.0526945,0.0727865,0.113484", \
            "0.0316036,0.0376134,0.0428795,0.0517033,0.0662647,0.0896769,0.127281");
  }
```

- Reference to the Timing_7_7 (transition,load) template
- Same kind of table for a rising transition of the output.
- Coherency : The maximum transition time (0.127281) is less than the default_max_transition

Nangate 45nm Open Cell Library

NAND2_X4 : Falling Transition time of ZN signal

```
fall_transition(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00313418,0.00633765,0.00970606,0.0164353,0.0298921,0.0567985,0.110610", \
            "0.00315002,0.00633771,0.00970602,0.0164361,0.0298928,0.0567975,0.110614", \
            "0.00594783,0.00855601,0.0108711,0.0165314,0.0298930,0.0567989,0.110613", \
            "0.0100557,0.0135596,0.0166079,0.0217381,0.0314545,0.0568000,0.110613", \
            "0.0155905,0.0199433,0.0237401,0.0301861,0.0406656,0.0599695,0.110612", \
            "0.0227162,0.0279150,0.0324341,0.0400918,0.0526945,0.0727865,0.113484", \
            "0.0316036,0.0376134,0.0428795,0.0517033,0.0662647,0.0896769,0.127281");
  }
```

- Reference to the Timing_7_7 (transition,load) template
- Same kind of table for a rising transition of the output.
- Coherency : The maximum transition time (0.127281) is less than the default_max_transition

Nangate 45nm Open Cell Library

NAND2_X4 : Falling Transition time of ZN signal

```
fall_transition(Timing_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.00313418,0.00633765,0.00970606,0.0164353,0.0298921,0.0567985,0.110610", \
            "0.00315002,0.00633771,0.00970602,0.0164361,0.0298928,0.0567975,0.110614", \
            "0.00594783,0.00855601,0.0108711,0.0165314,0.0298930,0.0567989,0.110613", \
            "0.0100557,0.0135596,0.0166079,0.0217381,0.0314545,0.0568000,0.110613", \
            "0.0155905,0.0199433,0.0237401,0.0301861,0.0406656,0.0599695,0.110612", \
            "0.0227162,0.0279150,0.0324341,0.0400918,0.0526945,0.0727865,0.113484", \
            "0.0316036,0.0376134,0.0428795,0.0517033,0.0662647,0.0896769,0.127281");
  }
```

- Reference to the Timing_7_7 (transition,load) template
- Same kind of table for a rising transition of the output.
- Coherency : The maximum transition time (0.127281) is less than the default_max_transition

Nangate 45nm Open Cell Library

NAND2_X4 : Internal Dynamic power consumption of the gate

```
internal_power () {
  related_pin          : "A1";
  fall_power(Power_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.795787,0.940878,0.980508,1.014321,1.042872,1.047780,1.052940", \
            "0.527188,0.716998,0.831193,0.921873,0.985745,1.018615,1.041402", \
            "0.838523,0.654409,0.697793,0.801639,0.888976,0.958862,1.007789", \
            "2.454897,1.823314,1.436914,1.141771,1.072669,1.059437,1.049585", \
            "5.068604,4.189900,3.531058,2.676582,1.933285,1.575694,1.350992", \
            "8.605884,7.786085,6.914839,5.578610,4.057340,2.851663,2.142791", \
            "13.235730,12.471150,11.622380,9.965538,7.625804,5.289704,3.673908");
  }
```

- Internal energy consumption (Joules...) used for a fall transition of Z1 caused by a A1 transition .
- Correlated with the input transition time and the capacitive load.
- All cases should be tabulated...
- Warning : This doesn't take into account the energy stored in the load capacitor itself.
- Question : How to explain this kind of measurements ?.

Nangate 45nm Open Cell Library

NAND2_X4 : Internal Dynamic power consumption of the gate

```
internal_power () {
  related_pin          : "A1";
  fall_power(Power_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.795787,0.940878,0.980508,1.014321,1.042872,1.047780,1.052940", \
            "0.527188,0.716998,0.831193,0.921873,0.985745,1.018615,1.041402", \
            "0.838523,0.654409,0.697793,0.801639,0.888976,0.958862,1.007789", \
            "2.454897,1.823314,1.436914,1.141771,1.072669,1.059437,1.049585", \
            "5.068604,4.189900,3.531058,2.676582,1.933285,1.575694,1.350992", \
            "8.605884,7.786085,6.914839,5.578610,4.057340,2.851663,2.142791", \
            "13.235730,12.471150,11.622380,9.965538,7.625804,5.289704,3.673908");
  }
```

- Internal energy consumption (Joules...) used for a fall transition of Z1 caused by a A1 transition .
- Correlated with the input transition time and the capacitive load.
- All cases should be tabulated...
- Warning : This doesn't take into account the energy stored in the load capacitor itself.
- Question : How to explain this kind of measurements ?.

Nangate 45nm Open Cell Library

NAND2_X4 : Internal Dynamic power consumption of the gate

```
internal_power () {
  related_pin          : "A1";
  fall_power(Power_7_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    index_2 ("0.365616,7.419590,14.839200,29.678400,59.356800,118.714000,237.427000");
    values ("0.795787,0.940878,0.980508,1.014321,1.042872,1.047780,1.052940", \
            "0.527188,0.716998,0.831193,0.921873,0.985745,1.018615,1.041402", \
            "0.838523,0.654409,0.697793,0.801639,0.888976,0.958862,1.007789", \
            "2.454897,1.823314,1.436914,1.141771,1.072669,1.059437,1.049585", \
            "5.068604,4.189900,3.531058,2.676582,1.933285,1.575694,1.350992", \
            "8.605884,7.786085,6.914839,5.578610,4.057340,2.851663,2.142791", \
            "13.235730,12.471150,11.622380,9.965538,7.625804,5.289704,3.673908");
  }
```

- Internal energy consumption (Joules...) used for a fall transition of Z1 caused by a A1 transition .
- Correlated with the input transition time and the capacitive load.
- All cases should be tabulated...
- Warning : This doesn't take into account the energy stored in the load capacitor itself.
- Question : How to explain this kind of measurements ?.

Outline

Nangate 45nm Open Cell Library

DFF_X2 : Global data

```
cell (DFF_X2) {
  drive_strength      : 2;
  ff ("IQ" , "IQN") {
    next_state          : "D";
    clocked_on          : "CK";
}
```

- Global information on the cell
- Buffer size X2
- The gate is a D flip-flop working on the rising edge of CK
- The gate has two outputs Q and QN

Nangate 45nm Open Cell Library

DFF_X2 : Global data

```
cell (DFF_X2) {
  drive_strength      : 2;
  ff ("IQ" , "IQN") {
    next_state          : "D";
    clocked_on          : "CK";
}
```

- Global information on the cell
- Buffer size X2
- The gate is a D flip-flop working on the rising edge of CK
- The gate has two outputs Q and QN

Nangate 45nm Open Cell Library

DFF_X2 : Global data

```
cell (DFF_X2) {
  drive_strength      : 2;
  ff ("IQ" , "IQN") {
    next_state        : "D";
    clocked_on        : "CK";
}
```

- Global information on the cell
- Buffer size X2
- The gate is a D flip-flop working on the rising edge of CK
- The gate has two outputs Q and QN

Nangate 45nm Open Cell Library

DFF_X2 : Global data

```
cell (DFF_X2) {
  drive_strength      : 2;
  ff ("IQ" , "IQN") {
    next_state          : "D";
    clocked_on          : "CK";
}
```

- Global information on the cell
- Buffer size X2
- The gate is a D flip-flop working on the rising edge of CK
- The gate has two outputs Q and QN

Nangate 45nm Open Cell Library

DFF_X2 : Leakage Power

```
cell_leakage_power  : 115.103670;

 leakage_power () {
  when            : "!CK & !D & !Q & QN";
  value           : 107.651390;
 }
 leakage_power () {
  when            : "!CK & !D & Q & !QN";
  value           : 115.805800;
 }
 ...
```

- The leakage power is a function of the state of the cell.
- A mean value.
- As the cell is sequential the leakage power is also a function of the outputs ! !.
- Here 8 cases have to be measured.

Nangate 45nm Open Cell Library

DFF_X2 : Leakage Power

```
cell_leakage_power  : 115.103670;

 leakage_power () {
  when            : "!CK & !D & !Q & QN";
  value           : 107.651390;
 }
 leakage_power () {
  when            : "!CK & !D & Q & !QN";
  value           : 115.805800;
 }
 ...
```

- The leakage power is a function of the state of the cell.
- A mean value.
- As the cell is sequential the leakage power is also a function of the outputs ! !.
- Here 8 cases have to be measured.

Nangate 45nm Open Cell Library

DFF_X2 : Leakage Power

```
cell_leakage_power  : 115.103670;

 leakage_power () {
  when            : "!CK & !D & !Q & QN";
  value           : 107.651390;
 }
 leakage_power () {
  when            : "!CK & !D & Q & !QN";
  value           : 115.805800;
 }
 ...
```

- The leakage power is a function of the state of the cell.
- A mean value.
- As the cell is sequential the leakage power is also a function of the outputs ! !.
- Here 8 cases have to be measured.

Nangate 45nm Open Cell Library

DFF_X2 : Leakage Power

```
cell_leakage_power  : 115.103670;

 leakage_power () {
  when            : "!CK & !D & !Q & QN";
  value           : 107.651390;
 }
 leakage_power () {
  when            : "!CK & !D & Q & !QN";
  value           : 115.805800;
 }
 ...
```

- The leakage power is a function of the state of the cell.
- A mean value.
- As the cell is sequential the leakage power is also a function of the outputs ! !.
- Here 8 cases have to be measured.

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin     : "CK";
   timing_type     : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".
- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin     : "CK";
   timing_type     : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".

- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin     : "CK";
   timing_type     : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".

- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin    : "CK";
   timing_type    : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".

- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin     : "CK";
   timing_type     : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".

- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hold constraint on the D input

```
timing () {
   related_pin     : "CK";
   timing_type     : hold_rising;
   fall_constraint(Hold_3_3) {
    index_1 ("0.00117378,0.0449324,0.198535");
    index_2 ("0.00117378,0.0449324,0.198535");
    values ("0.000950,0.009897,0.009901", \
            "0.004801,0.011035,0.005683", \
            "0.144217,0.153663,0.144977");
   }
```

- "Hold time" from rising of clk for a rising transition of D.
- Tabulated (Hold_3_3)
- Index 1 : Transition time of D
- Index 2 : Transition time of CK
- Same kind of table for the "Setup Time".

- QUESTION : What about the output load capacitance ?

Nangate 45nm Open Cell Library

DFF_X2 : Hidden power for a transition of D

```
internal_power () {

   when            : "!CK & !Q & QN";

   fall_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("4.354644,4.333607,4.304507,4.328622,4.507989,4.894921,5.519367");
   }
   rise_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("3.211098,3.175770,3.145376,3.177001,3.349767,3.724420,4.327453");
   }

  }...
```

- Energy used for a transition of D (no transition on CLK or the outputs)
- Depends only on then transition time of D.
- Warning : Doesnt take into account energy stored in the input capacitance itself.
- 4x2 cases linked to the state of the flip-flop and the value of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Hidden power for a transition of D

```
internal_power () {

   when            : "!CK & !Q & QN";

   fall_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("4.354644,4.333607,4.304507,4.328622,4.507989,4.894921,5.519367");
   }
   rise_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("3.211098,3.175770,3.145376,3.177001,3.349767,3.724420,4.327453");
   }

  }...
```

- Energy used for a transition of D (no transition on CLK or the outputs)
- Depends only on then transition time of D.
- Warning : Doesnt take into account energy stored in the input capacitance itself.
- 4x2 cases linked to the state of the flip-flop and the value of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Hidden power for a transition of D

```
internal_power () {

   when            : "!CK & !Q & QN";

   fall_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("4.354644,4.333607,4.304507,4.328622,4.507989,4.894921,5.519367");
   }
   rise_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("3.211098,3.175770,3.145376,3.177001,3.349767,3.724420,4.327453");
   }

  }...
```

- Energy used for a transition of D (no transition on CLK or the outputs)
- Depends only on then transition time of D.
- Warning : Doesnt take into account energy stored in the input capacitance itself.
- 4x2 cases linked to the state of the flip-flop and the value of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Hidden power for a transition of D

```
internal_power () {

   when            : "!CK & !Q & QN";

   fall_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("4.354644,4.333607,4.304507,4.328622,4.507989,4.894921,5.519367");
   }
   rise_power(Hidden_power_7) {
    index_1 ("0.00117378,0.00472397,0.0171859,0.0409838,0.0780596,0.130081,0.198535");
    values ("3.211098,3.175770,3.145376,3.177001,3.349767,3.724420,4.327453");
   }

  }...
```

- Energy used for a transition of D (no transition on CLK or the outputs)
- Depends only on then transition time of D.
- Warning : Doesnt take into account energy stored in the input capacitance itself.
- 4x2 cases linked to the state of the flip-flop and the value of CK.

Nangate 45nm Open Cell Library

DFF_X2 : CK clock constraints

```
...
clock      : true;
...
timing () {

  related_pin     : "CK";
  timing_type     : min_pulse_width;
  fall_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.054590,0.069863,0.198733");
  }
  rise_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.080840,0.080924,0.198733");
  }
}
...
internal_power() {...
}...
```

- CK is clock...
- The minimum duration of the "1" state is tabulated.
- This duration is a function of the transition time of the clock.
- With hidden power consumption when D and Q are identical. . .

Nangate 45nm Open Cell Library

DFF_X2 : CK clock constraints

```
...
clock      : true;
...
timing () {

  related_pin     : "CK";
  timing_type     : min_pulse_width;
  fall_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.054590,0.069863,0.198733");
  }
  rise_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.080840,0.080924,0.198733");
  }
}
...
internal_power() {...
}...
```

- CK is clock...
- The minimum duration of the "1" state is tabulated.
- This duration is a function of the transition time of the clock.
- With hidden power consumption when D and Q are identical. . .

Nangate 45nm Open Cell Library

DFF_X2 : CK clock constraints

```
...
clock      : true;
...
timing () {

  related_pin     : "CK";
  timing_type     : min_pulse_width;
  fall_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.054590,0.069863,0.198733");
  }
  rise_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.080840,0.080924,0.198733");
  }
}
...
internal_power() {...
}...
```

- CK is clock...
- The minimum duration of the "1" state is tabulated.
- This duration is a function of the transition time of the clock.
- With hidden power consumption when D and Q are identical. . .

Nangate 45nm Open Cell Library

DFF_X2 : CK clock constraints

```
...
clock      : true;
...
timing () {

  related_pin     : "CK";
  timing_type     : min_pulse_width;
  fall_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.054590,0.069863,0.198733");
  }
  rise_constraint(Pulse_width_3) {
   index_1 ("0.00117378,0.0449324,0.198535");
   values ("0.080840,0.080924,0.198733");
  }
}
...
internal_power() {...
}...
```

- CK is clock...
- The minimum duration of the "1" state is tabulated.
- This duration is a function of the transition time of the clock.
- With hidden power consumption when D and Q are identical. . .

Nangate 45nm Open Cell Library

DFF_X2 : Output signals (timing/power)

- Warning : All events on outputs are related to the CK transition
- Transition times are functions of the CK transition time and of the ouput load capacitance.
- Propagation times are functions of the CK transition time and of the ouput load capacitance.
- Power consumption tabulated for transition of Q due to a transition of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Output signals (timing/power)

- Warning : All events on outputs are related to the CK transition
- Transition times are functions of the CK transition time and of the ouput load capacitance.
- Propagation times are functions of the CK transition time and of the ouput load capacitance.
- Power consumption tabulated for transition of Q due to a transition of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Output signals (timing/power)

- Warning : All events on outputs are related to the CK transition
- Transition times are functions of the CK transition time and of the ouput load capacitance.
- Propagation times are functions of the CK transition time and of the ouput load capacitance.
- Power consumption tabulated for transition of Q due to a transition of CK.

Nangate 45nm Open Cell Library

DFF_X2 : Output signals (timing/power)

- Warning : All events on outputs are related to the CK transition
- Transition times are functions of the CK transition time and of the ouput load capacitance.
- Propagation times are functions of the CK transition time and of the ouput load capacitance.
- Power consumption tabulated for transition of Q due to a transition of CK.

Outline

Liberty files

Limitations of the NLDM model

- The examined NLDM model (Non Linear Delay Model) is not enough accurate for recent technologies.
- "IR drop" simulation needs a more sophisticated model.
- Evolution proposed par Synopsys (CCS pour Composite Current Source).
- Evolution proposed par Cadence (ECSM pour Effective Current Source Model).

Liberty files

Limitations of the NLDM model

- The examined NLDM model (Non Linear Delay Model) is not enough accurate for recent technologies.
- "IR drop" simulation needs a more sophisticated model.
- Evolution proposed par Synopsys (CCS pour Composite Current Source).
- Evolution proposed par Cadence (ECSM pour Effective Current Source Model).

Liberty files

Limitations of the NLDM model

- The examined NLDM model (Non Linear Delay Model) is not enough accurate for recent technologies.
- "IR drop" simulation needs a more sophisticated model.
- Evolution proposed par Synopsys (CCS pour Composite Current Source).
- Evolution proposed par Cadence (ECSM pour Effective Current Source Model).

Liberty files

Limitations of the NLDM model

- The examined NLDM model (Non Linear Delay Model) is not enough accurate for recent technologies.
- "IR drop" simulation needs a more sophisticated model.
- Evolution proposed par Synopsys (CCS pour Composite Current Source).
- Evolution proposed par Cadence (ECSM pour Effective Current Source Model).

Liberty files

Cadence ECSM : the model



Liberty files

Cadence ECSM : IRDROP simulation



70K instance design

Liberty files

New models

- The input capacitance is tabulated.
- The output model is a non linear current or voltage source
- Current/Voltages are tabulated as functions of time.
- Complex models but results near electrical simulation results...
- The 3 kind of models are distributed for the foundries clients (NLDM :51Mo, ECSM :291Mo, CCS :781Mo)

Liberty files

New models

- The input capacitance is tabulated.
- The output model is a non linear current or voltage source
- Current/Voltages are tabulated as functions of time.
- Complex models but results near electrical simulation results...
- The 3 kind of models are distributed for the foundries clients (NLDM :51Mo, ECSM :291Mo, CCS :781Mo)

Liberty files

New models

- The input capacitance is tabulated.
- The output model is a non linear current or voltage source
- Current/Voltages are tabulated as functions of time.
- Complex models but results near electrical simulation results...
- The 3 kind of models are distributed for the foundries clients (NLDM :51Mo, ECSM :291Mo, CCS :781Mo)

Liberty files

New models

- The input capacitance is tabulated.
- The output model is a non linear current or voltage source
- Current/Voltages are tabulated as functions of time.
- Complex models but results near electrical simulation results...
- The 3 kind of models are distributed for the foundries clients (NLDM :51Mo, ECSM :291Mo, CCS :781Mo)

Liberty files

New models

- The input capacitance is tabulated.
- The output model is a non linear current or voltage source
- Current/Voltages are tabulated as functions of time.
- Complex models but results near electrical simulation results...
- The 3 kind of models are distributed for the foundries clients (NLDM :51Mo, ECSM :291Mo, CCS :781Mo)

Liberty files

Why a lecture on this syntax ?

- The designer may add it's own macro-cells to existing libraries.
- From time to time, the designer have to tweak the liberty file in order to have correct behavior.
- In hierarchical designs, tools may generate black-box Liberty files at the block level.
- In order write efficients synthesis scripts:.

Liberty files

Why a lecture on this syntax ?

- The designer may add it's own macro-cells to existing libraries.
- From time to time, the designer have to tweak the liberty file in order to have correct behavior.
- In hierarchical designs, tools may generate black-box Liberty files at the block level.
- In order write efficients synthesis scripts:.

Liberty files

Why a lecture on this syntax ?

- The designer may add it's own macro-cells to existing libraries.
- From time to time, the designer have to tweak the liberty file in order to have correct behavior.
- In hierarchical designs, tools may generate black-box Liberty files at the block level.
- In order write efficients synthesis scripts:.

Liberty files

Why a lecture on this syntax ?

- The designer may add it's own macro-cells to existing libraries.
- From time to time, the designer have to tweak the liberty file in order to have correct behavior.
- In hierarchical designs, tools may generate black-box Liberty files at the block level.
- In order write efficients synthesis scripts:.