



UART debug messages available via a USB port and a 3 pin jumper for TX, RX, and GND UART connections






Id: 2/8



Power Monitor and Supply

PMS has an INA219 current sensor
for each board/node in the
PCB. Each takes in the 5V from it's
parent board and supplies 5V to said
board's circuit (its peripherals)
thus enabling monitoring



Sheet: /PMS_APM/
File: PMS_APM.kicad_sch

Title:


Size: A4

Date:




KiCad E.D.A. 10.0.3

Rev:

Id: 4/8



Sheet: /THERMISTORS_APM/ File: THERMISTORS_APM.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. 10.0.3		Id: 5/8



Sheet: /STORAGE_APM/
File: STORAGE_APM.kicad_sch

Title:



Size: A4	Date:
----------	-------

KiCad E.D.A. 10.0.3

Date:

Rev:

Id: 6/8



Sheet: /AUDIO_APM/
File: AUDIO_APM.kicad_sch

Title:




Size: A4
KiCad E.D.A. 10.0.3

Date:

Rev:
Id: 7/8

Dual FPC STM32<->Tang Nano 20K FPGA connection configuration. The STM32 side has two connectors where only one can be active at a time

- Configuration 1: FPGA_FFC with SPI, QSPI, UART connections.
- Configuration 2: FPGA_FMC with 16 bit muxed FMC configuration resulting in a 128kb shared address space between the STM32 & FPGA



Sheet: /FPGA_INTERFACE/
File: FPGA_INTERFACE.kicad_sch

Title:

Size: A4

Date:

KiCad E.D.A. 10.0.3

Rev:

Id: 8/8