


UART -> USB Debug Port

UART debug messages available via a USB port and a 3 pin jumper for TX, RX, and GND UART connections



Sheet: /USB_debug_APM/
File: USB_debug_APM.kicad_sch

Title:


Size: A4

Date:

KiCad E.D.A. 10.0.4





Rev:

Id: 2/8



Power Monitor and Supply

PMS has an INA219 current sensor for each board/node in the PCB. Each takes in the 5V from it's parent board and supplies 5V to said board's circuit (its peripherals) thus enabling monitoring




Sheet: /PMS_APM/
File: PMS_APM.kicad_sch


Title:

Size: A4
KiCad E.D.A. 10.0.4

Date:

Rev:
Id: 4/8





Sheet: /STORAGE_APM/
File: STORAGE_APM.kicad_sch

Title:



Size: A4

Date:

Rev:

KiCad E.D.A. 10.0.4

Id: 6/8



Sheet: /AUDIO_APM/
File: AUDIO_APM.kicad_sch

Title:

Size: A4
KiCad E.D.A. 10.0.4

Date:

Rev:
Id: 7/8

ACM FPGA Interface

Dual FPC STM32<->Tang Nano 20K FPGA connection configuration. The STM32 side has two connectors where only one can be active at a time

- Configuration 1: FPGA_FFC with SPI, QSPI, UART connections.
- Configuration 2: FPGA_FMC with:
 - 16 bit muxed data
 - and async FMCconfiguration resulting in a 64MB shared address space between the STM32 & FPGA

