

## Machine Dynamics Questions and Answers – Automatic Control

This set of Machine Dynamics Multiple Choice Questions & Answers (MCQs) focuses on “Automatic Control”.

- The result of the act of adjustment is called
  - response
  - command
  - process control
  - process controller

[View Answer](#)

Answer: b

Explanation: The result of the act of adjustment is called command. The subsequent result of the system to the command is known as response. The automatic control of variables is known as process control. The device which controls a process is called a process controller.

- The subsequent result of the system to the command is known as
  - response
  - command
  - process control
  - process controller

[View Answer](#)

Answer: a

Explanation: The result of the act of adjustment is called command. The subsequent result of the system to the command is known as response. The automatic control of variables is known as process control. The device which controls a process is called a process controller.

- The automatic control of variables is known as
  - response
  - command
  - process control
  - process controller

[View Answer](#)

Answer: c

Explanation: The result of the act of adjustment is called command. The subsequent result of the system to the command is known as response. The automatic control of variables is known as process control. The device which controls a process is called a process controller.

- The device which controls a process is called a
  - response
  - command
  - process control
  - process controller

[View Answer](#)

Answer: d

Explanation: The result of the act of adjustment is called command. The subsequent result of the system to the command is known as response. The automatic control of variables is known as process control. The device which controls a process is called a process controller.


- The device used to keep the variables at a constant desired value is called as
  - regulator
  - kinetic control
  - feed back
  - error detector

[View Answer](#)

Answer: a

Explanation: The device used to keep the variables at a constant desired value is called as regulator. The instrument measuring the output of the machine for comparison with the input to the machine is known as feedback. The automatic control of the displacement or velocity or acceleration of a member of a machine is called as kinetic control. A differential device used to measure the actual controlled quantity and to compare it continuously with the desired value is called error detector.

advertisement



- The instrument measuring the output of the machine for comparison with the input to the machine is known as
  - regulator
  - kinetic control
  - feed back
  - error detector

[View Answer](#)

Answer: c

Explanation: The device used to keep the variables at a constant desired value is called as regulator. The instrument measuring the output of the machine for comparison with the input to the machine is known as feedback. The automatic control of the displacement or velocity or acceleration of a member of a machine is called as kinetic control. A differential device used to measure the actual controlled quantity and to compare it continuously with the desired value is called error detector.

- The automatic control of the displacement or velocity or acceleration of a member of a machine is called as
  - regulator
  - kinetic control
  - feed back
  - error detector

[View Answer](#)

Answer: b

Explanation: The device used to keep the variables at a constant desired value is called as regulator. The instrument measuring the output of the machine for comparison with the input to the machine is known as feedback. The automatic control of the displacement or velocity or acceleration of a member of a machine is called as kinetic control. A differential device used to measure the actual controlled quantity and to compare it continuously with the desired value is called error detector.

- A differential device used to measure the actual controlled quantity and to compare it continuously with the desired value is called
  - regulator
  - kinetic control
  - feed back
  - error detector

[View Answer](#)

Answer: d

Explanation: The device used to keep the variables at a constant desired value is called as regulator. The instrument measuring the output of the machine for comparison with the input to the machine is known as feedback. The automatic control of the displacement or velocity or acceleration of a member of a machine is called as kinetic control. A differential device used to measure the actual controlled quantity and to compare it continuously with the desired value is called error detector.

- It is a device to change a signal which is in one physical form to a corresponding signal in another physical form.
  - amplification
  - transducer
  - feed back
  - none of the mentioned

[View Answer](#)

Answer: b

Explanation: Increasing the amplitude of the signal without affecting its waveform is known as amplification. The device to change a signal which is in one physical form to a corresponding signal in another physical form is known as transducer.

- Increasing the amplitude of the signal without affecting its waveform is known as
  - amplification
  - transducer
  - feed back
  - none of the mentioned

[View Answer](#)

Answer: a

Explanation: Increasing the amplitude of the signal without affecting its waveform is known as amplification. The device to change a signal which is in one physical form to a corresponding signal in another physical form is known as transducer.

### Sanfoundry Global Education & Learning Series – Machine Dynamics.

To practice all areas of Machine Dynamics, [here is complete set of 1000+ Multiple Choice Questions and Answers](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Machine Dynamics Questions and Answers – Analytical Synthesis for Slider Crank Mechanism](#)

» [Next - Machine Dynamics Questions and Answers – Open-Loop Transfer Function](#)

advertisement

### Recommended Posts:

- [Microprocessor Questions & Answers](#)
- [Java Programming Examples on Classes](#)
- [Analog Communications Questions and Answers](#)
- [C Programming Examples on File Handling](#)
- [MATLAB Questions and Answers](#)
- [VHDL Questions and Answers](#)
- [PLC Programming Examples](#)
- [C Tutorials](#)
- [Linear Integrated Circuits Questions and Answers](#)
- [Computational Fluid Dynamics Questions and Answers](#)
- [Unix Questions and Answers](#)
- [C Programming Questions and Answers](#)
- [Compilers Questions and Answers](#)
- [Linux Questions and Answers](#)
- [Machine Design Questions and Answers](#)
- [Machine Kinematics Questions and Answers](#)
- [Control Systems Questions and Answers](#)
- [Machine Tools & Machining Questions and Answers](#)
- [Machine Drawing Questions and Answers](#)
- [Machine Dynamics Questions and Answers](#)



**Manish Bhojasia**, a technology veteran with 20+ years @ Cisco & Wipro, is Founder and CTO at Sanfoundry. He is Linux Kernel Developer & SAN Architect and is passionate about competency developments in these areas. He lives in Bangalore and delivers focused training sessions to IT professionals in Linux Kernel, Linux Debugging, Linux Device Drivers, Linux Networking, Linux Storage, Advanced C Programming, SAN Storage Technologies, SCSI Internals & Storage Protocols such as iSCSI & Fiber Channel. Stay connected with him @ [LinkedIn](#) | [Instagram](#) | [Facebook](#) |

[Twitter](#)

### Subscribe Sanfoundry Newsletter and Posts

Name\*

Email\*

Subscribe

