

## Control Systems Questions and Answers – Time Response of Second Order Systems – II

This set of Control Systems Questions and Answers for Experienced people focuses on “ Time Response of Second Order Systems – II”.

1. What will be the nature of time response if the roots of the characteristic equation are located on the s-plane imaginary axis?
- Oscillations
  - Damped oscillations
  - No oscillations
  - Under damped oscillaations

[View Answer](#)

Answer: c  
Explanation: complex conjugate (non-multiple): oscillatory (sustained oscillations)  
Complex conjugate (multiple): unstable (growing oscillations).

2. Consider a system with transfer function  $G(s) = \frac{s+6}{Ks^2+s+6}$ . Its damping ratio will be 0.5 when the values of K is:

- 2/6
- 3
- 1/6
- 6

[View Answer](#)

Answer: c  
Explanation:  $s+\frac{6}{K}[\frac{s^2+s}{K+6/K}]$  Comparing with  $s^2+2\zeta\omega_n s+\omega_n^2$   
 $\omega_n = \sqrt{6/K}$   
 $2\zeta\omega_n = 1/K$   
 $2*0.5*\sqrt{6/K} = 1/K$   
 $K = 1/6$ .

3. The output in response to a unit step input for a particular continuous control system is  $c(t) = 1 - e^{-t}$ . What is the delay time  $T_d$ ?

- 0.36
- 0.18
- 0.693
- 0.289

[View Answer](#)

Answer: c  
Explanation: The output is given as a function of time. The final value of the output is  $\lim_{t \rightarrow \infty} c(t) = 1$ ; . Hence  $T_d$  (at 50% of the final value) is the solution of  $0.5 = 1 - e^{-T_d}$ , and is equal to  $\ln 2$  or 0.693 sec.

4. Which one of the following is the most likely reason for large overshoot in a control system?

- High gain in a system
- Presence of dead time delay in a system
- High positive correcting torque
- High retarding torque

[View Answer](#)

Answer: c  
Explanation: Large overshoot refers to the maximum peak in the response of the closed loop system and this is mainly due to the high positive correcting torque.

advertisement

5. For the system  $2/s+1$ , the approximate time taken for a step response to reach 98% of its final value is:

- 1s
- 2s
- 4s
- 8s

[View Answer](#)

Answer: c  
Explanation:  $C(s)/R(s) = 2/s+1$   
 $R(s) = 1/s$  (step input)  
 $C(s) = 2/(s+1)$   
 $c(t) = 2[1 - e^{-t}]$  1.96 =  $2[1 - e^{-T}]$   $T = 4$ sec.

6. The unit step response of a second order system is  $1 - e^{-5t} - 5te^{-5t}$ . Consider the following statements:

- The under damped natural frequency is 5 rad/s.
  - The damping ratio is 1.
  - The impulse response is  $25te^{-5t}$ .
- Which of the statements given above are correct?

- Only 1 and 2
- Only 2 and 3
- Only 1 and 3
- 1,2 and 3

[View Answer](#)

Answer: d  
Explanation:  $C(s)/R(s) = 1/s - 1/s+5-5/(s+5)^2$   
 $C(s) = 25/s(s^2+10s+25)$   
 $R(s) = 1/s$   
 $G(s) = 25/(s^2+10s+25)$   
 $\omega_n = \sqrt{25}$   
 $\omega_n = 5$  rad/sec  
 $\zeta = 1$ .

7. The loop transfer function of controller  $G_c(s)$  is :

- $1+0.1s/s$
- $-1+0.1s/s$
- $-s/s+1$
- $s/s+1$

[View Answer](#)

Answer: a  
Explanation: The transfer function of the controller is  $0.1s+1/s$   
 $G_c(s) = 0.1s+1/s$ .

8. The peak percentage overshoot of the closed loop system is :

- 5.0%
- 10.0%
- 16.3%
- 1.63%

[View Answer](#)

Answer: c  
Explanation:  $C(s)/R(s) = 1/s^2+s+1$   
 $C(s)/R(s) = \omega_n^2/s^2+2\zeta\omega_n s+\omega_n^2$   
Compare both the equations,  
 $\omega_n = 1$  rad/sec  
 $2\zeta\omega_n = 1$   
 $M_p = 16.3\%$

9. Consider a second order all-pole transfer function model, if the desired settling time(5%) is 0.60 sec and the desired damping ratio 0.707, where should the poles be located in s-plane?

- $-5+j4\sqrt{2}$
- $-5+j5$
- $-4+j5\sqrt{2}$
- $-4+j7$

[View Answer](#)

Answer: b  
Explanation:  $\zeta = 1/\sqrt{2}$   
 $\omega_n = 5$   
 $s = -5+j5$ .

10. Which of the following quantities give a measure of the transient characteristics of a control system, when subjected to unit step excitation.

- Maximum overshoot
  - Maximum undershoot
  - Overall gain
  - Delay time
  - Rise time
  - Fall time
- 1,3 and 5
  - 2, 4 and 5
  - 2,4 and 6
  - 1,4 and 5

[View Answer](#)

Answer: d  
Explanation: Maximum overshoot, rise time and delay time are the major factor of the transient behaviour of the system and determines the transient characteristics.

### Sanfoundry Global Education & Learning Series – Control Systems.

To practice all areas of Control Systems for Experienced people, [here is complete set of 1000+ Multiple Choice Questions and Answers](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Control Systems Questions and Answers – Time Response of Second Order Systems – I](#)

[» Next - Control Systems Questions and Answers – Time Response of Second Order Systems – III](#)

### Recommended Posts:

- [1. Mass Transfer Questions and Answers](#)
- [2. MATLAB Questions and Answers](#)
- [3. Heat Transfer Operations Questions and Answers](#)
- [4. Electronic Devices and Circuits Questions and Answers](#)
- [5. Polymer Engineering Questions and Answers](#)
- [6. Heat Transfer Questions and Answers](#)
- [7. IC Engine Questions and Answers](#)
- [8. Linear Integrated Circuits Questions and Answers](#)
- [9. Network Theory Questions and Answers](#)
- [10. Power Systems Questions and Answers](#)
- [11. Electric Circuits Questions and Answers](#)
- [12. Signals & Systems Questions and Answers](#)
- [13. Control Systems Questions and Answers](#)
- [14. MATLAB Questions and Answers – Impulse Response – 1](#)
- [15. Control Systems Questions and Answers – Control of the Effects of Disturbance Signals by Use of Feedback](#)
- [16. Signals & Systems Questions and Answers – Convolution : Impulse Response Representation for LTI Systems – 1](#)
- [17. Signals & Systems Questions and Answers – Convolution : Impulse Response Representation for LTI Systems – 2](#)
- [18. Control Systems Questions and Answers – Frequency Response](#)
- [19. Control Systems Questions and Answers – Design Considerations for Higher-Order Systems](#)
- [20. Control Systems Questions and Answers – Optimal Control Problems-2](#)



**Manish Bhojasia**, a technology veteran with 20+ years @ Cisco & Wipro, is Founder and CTO at Sanfoundry. He is Linux Kernel Developer & SAN Architect and is passionate about competency developments in these areas. He lives in Bangalore and delivers focused training sessions to IT professionals in Linux Kernel, Linux Debugging, Linux Device Drivers, Linux Networking, Linux Storage, Advanced C Programming, SAN Storage Technologies, SCSI Internals & Storage Protocols such as iSCSI & Fiber Channel. Stay connected with him @ [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#)

### Subscribe Sanfoundry Newsletter and Posts

Name\*

Email\*

Subscribe