

ASSIGNMENT 1

AKILESH K

Task1

1)

```
mysql> CREATE TABLE customers (  
->  
->  customerid INT,  
->  firstname varchar(25),  
->  lastname varchar(25),  
->  email varchar(35),  
->  phone varchar(20),  
->  address varchar(25),  
->  PRIMARY KEY (customerid) );  
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> CREATE TABLE products(  
(->  productid int,  
(->  productname varchar(25),  
(->  description TEXT,  
al->  price double,  
cl->  PRIMARY KEY (productid)  
t(-> ) ;  
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> CREATE TABLE orders (  
->  orderid INT,  
->  customerid INT,  
->  orderdate DATE,  
->  totalamount DOUBLE,  
->  PRIMARY KEY (orderid),  
->  FOREIGN KEY (customerid) REFERENCES customers(customerid)  
->  
-> );  
Query OK, 0 rows affected (0.07 sec)
```

```

ERROR 1072 (42000): Key column 'orderdetails' doesn't exist in table
mysql> CREATE TABLE orderdetails (
  -> orderdetailsid INT,
  -> orderid INT,
  -> productid INT,
  -> quantity INT,
  -> PRIMARY KEY (orderdetailsid),
  -> FOREIGN KEY (orderid) REFERENCES orders(orderid),
  ->
  -> FOREIGN KEY (productid) REFERENCES products(productid)
  ->
  -> );
Query OK, 0 rows affected (0.07 sec)

```

```

mysql> CREATE TABLE inventory (
  -> inventoryid INT,
  -> productid INT,
  -> quantityinstock INT,
  -> laststockupdate DATE,
  -> PRIMARY KEY (inventoryid),
  -> FOREIGN KEY (productid) REFERENCES products(productid)
  ->
  -> );
Query OK, 0 rows affected (0.05 sec)

```

```

mysql> INSERT INTO customers (customerid,firstname,lastname,email,phone,address)
  -> VALUES
  -> ("2","Benjamin","May","benjamin@icloud.net","1-573-762-5734","Ap #774-4948 Hendrerit Av."),
  -> ("10","Jonah","Boyle","jonah2869@yahoo.org","(555) 377-2867","3852 In. Rd."),
  -> ("7","Burton","Hicks","burton2976@protonmail.ca","(889) 371-0537","924-9041 Nullam Rd."),
  -> ("5","Aiko","Barry","aiko@outlook.com","1-344-918-8823","2780 Non. Street"),
  -> ("9","Lani","Moon","lani6109@protonmail.com","(225) 833-2432","743-1961 Sapient Road");
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

```

```

mysql> INSERT INTO products (productid, productname, description, price)
  -> VALUES ("32", "imac", "pc", "30"),
  -> ("44", "iphone", "red", "250"),
  -> ("65", "earpods", "white", "40"),
  -> ("73", "smartwatch", "esim", "300"),
  -> ("23", "keyboard", "gaming", "1000");
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0

```

```
mysql> INSERT INTO orders (orderid, customerid, orderdate, totalamount)
-> VALUES ("331", "2", "2023-07-21", "300"),
-> ("638", "10", "2023-11-30", "1000"),
-> ("524", "9", "2023-12-05", "500"),
-> ("742", "5", "2023-11-13", "700"),
-> ("937", "9", "2023-09-26", "2000") ;
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0
```

```
mysql> INSERT INTO orderdetails (orderdetailsid, orderid, productid, quantity)
-> VALUES ("837", "331", "32", "10"),
-> ("625", "638", "44", "2"),
-> ("807", "524", "65", "8"),
-> ("532", "742", "73", "22"),
-> ("972", "937", "23", "5")
-> ;
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0
```

```
mysql> INSERT INTO inventory (inventoryid, productid, quantityinstock, laststockupdate)
-> VALUES ("4235", "32", "19", "2023-08-28"),
-> ("7452", "44", "10", "2023-12-01"),
-> ("8363", "65", "30", "2023-12-07"),
-> ("6746", "73", "100", "2023-11-30"),
-> ("2679", "23", "25", "2023-10-13") ;
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0
```

2)

```
mysql> show tables;
+-----+
| Tables_in_techshop |
+-----+
| customers           |
| inventory            |
| orderdetails         |
| orders               |
| products             |
+-----+
5 rows in set (0.00 sec)
```

3)

Customers	Products	Orders	Order Details
customerid Pk 1-----*	productid Pk 1-----*	orderid Pk 1-----	orderdetailsid pk
firstname	productname	customerid FK	orderid
lastname	description	orderdate	productid FK
email	price	totalamount	quantity
phone			
address			

Inventory
inventoryidpk
productid fk 1-----
quantityinstock
laststockupdate

Task 2

1)

```
mysql> select firstname,lastname,email from customers;
```

firstname	lastname	email
Benjamin	May	benjamin@icloud.net
Aiko	Barry	aiko@outlook.com
Burton	Hicks	burton2976@protonmail.ca
Lani	Moon	lani6109@protonmail.com
Jonah	Boyle	jonah2869@yahoo.org

5 rows in set (0.00 sec)

2)

```
mysql> select orders.orderid ,orders.orderdate,customers.firstname,customers.lastname from customers
,orders where customers.customerid=orders.customerid;
```

orderid	orderdate	firstname	lastname
331	2023-07-21	Benjamin	May
742	2023-11-13	Aiko	Barry
524	2023-12-05	Lani	Moon
937	2023-09-26	Lani	Moon
638	2023-11-30	Jonah	Boyle

5 rows in set (0.00 sec)

3)

```
mysql> INSERT INTO customers (customerid,firstname,lastname,email,phone,address)
-> VALUES
-> ("2","Benjamin","May","benjamin@icloud.net","1-573-762-5734","Ap #774-4948 Hendrerit Av.")
```

4)

```
mysql> update products set price=(price *0.1)+price ;
Query OK, 5 rows affected (0.02 sec)
Rows matched: 5 Changed: 5 Warnings: 0
```

```
mysql> select * from products;
```

productid	productname	description	price
23	keyboard	gaming	1100
32	imac	pc	33
44	iphone	red	275
65	earpods	white	44
73	smartwatch	esim	330

```
5 rows in set (0.00 sec)
```

5)

```
mysql> DELETE FROM OrderDetails
-> WHERE orderid = 3
```

6)

```
mysql> INSERT INTO orders (orderid, customerid, orderdate, totalamount)
-> VALUES ("331", "2", "2023-07-21", "300"),
```

7)

```
mysql> update customers set address="st george street,12" where customerid=10;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1 Changed: 1 Warnings: 0
```

8)

```
mysql> update orders,orderdetails,products set orders.totalamount=products.price*orderdetails.quantity
where orderdetails.productid=products.productid and orders.orderid=orderdetails.orderid;
Query OK, 5 rows affected (0.02 sec)
Rows matched: 5 Changed: 5 Warnings: 0
```

```
mysql> select * from orders;
```

orderid	customerid	orderdate	totalamount
331	2	2023-07-21	330
524	9	2023-12-05	352
638	10	2023-11-30	550
742	5	2023-11-13	7260
937	9	2023-09-26	5500

```
5 rows in set (0.00 sec)
```

9)

```
mysql> INSERT INTO orders (orderid, customerid, orderdate, totalamount)
-> VALUES ("331", "2", "2023-07-21", "300"),
```

10)

```
mysql> INSERT INTO orders (orderid, customerid, orderdate, totalamount)
-> VALUES ("331", "2", "2023-07-21", "300"),
```

11)

12)

```
mysql> UPDATE Customers
-> SET number_of_orders = (
-> SELECT COUNT(*)
-> FROM Orders
-> WHERE Orders.customerid = Customers.customerid
-> );
```

Task 3

1)

```
mysql> SELECT o.orderid,o.orderdate,o.totalamount,c.firstname AS customer_firstname,c.lastname AS customer_lastname FROM
orders o JOIN customers c ON o.customerid = c.customerid;
```

orderid	orderdate	totalamount	customer_firstname	customer_lastname
331	2023-07-21	330	Benjamin	May
524	2023-12-05	352	Lani	Moon
638	2023-11-30	550	Jonah	Boyle
742	2023-11-13	7260	Aiko	Barry
937	2023-09-26	5500	Lani	Moon

5 rows in set (0.04 sec)

2)

```
mysql> SELECT pr.productid,pr.productname,SUM(od.quantity * pr.price) AS total_revenue FROM orderdetails od JOIN
products pr ON od.productid = pr.productid JOIN orders o ON od.orderid = o.orderid JOIN customers c ON o.customer
id = c.customerid JOIN inventory i ON pr.productid = i.productid GROUP BY pr.productid;
```

productid	productname	total_revenue
73	smartwatch	7260
44	iphone	550
65	earpods	352
32	imac	330
23	keyboard	5500

5 rows in set (0.01 sec)

mysql>

3)

```
mysql> SELECT c.customerid,c.firstname,c.lastname FROM customers c WHERE EXISTS (SELECT 1 FROM orders
o WHERE o.customerid = c.customerid);
```

customerid	firstname	lastname
2	Benjamin	May
5	Aiko	Barry
9	Lani	Moon
10	Jonah	Boyle

4 rows in set (0.00 sec)

4)

```
mysql> SELECT pr.productid,pr.productname, SUM(od.quantity) AS total_quantity_ordered FROM orderdetails
od JOIN products pr ON od.productid = pr.productid GROUP BY pr.productid, pr.productname ORDER BY tota
l_quantity_ordered DESC LIMIT 1;
```

productid	productname	total_quantity_ordered
73	smartwatch	22

1 row in set (0.01 sec)

mysql>

5)

6)

```
mysql> SELECT c.customerid,c.firstname,c.lastname,AVG(o.totalamount) FROM customers c JOIN orders o ON
c.customerid = o.customerid GROUP BY c.customerid;
+-----+-----+-----+-----+
| customerid | firstname | lastname | AVG(o.totalamount) |
+-----+-----+-----+-----+
|          2 | Benjamin | May      |          330       |
|          9 | Lani     | Moon     |          2926      |
|         10 | Jonah    | Boyle    |          550       |
|          5 | Aiko     | Barry    |          7260      |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
```

7)

```
mysql> SELECT o.orderid,c.customerid,c.firstname,c.lastname,o.totalamount AS total_revenue FROM orders
o JOIN customers c ON o.customerid = c.customerid ORDER BY total_revenue DESC LIMIT 1;
+-----+-----+-----+-----+-----+
| orderid | customerid | firstname | lastname | total_revenue |
+-----+-----+-----+-----+-----+
|       742 |          5 | Aiko      | Barry    |          7260 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

8)

```
mysql> SELECT p.productid,p.productname,p.description,COUNT(od.productid) AS order_count FROM products p
LEFT JOIN orderdetails od ON p.productid = od.productid GROUP BY p.productid ORDER BY order_count DESC;
+-----+-----+-----+-----+
| productid | productname | description | order_count |
+-----+-----+-----+-----+
|         23 | keyboard    | gaming      |            1 |
|         32 | imac        | pc          |            1 |
|         44 | iphone      | red         |            1 |
|         65 | earpods     | white       |            1 |
|         73 | smartwatch  | esim        |            1 |
+-----+-----+-----+-----+
5 rows in set (0.01 sec)

mysql>
```

9)

```
mysql> SELECT c.customerid,c.firstname,c.lastname FROM customers c JOIN orders o ON c.customerid = o.cust
omerid JOIN orderdetails od ON o.orderid = od.orderid JOIN products p ON od.productid = p.productid WHERE
p.productname = 'iphone';
+-----+-----+-----+
| customerid | firstname | lastname |
+-----+-----+-----+
|          10 | Jonah    | Boyle    |
+-----+-----+-----+
1 row in set (0.01 sec)

mysql>
```

10)


```
mysql> SELECT SUM(totalamount) AS total_revenue FROM orders WHERE orderdate BETWEEN '2023-06-23'
AND '2023-08-15';
+-----+
| total_revenue |
+-----+
|          330 |
+-----+
1 row in set (0.00 sec)

mysql>
```

Task 4

1)

```
mysql> SELECT customerid,firstname,lastname FROM customers WHERE customerid NOT IN (SELECT custom
erid FROM orders);
+-----+-----+-----+
| customerid | firstname | lastname |
+-----+-----+-----+
|          7 | Burton   | Hicks    |
+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

2)

```
mysql> SELECT COUNT(*) AS total_products FROM products;
+-----+
| total_products |
+-----+
|          5 |
+-----+
1 row in set (0.02 sec)
```

3)

```
mysql> SELECT SUM(totalamount) AS total_revenue FROM orders;
+-----+
| total_revenue |
+-----+
|        13992 |
+-----+
1 row in set (0.00 sec)

mysql>
```

4)

5)

```
mysql> SELECT customerid,firstname,lastname,(SELECT SUM(totalamount) FROM orders WHERE customerid = c.customerid) AS total_revenue FROM customers c WHERE customerid = '10';
+-----+-----+-----+-----+
| customerid | firstname | lastname | total_revenue |
+-----+-----+-----+-----+
|          10 | Jonah    | Boyle    |          550 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

6)

```
mysql> SELECT customerid,firstname,lastname,(SELECT COUNT(orderid) FROM orders WHERE customerid = c.customerid ) AS order_count
-> FROM customers c ORDER BY order_count DESC LIMIT 1;
+-----+-----+-----+-----+
| customerid | firstname | lastname | order_count |
+-----+-----+-----+-----+
|          9 | Lani     | Moon     |          2 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

7)

```
mysql> SELECT p.productid, p.productname,(SELECT SUM(od.quantity) FROM orderdetails od WHERE od.productid = p.productid) AS total
-> FROM products p ORDER BY total DESC LIMIT 1;
+-----+-----+-----+
| productid | productname | total |
+-----+-----+-----+
|          73 | smartwatch |    22 |
+-----+-----+-----+
1 row in set (0.00 sec)
```

8)

```
mysql> SELECT c.customerid,c.firstname,c.lastname,
-> (SELECT SUM(od.quantity * p.price) AS total_spending FROM orderdetails od JOIN products p ON od.productid = p.productid JOIN orders o ON od.orderid = o.orderid WHERE o.customerid = c.customerid ) AS total
-> FROM customers c ORDER BY total DESC LIMIT 1;
+-----+-----+-----+-----+
| customerid | firstname | lastname | total |
+-----+-----+-----+-----+
|          5 | Aiko     | Barry    |   7260 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

mysql>
```

9)

```
mysql> SELECT c.customerid,c.firstname,c.lastname,(SELECT SUM(o.totalamount) / COUNT(o.orderid) AS a
verage_order_value FROM orders o WHERE o.customerid = c.customerid) AS average
-> FROM customers c;
```

customerid	firstname	lastname	average
2	Benjamin	May	330
5	Aiko	Barry	7260
7	Burton	Hicks	NULL
9	Lani	Moon	2926
10	Jonah	Boyle	550

```
5 rows in set (0.01 sec)

mysql>
```

10)

```
mysql> SELECT c.customerid,c.firstname,c.lastname,(SELECT COUNT(o.orderid) FROM orders o WHERE o.
customerid = c.customerid) AS no
-> FROM customers c;
```

customerid	firstname	lastname	no
2	Benjamin	May	1
5	Aiko	Barry	1
7	Burton	Hicks	0
9	Lani	Moon	2
10	Jonah	Boyle	1

```
5 rows in set (0.00 sec)

mysql>
```