TRACE-RPG: Auditable Neuro-Symbolic Commit Gates for Interactive Game Worlds

Anonymous Author(s)

***Abstract*—LLMs can generate expressive quests and dialogue, but fluent/schema-valid text does not show that an event is executable, authorized, or consistent with canonical game state. We present TRACE-RPG, a symbolic commit gate treating events as untrusted transaction proposals. A type-strict parser, external action policy, and seven deterministic checks in six state-relative families decide transitions; failed candidates receive at most $K + 1$ recorded repair attempts, and passing candidates are revalidated before mutation. The validator-error-guided operator ρ reads only the prior candidate and typed validation errors (its sole state-derived input) and never accesses authoritative `WorldState` directly. Unkeyed SHA-256 content links, state-semantic replay, and assignment-complete accounting audit terminal outcomes. Four separate lanes cover offline conformance on one authored world, single-model live screening, closed-world knowledge-graph link simulation without runtime authority, and a participant-free Godot engineering slice. Offline evidence is mechanism-only. At K=1, live screening observed guided 5/5 versus blind 0/5 commits only in a deliberately repairable policy-blind regime and remains pilot-only. No lane establishes population efficacy, model superiority, player experience, or commercial-engine performance.**

***Index Terms*—game AI, interactive narrative, symbolic validation, constrained generation, reproducibility**

I. Introduction

INTERACTIVE generation is not only language: a natural candidate may require an absent item, assert a fact unknown to its speaker, disclose forbidden quest information, introduce an unauthorized effect, or regress a quest stage. Executable text environments distinguish plausible utterances from valid transitions [1], [2]; grounded dialogue and personalized quest systems show the value of quest, entity, and graph context [3], [4], but context does not authorize canonical mutation. **TRACE-RPG treats generated events as untrusted transaction proposals and permits canonical mutation only through an external, deterministic commit gate.** Fig. 1 reads one transaction left to right.

Structural constraints restrict generated structures through grammar-constrained decoding, query languages, and incremental parsers [5], [6], [7], but a syntactically admissible event can remain false relative to the current world. Retrieval and memory provide evidence [8], [9], [10], not state-transition authority.

TRACE-RPG combines these concerns in an auditable transaction protocol. Contributions:

1) **C1—Contracts:** versioned trust-boundary contracts/parser (Sec. IV; E1, ENG1);
2) **C2—Controller:** seven checks across six state-relative families; bounded repair, unchanged fallback, and pre-commit revalidation (Sec. IV-C; E1, ENG1);
3) **C3—Audit:** SHA-256-linked records, state-semantic replay, and episode-continuity checks (Sec. IV-D; E1, ENG1);
4) **C4—Harness:** assignment-complete offline conformance retaining a classified terminal row even when no proposal trace can exist (Sec. V; E1); and
5) **C5—Repair:** typed $\rho(a, E)$ versus blind retry/state-reading oracle (Sec. IV-C; E1, E2).

TABLE I
CONTRIBUTIONS, PRIOR TOPICS, EVIDENCE LANES, AND INFERENCE CEILINGS (GENERATED FROM THE STRUCTURED MATRICES)

ID	Contribution	Prior topics (refs)	Lanes	Inference ceiling
C1	Trust-boundary contracts	T1, T2, T3 (17)	E1, ENG1	encoded-field contract conformance
C2	Validate–repair–commit controller	T1, T8 (14)	E1, ENG1	mechanism behavior on frozen cases
C3	Audit-linked evidence layer	T4, T7, T8 (6)	E1, ENG1	integrity/replay on named fixtures
C4	Assignment-complete harness	T1, T4, T6, T7 (20)	E1	exact designed-case accounting
C5	Counterexample-guided operator ρ	T1, T8, T9 (8)	E1, E2	frozen classes + one regime screen

T1 = grounded game worlds; T2 = retrieval/memory agents; T3 = structured generation; T4 = environments/benchmarks; T5 = player experience; T6 = human/LLM evaluation; T7 = statistics/reproducibility; T8 = planning/runtime interposition; T9 = feedback repair. Lanes are defined in Table IV. All rows are authored-fixture verified; none supports an efficacy claim.

Fixed-goal NPC operation is additive descriptive evidence under NPC-ENG1/NPC-SCR1—not C6 or a C-RESULT—and is distinct from core Python–hard-policy and normal-play paths; Sec. V fixes its ownership, counts, role gates, provenance, and nonclaim boundaries. Table I binds C1–C5 to prior-work topics, evidence lanes, and inference ceilings; Table IV defines the lanes (both generated from machine-checked matrices).

Lanes are non-interchangeable (Table IV): E1 is deterministic conformance on one authored world; E2 is pilot-only five-call-per-cell screening with unpinned revision, uncontrolled seeds, and constructed states; E3 is closed-world typed-link scoring without runtime retrieval; ENG1 is the legacy Godot slice; NPC-ENG1/NPC-SCR1 use separate fixed-goal denominators and provenance. No lane supports population efficacy, model ranking, player benefit, retrieval benefit, or C6.

Manuscript submitted for anonymous review.




Fig. 1. One generated event as a transaction. A typed candidate crosses the trust boundary; seven checks in six state-relative families consult external policy and c_t. Typed errors E feed bounded ρ (dashed) or unchanged fallback; passing candidates are rechecked, committed, recorded, and replayed. Tags mark measurement scope, not claims: the core path is E1/E2, legacy ENG1 only; additive NPC `npc-goal-recovery/1.1.0` is a distinct Godot-authoritative intent/planning path, not a demonstrated core Python–hard-policy round trip. The lower strip is the committed-snapshot ledger grammar.

II. Related Work and Research Gap

A. Interactive Narrative and Game Agents

KNUDGE grounds branching NPC dialogue in quest and entity specifications [3]; knowledge-graph quest generation [4], memory–reflection–planning agents [11], and trainable role-playing agents [12] address complementary aspects of grounded, believable behavior. Player-facing studies evaluate preference and perceived dialogue quality [13], [14], [15], and a 2025 preprint reports role-sensitive stability–improvisation trade-offs [16]; both motivate separating hard admissibility from optional naturalness and player-experience constructs.

Experience-driven generation, observer-labelled engagement, and limits of vision-language engagement inference motivate future affect work [17], [18], [19]; affect is non-authoritative and absent here.

B. Environments and Benchmarks

TextWorld and ScienceWorld expose explicit interactive state [1], [2], MineDojo adds open-ended embodied tasks [20], and GVGAI separates agent, game, and content tracks [21]. AgentBench, AgentBoard, SOTOPIA, and BALROG evaluate agents across heterogeneous, process-diagnosed, social, and long-horizon game settings [22], [23], [24], [25]; automated play-style agents complement rather than replace human evaluation [26]. Across these reviewed environments and benchmarks, we did not identify a single protocol that combines transactional authorization, typed repair, semantic replay, and assignment-complete accounting; this is a scope-limited review finding, not a first-ever claim. NCP-Bench adds a long-horizon interactive-narrative benchmark for commitment and fact consistency, but it does not evaluate TRACE-RPG or player outcomes [27].

C. Constraints, Neuro-Symbolic Validation, and Retrieval

Constrained decoders improve output structure [5], [6], [7]; TRACE-RPG instead treats structure as an input condition to independent state-relative authorization. The same generate-and-verify division is established outside games: LLM-Modulo frameworks let a model propose plans that external sound critics accept or reject [28], and SayCan admits a language-proposed skill only after a state-dependent affordance check [29]. AgentSpec expresses runtime rules for LLM agents as trigger–predicate–enforcement triples [30]; TRACE-RPG fixes the predicates to game state and adds a repair contract and replayable records. Setting the DC grounds D&D agents in tool calls with precondition checks [31], whereas TRACE-RPG admits free-text proposals only after parsing and external policy evaluation. STORY2GAME lets the LLM generate the action preconditions and effects it plays under [32]; here the policy is authored independently of the proposer. TRACE-RPG instantiates the critic as a deterministic, state-relative commit gate that returns typed counterexamples. Game-specific comparators span complementary boundaries: PANGeA validates content by asking an LLM to judge and refine it against designer rules [33]; IVIE incrementally generates interactive-fiction worlds with symbolic validation [34]; and a 2026 successor restricts the LLM to selecting authored world-state transformations [35], gaining consistency by construction while leaving this paper's transaction, audit-record, and repair-operator questions as separate evidence targets. No comparison implies superiority: validity is only validity for the predicates a system encodes. JSONSchemaBench measures structural constrained-output compliance, coverage, and quality; those measures do not establish state-relative semantic authorization [36].

G-Retriever, HippoRAG, and Mem0 address subgraph retrieval and long-term memory [8], [9], [10]; Generative Agents and Character-LLM address behavioral memory and persona [11], [12]. TRACE-RPG may consume such context but grants it no commit authority; benefits are unmeasured.

D. Auditability and Reproducibility

Process metrics, sparse-run caution, reproducibility, and environmental reporting motivate failure retention and frozen artifacts [23], [37], [38], [39]. Human/LLM evaluation and future participant analyses require construct/rater/bias controls, justified margins, and random-effects structures [40], [41], [42], [43], [44], [45]. Record-and-replay supports experience reuse [46]; TRACE-RPG claims only semantic replay of admitted transitions. Leakage checks protect frozen denominators but do not create efficacy evidence [47].

The bounded novelty is the implemented combination, not its individual parts. Prior work covers runtime enforcement [30], symbolic game-state management [31], [32], feedback

repair [48], record/replay [46], action interposition [49], classical preconditions/effects [50], permitted-transition enforcement [51], transaction abort [52], authored social logic [53], and belief-aware narrative planning [54]. TRACE-RPG combines these at a game-state commit boundary: C1–C2 enforce independent contracts and validate–repair–commit; C3–C4 add checksum-linked/state-semantic replay, episode continuity, and assignment-complete accounting; C5 isolates typed-error repair. Absence from a report is not absence from an implementation.

III. Problem Definition and Guarantee Boundary

For exposition, the controller input used by validation at step t is decomposed as $c_t = (G_t, q_t)$, where G_t denotes typed snapshot fields and q_t denotes the externally authored action-policy, disclosure, and quest-stage constraints stored with that snapshot. Terminal record history $h_{<t}$ is maintained separately from the `WorldState` snapshot; no validation predicate reads it, and the implementation does not reconstruct state from the log. In this one-step model, an accepted transition updates G_t under q_t and carries q_t forward unchanged; policy-version rotation is outside the transition. Retrieval, narrative scores, model rationales, memory summaries, and any future affect estimate are non-authoritative proposal context.

An untrusted proposer emits candidate a_t. Strict parsing first enforces the shared candidate-key contract, including rejection of unknown top-level fields, and establishes the declared schema. The validator returns

$$V(c_t, a_t) = (v_{\text{policy}}, v_{\text{pre}}, v_{\text{reach}}, v_{\text{know}}, v_{\text{disc}}, v_{\text{elig}}, v_{\text{stage}}, E_t), \tag{1}$$

where E_t is a structured error set. Mutation is

$$c_{t+1} = \begin{cases} T(c_t, a_t), & \bigwedge_{i=1}^{7} v_i = 1, \\ c_t, & \text{otherwise.} \end{cases} \tag{2}$$

The controller asserts the following implementation invariants under its encoded contracts; the pilot tests their mechanisms with deterministic valid, invalid, repair, fallback, replay, and fault-injection fixtures rather than presenting general theorems. **I1 (exhausted-failure immutability):** if no returned candidate through budget K validates, or proposal/controller execution fails before commit, the returned state equals the supplied prior state. **I2 (bounded recorded attempts):** provided every proposal and repair callback returns, repair budget $K \geq 0$ admits at most $K + 1$ recorded candidate attempts; a successful commit adds one defensive validation immediately before mutation. The runtime does not enforce callback deadlines, so I2 is not a wall-clock termination guarantee. **I3 (effect authorization):** an accepted candidate contains no declared fact effect in `CandidateAction.effects` outside `ActionPolicy.allowed_effects`, and any quest-stage target is explicitly authorized by that policy. **I4 (state-semantic replay):** with the frozen schemas and deterministic transitions, an accepted trace reconstructs its stated terminal state.

These invariants assume correct policy authorship, faithful extraction into declared candidate fields, deterministic software versions, returning callbacks, and single-process file ownership. Replay revalidates the recorded structured candidate and transition; it does *not* verify the provenance, prompts, or stochastic generation of intermediate repairs, and natural-language implications omitted from structured fields remain outside the guarantee.

TABLE II
Encoded Validator Boundary

Predicate	Rejects	On failure
Action policy	unknown action/type	unchanged
Precondition	absent/false requirement	unchanged
Reachability	inaccessible object	unchanged
NPC knowledge	undeclared known fact	unchanged
Disclosure	forbidden fact	unchanged
Quest eligibility	ineligible quest action	unchanged
Quest stage	regressive or unauthorized stage	unchanged

IV. TRACE-RPG Architecture and Algorithms

A. Trust Boundary and Contracts

Fig. 1 places the model or recorded adapter outside the canonical owner. The parser rejects ambiguous numeric and collection types for known fields and unknown top-level candidate fields; the action policy is supplied separately and defines required preconditions and allowed effects; the versioned game bridge carries observations, proposals, validations, rejections, fallbacks, or commits, and only a valid commit authorizes canonical mutation. This decouples interfaces without demonstrating commercial-engine portability. The evidence supports unknown-key rejection parity only; it does not establish equivalence of proposal defaults and replay parsing.

B. Fixed-goal NPC integration

The NPC lane uses `npc-goal-recovery/1.1.0` and a mechanically exact generated runtime mirror. Config, disclosure-policy, and `project.godot` hashes are recorded by SHA-256 prefixes `d63f5679f360`, `af0a1075294b`, and `2e7966bf2ac6`; full digests are in `research/academic-pipeline/npc-goal-recovery/verified-run-002/`. Before writing, Godot synchronously checks session/epoch/request/scenario/NPC/goal/version, policy/config hashes, revision/state hash, deadline/budget, and issued-action binding. The service listens on `127.0.0.1:8768`; browser origins are `localhost` and `127.0.0.1:8877`, not 8767. Codex is the non-authoritative OAuth interpreter that proposes typed intent; Python validates and verifies typed claims and computes the public-projection plan; Godot alone authorizes and writes canonical state. P has no rule fallback. The fixed harbor-signal goal is version 1 for `captain_mira`; no utterance or model output may replace it. Utterance requests commit raw UTF-8 bytes via `raw_utterance_sha256`; observation-only requests carry `utterance:null` and a null digest, checked before interpretation. The closed loop is proposal → verification → public-projection BFS plan → player/NPC role gate → actual result → observation-only replan. Python validates

$a \leftarrow \textsc{Propose}(c)$; $j \leftarrow 0$
repeat
  $(ok, E) \leftarrow V(c, a)$; $\textsc{Record}(a, E)$
  if ok **then**
    assert $V(c, a).ok$; **return** $\textsc{Commit}(c, a)$
  if $j = K$ **then return** $\textsc{Fallback}(c)$
  $a \leftarrow \textsc{Repair}(c, a, E)$; $j \leftarrow j + 1$
until terminal

Fig. 2. Validate–repair–commit procedure. At most $K+1$ candidate attempts are recorded; the successful path performs a defensive validation before mutation.

and verifies typed claims from public flags; BFS emits only the enabled first step toward the fixed goal and never reads hidden state. `acquire_object`/`install_lens` are `player_request`; `reveal_hint` is Mira-only `commit_world` when known and disclosure-authorized; `clarify`/`negotiate` are dialogue-only. No public route yields `NO_ROUTE` and no physical step. Replanning uses only the returned observation/state reference, not the prior utterance or a changed goal. Episode budgets and deadlines persist across utterance epochs; intent calls, action attempts, replans, and BFS expansions are cumulative, while only actual inference consumes process quota. Applied acquire/install/reveal advance revision and state hash exactly once; applied dialogue and non-applied outcomes preserve state; `STALE` is rejected. Replay uses redacted recorded-intent traces with zero model calls; native replay reexecutes immutable input via `--npc-experiment` as `engine_fixture_reexecution`, never `--npc-replay`. UI cancellation invalidates local directives only; provider work may finish, and `core.cancel` no-publication is a unit/controller property, not a live-route claim.

C. Validate–Repair–Commit

Fig. 2 gives the controller's dependency-free pseudocode. "Record" denotes an append to the in-memory trace representation; persistent writing occurs only after terminal consistency checks.

Validation errors are exposed to a repair callback as structured error codes. Repair never directly mutates state, and exhaustion returns an unchanged deterministic fallback. Fig. 1 shows the terminal paths. The pilot compares two implemented callbacks. The *typed validator-error-guided operator* (implemented as `counterexample_guided_repair`) reads only the prior candidate a and typed validator errors E; these errors are its sole state-derived input, and it never accesses authoritative `WorldState` directly:

$$\rho(a, E) = a \oplus \bigcup_{e \in E} \delta(e), \tag{3}$$

where each $\delta(e)$ is the deterministic per-error-class edit of Table III and $\oplus$ applies the resulting field edits. Each edit touches at most one candidate field per error entity, so the number of changed fields per attempt is bounded by $|E|$; applying ρ twice with the same error set is a fixed point only for that identical E, not a convergence claim across changing error sets or attempts; and an entity simultaneously demanded and rejected on the same field is declared irreparable and left untouched. The *state-reading reference callback* instead discards the error set and reconstructs the policy-governed fields (preconditions, effects, and both quest-stage fields) directly from the authoritative state; it deliberately never edits declaration-integrity fields (required objects, used facts, disclosed facts), because those are authored declarations rather than state-derived repairs.

TABLE III
PER-ERROR-CLASS EDITS OF THE GUIDED OPERATOR ρ

Validator error class	Edit $\delta(e)$ on the candidate
Policy precondition omission	insert the named predicate
Policy effect omission	insert the named effect
Policy effect violation	drop the named effect
Unsatisfied precondition	drop the named predicate
Unauthorized stage mutation	clear `quest_stage_effect`
Unknown action type	no-op (no registered alternative)
Unreachable object; knowledge, disclosure, and stage classes	no-op (candidate-local edit would launder or needs state)

D. Integrity, Semantic Replay, and Accounting

Each result row carries an unkeyed SHA-256 *integrity checksum*, and proposal outcomes link to a trace checksum; these detect accidental or tested content changes but are not signatures, writer identity, or protection against an actor who rewrites content and checksums. Semantic replay strictly parses the prior state and every recorded candidate/validation pair, requires every nonfinal attempt to be invalid, recomputes the terminal transition, compares the stated final state, and requires continuity between adjacent JSONL records; it does not re-execute the repair step that produced candidate $j + 1$.

The terminal record classes are commit, symbolic fallback, adapter failure, and controller failure. A controller-failure row remains in the frozen assignment denominator and leaves state unchanged, but it may legitimately lack a completed proposal trace because no candidate outcome was produced. Accordingly, result completeness does not imply trace existence for every terminal row. The pre-execution assignment key contains run, arm, scenario, seed, model, revision, controller-configuration hash, assignment-input hash, and prior-state hash. Aggregation rejects duplicate, missing, or unexpected keys and separately reports symbolic, adapter, and controller failures.

V. EVIDENCE LANES AND BOUNDARIES

Table IV fixes each lane's design, unit, comparison, and ceiling before any count is read.

A. *E1* Offline Conformance Design

The pilot asks whether (PQ1) valid candidates commit while named invalid-policy cases remain unchanged; (PQ2) rejection-only, blind unchanged retry, ρ, and the state-reading reference callback produce the expected outcome in every frozen repairability class; (PQ3) frozen checksum, state-semantic, linkage, and continuity mutations are rejected by

TABLE IV
EVIDENCE LANES AT A GLANCE: DESIGN, UNIT, COMPARISON, AND CEILING (GENERATED FROM THE EXPERIMENT MATRIX)

Lane	Design	Unit / budget	Comparison	Ceiling
E1	Offline conformance: authored frozen fixtures, one world	13 gate; 12 repair/arm; 10 faults; 7 adapter; 3 guards	reject vs blind vs ρ vs oracle	mechanism conformance
E2	Screening-pilot-only RQ2: one hosted proposer, matched candidate	5 cells $\times$ 5 calls; $K{=}1$	ρ vs blind per regime	screening-pilot-only transfer screen
E3	KG/ontology simulation: closed-world typed-link holdout	43 nodes; 106 ref. edges; 24 typed; 210 scores	degree baseline vs 6 fixed strategies	construction result only
ENG1	Engineering-only Godot/Web: engine-local policy mirror, no participants	4 fixtures; 52 checks; 8 smoke; 5 archetypes	authored fixture paths	engineering-only conformance

Lanes are non-interchangeable with different denominators; E2 is screening-pilot-only and ENG1 is engineering-only. None establishes population efficacy, model ranking, player experience, retrieval benefit, or commercial-engine performance.

their designated check operations and an injected second-file append failure triggers the pair-write rollback check; (PQ4) strict adapters and assignment manifests retain exactly one classified terminal row per assigned case or fail closed; and (PQ5) proposal and replay parsers both reject an otherwise-valid candidate carrying one unknown top-level key.

Cases are purposively designed conformance fixtures in four domains (validator/state isolation, repair-arm comparison, record/trace fault injection, adapter/accounting contracts), not samples from a model or game population. Every repair fixture declares a frozen repairability class before execution: *guided-repairable* (the error payload alone suffices for ρ), *oracle-only* (repair needs the authoritative state), or *irreparable* (no arm may commit); the 13 gate fixtures comprise one valid control plus 12 isolated negatives, while the 12 repair cases form a separate arm denominator; each class's expected outcome per arm is part of the fixture contract, unique cases form the denominators, and all expectations precede execution.

Measures are exact counts: validator-class agreement; rejected or failed cases with state mutation; commit and attempt outcomes by arm and repairability class; detectable faults rejected by their designated operation; replayed traces; rejected manifest violations; and proposal/replay parity on the unknown-key regression, which is parser-contract parity rather than a safety outcome. Exception class alone does not identify a stable detector layer, so no detector attribution is reported, and no p-values or population intervals are attached. Adapter cases carry JSON-Schema-pinned synthetic latency and token constants that exercise accounting propagation only. The frozen offline packet binds fixtures, assignments, schemas, results with embedded traces, code revision, and checksums, following reproducibility and measurement-boundary guidance [38], [39].

B. *E2 Live RQ2 Screening*

The live extension compares blind unchanged retry with ρ at matched $K{=}1$: per cell, five seed-indexed calls to the hosted proposer `gpt-5.6-sol` request one candidate, and the same candidate feeds both arms, eliminating within-call proposal differences. Conditions vary policy visibility and whether a trivial zero-effect route exists. The frozen packet retains the current cells and the superseded v1 diagnostic, binds every receipt by SHA-256, and is labelled pilot-only. Because seed labels do not control the hosted sampler, the revision is unpinned, token accounting is unavailable, and constructed states are not population samples, we report exact counts and failure classes without p-values, confidence intervals, or model ranking.

C. *NPC-ENG1 Fixed-goal engineering lane*

NPC-ENG1 is a deterministic native 16-case rule-control lane covering bootstrap, identity/hash binding, intent/plan/role/result transitions, negative gates, stale/duplicate/deadline paths, and replay. Stable v5 defines 16 engineering assignments and 12 screening recipes; earlier packets are immutable provenance. Historical preflight diagnostics remain outside NPC-SCR1 outcomes; final statuses, counts, and latencies come only from the validated packet. This lane is protocol/engine evidence only; reproduction uses the validated packet at `research/academic-pipeline/npc-goal-recovery/verified-run-002/` and the repository runner/validator.

D. *NPC-SCR1 Descriptive screening*

NPC-SCR1 fixes 12 unique cases, two repetitions, and three arms (P/R/O): 72 screening assigned rows, 24 per arm. NPC-ENG1 contributes 16 engineering assignments (distinct from legacy ENG1 and E1), for 88 assigned rows over 28 unique case definitions ($R = 40$, $P = 24$, $O = 24$). For one game-owned Mira goal, all assigned rows—including pre-trigger, parse, deadline/cancel, duplicate/stale, controller, and no-route—remain in the denominator; recovery-eligible and unreachable strata stay separate. P is the authenticated Codex OAuth adapter without fallback; R is authored rule/grammar control; O is a protocol-declared same-family auxiliary from the same public input; the actual family match is unverified, and no independent gold is available. The auxiliary-source fraction is 100%, independent fraction zero. Codex proposes typed intent; Python validates/verifies claims and computes bounded BFS over the public projection; Godot alone authorizes and writes canonical state. Only player-request `acquire_object`/`install_lens` can cause physical action; Mira alone may commit authorized `reveal_hint` when `tide_marks_hint` is known and disclosure-authorized, while `clarify`/`negotiate` are dialogue-only. Role gates route player/Mira reveal and replanning uses observations. Screening is descriptive/provenance only—not recovery efficacy, semantic gold, accuracy ceiling, model ranking, or C6. Native012 is separate current-source Godot→HTTP→authenticated Codex NPC v1.1 engineering evidence (one intent, three observations, and separate zero-model-call replay), outside legacy ENG1 and the 16+72 pool; legacy ENG1 remains a source-bound Godot authored-trace




Fig. 3. Evidence-regime contrast using E1 frozen offline counts and E2 screening-pilot-only matched counts. E1 shows commits/cases for four arms over 12 initially invalid designed cases (0/12, 0/12, 5/12, 6/12). E2 keeps the Signal-v2/policy-blind contrast (ρ 5/5 vs. blind 0/5) separate from the goal-directed/goal-blind null regime (0/5 vs. 0/5). Raw counts are descriptive; denominators are not pooled and support no efficacy, population, model-ranking, or player-experience inference.

replay. Generated results provide observed counts for the assigned P/R/O rows; the normal-play full-loop episode demonstration remains a separate artifact outside this one-step protocol pool. The generator treats `aggregate.validation` fields as generation-time placeholders; admissibility is determined from `validation-report.json` plus a fresh strict validator, not aggregate validity flags (the generator enforces this).

E. *E3 KG/Ontology Link-Proposal Simulation*

The third lane is an engineering-only closed-world simulation, separate from the authoritative `WorldState`: 43 graph nodes and 106 reference edges, 24 reviewed typed edges, passing type/domain/range checks and six competency questions, with six graph-edge-withheld authored targets used both to select and summarize the retained strategy—not an untouched or external test set—and scored under seven fixed strategies. The retained typed-lexical strategy (S2) recovered 6/6 authored targets ($P = R = F_1 = 1.000$, realistic-tie $\mathrm{MRR} = 0.944$, Brier $= 0.131$, $\mathrm{Sem@3} = 1.000$); the degree baseline recovered none. These are construction results: not OWL/SHACL conformance, semantic completeness, runtime retrieval, or evidence of any efficacy claim.

VI. Pilot Results

A. Declared-Field Gate Conformance

The pilot loader admits a fixture set only when it isolates every implemented validator code exactly once alongside one valid control, so the 13/13 agreement and the observation of all 12 implemented error codes are *construction invariants of the harness*, not measured success rates. What the run adds is the part the loader does not enforce: each of the 12 isolated negative fixtures showed observed agreement with its authored expected code rather than reaching a different one, and every noncommit path preserved the complete canonical state. This is implementation conformance to an authored structured-field oracle over a single world state, not accuracy against independent semantic labels.

TABLE V
E1 Offline Conformance: Exact Repair-Arm Counts by Repairability Class (Designed Fixtures)

Arm	Info source	Commits / cases			Mean edits[e]
		G-rep.[f]	O-only[f]	Irrep.[f]	Fields
Rejection-only (K=0)	none	0/5	0/1	0/6	—
Blind unchanged retry	none	0/5	0/1	0/6	—
Validator-error-guided ρ	error set E	5/5	0/1	0/6	1.0
State-reading oracle	state+policy	5/5	1/1	0/6	1.0

[e] Mean changed candidate fields over committed repairs (minimality proxy); failed arm executions left the state unchanged. E1 uses 12 initially invalid designed cases: rejection-only/blind 0/12, 0/12; validator-error-guided ρ 5/12; state-reading oracle 6/12 commits. [f] Commits/cases. G-rep. = guided-repairable, O-only = oracle-only, Irrep. = irreparable (frozen repairability classes); these are not population efficacy or live-model quality.

TABLE VI
E1 Offline Conformance: Frozen-Pilot Checks and Terminal Outcomes (Rows Are Not Comparable)

Check or terminal family	Exact outcome	Interpretation
Gate fixture agreement	13/13	authored-oracle agreement
Known-boundary acceptance	2/2	encoded limit, not a safety pass
Closed unknown-key rejection	1/1	proposal/replay parser parity
Detectable integrity-fault rejection	10/10	designated check operations
Known provenance-boundary acceptance	1/1	repair provenance unauthenticated
Adapter terminal classes	1 commit; 1 fallback; 5 failures / 7 assigned	complete classification of 7 assignments
Manifest-guard rejection	3/3	injected faults failed closed

Rows have different denominators and favorable directions; they must not be ranked as rates. Every value is an exact audit fact for designed fixtures.

B. Repair-Arm Comparison on Designed Fixtures

The 12 initially invalid designed cases are partitioned into frozen repairability classes: 5 guided-repairable, 1 oracle-only, and 6 irreparable. Rejection-only and blind unchanged-candidate retry each committed 0/12. The validator-error-guided operator ρ committed 5/5 guided-repairable cases and, by design, 0/1 oracle-only and 0/6 irreparable cases; every ρ commit edited a mean of 1.0 candidate fields. ρ reads only the prior candidate and typed validator errors E; those errors are its sole state-derived input, and every failed arm execution left the canonical state unchanged. The state-reading reference callback committed 5/5 guided-repairable and 1/1 oracle-only cases, with 0/6 irreparable. These exact counts separate the three mechanisms on the designed fixtures: blind retry never converts a validator error into a commit, ρ converts exactly the cases whose error payload carries sufficient information, and the oracle additionally converts the case requiring state knowledge. The 5 committed guided cases initially carried `POLICY_PRECONDITION_OMISSION+UNSATISFIED_PRECONDITION`, `POLICY_EFFECT_OMISSION`, `POLICY_EFFECT_VIOLATION`, `UNSATISFIED_PRECONDITION`, `POLICY_QUEST_STAGE_EFFECT_VIOLATION`, respectively, and each

became valid through the corresponding Table III edit $\delta(e)$ alone. This is operator conformance on frozen fixtures, not repair quality of any live model.

C. Integrity, Boundaries, and Assignment Accounting

All 10 faults prespecified as detectable were rejected by their designated check operations (10/10). Because this pilot does not compare stable typed detector codes, it does not establish detector-layer attribution. Separately, the known provenance-boundary fixture substituted a different invalid precursor before the same recorded valid repair, recomputed the checksum, and passed replay as expected (1/1 undetected). Thus, the mechanism does not protect against a writer who can recompute unkeyed checksums, and replay does not authenticate the repair-generation operation. Two open boundary sentinels—unextracted narrative disclosure and simultaneous omission of a required object from candidate and policy—were intentionally accepted at the encoded layer (2/2), with 0 labelled as safety passes. The former unknown-top-level-field acceptance boundary was later reclassified as a closed negative regression: both proposal and replay parsers specifically rejected a complete 12-field candidate carrying one unknown key (1/1). This establishes parser rejection parity, not semantic safety. Among seven adapter/accounting assignments, outcomes were 1 commit, 1 symbolic fallback, and 5 adapter failures. Synthetic telemetry fields were populated and propagated for 2/7 assignments; these are schema-pinned constants verifying accounting-field propagation, not measurements. All 3/3 injected duplicate or missing-assignment guards failed closed. These are raw counts from synthetic offline fixtures.

D. Live Screening Pilot (Pilot-Only)

A separate screening pilot called the hosted proposer gpt-5.6-sol. It used 5 seed-indexed proposal calls per cell and repair budget $K = 1$; within each call, blind unchanged retry and ρ received the same initial candidate. The hosted revision was unpinned, token accounting was unavailable, and the seeds did not control the hosted sampler, so the calls are quasi-replicates rather than independent randomized samples. We report neither inferential statistics nor a model ranking.

In Table VII, a guided advantage appeared only in the policy-blind cell of the signal-repair state (Signal-v2), a state deliberately constructed to elicit guided-repairable errors. All 5/5 initial candidates were invalid; ρ committed 5/5, whereas blind retry committed 0/5. The other 4 current cells showed no guided advantage: 3 had already-valid initial candidates, and the frozen-base goal-directed cell had QSR in 5/5, a null regime with guided and blind commits of 0/5 and 0/5. All 15/15 noncommit arm outcomes in the current cells preserved the prior-state hash. This supports mechanism transfer only in that error regime, not population efficacy, model promotion, or a general sample-efficiency claim. Accordingly, the two screening observations are pilot-only; the confirmatory transfer claim remains open. In the superseded v1 diagnostic, guided repair reduced up to 3 co-occurring errors to one irreparable knowledge error but still could not commit, showing that partial per-error repairs do not compose when any residual error is irreparable.

TABLE VII
E2 SCREENING-PILOT-ONLY: LIVE SCREENING EXACT COUNTS (5 CELLS, 5 PROPOSALS PER CELL, K=1)

Base / condition	Initial valid	ρ vs blind commits	Δ	Initial errors
Frozen / visible	5/5	5/5 vs 5/5	+0	—
Frozen / blind	5/5	5/5 vs 5/5	+0	—
Frozen / goal-blind	0/5	0/5 vs 0/5	+0	QSR
Signal-v2 / visible	5/5	5/5 vs 5/5	+0	—
Signal-v2 / blind	0/5	**5/5 vs 0/5**	**+5**	PEO+PEV+PPO

QSR = quest-stage regression, PEO = policy-effect omission, PEV = policy-effect violation, PPO = policy-precondition omission. Δ is ρ commits minus blind commits for matched candidates. There are 5 cells with 5 calls each: 3 cells were initially valid (5/5), while the goal-blind cell had QSR in 5/5 and 0/5 and 0/5 commits in both arms (null regime). Only Signal-v2/blind separated (ρ 5/5 vs blind 0/5). All counts are screening-pilot-only, with no inferential statistics or model ranking.

E. Fixed-Goal NPC Operation (NPC-ENG1/NPC-SCR1)

Mira's fixed goal is to deliver the authorized tide lead after harbor-signal restoration. Python computes bounded BFS plans from typed intent and public observations. Acquire/install remain player actions; the NPC may only commit the authorized `reveal_hint`. Godot synchronously checks session/epoch/request/goal/policy/revision/hash before calling the existing writer without an await. Results and new observations determine the next plan, unlike single-candidate validator-error repair.

NPC-ENG1 comprises 16 deterministic R-arm engineering cases initialized from actual engine snapshots (assigned_failure=2, completed=14). NPC-SCR1 retains all 72 assignments and failures, 24 per P/R/O arm (assigned_failure=12, completed=60). P records 24 authenticated Codex CLI exec attempts, 24 returned decisions, and 4 assigned failures; these are not remote billing-call counts. Requested model: gpt-5.6-sol; recorded decision-model identifier: gpt-5.6-sol. The latter propagates the configured selector, not a provider revision; the provider revision is unavailable. Null identifiers remain unknown; global defaults are not evidence. R uses authored rules. O is a protocol-declared auxiliary under `same_model_family_auxiliary`. Actual model-family matching is unverified. No source is independent; O is neither an oracle nor semantic gold. Table VIII and Fig. 4 report bounded protocol-conformance fixed-case counts, not recovery-efficacy, superiority, or generalization estimates. Efficacy remains pending; tokens and cost are unmeasured. A read-only CLI and isolated working directory were used, but tool-free inference and adversarial confidentiality were not established. Verified pre-authored stale-control ACK rejections are P=4, R=4, O=4 per arm (SCR-T01 (stale_revision), SCR-T02 (stale_policy)); 12 instances had all corresponding negative-control gates passed. These rows remain assigned failures in the denominator, not method-performance outcomes; other assigned failures (0) remain unclassified.

Tables V and VI report exact designed-fixture counts: the 13/13 gate agreement is a loader construction invariant, each repair arm has 12 unique cases ($5+1+6$), and the five live cells

TABLE VIII
NPC-SCR1 FIXED-CASE EXECUTION COUNTS, SEPARATE FROM THE 16 NPC-ENG1 CASES; ALL ASSIGNED FAILURES REMAIN IN THE DENOMINATOR.

Arm	Assigned	Complete/fail	Goal reached	Recovery E/U
P	24	20/4	4	24/0
R	24	20/4	4	24/0
O	24	20/4	4	24/0

E: recovery eligible; U: unreachable; NA: unmeasured. Observed goal counts are not recovery rates. Valid replay does not turn a failed assignment into a completed one. O has zero independent sources.




Fig. 4. NPC-SCR1: $12 \times 2 \times 3 = 72$ assigned rows (24/arm); NPC-ENG1 adds 16, totaling 88 assignments over 28 definitions ($R/P/O = 40/24/24$), separate from legacy ENG1/E1 and the full-loop demo. P: authenticated Codex intent; R: authored rules; O: protocol-declared auxiliary (family unverified; no independent gold/rows). ENG-X01/SCR-X01 and v1–v4 remain provenance. Descriptive counts, not recovery efficacy, oracle comparison, normal-play, or player benefit.

contribute 25 proposal calls outside the offline denominator; neither supports a population or live-model estimate.

Only designated fixture checks admit offline rows; the separately hash-bound live packet never enters that denominator (Table IV).

ENG1. (Legacy; no live transport.) Godot 4.7.1 replays an authored trace: forbidden disclosure holds the prior hash; authorized commits reach the offline terminal hash (Fig. 5). Evidence is the trace/deterministic evaluation, not pixels. Committed facts populate the case-file board, hints, coach, and chain prompt; the fail-closed dashboard distinguishes checks, holds, unreached in-scope checks, and out-of-scope families. Its 52/52 core and four extension checks establish engine-local conformance only: no live model/Python transport, participants, narrative result, usability, or efficacy.


VII. Discussion

A. Established Scope

Results are mechanism-only: checks isolate state; declared repair/fallback paths hold; named corruptions reject; rows remain classified; no stable detector attribution. NPC ownership, boundaries, and descriptive-only count ceilings are fixed in Sec. V; they exclude efficacy, superiority, generalization, human benefit, cost equality, semantic gold, and accuracy ceilings.

State-reading handles oracle-only cases that ρ cannot handle; typed errors let ρ match it only on guided-repairable cases. Live blind-retry separation occurred only there; already-valid/irreparable null regimes, unpinned revision, and quasi-replicated calls preclude sample-efficiency/model-capability

(a) Held proposal: the gate family, the unchanged state, the next valid entry, and the rule learned



(b) Committed proposal: entry, contribution clause, and unlocked affordance



(c) End-card receipt after the three commits




Fig. 5. Presentation-only Godot ledger crops: three scripted stages of one authored fixture (1280×720 engineering captures; illustration, not evidence). (a) Held disclosure: named gate family, unchanged state, next valid entry, reusable rule. (b) Commit: entry, contribution from committed-snapshot delta only (added facts, quest 1>2, chain 2/3), unlocked affordance. (c) End card: three contributions, hold count, validator receipt and replay terminal hash (`4b2310...`). These committed-snapshot readouts (Fig. 1, lower strip) use no oracle labels, hidden facts, live model, or participants and support no usability, immersion, affect, efficacy, G4, or G6 claim.

claims. Self-Refine, Reflexion, and Self-Debugging are precedents [48], [55], [56]; ρ instead consumes deterministic pre-execution errors and isolates failed arms, but is not semantic repair, only analogous to counterexample-guided synthesis [57].

B. Relationship to Prior Work

Prior work cited above covers constrained decoders, retrieval/memory, executable benchmarks, and process-linked measurement; TRACE-RPG claims no outperformance. Planned (not executed): preregistered multi-model/oracle/blind-retry comparison, matched-validity retrieval/memory ablations, and a blinded matched-validity human study with justified power/mixed-effects; screening substitutes for none [40], [37], [45].

VIII. Threats, Ethics, and Artifact Scope

Nine boundaries apply: **L1:** encoded fields miss semantics; consistency is not behavior consistency [58], and narrative quality is unmeasured. **L2:** one world/live state gives no cross-world, cross-policy, or scale generalization. **L3:** state-reading is an oracle; classes/regimes do not establish repair quality/sample efficiency. **L4:** one hosted proposer has unpinned revision, no token accounting, and uncontrolled seeds; E2 screening has no Python–Godot authorization round trip. **L5:** no participant/affect data or comprehension/agency/enjoyment/immersion/benefit evidence. **L6:** unkeyed hashes provide integrity, not authentication/tamper resistance. **L7:** one-writer consistency leaves concurrency unverified. **L8:** one Godot fixture has startup-dominated samples above 16.7 ms; portability/performance are untested. **L9:**

fixtures/cells support no population, safety-rate, or model-ranking inference. Internal validity requires independent policy expectations/no leakage; reproducibility requires pinned software/artifacts. NPC deadlines, duplicate/stale/late-drop handling, cumulative budgets, and synchronous bindings are invariants, not measured latency/quality. Cancellation invalidates local state only; provider work may finish; `core.cancel` no-publication is unit/controller evidence, not a live-route guarantee. Fixed predicates/player requests; no human study, cross-world validation, independent gold labels, or C6 efficacy claim.

No participants or personal telemetry were collected. Planned human/affect work requires ethics review, consent, compensation disclosure, minimization, retention/deletion, and opt-out; LLM judges remain auxiliary and need calibration/bias controls [40], [41], [42], [43].

IX. Conclusion

TRACE-RPG gates payloads before mutation and audits outcomes via linked records/replay. Frozen fixtures establish conformance; live screening separates ρ from blind retry (5/5 vs. 0/5) only in the constructed repairable regime and remains pilot-only. Godot readouts expose committed-snapshot rules/contributions; cross-model/player/retrieval/memory/affect/commercial benefits remain untested. The boundaries of the additive NPC integration, native012 engineering demonstration, and legacy ENG1 replay are fixed in Sec. V. These are contract/provenance observations, not production-readiness, generalization, efficacy, or player-benefit claims.

Disclosure of AI Usage

LLMs assisted prose, code, test drafting, and citation-identity checks; a hosted model supplied labelled live-screening candidates. Counts come from deterministic runners or hash-bound receipts. UI art (portrait, seals, panel textures, case-file board, evidence icons, guide vignette) and the evidence-desk mesh are curated AI-generated assets with per-file provenance. In Fig. 5, all state values, hashes, and ledger lines are engine-rendered from committed snapshots. Authors verified claims against source artifacts and accept full responsibility. The additive NPC tables and figure are generated separately from the NPC-GOAL-RECOVERY packet; they preserve all assigned rows, bind project/protocol/schema hashes, and expose unavailable token/cost/model-revision fields as null rather than zero.

Data and Code Availability

The repository provides implementation/build sources, frozen offline/live packets, the Godot slice and deterministic evaluation, and machine-checked contribution, reference-topic, and experiment matrices generating Tables I and IV. No reviewer archive or DOI deposit is claimed.

References

[1] M.-A. Côté, Á. Kádár, X. Yuan *et al.*, "TextWorld: A learning environment for text-based games," in *Computer Games*, ser. Communications in Computer and Information Science. Springer International Publishing, 2019, vol. 1017, pp. 41–75.

[2] R. Wang, P. Jansen, M.-A. Côté, and P. Ammanabrolu, "ScienceWorld: Is your agent smarter than a 5th grader?" in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2022, pp. 11 279–11 298.

[3] N. Weir, R. Thomas, R. d'Amore, K. Hill, B. Van Durme, and H. Jhamtani, "Ontologically faithful generation of non-player character dialogues," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2024, pp. 9212–9242.

[4] T. Ashby, B. K. Webb, G. Knapp, J. Searle, and N. Fulda, "Personalized quest and dialogue generation in role-playing games: A knowledge graph- and language model-based approach," in *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*. ACM, 2023, pp. 1–20.

[5] S. Geng, M. Josifoski, M. Peyrard, and R. West, "Grammar-constrained decoding for structured NLP tasks without finetuning," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 10 932–10 952.

[6] L. Beurer-Kellner, M. Fischer, and M. Vechev, "Prompting is programming: A query language for large language models," *Proceedings of the ACM on Programming Languages*, vol. 7, no. PLDI, pp. 1946–1969, 2023.

[7] T. Scholak, N. Schucher, and D. Bahdanau, "PICARD: Parsing incrementally for constrained auto-regressive decoding from language models," in *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2021, pp. 9895–9901.

[8] X. He, Y. Tian, Y. Sun *et al.*, "G-Retriever: Retrieval-augmented generation for textual graph understanding and question answering," in *Advances in Neural Information Processing Systems*, vol. 37. Neural Information Processing Systems Foundation, 2024, pp. 132 876–132 907.

[9] B. Jiménez Gutiérrez, Y. Shu, Y. Gu, M. Yasunaga, and Y. Su, "HippoRAG: Neurobiologically inspired long-term memory for large language models," in *Advances in Neural Information Processing Systems*, vol. 37. Neural Information Processing Systems Foundation, 2024, pp. 59 532–59 569.

[10] P. Chhikara, D. Khant, S. Aryan, T. Singh, and D. Yadav, "Mem0: Building production-ready AI agents with scalable long-term memory," in *ECAI 2025*, ser. Frontiers in Artificial Intelligence and Applications, vol. 413. IOS Press, 2025, pp. 2993–3000.

[11] J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein, "Generative agents: Interactive simulacra of human behavior," in *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*. ACM, 2023, pp. 1–22.

[12] Y. Shao, L. Li, J. Dai, and X. Qiu, "Character-LLM: A trainable agent for role-playing," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 13 153–13 187.

[13] N. Akoury, Q. Yang, and M. Iyyer, "A framework for exploring player perceptions of LLM-generated dialogue in commercial video games," in *Findings of the Association for Computational Linguistics: EMNLP 2023*. Association for Computational Linguistics, 2023, pp. 2295–2311.

[14] M. Hochreiter, S. Kriglstein, and G. Wallner, "Beyond pre-defined scripts: Player perceptions on generative non-player character dialogues," in *Proceedings of the 31st International Conference on Intelligent User Interfaces*. ACM, 2026, pp. 2004–2018.

[15] M. Yin, H. Zu, W. Gu *et al.*, "How contextualized generative AI shapes player experience in games," *Entertainment Computing*, vol. 58, p. 101194, 2026.

[16] V. Figueiredo and D. Elumeze, "Symbolically scaffolded play: Designing role-sensitive prompts for generative NPC dialogue," 2025, preprint.

[17] G. N. Yannakakis and J. Togelius, "Experience-driven procedural content generation," *IEEE Transactions on Affective Computing*, vol. 2, no. 3, pp. 147–161, 2011.

[18] D. Melhart, D. Gravina, and G. N. Yannakakis, "Moment-to-moment engagement prediction through the eyes of the observer: PUBG streaming on Twitch," in *FDG '20: Proceedings of the 15th International Conference on the Foundations of Digital Games*. ACM, 2020, pp. 1–10.

[19] Z. Wang, Q. Guo, R. Singh, and X. Hu, "Do vision language models understand human engagement in games?" 2026, preprint.

[20] L. Fan, G. Wang, Y. Jiang *et al.*, "MineDojo: Building open-ended embodied agents with internet-scale knowledge," in *Advances in Neural Information Processing Systems*, vol. 35. Neural Information Processing Systems Foundation, 2022, pp. 18 343–18 362.

[21] D. Pérez-Liébana, J. Liu, A. Khalifa, R. D. Gaina, J. Togelius, and S. M. Lucas, "General video game AI: A multitrack framework for evaluating agents, games, and content generation algorithms," *IEEE Transactions on Games*, vol. 11, no. 3, pp. 195–214, 2019.

[22] X. Liu, H. Yu, H. Zhang *et al.*, "AgentBench: Evaluating LLMs as agents," in *International Conference on Learning Representations*, 2024, pp. 52 989–53 046.

[23] C. Ma, J. Zhang, Z. Zhu *et al.*, "AgentBoard: An analytical evaluation board of multi-turn LLM agents," in *Advances in Neural Information Processing Systems*, vol. 37. Neural Information Processing Systems Foundation, 2024, pp. 74 325–74 362.

[24] X. Zhou, H. Zhu, L. Mathur *et al.*, "SOTOPIA: Interactive evaluation for social intelligence in language agents," in *International Conference on Learning Representations*, 2024, pp. 40 975–41 019.

[25] D. Paglieri, B. Cupiał, S. Coward *et al.*, "BALROG: Benchmarking agentic LLM and VLM reasoning on games," in *International Conference on Learning Representations*, 2025, pp. 96 666–96 702.

[26] P. Le Pelletier de Woillemont, R. Labory, and V. Corruble, "Automated play-testing through RL based human-like play-styles generation," *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, vol. 18, no. 1, pp. 146–154, 2022.

[27] Y. Ma, J. Yan, B. Shi *et al.*, "Can LLM agents stick to the script? a benchmark for long-horizon consistency in interactive narratives," 2026, preprint (v1); ICML 2026 acceptance comment on arXiv, proceedings record unverified.

[28] S. Kambhampati, K. Valmeekam, L. Guan *et al.*, "Position: LLMs can't plan, but can help planning in LLM-Modulo frameworks," in *Proceedings of the 41st International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 235. PMLR, 2024, pp. 22 895–22 907.

[29] B. Ichter, A. Brohan, Y. Chebotar *et al.*, "Do as I can, not as I say: Grounding language in robotic affordances," in *Proceedings of the 6th Conference on Robot Learning (CoRL 2022)*, ser. Proceedings of Machine Learning Research, vol. 205. PMLR, 2023, pp. 287–318.

[30] H. Wang, C. M. Poskitt, and J. Sun, "AgentSpec: Customizable runtime enforcement for safe and reliable LLM agents," 2025, preprint (v3); ICSE 2026 acceptance stated on arXiv, proceedings record unverified.

[31] Z. Zeng, S. Li, J. Xi, A. Zhu, and P. Ammanabrolu, "Setting the DC: Tool-grounded D&D simulations to test LLM agents," in *NeurIPS 2025 Workshop on Generative and Protective AI for Content Creation (GenProCC)*, 2025, non-archival workshop paper; OpenReview/PDF list Zeng first, with Zeng and Li as equal contributors; NeurIPS/GenProCC lists display Li first.

[32] E. Zhou, S. Basavatia, M. Siam, Z. Chen, and M. O. Riedl, "STORY2GAME: Generating (almost) everything in an interactive fiction game," 2025, preprint.

[33] S. Buongiorno, L. Klinkert, Z. Zhuang, T. Chawla, and C. Clark, "PANGeA: Procedural artificial narrative using generative AI for turn-based, role-playing video games," *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment*, vol. 20, no. 1, pp. 156–166, 2024.

[34] M. Vaucher, S. Silveira, S. Góngora, and L. Chiruzzo, "IVIE: A neuro-symbolic approach to incremental and validated generation of interactive fiction worlds," in *Proceedings of the 17th International Conference on Computational Creativity (ICCC'26)*. Association for Computational Creativity, 2026, archival proceedings (ISBN); preprint arXiv:2606.13348.

[35] S. Góngora, L. Chiruzzo, G. Méndez, and P. Gervás, "World-state transformations for neuro-symbolic interactive storytelling," 2026, preprint.

[36] S. Geng, H. Cooper, M. Moskal *et al.*, "JSONSchemaBench: A rigorous benchmark of structured outputs for language models," 2025, preprint (v3).

[37] R. Agarwal, M. Schwarzer, P. S. Castro, A. Courville, and M. G. Bellemare, "Deep reinforcement learning at the edge of the statistical precipice," in *Advances in Neural Information Processing Systems*, vol. 34. Curran Associates, Inc., 2021, pp. 29 304–29 320.

[38] J. Pineau, P. Vincent-Lamarre, K. Sinha *et al.*, "Improving reproducibility in machine learning research: A report from the NeurIPS 2019 reproducibility program," *Journal of Machine Learning Research*, vol. 22, no. 164, pp. 1–20, 2021.

[39] P. Henderson, J. Hu, J. Romoff, E. Brunskill, D. Jurafsky, and J. Pineau, "Towards the systematic reporting of the energy and carbon footprints of machine learning," *Journal of Machine Learning Research*, vol. 21, no. 248, pp. 1–43, 2020.

[40] C. van der Lee, A. Gatt, E. van Miltenburg, S. Wubben, and E. Krahmer, "Best practices for the human evaluation of automatically generated text," in *Proceedings of the 12th International Conference on Natural Language Generation*. Association for Computational Linguistics, 2019, pp. 355–368.

[41] M. Karpinska, N. Akoury, and M. Iyyer, "The perils of using Mechanical Turk to evaluate open-ended text generation," in *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2021, pp. 1265–1285.

[42] L. Zheng, W.-L. Chiang, Y. Sheng *et al.*, "Judging LLM-as-a-judge with MT-Bench and Chatbot Arena," in *Advances in Neural Information Processing Systems*, vol. 36. Neural Information Processing Systems Foundation, 2023, pp. 46 595–46 623.

[43] G. H. Chen, S. Chen, Z. Liu, F. Jiang, and B. Wang, "Humans or LLMs as the judge? a study on judgement bias," in *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2024, pp. 8301–8327.

[44] D. Lakens, A. M. Scheel, and P. M. Isager, "Equivalence testing for psychological research: A tutorial," *Advances in Methods and Practices in Psychological Science*, vol. 1, no. 2, pp. 259–269, 2018.

[45] D. J. Barr, R. Levy, C. Scheepers, and H. J. Tily, "Random effects structure for confirmatory hypothesis testing: Keep it maximal," *Journal of Memory and Language*, vol. 68, no. 3, pp. 255–278, 2013.

[46] E. Feng, W. Zhou, Z. Liu *et al.*, "Get experience from practice: LLM agents with record & replay," 2025, preprint.

[47] Y. Sun, H. Wang, D. Li, G. Wang, and H. Zhang, "The emperor's new clothes in benchmarking? a rigorous examination of mitigation strategies for LLM benchmark data contamination," 2025, preprint (v1).

[48] A. Madaan, N. Tandon, P. Gupta *et al.*, "Self-Refine: Iterative refinement with self-feedback," in *Advances in Neural Information Processing Systems 36 (NeurIPS)*, 2023, pp. 46 534–46 594.

[49] M. O. Riedl, C. J. Saretto, and R. M. Young, "Managing interaction between users and agents in a multi-agent storytelling environment," in *Proceedings of the Second International Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS)*, 2003, pp. 741–748.

[50] R. E. Fikes and N. J. Nilsson, "STRIPS: A new approach to the application of theorem proving to problem solving," *Artificial Intelligence*, vol. 2, no. 3–4, pp. 189–208, 1971.

[51] F. B. Schneider, "Enforceable security policies," *ACM Transactions on Information and System Security*, vol. 3, no. 1, pp. 30–50, 2000.

[52] T. Haerder and A. Reuter, "Principles of transaction-oriented database recovery," *ACM Computing Surveys*, vol. 15, no. 4, pp. 287–317, 1983.

[53] R. Evans and E. Short, "Versu—a simulationist storytelling system," *IEEE Transactions on Computational Intelligence and AI in Games*, vol. 6, no. 2, pp. 113–130, 2014, predecessor title of IEEE Transactions on Games.

[54] S. G. Ware and C. Siler, "Sabre: A narrative planner supporting intention and deep theory of mind," in *Proceedings of the AAAI Conference on Artificial Intelligence and Interactive Digital Entertainment (AIIDE)*, vol. 17, no. 1, 2021, pp. 99–106.

[55] N. Shinn, F. Cassano, A. Gopinath, K. Narasimhan, and S. Yao, "Reflexion: Language agents with verbal reinforcement learning," in *Advances in Neural Information Processing Systems 36 (NeurIPS)*, 2023, pp. 8634–8652.

[56] X. Chen, M. Lin, N. Schärli, and D. Zhou, "Teaching large language models to self-debug," in *The Twelfth International Conference on Learning Representations (ICLR)*, 2024, accepted poster; OpenReview archival record; preprint arXiv:2304.05128.

[57] A. Solar-Lezama, L. Tancau, R. Bodík, S. Seshia, and V. Saraswat, "Combinatorial sketching for finite programs," in *Proceedings of the 12th International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS)*. ACM, 2006, pp. 404–415.

[58] Y. Huang, G. Chen, J. Yao *et al.*, "Beyond state consistency: Behavior consistency in text-based world models," 2026, preprint.