FIXED-GAME NATIVE RUNTIME COMPARISON I 8 ASSIGNED ROWS

One authored quest; n=2 per selector/representation cell; NR = not reported, not zero. Labels remain explicit; color is supplementary.

Row	Requested selector	Representation / repeat	Status	Goal	Host calls	Elapsed (s)	Safety R record-link / E engine
1	gpt-6.1-sol	general_rule / r1	HARNESS	NR	0	NR	NOT_OBSERVED R NR / E NOT_OBSERVED
2	gpt-6.1-sol	general_rule / r2	SUCCESS	YES	4	45.91	PASS R YES / E VALID
3	gpt-6.1-sol	ontology / r1	TIMEOUT	NO	2	84.66	PASS R YES / E VALID
4	gpt-6.1-sol	ontology / r2	TIMEOUT	NR	1	60.04	NO_COMMIT_OBSERVED R YES / E NOT_RUN
5	gpt-5.6-sol	general_rule / r1	SUCCESS	YES	4	41.09	PASS R YES / E VALID
6	gpt-5.6-sol	general_rule / r2	SUCCESS	YES	4	39.39	PASS R YES / E VALID
7	gpt-5.6-sol	ontology / r1	SUCCESS	YES	4	36.68	PASS R YES / E VALID
8	gpt-5.6-sol	ontology / r2	SUCCESS	YES	4	29.55	PASS R YES / E VALID

Endpoint outcomes, receipt-derived host calls, and dispatch-to-terminal elapsed time.

Typed-intent proposal; deterministic planner/checker and Godot commit retain authority.

No efficacy/superiority/noninferiority/player-benefit claim; provider metadata and request counts remain NR.