

EOM DIMon 3.1 Installation Instructions for Windows


Bart Heinsius

December 2, 2016

Version 3.1.02

Proposed metadata folder structure:

It is common practice to have separate SAS metadata folders for ETL programs, SAS Reports/SAS Stored Processes, and data. This document assumes installation in the SAS Metadata folder *My Company* shown here:




DIMon Batch Component Installation Instructions

Nr	Instruction												
1	<p>Use SAS Management Console to create a SAS/SHARE or DBMS library with libref DIMON assigned to your SAS DI Application Server to store the DIMon tables. Your batch user needs UPDATE access to the tables in this library. Your SAS General Server User (e.g., sassrv) needs READ access to the tables in this library.</p> <p>Notes:</p> <ul style="list-style-type: none"> - If you use a different libref than "DIMON" for your DIMon tables, add the following line to file "<sasappsrvcontextdir>\BatchServer\autoexec_usermods.sas": <pre>libname dimon (<your libref>);</pre> <ul style="list-style-type: none"> - For MySQL you need the following system variable in my.cnf: <pre>sql_mode='ANSI_QUOTES' # allow " as an identifier quote character (next to backtick)</pre> <ul style="list-style-type: none"> - For Postgres please follow instructions for optimization at http://support.sas.com/kb/52/585.html 												
2	<p>Create the required tables using the appropriate script for your database provided in installation package folder "SASBatch\SQL":</p> <table border="1"> <thead> <tr> <th>Engine</th><th>Script</th></tr> </thead> <tbody> <tr> <td>SAS/SHARE</td><td>dimon_create_tables_sas.sas</td></tr> <tr> <td>Postgres</td><td>dimon_create_tables_postgres.sql</td></tr> <tr> <td>MySQL</td><td>dimon_create_tables_mysql.sql</td></tr> <tr> <td>MS SQL Server</td><td>dimon_create_tables_sqlserver.sql</td></tr> <tr> <td>Oracle</td><td>dimon_create_tables_oracle.sql</td></tr> </tbody> </table>	Engine	Script	SAS/SHARE	dimon_create_tables_sas.sas	Postgres	dimon_create_tables_postgres.sql	MySQL	dimon_create_tables_mysql.sql	MS SQL Server	dimon_create_tables_sqlserver.sql	Oracle	dimon_create_tables_oracle.sql
Engine	Script												
SAS/SHARE	dimon_create_tables_sas.sas												
Postgres	dimon_create_tables_postgres.sql												
MySQL	dimon_create_tables_mysql.sql												
MS SQL Server	dimon_create_tables_sqlserver.sql												
Oracle	dimon_create_tables_oracle.sql												
3	<p>Register the tables that were created in step 2 in SAS metadata folder "/My Company/Shared Data/EOM DI Job Monitor".</p> <p>Deselect the following options when registering the tables:</p> <ul style="list-style-type: none"> - Enable case-sensitive DBMS object names - Enable special characters within table or column object name 												
4	<p>Import SAS metadata package "SASBatch\SASPackages\dimon-batch.spk" from the installation package to SAS metadata folder "/My Company/ETL/EOM DI Job Monitor/Jobs". Map the tables to the tables you registered in step 3.</p>												
5	<p>Copy all files in installation package folder "SASBatch\SASSteps" to folder "<sasappsrvcontextdir>\SASEnvironment\SASCode\Steps" on your SAS DI Application Server.</p>												

6	<p>Create directory "<sasappsrvcntextdir>\SASEnvironment\SASCode\dimon" on your SAS DI Application Server. Copy all files in installation package folder "SASBatch\SASCode" to this directory.</p> <p>If you store the DIMon tables in Postgres and access them through SAS/ACCESS to ODBC, you may run into the issue described at http://support.sas.com/kb/51/085.html. To fix, replace the SQL update statement in dimonFinishJob.sas with the following code:</p> <pre> proc sql noprint; connect to odbc(dsn=<your dsn>); execute (/* Insert Post-Job Statistics */ update dimon.dimon_job_runs set job_status_id = (select job_status_id from dimon.dimon_job_status where job_status_code = 'COMPLETED') , job_end_dts = current_timestamp , job_rc = &job_rc , update_user = %str(%)&sysuserid%str(%) , update_dts = now() where job_run_id = &job_run_id) by odbc; disconnect from odbc; quit; </pre>
7	<p>Copy files dimon_pre.bat and dimon_post.bat from installation package folder "SASBatch\BatchServer\Windows" to "<sasappsrvcntextdir>\BatchServer" on your SAS DI Application Server.</p> <p>DI Monitor uses the Windows date and time functions to compose log and lst file names. The output of these functions differs by locale. DI Monitor expects the English (US) locale; if you have set a different locale on your machine, modify the following lines in file dimon_pre.bat:</p> <pre> SET HOUR_TIME=%time:~0,2% IF %HOUR_TIME% leq 9 (set HOUR_TIME=0%HOUR_TIME: =%) SET DATETIME=%date:~10,4%.%date:~4,2%.%date:~7,2%_%HOUR_TIME%.%time:~3,2%.%time:~6,2% </pre> <p>so that DATETIME contains a date/time in the format YYYY.MM.DD_HH.MM.SS Example: 2016.11.30_22.31.40</p> <p>Note that this is very important; an incorrect date can cause errors when the SAS batch job is submitted. To help debugging you can set DIMONDEBUG=YES in dimon_pre.bat which creates file %TEMP%\dimon-debug.txt containing a list of environment variables.</p>
8	<p>Make a backup copy of file "<sasappsrvcntextdir>\BatchServer\sasbatch.bat" on your SAS DI Application Server.</p>
9	<p>Edit <sasappsrvcntextdir>\BatchServer\sasbatch.bat on your SAS DI Application Server:</p>


	<p>Right before the line:</p> <pre>"%SAS_COMMAND%" %CMD_OPTIONS% %*%:</pre> <p>insert the following lines:</p> <pre>REM EOM DI Monitor - prolog -- begin call %APPSERVER_ROOT%\BatchServer\dimon_pre.bat REM EOM DI Monitor - prolog - end</pre> <p>Right after the line:</p> <pre>"%SAS_COMMAND%" %CMD_OPTIONS% %*%:</pre> <p>insert the following lines:</p> <pre>REM EOM DI Monitor - epilog -- begin set JOB_RC=%ERRORLEVEL% call %APPSERVER_ROOT%\BatchServer\dimon_post.bat EXIT /b %JOB_RC% REM EOM DI Monitor - epilog -- end</pre> <p>Replace the line:</p> <pre>"%SAS_COMMAND%" %CMD_OPTIONS% %*%</pre> <p>with</p> <pre>"%SAS_COMMAND%" %CMD_OPTIONS% %* -log "%SASLOGFILE%" -print "%SASLSTFILE%"</pre> <p>Note the difference between %*% in the original command and %* in the modified command.</p>
10	<p>Add the following line to file "<sasappsrvcontextdir>\BatchServer\autoexec_usermods.sas":</p> <pre>options fullstimer;</pre>
11	<p>Using SAS DI Studio, run DI Studio job "/My Company/ETL/EOM DI Job Monitor/Jobs/DIMon_Load_Flows_and_Jobs" that you imported in step 4, on your SAS DI Application Server.</p> <p>You can ignore the warning that there are transformations that may be out of order in the job.</p>
12	<p>Deploy the SAS DI Studio jobs imported in step 4 for scheduling on your SAS DI Application Server.</p> <p>Use the SAS Management Console Schedule Manager plug-in to create a flow with the following deployed jobs:</p> <ol style="list-style-type: none"> 1. DIMon_Load_Flows_and_Jobs 2. DIMon_Statistics



DIMon Web Application Installation Instructions

Nr	Instruction									
1	Import SAS metadata package "Webapp\SASPackages\dimon-webapp.spk" into SAS metadata folder "/My Company/Application Support/EOM DI Job Monitor/Stored Processes". Assign the Stored Processes to run on your SAS Web Application Server (if you have that).									
2	Copy the content of folder "Webapp\Webapps" to directory "<SASConfigDir>\Web\WebServer\htdocs\" on your SAS Web Application Server.									
3	Copy the content of folder "Webapp\SASMacro" to directory "<sasappsrvcctxtdir>\SASEnvironment\SASMacro" on your SAS Web Application Server.									
4	<div>Edit file "<sasappsrvcctxtdir>\SASEnvironment\SASMacro\dimon_init.sas" on your SAS Web Application Server and update the settings/paths:</div> <table><tr><th>Setting</th><th>Description</th><th>Default value</th></tr><tr><td>sproot</td><td>Folder where dimon-webapp.spk was imported to</td><td>/My Company/Application Support/EOM DI Job Monitor/Stored Processes</td></tr><tr><td>webroot</td><td>Relative URL path to where the webapps components were copied to in step 2</td><td>/eom/dimon</td></tr></table> <div>If you use a different libref than "DIMON" for your DIMon tables, set that in the section marked yellow below:</div> <pre>%if (%sysfunc(libref(dimon)) ne 0) %then %do; /* assign dimon library */ %put NOTE: Assigning library DIMON; libname dimon (dimonsas); %end; /* assign dimon library */ libname dimon list;</pre>	Setting	Description	Default value	sproot	Folder where dimon-webapp.spk was imported to	/My Company/Application Support/EOM DI Job Monitor/Stored Processes	webroot	Relative URL path to where the webapps components were copied to in step 2	/eom/dimon
Setting	Description	Default value								
sproot	Folder where dimon-webapp.spk was imported to	/My Company/Application Support/EOM DI Job Monitor/Stored Processes								
webroot	Relative URL path to where the webapps components were copied to in step 2	/eom/dimon								
5	<div>If you chose a different metadata location in Step 1 than the default ("/My Company/Application Support/EOM DI Job Monitor/Stored Processes"), update file "<SASConfigDir>\Web\WebServer\htdocs\leom\dimon\index.html" to reflect that in the sections marked yellow below:</div> <div><pre>1 <!DOCTYPE HTML> 2 <html lang="en-US"> 3 <head> 4 <meta charset="UTF-8"> 5 <meta http-equiv="refresh" content= 6 "1;/SASStoredProcess/do?_program=/My+Company/Application+Support/EOM+DI+Job+Monitor/Stored+Processes/dimon"> 7 <script type="text/javascript"> 8 var parms = window.location.search.substr(1); 9 window.location.href = 10 "/SASStoredProcess/do?_program=/My+Company/Application+Support/EOM+DI+Job+Monitor/Stored+Processes/dimon" 11 + (parms == "" ? '' : '%' + parms); 12 </script> 13 <title>Page Redirection</title> 14 </head> 15 <body> 16 <!-- Note: don't tell people to 'click' the link, just tell them that it is a link. --> 17 If you are not redirected automatically, follow this link to the EOM DI 19 Monitor 20 </body> 21 </html></pre></div>									

- 6 Start the EOM DI Job Monitor web application by navigating your browser to <http://your-sasweb-server/eom/dimon/> . If you don't have any flows scheduled yet you should see the following:



-- END OF INSTRUCTIONS DIMON WEB APPLICATION COMPONENT