



H1(G2)/AC1(G2)

SINGLE-PHASE **HYBRID/AC INVERTER**



HIGH VOLTAGE

Includes high-voltage batteries for maximum round-trip efficiency.



EASY INSTALLATION

Flexible configuration, plug and play set-up, built-in fuse protection.



IP65 RATED

Engineered to last with maximum flexibility. Suitable for outdoor installation.



REMOTE MONITORING

Monitor your system remotely via smartphone app or web portal.



Advanced System Monitoring
with **FoxCloud V2.0**

REFINED – POWERFUL – FLEXIBLE

Harness the power of the sun day and night with the ground-breaking range of Hybrid & AC inverter from Fox ESS. Full of advanced features and compatible with our very own range of high-voltage batteries, the hybrid range from Fox ESS.

3kW ...>> 6kW



For more information about the Fox ESS range, visit:
www.fox-ess.com



up to
6kW
charge/
discharge

TECHNICAL SPECIFICATIONS

MODEL	H1-3.0-E-G2 AC1-3.0-E-G2	H1-3.7-E-G2 AC1-3.7-E-G2	H1-4.6-E-G2 AC1-4.6-E-G2	H1-5.0-E-G2 AC1-5.0-E-G2	H1-6.0-E-G2 AC1-6.0-E-G2	H1-4.6-E1-G2 AC1-4.6-E1-G2	H1-5.0-E1-G2 AC1-5.0-E1-G2
INPUT PV (ONLY FOR HYBRID)							
Max. PV Array Power [Wp]	6000	7400	9200	10000	12000	9200	10000
Max. Input Power [W]	4500 A:2250 B:2250	5500 A:2750 B:2750	6900 A:3450 B:3450	7500 A:3750 B:3750	9000 A:4500 B:4500	6900 A:3450 B:3450	7500 A:3750 B:3750
Max. Input Voltage [V]				600			
Start-up Input Voltage [V]				75			
Rated Input Voltage [V]				360			
MPPT Operating Voltage Range [V]				80 ~ 550			
Max. Input Current [A]				16 / 16			
Max. Short-circuit Current [A]				20 / 20			
No. of Independent MPP Trackers				2			
No. of Strings per MPP Tracker				1			
BATTERY CONNECTION							
Battery Type	Lithium Battery (LFP)						
Battery Voltage [V]	80 ~ 480						
Max. Charge/Discharge Current [A]	40						
Communication Interface	CAN(communicate with inverter, upgrade BMS)						
AC INPUT AND OUTPUT (GRID)							
Max. AC Input Power [VA]	6000	7680	9200	10000	12000	9200	10000
Max. AC Input Current (per phase) [A]	27.3	34.9	41.8	45.5	54.5	41.8	45.5
Rated Output Power [W]	3000	3680	4600	5000	6000	4600	5000
Rated Apparent Power [VA]	3000	3680	4600	5000	6000	4600 ²	5000 ³
Max. Output Apparent Power [VA]	3300	4048/3680 ¹	5060	5500	6600	4600	5000
Rated Output Current (per phase) [A](For AUS)	13.0	16.0	20.0	21.7	26.1	20.0	21.7
Max. Output Current [A]	15.0	18.4	23.0	25.0	30.0	20.9	22.7
Rated Grid Voltage [V]	220/230/240						
Rated Grid Frequency [Hz]	50/60						
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)						
THDi [%]	<3 @rated power						
EPS OUTPUT (WITH BATTERY)							
Max. Output Apparent Power [VA]	3000	3680	4600	5000	6000	4600	5000
Rated Output Power [W]	3000	3680	4600	5000	6000	4600	5000
Peak Output Apparent Power (60s) [VA]	3600	4400	5500	6000	7200	5500	6000
Max. Current (per phase) [A]	13.6	16.7	20.9	22.7	27.3	20.9	22.7
Rated Output Voltage [V]	220/230/240						
Rated Output Frequency [Hz]	50/60						
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)						
THDv (linear Load) [%]	<2 @rated power						
Parallel operation [PCS]	10						
Switch time [ms]	<20						
EFFICIENCY							
Euro Efficiency [%]	95.26	95.70	96.23	96.30	96.33	96.23	96.30
Max. Efficiency [%]	97.01	97.08	97.04	97.08	97.08	97.04	97.08
Max. Battery Charge Efficiency (PV to BAT) (@full load) [%]				98.50			
Max. Battery Discharge Efficiency (BAT to AC) (@full load) [%]				97.00			
PROTECTION							
Insulation Monitoring				YES			
Residual Current Monitoring				YES			
DC Reverse Polarity Protection				YES			
Anti-islanding Protection				Active Frequency Drift with Positive Feedback			
AC Short-circuit Protection				YES			
AC Overcurrent/Overvoltage Protection				YES			
DC Switch				YES			
Battery Wack-up Function				YES			
Over Voltage category				III(AC), II(DC)			
AFCI				Optional			
GENERAL DATA							
Dimensions (WxHxD) [mm]				434*418*185			
Weight [kg]				22			
Installation				Wall-Mounted			
Topology				Non-isolated			
Cooling Method				Natural			
Noise Emission [dB]				35			
Max. Operating Altitude [m]				2000			
Operating Temperature Range [°C]				-25 ~ 60			
Humidity (No Condensation) [%]				0 ~ 100			
Ingress protection				IP65			
Standby consumption[W]				< 15			
Monitoring Module				WiFi, LAN(optional) , 4G(optional)			
Communication				RS485, DRM, Ripple Control, USB, CAN			
Display				LCD, App, Website			
Country Of Manufacture				China			
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)							
Safety				EN 62109-1, EN 62109-2			
EMC				EN 61000-6-2, EN 61000-6-3			
Grid Regulation				EN50549-1, C10 / 11, VDE-AR-N 4105, G98, G99, CEI 0-21, NRS 097-2-1, AS / NZS 4777.2			

* More technical characteristics are available on demand and customized.
1、 3680 for G98. 2、 4600 for German and Belgium. 3、 5000 for Belgium.