



Stackable AIO

SINGLE-PHASE **HYBRID/AC**



FLEXIBILITY

Modular design to meet various backup scenarios.



EASY INSTALLATION

Integrated configuration, plug and play set-up.



IP66 RATED

Engineered to last with maximum flexibility. Suitable for outdoor installation.



REMOTE MONITORING

Monitor your system remotely via smartphone app or web portal.



Advanced System Monitoring
with **FoxCloud V2.0**

Stackable AIO is the latest generation of an integrated residential energy storage system, modular designed to meet various installation scenarios.

3.7kW ...>> 11kW



For more information about the Fox ESS range, visit:
www.fox-ess.com

AIO-AC1 (ac-coupled)
variants available.



PQ INVERTER

EQ BATTERY

TECHNICAL SPECIFICATIONS

Stackable AIO-HI-3.7

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/	8.64 with 4S EQ2900-S &EQ2900-S(w)/	11.52 with 4S EQ2900-S &EQ2900-S(w)/	14.40 with 5S EQ2900-S &EQ2900-S(w)/	17.28 with 6S EQ2900-S &EQ2900-S(w)/	20.16 with 7S EQ2900-S &EQ2900-S(w)/
	8.64 with 4S EQ4300-S &EQ4300-S(w)/	12.96 with 4S EQ4300-S &EQ4300-S(w)/	17.28 with 4S EQ4300-S &EQ4300-S(w)/	21.60 with 5S EQ4300-S &EQ4300-S(w)/	25.92 with 6S EQ4300-S &EQ4300-S(w)/	30.24 with 7S EQ4300-S &EQ4300-S(w)/
	6.40 with 2S EQ3300-S &EQ3300-S(w)/	9.60 with 2S EQ3300-S &EQ3300-S(w)/	12.80 with 2S EQ3300-S &EQ3300-S(w)/	16.00 with 2S EQ3300-S &EQ3300-S(w)/	19.20 with 2S EQ3300-S &EQ3300-S(w)/	-
	9.84 with 4S EQ5000-S &EQ5000-S(w)	14.76 with 4S EQ5000-S &EQ5000-S(w)	19.68 with 4S EQ5000-S &EQ5000-S(w)	24.60 with 5S EQ5000-S &EQ5000-S(w)	29.52 with 6S EQ5000-S &EQ5000-S(w)	-

PV INPUT

Max. solar STC power [kW]	7400
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT 1: 32; MPPT 2: 16
MPPT & Strings	MPPT 1: 2 Strings; MPPT 2: 1 String

AC OUTPUT

Nominal AC power [W]	3680
Max. apparent output power [VA]	3680
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge & discharge current [A]	50&50					
Max. continous charge & discharge power [W]	5550&3680					
Communication	CAN2.0					

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	3680						
Rated output power Without PV [W]	3680						
Max. apparent output power [VA]	3680						
Peak output power for 60 sec. [W]	4995						
Max. Continuous AC output current [A]	16.0						
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/55.7	75.1/75.1/83.5	100.2/100.2/110	110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -

Weight [kg]	Inverter	49
	Battery module	31/37/36/43.5
	Base	3.5

Enclosure rating	Power Qube	IP66
	EQ battery	IP55

Operation temperature range [°C]	Power Qube	-25 ~ +60 (Derating at 40)
	EQ battery	-10 ~ +55

Relative humidity [%]	Power Qube	0 ~ 100 (No Condensation)
	EQ battery	5 ~ 95 (No Condensation)

Typical noise emission [dB]	<35
-----------------------------	-----

Max. operation altitude [ft/m]	6,560 (2000)
--------------------------------	--------------

Internal Consumption at Night [W]	<25
-----------------------------------	-----

Cooling Method	Natural convection
----------------	--------------------

Mounting	Ground mounting
----------	-----------------

Display	LED, APP, Website
---------	-------------------

Communication	WLAN
---------------	------

Interface	CAN2.0, RS485, Meter, CT, ISO alarm
-----------	-------------------------------------

TECHNICAL SPECIFICATIONS

Stackable AIO-H1-5.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

PV INPUT

Max. solar STC power [kW]	10000
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT 1: 32; MPPT 2: 16
MPPT & Strings	MPPT 1: 2 Strings; MPPT 2: 1 String

AC OUTPUT

Nominal AC power [W]	5000
Max. apparent output power [VA]	5000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5500/ 5760&5500/ 6400&5500/ 6400&5500	7500&5500	7500&5500	7500&5500	7500&5500	7500&5500

Communication	CAN2.0
---------------	--------

EPS OUTPUT (WITH BATTERY)

Rated output power [W]							5000
Rated output power Without PV [W]							5000
Max. apparent output power [VA]							5500
Peak output power for 60 sec. [W]							6750
Max. Continuous AC output current [A]							25.0
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110	

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/	570*932*380/	570*1052*380/	570*1172*380/	570*1292*380/	570*1412*380/
	570*848*380/	570*986*380/	570*1124*380/	570*1262*380/	570*1400*380/	570*1538*380/
	570*842*380/	570*977*380/	570*1112*380/	570*1247*380/	570*1382*380/	-/
	570*842*380	570*977*380	570*1112*380	570*1247*380	570*1382*380	-
Weight [kg]	Inverter	49				
	Battery module	31/37/36/43.5				
	Base	3.5				
Enclosure rating	Power Qube	IP66				
	EQ battery	IP55				
Operation temperature range [°C]	Power Qube	-25 ~ +60 (Derating at 40)				
	EQ battery	-10 ~ +55				
Relative humidity [%]	Power Qube	0 ~ 100 (No Condensation)				
	EQ battery	5 ~ 95 (No Condensation)				
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-HI-6.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

PV INPUT

Max. solar STC power [kW]	12000
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT 1: 32; MPPT 2: 16
MPPT & Strings	MPPT 1: 2 Strings; MPPT 2: 1 String

AC OUTPUT

Nominal AC power [W]	6000
Max. apparent output power [VA]	6000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400/ 6400&6400	8640&6600/ 8640&6600/ 9000&6600/ 9000&6600	9000&6600	9000&6600	9000&6600	9000&6600

Communication CAN2.0

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	6000					
Rated output power Without PV [W]	5760/5760/ 6000/6000	6000	6000	6000	6000	6000
Max. apparent output power [VA]	6600					
Peak output power for 60 sec. [W]	8100					
Max. Continuous AC output current [A]	30.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter						
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube						
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40) -10 ~ +55					
Power Qube						
EQ battery						
Relative humidity [%]	0 ~ 100 (No Condensation) 5 ~ 95 (No Condensation)					
Power Qube						
EQ battery						
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-HI-7.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

PV INPUT

Max. solar STC power [kW]	14000
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT 1: 32; MPPT 2: 16
MPPT & Strings	MPPT 1: 2 Strings; MPPT 2: 1 String

AC OUTPUT

Nominal AC power [W]	7000
Max. apparent output power [VA]	7000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400/ 6400&6400	8640&7700/ 8640&7700/ 9600&7700/ 9600&7700	10500&7700	10500&7700	10500&7700	10500&7700

Communication	CAN2.0
---------------	--------

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	7000					
Rated output power Without PV [W]	5760/5760/ 6400/6400	7000	7000	7000	7000	7000
Max. apparent output power [VA]	7700					
Peak output power for 60 sec. [W]	9450					
Max. Continuous AC output current [A]	35.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube	IP66					
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40) -10 ~ +55					
Power Qube	-25 ~ +60 (Derating at 40)					
EQ battery	-10 ~ +55					
Relative humidity [%]	0 ~ 100 (No Condensation) 5 ~ 95 (No Condensation)					
Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-HI-9.0-W-Z

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

PV INPUT

Max. solar STC power [kW]	18000
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT I: 32; MPPT 2&3: 16
MPPT & Strings	MPPT I: 2 Strings; MPPT 2&3: 1 String

AC OUTPUT

Nominal AC power [W]	9000
Max. apparent output power [VA]	9000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400/ 6400&6400	8640&8640/ 8640&8640/ 9600&9600/ 9600&9600	11520&9900/ 11520&9900/ 12800&9900/ 12800&9900	13500&9900	13500&9900	13500&9900

Communication CAN2.0

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	9000					
Rated output power Without PV [W]	5760/5760/ 6400/6400	8640/8640/ 9000/9000	9000	9000	9000	9000
Max. apparent output power [VA]	9900					
Peak output power for 60 sec. [W]	12150					
Max. Continuous AC output current [A]	45.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube	IP55					
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40) -10 ~ +55					
Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-H1-11.0-W-Z

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

PV INPUT

Max. solar STC power [kW]	22000
Max. PV input voltage [V]	600
MPPT voltage range [V]	80 ~ 500
Max. PV input current per MPPT [A]	MPPT I: 32; MPPT 2&3: 16
MPPT & Strings	MPPT I: 2 Strings; MPPT 2&3: 1 String

AC OUTPUT

Nominal AC power [W]	11000
Max. apparent output power [VA]	11000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/ 128/128	172.8/172.8/ 192/192	230.4/230.4/ 256/256	288/288/ 320/320	345.6/345.6/ 384/384	403.2/403.2/ -/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400/ 6400&6400	8640&8640/ 8640&8640/ 9600&9600/ 9600&9600	11520&11520/ 11520&11520/ 12800&12100/ 12800&12100	14400&12100/ 14400&12100/ 16000&12100/ 16000&12100	16500&12100	16500&12100

Communication CAN2.0

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	11000					
Rated output power Without PV [W]	5760/5760/ 6400/6400	8640/8640/ 9600/9600	11000	11000	11000	11000
Max. apparent output power [VA]	12100					
Peak output power for 60 sec. [W]	14850					
Max. Continuous AC output current [A]	55.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter						
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube						
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40) -10 ~ +55					
Power Qube						
EQ battery	0 ~ 100 (No Condensation) 5 ~ 95 (No Condensation)					
Relative humidity [%]						
Power Qube						
EQ battery						
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-3.7

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/	8.64 with 4S EQ2900-S &EQ2900-S(w)/	11.52 with 4S EQ2900-S &EQ2900-S(w)/	14.40 with 5S EQ2900-S &EQ2900-S(w)/	17.28 with 6S EQ2900-S &EQ2900-S(w)/	20.16 with 7S EQ2900-S &EQ2900-S(w)/
	8.64 with 4S EQ4300-S &EQ4300-S(w)/	12.96 with 4S EQ4300-S &EQ4300-S(w)/	17.28 with 4S EQ4300-S &EQ4300-S(w)/	21.60 with 5S EQ4300-S &EQ4300-S(w)/	25.92 with 6S EQ4300-S &EQ4300-S(w)/	30.24 with 7S EQ4300-S &EQ4300-S(w)/
	6.40 with 2S EQ3300-S &EQ3300-S(w)/	9.60 with 2S EQ3300-S &EQ3300-S(w)/	12.80 with 2S EQ3300-S &EQ3300-S(w)/	16.00 with 2S EQ3300-S &EQ3300-S(w)/	19.20 with 2S EQ3300-S &EQ3300-S(w)/	-
	9.84 with 4S EQ5000-S &EQ5000-S(w)	14.76 with 4S EQ5000-S &EQ5000-S(w)	19.68 with 4S EQ5000-S &EQ5000-S(w)	24.60 with 5S EQ5000-S &EQ5000-S(w)	29.52 with 6S EQ5000-S &EQ5000-S(w)	-

AC OUTPUT

Nominal AC power [W]	3680
Max. apparent output power [VA]	3680
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion
Nominal battery voltage [V]	115.2/115.2/128 172.8/172.8/192 230.4/230.4/256 288/288/320 345.6/345.6/384 403.2/403.2/-
Max. continous charge &discharge current [A]	50&50
Max. continous charge &discharge power [W]	3700&3680

Communication	CAN2.0
---------------	--------

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	3680
Max. apparent output power [VA]	3680
Peak output power for 60 sec. [W]	4995
Max. Continuous AC output current [A]	16.0
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/55.7/55.7 75.1/75.1/83.5/83.5 100.2/100.2/110/110 110 110 110

GENERAL DATA

Hybrid inverter Qty	1
Battery modules Qty	2 3 4 5 6 7
Base Qty	1
Dimension (W*H*D) [mm]	570*812*380/570*848*380/570*842*380/570*842*380 570*932*380/570*986*380/570*977*380/570*977*380 570*1052*380/570*1124*380/570*1112*380/570*1112*380 570*1172*380/570*1262*380/570*1247*380/570*1247*380 570*1292*380/570*1400*380/570*1382*380/570*1382*380 570*1412*380/570*1538*380/-/-
Weight [kg] Inverter	49
Battery module	31/37/36/43.5
Base	3.5
Enclosure rating Power Qube	IP66
EQ battery	IP55
Operation temperature range [°C] Power Qube	-25 ~ +60 (Derating at 40)
EQ battery	-10 ~ +55
Relative humidity [%] Power Qube	0 ~ 100 (No Condensation)
EQ battery	5 ~ 95 (No Condensation)
Typical noise emission [dB]	<35
Max. operation altitude [ft/m]	6,560 (2000)
Internal Consumption at Night [W]	<25
Cooling Method	Natural convection
Mounting	Ground mounting
Display	LED, APP, Website
Communication	WLAN
Interface	CAN2.0, RS485, Meter, CT, ISO alarm

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-5.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

AC OUTPUT

Nominal AC power [W]	5000
Max. apparent output power [VA]	5000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion
Nominal battery voltage [V]	115.2/115.2/128 172.8/172.8/192 230.4/230.4/256 288/288/320 345.6/345.6/384 403.2/403.2/-
Max. continous charge &discharge current [A]	50&50
Max. continous charge &discharge power [W]	5000&5500

Communication	CAN2.0
---------------	--------

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	5000
Max. apparent output power [VA]	5500
Peak output power for 60 sec. [W]	6750
Max. Continuous AC output current [A]	25.0
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7 75.1/75.1/ 83.5/83.5 100.2/100.2/ 110/110 110 110 110

GENERAL DATA

Hybrid inverter Qty	1
Battery modules Qty	2 3 4 5 6 7
Base Qty	1
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380 570*932*380/ 570*986*380/ 570*977*380/ 570*977*380 570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380 570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380 570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380 570*1412*380/ 570*1538*380/ -/ -
Weight [kg] Inverter	49
Battery module	31/37/36/43.5
Base	3.5
Enclosure rating Power Qube	IP66
EQ battery	IP55
Operation temperature range [°C] Power Qube	-25 ~ +60 (Derating at 40)
EQ battery	-10 ~ +55
Relative humidity [%] Power Qube	0 ~ 100 (No Condensation)
EQ battery	5 ~ 95 (No Condensation)
Typical noise emission [dB]	<35
Max. operation altitude [ft/m]	6,560 (2000)
Internal Consumption at Night [W]	<25
Cooling Method	Natural convection
Mounting	Ground mounting
Display	LED, APP, Website
Communication	WLAN
Interface	CAN2.0, RS485, Meter, CT, ISO alarm

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-6.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

AC OUTPUT

Nominal AC power [W]	6000
Max. apparent output power [VA]	6000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/128	172.8/172.8/192	230.4/230.4/256	288/288/320	345.6/345.6/384	403.2/403.2/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6000&6400	6000&6600	6000&6600	6000&6600	6000&6600	6000&6600
Communication	CAN2.0					

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	6000					
Max. apparent output power [VA]	6600					
Peak output power for 60 sec. [W]	8100					
Max. Continuous AC output current [A]	30.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube	IP66					
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40)					
Power Qube	-25 ~ +60 (Derating at 40)					
EQ battery	-10 ~ +55					
Relative humidity [%]	0 ~ 100 (No Condensation)					
Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-7.0

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

AC OUTPUT

Nominal AC power [W]	7000
Max. apparent output power [VA]	7000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/128	172.8/172.8/192	230.4/230.4/256	288/288/320	345.6/345.6/384	403.2/403.2/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400	7000&7700	7000&7700	7000&7700	7000&7700	7000&7700
Communication	CAN2.0					

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	7000					
Max. apparent output power [VA]	7700					
Peak output power for 60 sec. [W]	9450					
Max. Continuous AC output current [A]	35.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube	IP66					
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40)					
Power Qube	-25 ~ +60 (Derating at 40)					
EQ battery	-10 ~ +55					
Relative humidity [%]	0 ~ 100 (No Condensation)					
Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-9.0-W-Z

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

AC OUTPUT

Nominal AC power [W]	9000
Max. apparent output power [VA]	9000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/128	172.8/172.8/192	230.4/230.4/256	288/288/320	345.6/345.6/384	403.2/403.2/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400	8640&8640/ 8640&8640/ 9000&9600	9000&9900	9000&9900	9000&9900	9000&9900

Communication CAN2.0

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	9000					
Max. apparent output power [VA]	9900					
Peak output power for 60 sec. [W]	12150					
Max. Continuous AC output current [A]	45.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg]	49					
Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating	IP66					
Power Qube	IP66					
EQ battery	IP55					
Operation temperature range [°C]	-25 ~ +60 (Derating at 40)					
Power Qube	-25 ~ +60 (Derating at 40)					
EQ battery	-10 ~ +55					
Relative humidity [%]	0 ~ 100 (No Condensation)					
Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					

TECHNICAL SPECIFICATIONS

Stackable AIO-AC-11.0-W-Z

STACKABLE AIO ENERGY STORAGE

Total energy [kWh]	5.76 with 4S EQ2900-S &EQ2900-S(w)/ 8.64 with 4S EQ4300-S &EQ4300-S(w)/ 6.40 with 2S EQ3300-S &EQ3300-S(w)/ 9.84 with 4S EQ5000-S &EQ5000-S(w)	8.64 with 4S EQ2900-S &EQ2900-S(w)/ 12.96 with 4S EQ4300-S &EQ4300-S(w)/ 9.60 with 2S EQ3300-S &EQ3300-S(w)/ 14.76 with 4S EQ5000-S &EQ5000-S(w)	11.52 with 4S EQ2900-S &EQ2900-S(w)/ 17.28 with 4S EQ4300-S &EQ4300-S(w)/ 12.80 with 2S EQ3300-S &EQ3300-S(w)/ 19.68 with 4S EQ5000-S &EQ5000-S(w)	14.40 with 5S EQ2900-S &EQ2900-S(w)/ 21.60 with 5S EQ4300-S &EQ4300-S(w)/ 16.00 with 2S EQ3300-S &EQ3300-S(w)/ 24.60 with 5S EQ5000-S &EQ5000-S(w)	17.28 with 6S EQ2900-S &EQ2900-S(w)/ 25.92 with 6S EQ4300-S &EQ4300-S(w)/ 19.20 with 2S EQ3300-S &EQ3300-S(w)/ 29.52 with 6S EQ5000-S &EQ5000-S(w)	20.16 with 7S EQ2900-S &EQ2900-S(w)/ 30.24 with 7S EQ4300-S &EQ4300-S(w)/ - - -
--------------------	---	---	---	---	---	---

AC OUTPUT

Nominal AC power [W]	11000
Max. apparent output power [VA]	11000
Nominal AC output voltage [V]	220&230&240
Output power factor	>0.99(0.8leading ~ 0.8 lagging)
Total harmonic distortion [%]	<3

EQ BATTERY

Battery type	Li-ion					
Nominal battery voltage [V]	115.2/115.2/128	172.8/172.8/192	230.4/230.4/256	288/288/320	345.6/345.6/384	403.2/403.2/-
Max. continous charge &discharge current [A]	50&50					
Max. continous charge &discharge power [W]	5760&5760/ 5760&5760/ 6400&6400	8640&8640/ 8640&8640/ 9600&9600	11000&11520	11000&11520	11000&11520	11000&11520
Communication	CAN2.0					

EPS OUTPUT (WITH BATTERY)

Rated output power [W]	11000					
Max. apparent output power [VA]	12100					
Peak output power for 60 sec. [W]	14850					
Max. Continuous AC output current [A]	55.0					
Load Start Capacity for 2 sec. [A] LRA	50.1/50.1/ 55.7/55.7	75.1/75.1/ 83.5/83.5	100.2/100.2/ 110/110	110	110	110

GENERAL DATA

Hybrid inverter Qty	1					
Battery modules Qty	2	3	4	5	6	7
Base Qty	1					
Dimension (W*H*D) [mm]	570*812*380/ 570*848*380/ 570*842*380/ 570*842*380	570*932*380/ 570*986*380/ 570*977*380/ 570*977*380	570*1052*380/ 570*1124*380/ 570*1112*380/ 570*1112*380	570*1172*380/ 570*1262*380/ 570*1247*380/ 570*1247*380	570*1292*380/ 570*1400*380/ 570*1382*380/ 570*1382*380	570*1412*380/ 570*1538*380/ -/ -
Weight [kg] Inverter	49					
Battery module	31/37/36/43.5					
Base	3.5					
Enclosure rating Power Qube	IP66					
EQ battery	IP55					
Operation temperature range [°C] Power Qube	-25 ~ +60 (Derating at 40)					
EQ battery	-10 ~ +55					
Relative humidity [%] Power Qube	0 ~ 100 (No Condensation)					
EQ battery	5 ~ 95 (No Condensation)					
Typical noise emission [dB]	<35					
Max. operation altitude [ft/m]	6,560 (2000)					
Internal Consumption at Night [W]	<25					
Cooling Method	Natural convection					
Mounting	Ground mounting					
Display	LED, APP, Website					
Communication	WLAN					
Interface	CAN2.0, RS485, Meter, CT, ISO alarm					