



FORTEST

Testing Technology. Together.

Rev0 - 18/04/2019

UART - COM Port Resources on T-Series

Model Name	COM1	COM2																																												
T6000	<table><tr><th colspan="2">COM1</th></tr><tr><th>Pin</th><th>Descrizione</th></tr><tr><td>1</td><td>-</td></tr><tr><td>2</td><td>TX (RS232) – C2</td></tr><tr><td>3</td><td>RX (RS232) – C2</td></tr><tr><td>4</td><td>-</td></tr><tr><td>5</td><td>GND</td></tr><tr><td>6</td><td>TX (RS232) – C1</td></tr><tr><td>7</td><td>RX (RS232) – C1</td></tr><tr><td>8</td><td>-</td></tr><tr><td>9</td><td>-</td></tr></table>	COM1		Pin	Descrizione	1	-	2	TX (RS232) – C2	3	RX (RS232) – C2	4	-	5	GND	6	TX (RS232) – C1	7	RX (RS232) – C1	8	-	9	-	<table><tr><th colspan="2">COM2</th></tr><tr><th>Pin</th><th>Descrizione</th></tr><tr><td>1</td><td>GND</td></tr><tr><td>2</td><td>CAN L</td></tr><tr><td>3</td><td>-</td></tr><tr><td>4</td><td>I/O 1</td></tr><tr><td>5</td><td>CAN H</td></tr><tr><td>6</td><td>RS485 A</td></tr><tr><td>7</td><td>RS485 B\</td></tr><tr><td>8</td><td>I/O 2</td></tr><tr><td>9</td><td>I/O 3</td></tr></table>	COM2		Pin	Descrizione	1	GND	2	CAN L	3	-	4	I/O 1	5	CAN H	6	RS485 A	7	RS485 B\	8	I/O 2	9	I/O 3
	COM1																																													
	Pin	Descrizione																																												
	1	-																																												
	2	TX (RS232) – C2																																												
	3	RX (RS232) – C2																																												
	4	-																																												
	5	GND																																												
	6	TX (RS232) – C1																																												
	7	RX (RS232) – C1																																												
8	-																																													
9	-																																													
COM2																																														
Pin	Descrizione																																													
1	GND																																													
2	CAN L																																													
3	-																																													
4	I/O 1																																													
5	CAN H																																													
6	RS485 A																																													
7	RS485 B\																																													
8	I/O 2																																													
9	I/O 3																																													
	C1 : UART communication ForTest protocol , Modbus RTU, Trace end of test C2 : Barcode, Printer	RS485 : UART communication ForTest, Modbus RTU																																												
T8000	<table><tr><th colspan="2">COM1</th></tr><tr><th>Pin</th><th>Descrizione</th></tr><tr><td>1</td><td>CANH (OPT)</td></tr><tr><td>2</td><td>TXRS232 SER1</td></tr><tr><td>3</td><td>RX RS232 SER1</td></tr><tr><td>4</td><td>CANL (OPT)</td></tr><tr><td>5</td><td>GND</td></tr><tr><td>6</td><td>TX RS232 SER0</td></tr><tr><td>7</td><td>RX RS232 SER0</td></tr><tr><td>8</td><td>RS485 B\</td></tr><tr><td>9</td><td>RS485 A</td></tr></table>	COM1		Pin	Descrizione	1	CANH (OPT)	2	TXRS232 SER1	3	RX RS232 SER1	4	CANL (OPT)	5	GND	6	TX RS232 SER0	7	RX RS232 SER0	8	RS485 B\	9	RS485 A	<table><tr><th colspan="2">COM2</th></tr><tr><th>Pin</th><th>Descrizione</th></tr><tr><td>1</td><td>TTY_T+/\ OutAn</td></tr><tr><td>2</td><td>TTY_R+</td></tr><tr><td>3</td><td>TTY_R-</td></tr><tr><td>4</td><td>TTY_T-</td></tr><tr><td>5</td><td>GND</td></tr><tr><td>6</td><td>OUT0</td></tr><tr><td>7</td><td>OUT1</td></tr><tr><td>8</td><td>Out Vacuum</td></tr><tr><td>9</td><td>GND</td></tr></table>	COM2		Pin	Descrizione	1	TTY_T+/\ OutAn	2	TTY_R+	3	TTY_R-	4	TTY_T-	5	GND	6	OUT0	7	OUT1	8	Out Vacuum	9	GND
	COM1																																													
	Pin	Descrizione																																												
	1	CANH (OPT)																																												
	2	TXRS232 SER1																																												
	3	RX RS232 SER1																																												
	4	CANL (OPT)																																												
	5	GND																																												
	6	TX RS232 SER0																																												
	7	RX RS232 SER0																																												
8	RS485 B\																																													
9	RS485 A																																													
COM2																																														
Pin	Descrizione																																													
1	TTY_T+/\ OutAn																																													
2	TTY_R+																																													
3	TTY_R-																																													
4	TTY_T-																																													
5	GND																																													
6	OUT0																																													
7	OUT1																																													
8	Out Vacuum																																													
9	GND																																													
	SER0 : UART communication ForTest protocol, Modbus RTU, Trace end of test SER1 : Barcode, Printer																																													



ForTest Italia Srl
Sede legale:
Via Marsala 17 - 41037 Mirandola (MO) - IT

Sede Operativa:
Comparto Alfieri Maserati, sez. 2A
Via Sibilla Aleramo n.7
41123 Modena (MO) - IT

P.I. / C.F. IT02934911203 REA MO-378687
Phone +39 059 557250
Fax +39 059 579022
www.fortest.com
info@fortest.com