

File permissions in Linux

Project description

The research team at my organization needs to update the file permissions for certain files and directories within the `projects` directory. The permissions do not currently reflect the level of authorization that should be given. Checking and updating these permissions will help keep their system secure. To complete this task, I performed the following tasks:

Check file and directory details

The following code demonstrates how I used Linux commands to determine the existing permissions set for a specific directory in the file system.

```
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-rw--w--- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$
```

The first line of the screenshot displays the command I entered, and the other lines display the output. The code lists all contents of the `projects` directory. I used the `ls` command with the `-la` option to display a detailed listing of the file contents that also returned hidden files.

Describe the permissions string

The 10-character string can be deconstructed to determine who is authorized to access the file and their specific permissions. The characters and what they represent are as follows:

- **1st character:** This character is either a `d` or hyphen (`-`) and indicates the file type. If it's a `d`, it's a directory. If it's a hyphen (`-`), it's a regular file.
- **2nd-4th characters:** These characters indicate the read (`r`), write (`w`), and execute (`x`) permissions for the user. When one of these characters is a hyphen (`-`) instead, it indicates that this permission is not granted to the user.

- **5th-7th characters:** These characters indicate the read (`r`), write (`w`), and execute (`x`) permissions for the group. When one of these characters is a hyphen (`-`) instead, it indicates that this permission is not granted for the group.
- **8th-10th characters:** These characters indicate the read (`r`), write (`w`), and execute (`x`) permissions for other. This owner type consists of all other users on the system apart from the user and the group. When one of these characters is a hyphen (`-`) instead, that indicates that this permission is not granted for other.

Change file permissions

The organization determined that other shouldn't have write access to any of their files. To comply with this, I referred to the file permissions that I previously returned. I determined `project_k.txt` must have the write access removed for other.

The following code demonstrates how I used Linux commands to do this:

```
researcher2@5d738f0f927b:~/projects$ chmod o-w project_k.txt
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-rw--w--- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx--x-- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$
```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. The `chmod` command changes the permissions on files and directories.

Change file permissions on a hidden file

The following code demonstrates how I used Linux commands to change the permissions:

```

researcher2@3213bbc1d047:~/projects$ chmod u-w,g-w,g+r .project_x.txt
researcher2@3213bbc1d047:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec 20 15:36 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec 20 15:36 ..
-r--r----- 1 researcher2 research_team  46 Dec 20 15:36 .project_x.txt
drwx--x--- 2 researcher2 research_team 4096 Dec 20 15:36 drafts
-rw-rw-rw- 1 researcher2 research_team  46 Dec 20 15:36 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec 20 15:36 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec 20 15:36 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec 20 15:36 project_t.txt
researcher2@3213bbc1d047:~/projects$

```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. I know `.project_x.txt` is a hidden file because it starts with a period (`.`). In this example, I removed write permissions from the user and group, and added read permissions to the group. I removed write permissions from the user with `u-w`. Then, I removed write permissions from the group with `g-w`, and added read permissions to the group with `g+r`.

Change directory permissions

Only the `researcher2` user to have access to the `drafts` directory and its contents. This means that no one other than `researcher2` should have execute permissions.

The following code demonstrates how I used Linux commands to change the permissions:

```

researcher2@5d738f0f927b:~/projects$ chmod g-x drafts
researcher2@5d738f0f927b:~/projects$ ls -la
total 32
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 .
drwxr-xr-x 3 researcher2 research_team 4096 Dec  2 15:27 ..
-r--r----- 1 researcher2 research_team  46 Dec  2 15:27 .project_x.txt
drwx----- 2 researcher2 research_team 4096 Dec  2 15:27 drafts
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_k.txt
-rw-r----- 1 researcher2 research_team  46 Dec  2 15:27 project_m.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_r.txt
-rw-rw-r-- 1 researcher2 research_team  46 Dec  2 15:27 project_t.txt
researcher2@5d738f0f927b:~/projects$

```

The first two lines of the screenshot display the commands I entered, and the other lines display the output of the second command. I previously determined that the group had

execute permissions, so I used the `chmod` command to remove them. The `researcher2` user already had execute permissions, so they did not need to be added.

Summary

Changed file permissions for just who are allowed to read, write or execute. That way improving the security. The first step in this was using `ls -la` to check the permissions for the directory. This informed my decisions in the following steps. I then used the `chmod` command multiple times to change the permissions on files and directories.