

In [119...

%run

Import.ipynb

Introduction

This report uses logistic regression to determine the log odds relationship between the presence of government responses to covid-19 and the presence of cases of the virus.

Import dataset.

In [121...

df=Json('df1: government responses to covid19')

df.excel('Gov_Responses2Covid19_last.xlsx', 'Dataset')

df1=json_storage['df1: government responses to covid19']

df1

Out[121...

	country	geoid	iso	d	cases	deaths	school	school_local	domestic	domestic_local	...	wage	credit	taxc	taxd	export	rate	Rigidity_Public_Health	Economic_Measures	population_2019	continent
0	Aruba	AW	ABW	2020-01-01 00:00:00	0.0	0.0	0.0	0.0	NaN	NaN	...	0.0	0.0	0.0	0.0	0.0	0.0	NaN	0.000000	106310.0	America
1	Aruba	AW	ABW	2020-01-02 00:00:00	0.0	0.0	0.0	0.0	NaN	NaN	...	0.0	0.0	0.0	0.0	0.0	0.0	NaN	0.000000	106310.0	America
2	Aruba	AW	ABW	2020-01-03 00:00:00	0.0	0.0	0.0	0.0	NaN	NaN	...	0.0	0.0	0.0	0.0	0.0	0.0	NaN	0.000000	106310.0	America
3	Aruba	AW	ABW	2020-01-04 00:00:00	0.0	0.0	0.0	0.0	NaN	NaN	...	0.0	0.0	0.0	0.0	0.0	0.0	NaN	0.000000	106310.0	America
4	Aruba	AW	ABW	2020-01-05 00:00:00	0.0	0.0	0.0	0.0	NaN	NaN	...	0.0	0.0	0.0	0.0	0.0	0.0	NaN	0.000000	106310.0	America
...
62695	Hong Kong	HK	HKG	2020-09-29 00:00:00	NaN	NaN	1.0	0.0	0.0	0.0	...	1.0	0.0	0.0	1.0	1.0	1.0	0.461539	0.714286	NaN	NaN
62696	Hong Kong	HK	HKG	2020-09-30 00:00:00	NaN	NaN	1.0	0.0	0.0	0.0	...	1.0	0.0	0.0	1.0	1.0	1.0	0.461539	0.714286	NaN	NaN
62697	Macau	MO	MAC	2020-09-30 00:00:00	NaN	NaN	1.0	0.0	0.0	0.0	...	1.0	1.0	1.0	0.0	0.0	1.0	0.250000	0.714286	NaN	NaN
62698	Hong Kong	HK	HKG	2020-10-01 00:00:00	NaN	NaN	1.0	0.0	0.0	0.0	...	1.0	0.0	0.0	1.0	1.0	1.0	0.461539	0.714286	NaN	NaN
62699	Macau	MO	MAC	2020-10-01 00:00:00	NaN	NaN	1.0	0.0	0.0	0.0	...	1.0	1.0	1.0	0.0	0.0	1.0	0.250000	0.714286	NaN	NaN

62700 rows × 43 columns

Data Mining

In [123...

df1.info(verbose=True)

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 62700 entries, 0 to 62699
Data columns (total 43 columns):
#   Column                                Non-Null Count  Dtype
---  -
0   country                               62700 non-null  object
1   geoid                                 62425 non-null  object
2   iso                                   62700 non-null  object
3   d                                     62700 non-null  object
4   cases                                57750 non-null  float64
5   deaths                               57750 non-null  float64
6   school                               45758 non-null  float64
7   school_local                         45758 non-null  float64
8   domestic                             55275 non-null  float64
9   domestic_local                       55275 non-null  float64
10  travel                               55275 non-null  float64
11  travel_partial                       55275 non-null  float64
12  travel_dom                           55275 non-null  float64
13  travel_dom_partial                   55275 non-null  float64
14  curf                                 55275 non-null  float64
15  curf_partial                         55275 non-null  float64
16  mass                                 55275 non-null  float64
17  mass_partial                         55275 non-null  float64
18  elect                                14834 non-null  float64
19  elect_partial                       14834 non-null  float64
20  sport                                55275 non-null  float64
21  sport_partial                       55275 non-null  float64
22  rest                                 55275 non-null  float64
23  rest_local                           55275 non-null  float64
24  testing                              55275 non-null  float64
25  testing_narrow                       55275 non-null  float64
26  masks                                51459 non-null  float64
27  masks_partial                       51459 non-null  float64
28  surveillance                         55275 non-null  float64
29  surveillance_partial                 55275 non-null  float64
30  state                                55275 non-null  float64
31  state_partial                       55275 non-null  float64
32  cash                                 54450 non-null  float64
33  wage                                 54450 non-null  float64
34  credit                               54450 non-null  float64
35  taxc                                 54450 non-null  float64
36  taxd                                 54450 non-null  float64
37  export                               54450 non-null  float64
38  rate                                 54450 non-null  float64
39  Rigidity_Public_Health               55275 non-null  float64
40  Economic_Measures                    54450 non-null  float64
41  population_2019                      57750 non-null  float64
42  continent                             61875 non-null  object
dtypes: float64(38), object(5)
memory usage: 20.6+ MB
```

Data Cleaning

Cleans government responses to covid 19 dataframe by replacing undesired values with desired ones, and dropping undesired columns.

In [125...

df1=df1.replace(np.nan, 0)
df1=df1.drop('geoid', axis=1)
df1=df1.drop('iso', axis=1)
df1=df1.drop('country', axis=1)
df1=df1.drop('continent', axis=1)

```
df1=df1.drop('d', axis=1)
df1=df1.drop('deaths', axis=1)
df1=df1.drop('population_2019', axis=1)
df1=df1.drop('school_local', axis=1)
df1=df1.drop('domestic_local', axis=1)
df1=df1.drop('travel_partial', axis=1)
df1=df1.drop('travel_dom_partial', axis=1)
df1=df1.drop('curf_partial', axis=1)
df1=df1.drop('mass_partial', axis=1)
df1=df1.drop('elect_partial', axis=1)
df1=df1.drop('sport_partial', axis=1)
df1=df1.drop('rest_local', axis=1)
df1=df1.drop('testing_narrow', axis=1)
df1=df1.drop('masks_partial', axis=1)
df1=df1.drop('surveillance_partial', axis=1)
df1=df1.drop('state_partial', axis=1)
df1=df1.drop('Rigidity_Public_Health', axis=1)
df1=df1.drop('Economic_Measures', axis=1)
df1
```

Out[125...

	cases	school	domestic	travel	travel_dom	curf	mass	elect	sport	rest	...	masks	surveillance	state	cash	wage	credit	taxc	taxd	export	rate
0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
...
62695	0.0	1.0	0.0	1.0	0.0	0.0	1.0	1.0	1.0	0.0	...	1.0	0.0	0.0	1.0	1.0	0.0	0.0	1.0	1.0	1.0
62696	0.0	1.0	0.0	1.0	0.0	0.0	1.0	1.0	1.0	0.0	...	1.0	0.0	0.0	1.0	1.0	0.0	0.0	1.0	1.0	1.0
62697	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	1.0	1.0	...	0.0	0.0	0.0	1.0	1.0	1.0	1.0	0.0	0.0	1.0
62698	0.0	1.0	0.0	1.0	0.0	0.0	1.0	1.0	1.0	0.0	...	1.0	0.0	0.0	1.0	1.0	0.0	0.0	1.0	1.0	1.0
62699	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	1.0	1.0	...	0.0	0.0	0.0	1.0	1.0	1.0	1.0	0.0	0.0	1.0

62700 rows × 21 columns

The model will be determining whether cases of the virus were present. Makes all values where cases were above 0 into 1.

In [127...

```
df1['cases']=df1['cases'][df1['cases'] > 0] = 1
```

Data Exploration

There is no class imbalance.

In [128...

```
sns.countplot(y_train, palette='Set3')
plt.xticks(rotation=90)
```

Out[128...

```
(array([0, 1]), [Text(0, 0, '0.0'), Text(1, 0, '1.0')])
```



Government Regulation Features

The Governments' responses to COVID19 are the measures implemented by governments worldwide in response to the Coronavirus pandemic. There are two types of measures: public health measures and economic measures. .

The variables are :

- cases: binary variable equal to 1 if there were cases of SARS-CoV-2 and 0 otherwise;
- school: binary variable equal to 1 if schools were closed and 0 otherwise;
- domestic: binary variable equal to 1 if there was a domestic lockdown and 0 otherwise;
- travel: binary variable equal to 1 if travel restrictions were implemented and 0 otherwise;
- travel_dom: binary variable equal to 1 if travel restrictions within the country (e.g. inter-region travels) were implemented and 0 otherwise;
- curf: binary variable equal to 1 if a curfew was implemented and 0 otherwise;
- mass: binary variable equal to 1 if bans on mass gatherings were implemented and 0 otherwise;
- elect: binary variable equal to 1 if some elections were postponed and 0 otherwise;
- sport: binary variable equal to 1 if bans on sporting and large events were implemented and 0 otherwise;
- rest: binary variable equal to 1 if restaurants were closed and 0 otherwise;
- testing: binary variable equal to 1 if there was a public testing policy and 0 otherwise;
- surveillance: binary variable equal to 1 if mobile app or bracelet surveillance was implemented and 0 otherwise;
- masks binary variable equal to 1 if the obligationsto wear masks in public spaces was implemented and 0 otherwise;
- state: binary variable equal to 1 if the state of emergency is declared and 0 otherwise;
- cash: binary variable equal to 1 if cash transfers are implemented and 0 otherwise;
- wage: binary variable equal to 1 if wage support is implemented and 0 otherwise;
- credit: binary variable equal to 1 if credit schemes are implemented and 0 otherwise;
- taxc: binary variable equal to 1 if tax credits are implemented and 0 otherwise;
- taxd: binary variable equal to 1 if tax delays are implemented and 0 otherwise;
- export: binary variable equal to 1 if supports to importers or exporters are implemented and 0 otherwise;
- rate: binary variable equal to 1 if the Central Bank lowered the interest rates and 0 otherwise;

Feature Engineering

Makes the dependent variable y be the cases and the independent variables X be the government regulations. Then, splits data, 80/20, into a train test split.

```
In [129... y=df1[['cases']]
X=df1.drop(['cases'], axis=1)

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```


Binary logistic regression assumptions are a binary dependent variable, independent observations, linear continuous variables, no strongly influential outliers, independent variables with no multicollinearity, and a large sample size. The dependent variable is zero or one, the observations are not repeated measurements made on each experimental unit or matched -- when pairs of data are matched based on similar features, there are no continuous variables, the data are zeros and ones so there are no outliers, and the data has 50160 rows.

Check for multicollinearity.

```
In [25]: x_corr=X_train.corr(method='pearson')
plt.figure(figsize=[20, 20])
sns.heatmap(x_corr)
```

```
Out[25]: <AxesSubplot:>
```





```
In [26]: correlation=[]
for columnName1, columnData1 in X_train.iteritems():
    for columnName2, columnData2 in X_train.iteritems():
        if abs(columnData1.corr(columnData2)) > .7:
            correlation.append((columnName1, columnName2, abs(columnData1.corr(columnData2))))
correlation
```

```
Out[26]: [('school', 'school', 1.0),
 ('domestic', 'domestic', 0.9999999999999999),
 ('travel', 'travel', 1.0),
 ('travel_dom', 'travel_dom', 0.9999999999999999),
 ('curf', 'curf', 1.0),
 ('mass', 'mass', 0.9999999999999999),
 ('mass', 'sport', 0.7186910509080194),
 ('elect', 'elect', 1.0),
 ('sport', 'mass', 0.7186910509080194),
 ('sport', 'sport', 1.0),
 ('rest', 'rest', 1.0),
 ('testing', 'testing', 1.0),
 ('masks', 'masks', 1.0),
 ('surveillance', 'surveillance', 1.0),
 ('state', 'state', 1.0),
 ('cash', 'cash', 1.0),
 ('wage', 'wage', 1.0),
 ('credit', 'credit', 1.0),
 ('taxc', 'taxc', 1.0),
 ('taxd', 'taxd', 1.0),
 ('export', 'export', 1.0),
 ('rate', 'rate', 1.0)]
```

Remove multicollinear feature from X.

```
In [ ]: X_train=X_train.drop('sport', axis=1)
        X_test=X_test.drop('sport', axis=1)
```

Logistic Regression Model

The Logistic function, logit(P), starts with setting the log odds equal to the parameters. Exponentiate both sides of the equation and cross multiply 1-P to get the logistic function.

$$\ln(\frac{P}{1-P}) = \alpha + \beta x$$

$$\frac{P}{1-P} = e^{\alpha+\beta x}$$

$$P = \frac{e^{\alpha+\beta x}}{1 + e^{\alpha+\beta x}}$$

The probability of class 1 is the logistic function and of class 0 is one minus the logistic function.

$$P(Class = 1|X = x) = \frac{e^{\alpha+\beta x}}{1 + e^{\alpha+\beta x}}$$


$$P(Class = 0|X = x) = 1 - \frac{e^{\alpha+\beta x}}{1 + e^{\alpha+\beta x}}$$

Take the inverse of P to get the desired sigmoid function.

$$\sigma(x) = P^{-1} = \frac{1}{1 + e^{-(\alpha+\beta x)}}$$

```
In [27]: Image(filename='sigmoid_function.png')
```

Out[27]:




The predicted labels are binary so each label is a Bernoulli random variable from a Bernoulli probability mass function.

$$P(x;p) = \begin{cases} p & : x = 1 \\ 1 - p & : x = 0 \end{cases}$$

```
In [28]: Image(filename='bernoulli(p) color.png')
```

Out[28]:



MLE, maximum likelihood estimation, finds the parameters, θ , that maximize the log likelihood probability, a model comparative metric, that a value belongs to a class.

$$MLE = \prod_i^N P(Y = y_i | X = x_i)$$

$$\operatorname{argmax} LL(\theta) = \sum_i^N y_i * \log(\sigma(\theta^T * x_i)) + (1 - y_i) * \log(1 - \sigma(\theta^T * x_i))$$

Solve for θ that maximizes the the log likelihood by solving for the partial derivative of the log likelihood with respect to θ and gradiently accend toward the maximum of the LL function.

$$\nabla \frac{\partial LL(\theta)}{\partial \theta_j} = \sum_i^N [y_i - \theta^T * x_i] x_{ij}$$

Iteratively accend toward maximum LL with an η stepsize.

$$\theta_j^{new} = \theta_j^{previous} + \eta * \nabla \frac{\partial LL(\theta^{previous})}{\partial \theta_j^{previous}}$$

The McFadden R squared, a model comparative metric, is 1 minus the log likelihood of the full model, which is like the sum of squared residuals, devided by the log likelihood of the intercept model, which is like the total sum of squares.

$$R^2_{McF} = 1 - \frac{\ln L(M_{full})}{\ln L(M_{int})}$$

Conduct logistic regression model from statsmodels for regression results.

In [29]:

log_reg = sm.Logit(y_train, X_train).fit()
log_reg.summary()

Optimization terminated successfully.
Current function value: 0.572517
Iterations 6

Out[29]:

Logit Regression Results

Dep. Variable:	cases	No. Observations:	50160
Model:	Logit	Df Residuals:	50140
Method:	MLE	Df Model:	19
Date:	Tue, 23 Mar 2021	Pseudo R-squ.:	0.1738
Time:	17:29:15	Log-Likelihood:	-28717.
converged:	True	LL-Null:	-34758.
Covariance Type:	nonrobust	LLR p-value:	0.000

	coef	std err	z	P> z	[0.025	0.975]
school	-0.2966	0.025	-11.709	0.000	-0.346	-0.247
domestic	0.5533	0.036	15.454	0.000	0.483	0.623
travel	-0.5380	0.032	-16.877	0.000	-0.601	-0.476
travel_dom	0.1094	0.033	3.285	0.001	0.044	0.175
curf	0.1600	0.032	4.994	0.000	0.097	0.223
mass	0.3283	0.035	9.252	0.000	0.259	0.398
elect	0.5081	0.033	15.629	0.000	0.444	0.572
sport	0.1457	0.034	4.280	0.000	0.079	0.212
rest	0.4066	0.031	13.201	0.000	0.346	0.467

testing	-0.0520	0.030	-1.718	0.086	-0.111	0.007
masks	0.7603	0.030	24.965	0.000	0.701	0.820
surveillance	0.3923	0.041	9.499	0.000	0.311	0.473
state	-0.1509	0.028	-5.367	0.000	-0.206	-0.096
cash	0.7565	0.033	23.247	0.000	0.693	0.820
wage	-0.0775	0.032	-2.410	0.016	-0.141	-0.014
credit	0.0900	0.032	2.796	0.005	0.027	0.153
taxc	-0.3755	0.029	-12.792	0.000	-0.433	-0.318
taxd	0.4425	0.031	14.310	0.000	0.382	0.503
export	0.1836	0.036	5.131	0.000	0.113	0.254
rate	-0.0836	0.030	-2.809	0.005	-0.142	-0.025

Remove statistically insignificant feature.

In [31]:

X_train=X_train.drop('testing', axis=1)

In [32]:

log_reg = sm.Logit(y_train, X_train)
model=log_reg.fit()
model.summary()

Optimization terminated successfully.
Current function value: 0.572547
Iterations 6

Out[32]:

Logit Regression Results			
Dep. Variable:	cases	No. Observations:	50160
Model:	Logit	Df Residuals:	50141
Method:	MLE	Df Model:	18
Date:	Tue, 23 Mar 2021	Pseudo R-squ.:	0.1737
Time:	17:30:49	Log-Likelihood:	-28719.
converged:	True	LL-Null:	-34758.
Covariance Type:	nonrobust	LLR p-value:	0.000

	coef	std err	z	P> z	[0.025	0.975]
school	-0.2940	0.025	-11.625	0.000	-0.344	-0.244
domestic	0.5552	0.036	15.518	0.000	0.485	0.625
travel	-0.5417	0.032	-17.017	0.000	-0.604	-0.479
travel_dom	0.1073	0.033	3.226	0.001	0.042	0.173
curf	0.1619	0.032	5.057	0.000	0.099	0.225
mass	0.3236	0.035	9.146	0.000	0.254	0.393
elect	0.5072	0.032	15.606	0.000	0.443	0.571
sport	0.1403	0.034	4.137	0.000	0.074	0.207
rest	0.4030	0.031	13.109	0.000	0.343	0.463

masks	0.7515	0.030	25.031	0.000	0.693	0.810
surveillance	0.3802	0.041	9.341	0.000	0.300	0.460
state	-0.1474	0.028	-5.255	0.000	-0.202	-0.092
cash	0.7581	0.033	23.305	0.000	0.694	0.822
wage	-0.0819	0.032	-2.555	0.011	-0.145	-0.019
credit	0.0879	0.032	2.733	0.006	0.025	0.151
taxc	-0.3738	0.029	-12.740	0.000	-0.431	-0.316
taxd	0.4360	0.031	14.210	0.000	0.376	0.496
export	0.1784	0.036	5.006	0.000	0.109	0.248
rate	-0.0819	0.030	-2.756	0.006	-0.140	-0.024


The presence of the independent variables increases or decreases the log odds of the presence of the dependent variable based on the sign of the parameter coefficients. The government regulations of school closures, travel restrictions, state of emergency declarations, wage support, tax credits, and interest rate lowering decreased the log odds of the presence of virus cases.

Goodness-of-fit tests determine whether the predicted probabilities deviate from the observed probabilities. Deviance is the difference of likelihoods between the fitted model and the residuals. 0 predicted residuals are negative and 1 predicted residuals are positive. $\hat{\mu}_i$ are the fitted values and y_i are the observed values.

$$DevianceResiduals = \sum_i^N \sqrt{2[y_i * \log(y_i/\hat{\mu}_i) + (n_i - y_i) * \log(n_i - y_i/n_i - \hat{\mu}_i)]}$$

In [33]:

```
fig, ax = plt.subplots(1, figsize=(10, 8))
sns.regplot(model.fittedvalues, model.resid_dev, ax= ax,
            color="black", scatter_kws={"s": 5},
            line_kws={"color": "b", "alpha":1, "lw":2}, lowess=True)
plt.title("Deviance Residuals \n against Fitted Values")
plt.xlabel("Predictor Values")
plt.ylabel("Deviance Residuals")
plt.show()
```




$$PearsonResiduals = \sum_i^N \frac{y_i - \hat{\mu}_i}{\sqrt{\hat{\mu}_i(n_i - \hat{\mu}_i)/n_i}}$$

```
In [34]: fig, ax = plt.subplots(1, figsize=(10, 8))
sns.regplot(model.fittedvalues, model.resid_pearson, ax= ax,
            color="black", scatter_kws={"s": 5},
            line_kws={"color": "r", "alpha": 1, "lw": 2}, lowess=True)

plt.title("Pearson Residuals \n against Fitted Values")
plt.xlabel("Predictor Values")
plt.ylabel("Pearson Residuals")
```

```
Out[34]: Text(0, 0.5, 'Pearson Residuals')
```



Pearson's chi-squared test is a goodness-of-fit test that determines whether categorical observed values, O , are consistent with their corresponding expected values, E .

$$\chi^2 = \sum_i^N \frac{(O_i - E_i)^2}{E_i}$$

$$E(x) = \sum_i^N x_i * p(x_i)$$

```
In [43]: stat, p = chisquare(model.resid_pearson)#Null Hypothesis: no significant difference between the observed and the expected values
print('Stat:', stat, 'P-value:', p)
alpha=.05
if p>alpha:
    print('Don\'t reject null of no significant difference between the observed and the expected values.')
else:
    print('Reject null of no significant difference between the observed and the expected values.')
```

Stat: -145098.9073862549 P-value: 1.0


Don't reject null of no significant difference between the observed and the expected values.

Conduct logistic regression model from sklearn for classification results.


```
In [44]: logistic_regression = LogisticRegression()
logistic_regression.fit(X_train, y_train)
y_hat_train = logistic_regression.predict(X_train)
```

```
In [45]: Image(filename='lr.png')
```

Out[45]:



For the train set, the model has 20765 true positives, 20242 true negatives, 4834 false positives, and 4319 false negatives.



$$precision = \frac{TP}{TP + FP}$$

$$recall = \frac{TP}{TP + FN}$$

$$f1 = \frac{2 * precision * recall}{precision + recall}$$


$$accuracy = \frac{TP + TN}{TP + FN + TN + FP}$$

$$specificity = \frac{TN}{TN + FP}$$

In [49]:

Metrics(y_train, y_hat_train)

Precision Score: 0.8072260328601053
 Recall Score: 0.8241521110703962
 F1 Score: 0.8156012651852449
 Accuracy Score: 0.817523923444976
 Specificity Score: 0.8278185297400733



$$TruePositiveRate = \frac{TP}{TP + FN}$$

$$FalsePositiveRate = \frac{FP}{FP + TN}$$


$$ReceiverOperatingCharacteristic = \frac{TPR}{FPR}$$

$$AreaUnderCurve = \int_a^b TPR(FPR^{-1}(x))dx$$

In [60]:

roc(y_train, y_hat_train)

AUC: 0.8176583048418117




The log loss, a cost function, is the cross entropy between the distribution of the true labels and the predictions. Entropy measures unpredictability and cross entropy incorporates the entropy of the predicted distribution with of the true distribution. The log loss multiplies -1 by the log likelihood to identify that lower scores are better, devides the result by the sample size, and reults in the mean loss. As the loss approaches 0, the probability of correct classification increases.

$$NegativeLogLoss = -\frac{1}{N} \sum_i^N y_i * \log(\sigma(\theta^T * x_i)) + (1 - y_i) * \log(1 - \sigma(\theta^T * x_i))$$

```
In [51]: Image(filename='log_loss.png')
```

```
Out[51]:
```



```
In [52]: cv_score = cross_val_score(logistic_regression, X_train, y_train, cv=5, scoring='neg_log_loss')
mean_cv_score = np.mean(cv_score)
print('Mean Cross Validation of Cost Function')
print(f"Negative Log Loss Score: {mean_cv_score}")
```

Mean Cross Validation of Cost Function
Negative Log Loss Score: -0.42917685692963775


Test model on test set.

```
In [53]: logistic_regression.fit(X_test, y_test)

y_hat_test = logistic_regression.predict(X_test)
```


For the test set, the model has 5233 true positives, 5043 true negatives, 1201 false positives, and 1063 false negatives.

```
In [62]: con_mat(y_test, y_hat_test)
```




```
In [56]: Metrics(y_test, y_hat_test)
```

Precision Score: 0.8076553491351698
Recall Score: 0.8259089420242385
F1 Score: 0.8166801619433198
Accuracy Score: 0.8194577352472089
Specificity Score: 0.8311626429479034



```
In [61]: roc(y_test,y_hat_test)
```

AUC: 0.8196221738408417



Conclusion

The logit model suggests that the government regulations of school closures, travel restrictions, state of emergency declarations, wage support, tax credits, and interest rate lowering decreased the log odds of the presence of virus cases. Government regulations such as disallowing public gatherings and mandating wearing masks did not decrease the log odds of the presence of virus cases. The virus travels in sneezed or coughed droplets of mucus or saliva, is airborne for a few moments, and then lands on a surface. Instead of wearing masks and preventing gatherings, carrying a handkerchiefs in which people could sneeze or cough and sanitizing areas where people gather would be sufficient in preventing the spread of SARS-CoV-2.

In []: