

1 Summary

This is a note for [1]. The implementation code for this paper can be found at ¹.

The important components are as follows:

1. RNN language model
2. Morphological priors
3. Latent word embedding b_w .
4. Morpheme embedding u_m .
5. Variational distribution $Q(b)$

2 Latent Word Embedding and Morpheme Embedding

Each morpheme is segmented in unsupervised fashion according to Morfessor. For example, $u_{-ism} = (-0.24, 5, -111)$.

When inferring $P(x)$, we will have to infer $P(b)$ too since $P(b)$ appears in the lower variational bound.

$$b_{w,i} \sim \text{Bernoulli}(\text{sigmoid}(\sum_{m \in M_w} u_{m,i}))$$

i.e. for outcomes or the range of a probabilistic variable $b_{w,i}$ is either 0 or 1,

$$P(b_{w,i}) = \text{sigmoid}(\sum_{m \in M_w} u_{m,i})^{b_{w,i}} (1 - \text{sigmoid}(\sum_{m \in M_w} u_{m,i}))^{1-b_{w,i}}$$

So let's look into an example. Let $M = \text{perfection}, -ism$ $u_{\text{perfection}} = (0, -1.1, 1)$

$u_{-ism} = (2, 5.1, 3)$

When $w = \text{perfectionism}$, then

$$b_{w,0} \sim \text{Bernoulli}(\text{sigmoid}(0 + 2)) \approx 0.88$$

$$b_{w,1} \sim \text{Bernoulli}(\text{sigmoid}(-1.1 + 5.1)) \approx 0.98$$

$$b_{w,2} \sim \text{Bernoulli}(\text{sigmoid}(1 + 3)) \approx 0.98$$

$$\text{So } P(b_w = (1, 1, 1)) = 0.88 * 0.98 * 0.98 \approx 0.84.$$

3 Hidden state

The hidden state at time h_t (vector) is

$$h_t = \text{sigmoid}(\Theta h_{t-1} + b_{x_t})$$

where x_t is the word corresponding to the position t , and Θ is the parameter for the recurrence function (recurrent weights²).

¹<https://github.com/rguthrie3/MorphologicalPriorsForWordEmbeddings>

²http://peterroelants.github.io/posts/rnn_implementation_part01/

4 What is going on inside $D_{KL}(Q(b)||P(b))$?

$$\begin{aligned} D_{KL}(q(b_{w,i})||P(b_{w,i})) &= q(b_{w,i}) \log\left(\frac{q(b_{w,i})}{P(b_{w,i})}\right) \\ &= q(b_{w,i})(\log(q(b_{w,i})) - \log(P(b_{w,i}))) \\ &= q(b_{w,i})(\log(q(b_{w,i})) - b_{w,i} \log(\text{sigmoid}(\sum_{m \in M_w} u_{m,i})) - (1 - b_{w,i}) \log(1 - \text{sigmoid}(\sum_{m \in M_w} u_{m,i}))) \\ q(b_{w,i}; \gamma_{w,i}) &= \gamma_{w,i}^{b_{w,i}} (1 - \gamma_{w,i})^{1-b_{w,i}} \\ \log(q(b_{w,i}; \gamma_{w,i})) &= b_{w,i} \gamma_{w,i} + (1 - b_{w,i})(1 - \gamma_{w,i}) \end{aligned}$$

References

- [1] Parminder Bhatia, Robert Guthrie, and Jacob Eisenstein. Morphological priors for probabilistic neural word embeddings. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 490–500, Austin, Texas, November 2016. Association for Computational Linguistics.