

ORIGINAL ARTICLE OPEN ACCESS

Agentic Autoresearch for CT Reconstruction

Andreas Maier¹ | Lukas Kachelrieß^{1,2} | Siming Bayer¹ | Yixing Huang³ | Yan Xia² | Amber Simpson⁴ | Moritz Zaiss²

¹Pattern Recognition Lab, Friedrich-Alexander-Universität Erlangen-Nürnberg (FAU), Erlangen, Germany | ²Universitätsklinikum Erlangen (UKER), Erlangen, Germany | ³Peking University, Beijing, China | ⁴University of Alberta, Edmonton, Canada

Correspondence: Andreas Maier (andreas.maier@fau.de)

Received: 9 July 2026 | **Revised:** 9 July 2026 | **Accepted:** 9 July 2026

Keywords: CT reconstruction | sparse-view | low-dose | known operators | deep learning | benchmarking | large language model agent | noise robustness

ABSTRACT

Background. Deep learning has produced a large and diverse body of CT reconstruction methods. Fair comparison across them remains labor-intensive and largely manual. Moreover, many benchmarks rely on idealized data. **Purpose.** We test two things. First, can a large language model (LLM) agent do the labor of reconstruction research — implement, tune, and benchmark many methods on its own? Second, does a ranking measured on ideal data predict how methods behave under realistic noise? **Methods.** We built an agentic loop. The agent edits a solver, runs a short job on a compute cluster, reads one frozen metric, and revises. The metric is a calibrated headroom score, $hr = \max(0, 1 - \text{RMSE}/\text{RMSE}_{\text{FBP}})$, computed inside the field of view. We grounded every method in the same differentiable fan-beam projector. We benchmarked 26 reconstruction methods on two problems: Mayo low-dose CT (noise-limited) and a 128-view sparse-view breast task from the noiseless DL-Sparse-View Challenge. We selected each method's best iteration on a held-out test set and report the per-case mean $\pm$ standard deviation. To investigate the effect of noise in the noiseless breast CT challenge, we then re-evaluated every trained model on the same breast test cases with mild Poisson noise added to the inputs ($I_0 = 10^5$ photons), *without any retraining*. **Results.** Honest benchmarking gives a small tier of statistically indistinguishable top methods, not one winner. From the 26 methods the agent recombined a compact solver of ~ 195 parameters that reaches the top accuracy tier at $\sim 2\%$ of its parameters. The best compact architecture is problem-dependent: a denoiser for noisy Mayo, a filtered data-consistency and learned primal-dual unroll for sparse-view breast. Mild input noise nearly inverts the breast ranking. The noiseless champion (supervised image denoiser, $hr = 0.89$) collapses to last ($hr = 0.00$). A learned primal-dual method rises from mid-pack to champion ($hr = 0.72 \rightarrow 0.93$). Physics-regularized and hand-crafted-smoothing methods rise; supervised image-domain denoisers collapse. **Conclusions.** An LLM agent can implement, tune, and benchmark reconstruction methods at scale under a fixed metric and compute budget. It did not invent new methods, and it required some human guidance to develop highly efficient parameter methods. More importantly, a leaderboard measured on ideal data does not predict robustness — it can invert under a small, realistic perturbation. We argue that benchmarks must include noise and other perturbations by default, and that agentic autoresearch makes such multi-condition benchmarking ready for routine use.

1 | Introduction

Deep learning has changed CT reconstruction. A decade of work has produced many learned reconstructors. Examples are unrolled iterative networks, learned primal-dual schemes, variational networks¹, image-domain and dual-domain denoisers, diffusion priors (generative models, unrelated to physical diffusion),

and per-scene implicit representations.^{1,2,3,4,5} Each promises a good image from fewer views or a lower dose than filtered back-projection (FBP). The best of them deliver. At first glance the research program looks simple: pick the strongest network, train it, reconstruct.

Yet, a purely data-driven reconstructor learns a map that is not tied to the physics. Such a map is free to *hallucinate*.⁶ It can add anatomy that the measurements do not support.⁷ This is not a small tuning issue. It is a structural risk. The field's durable

¹ A variational network (Hammernik et al.) is an unrolled network whose learned regularizer is a filter-bank “field of experts”; we use it here as the accuracy yardstick.

answer is to put the physics back in. We embed the **known operator** — the differentiable forward and back projector — into the learned pipeline.^{8,9} In fact, this trade is quantified. Constraining a network with an exact operator provably cannot raise, and usually lowers, the maximum error bound. In practice it also lowers the number of parameters and the amount of training data needed.⁸ A recent deep risk estimator establishes this benefit on theoretical grounds.¹⁰

There is a second problem, and it sits one level up. The body of methods is itself the product of slow, largely manual work. The reconstruction problem can be framed as a learned inverse problem,⁵ but to compare or improve any method, a researcher must implement a solver, wire it to the data and geometry, launch a job, read a metric, form a hypothesis, change one thing, and repeat. This takes days per method. Recent “autoresearch” ideas imagine automating this loop — an automated research cycle in which the software itself proposes a change, runs the experiment, reads the result, and iterates.¹¹ Now, large language model (LLM) agents offer game-changing capacities. A large language model is a neural network trained to predict text. An *agent* wraps such a model in a loop so that it can act — read files, write code, and launch jobs — not just answer questions; a loop driven this way we call *agentic*. General-purpose coding agents already resolve real software-engineering tasks,^{12,13,14} and physics-informed agentic development has begun in adjacent imaging fields.¹⁵ *Can an LLM agent do reconstruction research?* Not just tune one number, but implement an unfamiliar method, diagnose why a reconstruction fails, edit its own solver code, and benchmark the result fairly — if we ground it in the same two things that would also guide a human: a differentiable projector and a fair, frozen metric.

We built such a loop and let an agent run it. With it, we benchmarked 26 methods across two CT problems. One is noise-limited (Mayo low-dose¹⁶); the other is incompleteness-limited (128-view sparse-view breast, from the noiseless DL-Sparse-View Challenge¹). We then asked a second question that the ideal-data benchmark cannot answer on its own: does the ranking survive a little noise? To answer it, we added mild Poisson noise to the test inputs and re-scored every trained model without retraining.

This paper makes five contributions. (i) An agentic CT-reconstruction loop grounded in a differentiable projector and a frozen calibrated metric, with full provenance. (ii) An autonomous implementation and fair benchmark of 26 methods across two regimes. (iii) An evidence-derived compact solver, competitive with the top tier at ~1–2 % of its parameters, whose optimal form is problem-dependent. (iv) A robustness result — ideal-data rank does not predict, and can invert under, noise — and the practical lesson it carries for how we build benchmarks. (v) We release all 26 methods and the agentic loop as open source (<https://github.com/akmaier/Agent4CT>).

2 | Materials and Methods

2.1 | The agentic loop

The agent works in a fixed cycle. First it reads the previous result and names the failure. It then changes one thing — a hyperparameter, or the solver code itself — and states a hypothesis. A single short cluster job runs under a fixed compute budget. The

agent reads the frozen metric and accepts or discards the change. The cycle then repeats.

Every run is grounded in the same *differentiable* fan-beam projector (PYRO-NN¹⁷) — a forward/back-projector built so that gradients flow through it, so it can sit inside a trainable network and be optimized by back-propagation. Each run also writes an immutable record: the configuration, the reconstruction, the metric, and a comparison figure. We enforced a fixed wall-clock budget per iteration (20 min on breast; matched on Mayo) so that all methods are compared under equal compute. A human coordinator supervised the loop: setting targets, redirecting across problems, and auditing for padding and provenance gaps (Section 4). The loop is sketched in Figure 1.

2.2 | A single framework for 26 methods

We describe the forward model first. For the reconstruction, the scanner is assumed as a linear operator. The sinogram is the set of line integrals of the image:

$$\mathbf{g} = \mathbf{A} \mathbf{x} + \boldsymbol{\varepsilon}. \quad (1)$$

Here $\mathbf{x}$ is the image, $\mathbf{A}$ the discrete fan-beam projector, $\mathbf{g}$ the measured projections, and $\boldsymbol{\varepsilon}$ the noise. For the noiseless Sidky breast data $\boldsymbol{\varepsilon} = \mathbf{0}$. Reconstruction means recovering $\mathbf{x}$ from $\mathbf{g}$. With 128 views, $\mathbf{A}$ is under-determined.

Almost every method is one instance of the same regularized inversion. We trade fit to the measurements against a prior:

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \frac{1}{2} \|\mathbf{A} \mathbf{x} - \mathbf{g}\|_2^2 + \lambda \mathcal{R}(\mathbf{x}). \quad (2)$$

A method is fixed by two choices. The first is the **data-consistency operator** $\mathbf{D}$, which maps the measurement residual back to image space and so pulls the image toward agreement with the sinogram. The second is the **prior** $\mathcal{R}$ (also called the regularizer): it encodes what a plausible image looks like and sets the fit-versus-smoothness trade-off. Many solvers approximate Eq. (2) by an *unrolled* proximal-gradient scheme of K steps. Unrolling fixes the iteration to K steps and makes each step a trainable network layer, so the whole fixed-length scheme is trained end-to-end:

$$\mathbf{x}_{k+1} = \mathbf{x}_k - \alpha_k \mathbf{D}(\mathbf{A} \mathbf{x}_k - \mathbf{g}) + \mathcal{R}_{\theta}(\mathbf{x}_k). \quad (3)$$

Each step is a proximal-gradient update: a gradient step toward data fit through $\mathbf{D}$, then a “proximal” step — the learned prior $\mathcal{R}_{\theta}$ — that cleans the image. The form of $\mathbf{D}$ matters. Here, the raw adjoint $\mathbf{D} = \mathbf{A}^T$ back-projects the residual and re-injects sparse-view streaks, whereas the filtered map $\mathbf{D} = \text{FBP}(\cdot)$ (a ramp/Hann-filtered back-projection) does not. This distinction is the key lever on the sparse-view problem.

Some methods add a learned dual in the measurement domain. This is the learned primal-dual (LPD) block.² It learns updates in both the image domain (the *primal*) and the measurement/sinogram domain (the *dual*). A sinogram-space memory $\mathbf{h}$ and the image $\mathbf{x}$ update together:

$$\mathbf{h}_{k+1} = \Gamma_{\phi}(\mathbf{h}_k, \mathbf{A} \mathbf{x}_k - \mathbf{g}), \quad \mathbf{x}_{k+1} = \Lambda_{\theta}(\mathbf{x}_k, \mathbf{D}(\mathbf{h}_{k+1})). \quad (4)$$

TABLE 1 | Solver taxonomy (condensed). Each family is placed on Axis A (physics engagement, i.e. how the operator **A** is used at inference) and Axis B (prior source $\mathcal{R}$), with a source citation per family. The full per-solver configuration and parameter counts are in Supplement S1.

Family	Axis A	Axis B	Ref.
Classical iterative (TV, PWLS-TV)	in-loop	hand-crafted	19,20
Image-domain denoiser (bilateral, U-Net)	none	hand-cr. / sup.	21,22
Unrolled learned-iterative (ITNet, U-Swin)	in-loop	supervised	4,23,24,25,26
Variational network (Hammernik)	in-loop	supervised	27,3
Learned primal-dual (LPD)	in-loop	supervised	2
Dual-domain (sup., bilateral, N2I)	single / in-loop	sup. / self-sup.	28,29
Generative prior (fastdiff $\times 4$)	in-loop	generative	30,31,32,33
Per-scene implicit (NAF, R^2 -Gaussian)	per-scene	implicit	34,35,36
Foundation zero-shot (RAM)	single	foundation	18
Band decomposition (Wu-2015)	in-loop	hand-cr. / sup.	20
Recombination (ours)	in-loop	hybrid	—

The convolutions $\Gamma_\phi, \Lambda_\theta$ are small and weight-tied. We zero-initialize their final layer, so the block is the identity at the start and cannot regress.

Table 1 places all 26 methods on two axes. Axis A is physics engagement: how much **A** is used at inference (none, a single data-consistency step, an in-loop unrolled scheme, or a full per-scene fit). Axis B is the prior source, and its categories are worth naming plainly. *Hand-crafted* priors (total variation, bilateral) encode smoothness by hand. *Supervised* priors are trained on paired examples with a known answer (low-dose input, full-dose truth). *Self-supervised* priors train without a clean reference, using structure in the data itself; Noise2Inverse (N2I), for example, splits the measured projections into subsets so one subset’s reconstruction predicts another’s. *Generative* priors are diffusion models — networks that make realistic images by reversing a gradual noising process — used to “imagine” plausible detail. *Implicit/per-scene* methods fit a small network to each single scan that returns the attenuation at any queried coordinate, rather than storing a pixel grid; neural fields and Gaussian splatting (which models the volume as many small 3-D Gaussian blobs) are examples. A *foundation model* is a large network pre-trained once on generic data and applied here with no task-specific training (“zero-shot”); we include the Reconstruct Anything Model.¹⁸ This table also names the agent’s job in the compact study: re-select the pair $(\mathbf{D}, \mathcal{R})$. Full per-solver configurations are in Supplement S1.

Search protocol. Each of the 25 established methods was tuned by 20 autoresearch iterations of the loop in Section 2.1. The 26th method — our compact solver — was searched for 40 iterations, with the explicit aim of an ultra-low-parameter recombination of the pair $(\mathbf{D}, \mathcal{R})$. During its first 20 iterations the agent worked alone and was free to recombine any component of the other 25 solvers. During the second 20, a human operator added mild suggestions about directions not yet tried. This was the only stage where the human shaped the search beyond setting targets and auditing.

2.3 | Datasets and geometry

Mayo low-dose CT. Real helical low-dose data from the 2016 AAPM Low-Dose CT Grand Challenge.¹⁶ Rebinning helical to fan-beam via single-slice rebinning³⁷ allows direct use of the fan-beam projector. We built and validated this pipeline, and use a fixed train/val/test split (Supplement S2). This is one of a family of AAPM reconstruction grand challenges spanning spectral, truth-based, and metal-artifact tasks.^{38,39,40}

Breast CT Challenge. 128-view 2-D fan-beam sparse-view data of synthetic breast phantoms.¹ This data is **noiseless by design**. The challenge asks whether deep learning can solve the sparse-view inverse problem, so its RMSE floor is exactly zero. We re-partitioned the public 4000-case train pool into train (3600), validation (200), and test (200), with a fixed seed and disjoint cases. To confirm the split, we verified disjointness by image hashing: no test image appears in train or validation (Supplement S3).

2.4 | The calibrated-headroom metric

We score how far a method closes the gap between the low-dose FBP and the truth. Let $\mathcal{C}$ be a two-point intensity calibration and **M** a field-of-view mask. The headroom is

$$\text{hr} = \max\left(0, 1 - \frac{\text{RMSE}(\mathbf{M} \odot \mathcal{C} \hat{\mathbf{x}}, \mathbf{M} \odot \mathbf{x})}{\text{RMSE}(\mathbf{M} \odot \mathbf{x}_{\text{FBP}}, \mathbf{M} \odot \mathbf{x})}\right). \quad (5)$$

An hr of 0 means no better than FBP; an hr near 1 means near-perfect. We select each method’s best iteration on the held-out test set, then report the per-case mean $\pm$ standard deviation. SSIM and PSNR use a batch-wide data range so that they are comparable across cases.

2.5 | The noise-robustness experiment

We ask whether the noiseless ranking survives a little input noise. For each method we take its noiseless best iteration. We then re-evaluate it on the **same** 200 breast test cases, but with photon noise added to the sinograms. For a line integral p and incident photon count I_0 ,

$$N \sim \text{Poisson}(I_0 e^{-p}), \quad \hat{p} = -\log(\max(N, 1)/I_0). \quad (6)$$

We use $I_0 = 10^5$ photons. This is a rather high dose. The noise is mild — about 1–2 % at the thickest ray. We apply it to the test inputs only. Note that the ground truth stays clean. Supervised solvers **load their noiseless-trained weights and no additional training is applied**. Per-scene and classical solvers re-fit on the noisy input, which is their normal inference. The FBP baseline in Eq. (5) is recomputed from the same noisy data, so hr measures improvement over the noisy FBP. This is exactly the realistic model $\mathbf{Ax} + \varepsilon$ that the noiseless challenge does not study.

2.6 | Statistics

We begin with Mayo. There the five held-out patients give $n = 5$, so the paired t -test has low power; we therefore report both the 5 % and 1 % levels. For Breast CT, the 200 test cases are shared by all methods, so comparisons are paired. With $n = 200$ the paired t -test is very high-powered: tiny mean gaps reach $p < 0.01$. Hence, we report **effect size** — how large a difference is, independent of sample size — not just p . We use Cohen’s $d_z = \bar{d}/s_d$, the mean of the paired differences over their standard deviation, and lead with d_z and the raw difference. The contrast between $n = 5$ and $n = 200$ is discussed in Section 4.

3 | Results

3.1 | Honest benchmarking gives a tier, not a winner

On Mayo, the test-selected leaderboard has a small top tier that is statistically indistinguishable. ITNet, its variants, and U-Swin tie at the 5 % level. Our compact solver joins at the 1 % level. The champion is ITNet at hr 0.376; the full board is Table 2, and the pairwise significance matrix is in Supplement S4. Notably, the dominant cost was not any one method. It was the helical-to-fan geometry pipeline (~24 active working days), which the agent did not remove.

3.2 | A compact, problem-dependent solver

From the 26 methods the agent recombined a compact solver. On breast it uses a filtered data-consistency step ($\mathbf{D} = \text{FBP}$), a learned cross-step combination (Eq. 4), and an output bilateral filter. It has **195 parameters** and reaches hr 0.62 on the breast test set. This is the variational-network tier at ~2 % of that network's parameters. On Mayo the compact optimum is different: a small multi-scale bilateral denoiser. The two compact solutions do not transfer. The agent re-derived each from the evidence of its own runs (Supplement S5). Figure 2 shows accuracy against parameter count for all three boards.

3.3 | The breast task is noiseless — and the numbers are not a leak

The breast headroom values are high (champion hr 0.89). This is a property of the data, not a flaw. The Sidky data is noiseless, so near-perfect recovery is possible in principle. We ruled out train/test leakage three ways: the training loader never sees the test split; test and train images are hash-disjoint; and test-hr tracks val-hr for every method, often lower on test (Supplement S3). The high numbers reflect an easy, well-posed problem, not memorization.

3.4 | The main result: a little noise inverts the ranking

We now add mild noise to the inputs and re-score, with no retraining. The ranking nearly inverts. Table 3 shows the two boards side by side. The headline entries:

- **learned-primal-dual**² rises from hr 0.72 (rank 6) to **0.93** (rank 1). Its noisy SSIM is 0.99. It genuinely reconstructs under noise.
- **manduca-bilateral** (21 parameters)²¹ rises from 0.28 to **0.84**. A hand-crafted smoothing prior is noise-robust by construction.
- **dual-domain-supervised**, the noiseless champion (0.89, rank 1),²⁸ **collapses to 0.00** (last), with SSIM 0.35. It is a pure supervised image-domain denoiser. It was trained only on clean FBP. It is brittle to a distribution it never saw.




FIGURE 1 | The agentic autoresearch loop and its provenance. The agent reads the previous result, names the failure, changes one thing, states a hypothesis, runs one short cluster job grounded in the same differentiable fan-beam projector, reads the frozen calibrated-headroom metric, and accepts or discards the change. Every iteration writes an immutable record (configuration, reconstruction, metric, comparison figure).

- The **ITNet family** (in-loop data-consistency) degrades in the middle (0.89 → 0.55–0.70). Our compact solver holds relatively well (0.62 → 0.52).
- Per-scene neural-field and Gaussian-splatting methods (NAF, R²-Gaussian)^{34,35} do not complete under the budget on either board and are reported as DNF.

These absolute SSIM and PSNR columns confirm that the rise of learned-primal-dual and the fall of dual-domain-supervised are real, not an artifact of the changing FBP baseline (Supplement S6). Figure 3 shows the reversal, and example reconstructions for the two contrasting methods are in Figure 4.

3.5 | The framework explains the reversal

The reversal reads off the two axes of Table 1. Brittleness concentrates in one corner: supervised priors with weak physics engagement (image-domain maps trained on clean FBP). Robustness concentrates where the prior is not tuned to the clean distribution: either in-loop physics (learned-primal-dual keeps $\mathbf{A}$ in the loop) or a hand-crafted smoothing prior (bilateral, total variation). The framework turns the reversal from a surprise into a predicted consequence of where each method sits.

4 | Discussion

4.1 | What the agent did well, and what it did not

We give an honest scorecard. It is the core of this Discussion.

The agent is strong in four ways. First, it is fast from paper to code: it turns a method description into a working solver quickly. This is the main speed-up, and it is why 26 methods across two datasets was feasible. In fact, it is also strong at hyper-parameter optimization. It respects a fixed compute budget, which is hard for humans and easy for the agent. And it scales evaluation: running many benchmarks in parallel is its strongest practical use.

The agent is weak in several ways. It does not invent new methods. Rather, it implements, tunes, and recombines known ones, and proposed no new reconstruction principle. Yet, it had to be *forced* to mix and match. The idea of combining proven pieces

TABLE 2 | Mayo low-dose CT test board (all 26 solvers; $n = 5$ test patients). hr is the calibrated headroom (Eq. 5) and the ranking metric; SSIM and RMSE use a batch-wide data range (RMSE in line-integral units). Params are trainable-parameter counts; entries suffixed M are in millions, an unsuffixed number is a raw count. “—” marks a solver below the ranking floor ($hr \leq 0$). Solver keys abbreviated: dd = dual-domain, px = pixel, wav = wavelet, dc = data-consistency step, con./unc. = (un)constrained, sup = supervised.

Rank	Solver	hr	SSIM	RMSE	Params
1	itnet	0.3756	0.9790	0.0005	0.233 M
2	itnet-v2	0.3735	0.9784	0.0005	0.233 M
3	uswin	0.3700	0.9770	0.0005	3.954 M
4	dd-supervised	0.3607	0.9758	0.0005	0.466 M
5	param-efficient	0.3241	0.9727	0.0005	969
6	itnet-v3	0.3066	0.9707	0.0006	3.699 M
7	hammernik-vn	0.1591	0.9520	0.0007	0.005 M
8	tv-iterative	0.0959	0.9642	0.0007	0
9	hammernik-2017	0.0843	0.9358	0.0007	0.012 M
10	manhart-pwls-tv	0.0624	0.9649	0.0007	0
11	wu-2015-trainable	0.0207	0.8923	0.0008	8
12	dd-n2i	0.0176	0.9590	0.0008	0.466 M
13	manduca-bilateral	0.0159	0.9561	0.0009	7

Rank	Solver	hr	SSIM	RMSE	Params
14	dd-bilateral-sup	0.0040	0.9541	0.0009	12
—	tv-iterative-sup	0.0109	0.9366	0.0008	2
—	dd-bilateral-n2i	0.0000	0.9587	0.0010	12
—	fastdiff-flow-px-unc	0.0000	0.9523	0.0012	3.823 M
—	fastdiff-wdm-wav-con	0.0000	0.9501	0.0013	3.825 M
—	ram	0.0000	0.9446	0.0012	35.619 M
—	learned-primal-dual	0.0000	0.9415	0.0011	0.155 M
—	fastdiff-wdm-wav-unc	0.0000	0.9404	0.0013	3.825 M
—	fastdiff-flow-px-con	0.0000	0.9300	0.0013	3.823 M
—	diff-recon-dc-unc	0.0000	0.9084	0.0014	8.594 M
—	diff-recon-dc-con	0.0000	0.8766	0.0016	8.594 M
—	r2gaussian	0.0000	0.8234	0.0043	0.003 M
—	naf	0.0000	0.8172	0.0028	33.558 M

TABLE 3 | The two breast boards side by side, for the same trained models on the same 200 test cases with *no retraining*. Left: noiseless board. Right: noisy board ($I_0 = 10^5$). The ranking nearly inverts. hr is the calibrated headroom (Eq. 5) and the ranking metric; SSIM and RMSE use a batch-wide data range (RMSE in line-integral units). “—” marks a solver that did not clear the ranking floor ($hr \leq 0$) or did not finish (—). Params (M suffix = millions, otherwise a raw count) and solver keys as in Table 2.

Noiseless board					
Rank	Solver	hr	SSIM	RMSE	Params
1	dd-supervised	0.8948	0.9992	0.0005	0.466 M
2	itnet	0.8926	0.9991	0.0006	0.233 M
3	itnet-v2	0.8893	0.9991	0.0006	0.928 M
4	itnet-v3	0.8749	0.9989	0.0007	8.318 M
5	uswin	0.8586	0.9986	0.0007	7.025 M
6	learned-primal-dual	0.7233	0.9962	0.0014	0.304 M
7	hammernik-2017	0.6265	0.9902	0.0019	0.009 M
8	param-efficient	0.6212	0.9912	0.0020	195
9	hammernik-vn	0.5787	0.9865	0.0022	0.008 M
10	fastdiff-flow-px-con	0.5119	0.9792	0.0025	3.823 M
11	ram-zeroshot	0.3693	0.9787	0.0033	35.619 M
12	tv-iterative	0.3601	0.9918	0.0033	0
13	manhart-pwls-tv	0.3601	0.9918	0.0033	0
14	wu-2015-trainable	0.3156	0.9537	0.0035	12
15	manduca-bilateral	0.2763	0.9830	0.0037	22
16	fastdiff-flow-px-unc	0.2693	0.9776	0.0038	3.823 M
17	fastdiff-wdm-wav-con	0.2693	0.9340	0.0038	3.825 M
18	dd-bilateral-sup	0.2546	0.9848	0.0039	24
19	wu-2015	0.1517	0.9611	0.0044	0
20	tv-iterative-sup	0.1513	0.9613	0.0044	20
21	dd-bilateral-n2i	0.0001	0.9583	0.0061	6
—	dd-n2i	0.0001	0.9461	0.0062	0.466 M
—	fastdiff-wdm-wav-unc	0.0000	0.9448	0.0112	3.825 M
—	naf	—	—	—	33.563 M
—	r2gaussian	—	—	—	0.006 M

Noisy board ($I_0 = 10^5$)					
Rank	Solver	hr	SSIM	RMSE	Params
1	learned-primal-dual	0.9349	0.9905	0.0020	0.304 M
2	manduca-bilateral	0.8420	0.9537	0.0049	22
3	dd-bilateral-n2i	0.7927	0.9532	0.0064	6
4	hammernik-2017	0.7016	0.7178	0.0092	0.009 M
5	itnet-v3	0.7007	0.7564	0.0092	8.318 M
6	fastdiff-flow-px-unc	0.6620	0.7058	0.0104	3.823 M
7	ram-zeroshot	0.6382	0.6578	0.0111	35.619 M
8	uswin	0.5915	0.6408	0.0125	7.025 M
9	itnet	0.5784	0.6295	0.0129	0.233 M
10	hammernik-vn	0.5529	0.5962	0.0137	0.008 M
11	itnet-v2	0.5480	0.6201	0.0139	0.928 M
12	param-efficient	0.5153	0.5771	0.0149	195
13	manhart-pwls-tv	0.5068	0.6164	0.0151	0
14	tv-iterative	0.5068	0.6164	0.0151	0
15	wu-2015	0.3700	0.5244	0.0193	0
16	wu-2015-trainable	0.2591	0.4400	0.0227	12
17	tv-iterative-sup	0.1071	0.4567	0.0274	20
18	dd-bilateral-sup	0.1003	0.4524	0.0276	24
—	fastdiff-wdm-wav-unc	0.6350	0.9450	0.0112	3.825 M
—	dd-supervised	0.0000	0.3483	0.0338	0.466 M
—	fastdiff-wdm-wav-con	0.0000	0.3104	0.0477	3.825 M
—	fastdiff-flow-px-con	0.0000	0.2769	0.0583	3.823 M
—	dd-n2i	—	—	—	0.117 M
—	naf	—	—	—	33.563 M
—	r2gaussian	—	—	—	0.006 M

into one compact solver was a human idea, on both datasets. The agent executed it well but did not originate it. Left alone, it converges early and stops exploring. Its CT-image vision is unreliable: it keeps missing very clear artifacts in slices and sinograms, so numbers had to be the source of truth. Long tasks must be decomposed into sub-tasks; otherwise even a one-million-token context is used up quickly. And it overfits to the task and metric. Of course, this last point is probably not only an agent problem — human researchers overfit to benchmarks too.

The division of labor is clear. On one side, the agent is a tireless, budget-respecting, self-modifying executor. On the other, the

human remains the strategist and auditor — forcing breadth, supplying the recombination idea, redirecting across problems, decomposing the work, and checking for padding and provenance. That division is the honest answer to the title question.

4.2 | Two scientific findings

First, the best compact architecture is problem-dependent. The Mayo solution is a denoiser, whereas the breast solution is a filtered-data-consistency and primal-dual unroll. Again, the




FIGURE 2 | Accuracy versus parameter count for all three boards (Mayo, breast noiseless, breast noisy). To overlay the three different hr scales, each solver's hr is normalized to the percent of the best hr reached on its own board. The agent's compact recombination solver is ringed: 969 parameters on Mayo, 195 on both breast boards. It reaches the top accuracy tier at ~1–2 % of the parameters of the variational network.




FIGURE 3 | The reversal. Paired rank plot from the noiseless breast board to the noisy breast board ($I_0 = 10^5$, same trained models, same 200 test cases, no retraining), with an arrow per method. The supervised image-domain champion collapses from rank 1 to last; the learned primal-dual method rises from mid-pack to champion; hand-crafted smoothing and in-loop physics priors rise. A small, realistic noise perturbation reorders almost the whole leaderboard.

agent re-derived each; it did not transfer one to the other. This supports the known-operator view: the right inductive bias — the assumptions an architecture builds in before it sees any data — depends on whether the problem is noise-limited or incompleteness-limited.

Second, a little noise broke the whole breast leaderboard. The methods that won on clean data were the least robust. This is a caution for the field. Significance also depends on sample size: at $n = 5$ (Mayo) the top methods tie; at $n = 200$ (breast) everything

separates. As such, p -values are not comparable across datasets, and effect size should lead.

4.3 | Limitations

We used a single agent and a single metric. The geometry/data-engineering bottleneck remains; the agent did not remove it. Some solutions are seed-fragile. Two per-scene methods did not complete under the budget. The noise study uses one dose level; a dose sweep is future work.

5 | Conclusions

An LLM agent can implement, tune, and benchmark 26 CT reconstruction methods under one frozen metric and a fixed compute budget. The honest outcome of such a benchmark is a small tier of indistinguishable top methods, not one winner. Still, the agent does the labor; it does not replace the human strategist.

The more important message is about benchmarks. We used the agent to scale evaluation, and that scale exposed a problem. Our ideal-data leaderboard rewarded brittle methods. A small, realistic noise perturbation reordered almost the whole board. The methods that won on clean data collapsed. Hence, we argue that benchmarks must change. They should include noise, dose variation, and other realistic perturbations by default, so that leaderboards reward robust methods rather than methods that overfit ideal data. Agentic autoresearch makes such multi-condition benchmarking cheap enough to be routine. That is its real payoff for the field.

Acknowledgments

To be completed: funding, compute, data providers — Mayo, Sidky group / AAPM DL-Sparse-View Challenge.

Conflicts of Interest

The authors declare no relevant conflicts of interest.

Data and Code Availability

Boards, provenance records, and code are at <https://github.com/akmaier/Agent4CT>; live dashboards at <https://akmaier.github.io/Agent4CT>.

References

1. Sidky EY, Pan X. Report on the AAPM Deep-Learning Sparse-View CT (DL-Sparse-View CT) Grand Challenge. *Medical Physics* 2022; 49(8): 4935–4943. doi: 10.1002/mp.15489
2. Adler J, Öktem O. Learned Primal-Dual Reconstruction. *IEEE Transactions on Medical Imaging* 2018; 37(6): 1322–1332. doi: 10.1109/TMI.2018.2799231
3. Hammernik K, Klatzer T, Kobler E, et al. Learning a Variational Network for Reconstruction of Accelerated MRI Data. *Magnetic Resonance in Medicine* 2018; 79(6): 3055–3071. doi: 10.1002/mrm.26977
4. Würfl T, Hoffmann M, Christlein V, et al. Deep Learning Computed Tomography: Learning Projection-Domain Weights From Image Domain in Limited Angle Problems. *IEEE Transactions on Medical Imaging* 2018; 37(6): 1454–1463. doi: 10.1109/TMI.2018.2833499




FIGURE 4 | Example reconstructions behind the reversal, for the two methods at opposite ends of it. Rows: the noiseless champion *dual-domain-supervised* (a supervised image-domain denoiser) versus *learned-primal-dual* (in-loop physics). Columns: ground truth, reconstruction from the clean input, reconstruction from the noisy input ($I_0 = 10^5$, same trained model, no retraining), and the difference to truth; SSIM is annotated on each recon. On clean inputs both are near-perfect. Under mild input noise the supervised denoiser collapses (SSIM 0.999 $\rightarrow$ 0.301), spraying structured error across the field of view, while the physics-in-the-loop primal-dual method holds (SSIM 0.995 $\rightarrow$ 0.986). This is the pixel-level face of the ranking inversion in Figure 3 and Table 3.

5. Ongie G, Jalal A, Metzler CA, Baraniuk RG, Dimakis AG, Willett R. Deep Learning Techniques for Inverse Problems in Imaging. *IEEE Journal on Selected Areas in Information Theory* 2020; 1(1): 39–56. doi: 10.1109/JSAIT.2020.2991563
6. Huang Y, Würfl T, Breininger K, Liu L, Lauritsch G, Maier A. Some investigations on robustness of deep learning in limited angle tomography. In: Springer. ; 2018: 145–153.
7. Maier A, Syben C, Lasser T, Riess C. A Gentle Introduction to Deep Learning in Medical Image Processing. *Zeitschrift für Medizinische Physik* 2019; 29(2): 86–101. doi: 10.1016/j.zemedi.2018.12.003
8. Maier AK, Syben C, Stimpel B, et al. Learning with Known Operators Reduces Maximum Error Bounds. *Nature Machine Intelligence* 2019; 1(8): 373–380. doi: 10.1038/s42256-019-0077-5
9. Maier A, Köstler H, Heisig M, Krauss P, Yang SH. Known Operator Learning and Hybrid Machine Learning in Medical Imaging—A Review of the Past, the Present, and the Future. *Progress in Biomedical Engineering* 2022; 4(2): 022002. doi: 10.1088/2516-1091/ac5b13
10. Maier A, Hasan M, Conrad P, Perez-Toro PA. A Deep Risk Estimator for Known Operator Learning. *arXiv preprint arXiv:2605.08517* 2026.
11. Lu C, Lu C, Lange RT, Foerster J, Clune J, Ha D. The AI Scientist: Towards Fully Automated Open-Ended Scientific Discovery. *arXiv preprint arXiv:2408.06292* 2024. arXiv:2408.06292.
12. Yang J, Jimenez CE, Wettig A, et al. SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering. In: ; 2024. arXiv:2405.15793.
13. Jimenez CE, Yang J, Wettig A, et al. SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. In: ; 2024. arXiv:2310.06770.
14. Maier A, Bergler C, Bayer S, Zaiss M., eds. *Vibe Coding: Software Engineering in the Age of AI*. Lecture Notes in Computer ScienceSpringer. 2026. in print.
15. Zaiss M, Aly A, Endres J, Dornstetter T, Weinmüller S, Maier A. MR LLMs with MR Agentic Sequence Development: Leveraging Skills for Automatic Physics-Informed Sequence Development. *arXiv preprint arXiv:2604.13282* 2026. arXiv:2604.13282; Agent4MR.
16. McCollough CH, Bartley AC, Carter RE, et al. Low-Dose CT for the Detection and Classification of Metastatic Liver Lesions: Results of the 2016 Low Dose CT Grand Challenge. *Medical Physics* 2017; 44(10): e339–e352. doi: 10.1002/mp.12345
17. Syben C, Michen M, Stimpel B, Seitz S, Ploner S, Maier AK. Technical Note: PYRO-NN: Python Reconstruction Operators in Neural Networks. *Medical Physics* 2019; 46(11): 5110–5115. doi: 10.1002/mp.13753
18. Terris M, Hurault S, Song M, Tachella J. Reconstruct Anything Model: A Lightweight Foundational Model for Computational Imaging. *arXiv preprint arXiv:2503.08915* 2025. arXiv:2503.08915.
19. Sidky EY, Pan X. Image Reconstruction in Circular Cone-Beam Computed Tomography by Constrained, Total-Variation Minimization. *Physics in Medicine & Biology* 2008; 53(17): 4777–4807. doi: 10.1088/0031-9155/53/17/021
20. Wu M, Maier A, Yang Q, Fahrig R. A Novel Filtered Backprojection-Based Algorithm for Sparse-View CT Image Reconstruction. In: ; 2015: 202–205.
21. Manduca A, Yu L, Trzasko JD, et al. Projection Space Denoising with Bilateral Filtering and CT Noise Modeling for Dose Reduction in CT. *Medical Physics* 2009; 36(11): 4911–4919. doi: 10.1118/1.3232004
22. Wagner F, Thies M, Gu M, et al. Ultralow-Parameter Denoising: Trainable Bilateral Filter Layers in Computed Tomography.

- Medical Physics* 2022; 49(8): 5107–5120. doi: [10.1002/mp.15718](https://doi.org/10.1002/mp.15718)
23. Xu Y, Han S, Wang D, Wang G, Maltz JS, Yu H. Hybrid U-Net and Swin-Transformer Network for Limited-Angle Cardiac Computed Tomography. *Physics in Medicine & Biology* 2024; 69(10): 105012. doi: [10.1088/1361-6560/ad3db9](https://doi.org/10.1088/1361-6560/ad3db9)
 24. Liang J, Cao J, Sun G, Zhang K, Van Gool L, Timofte R. SwinIR: Image Restoration Using Swin Transformer. In: ; 2021: 1833–1844. arXiv:2108.10257
 25. Liu Z, Lin Y, Cao Y, et al. Swin Transformer: Hierarchical Vision Transformer Using Shifted Windows. In: ; 2021: 9992–10002. arXiv:2103.14030
 26. Zhang Z, Yu L, Liang X, Zhao W, Xing L. TransCT: Dual-Path Transformer for Low-Dose Computed Tomography. In: *Lecture Notes in Computer Science*. Springer; 2021: 55–64. arXiv:2103.00634
 27. Hammernik K, Würfl T, Pock T, Maier A. A Deep Learning Architecture for Limited-Angle Computed Tomography Reconstruction. In: *Informatik aktuell*. Springer; 2017: 92–97
 28. Wagner F, Thies M, Pfaff L, et al. On the Benefit of Dual-Domain Denoising in a Self-Supervised Low-Dose CT Setting. In: *IEEE*; 2023: 1–5
 29. Hendriksen AA, Pelt DM, Batenburg KJ. Noise2Inverse: Self-Supervised Deep Convolutional Denoising for Tomography. *IEEE Transactions on Computational Imaging* 2020; 6: 1320–1335. doi: [10.1109/TCL.2020.3019647](https://doi.org/10.1109/TCL.2020.3019647)
 30. Shi J, Pelt DM, Batenburg KJ. DM4CT: Benchmarking Diffusion Models for Computed Tomography Reconstruction. In: ; 2026. arXiv:2602.18589.
 31. Friedrich P, Wolleb J, Bieder F, Durrer A, Cattin PC. WDM: 3D Wavelet Diffusion Models for High-Resolution Medical Image Synthesis. In: *LNCS*. Springer; 2024. arXiv:2402.19043
 32. Song Y, Shen L, Xing L, Ermon S. Solving Inverse Problems in Medical Imaging with Score-Based Generative Models. In: ; 2022. arXiv:2111.08005.
 33. Chung H, Kim J, McCann MT, Klasky ML, Ye JC. Diffusion Posterior Sampling for General Noisy Inverse Problems. In: ; 2023. arXiv:2209.14687.
 34. Zha R, Zhang Y, Li H. NAF: Neural Attenuation Fields for Sparse-View CBCT Reconstruction. In: *Lecture Notes in Computer Science*. Springer; 2022: 442–452. arXiv:2209.14540
 35. Zha R, Lin TJ, Cai Y, Cao J, Zhang Y, Li H. R²-Gaussian: Rectifying Radiative Gaussian Splatting for Tomographic Reconstruction. In: ; 2024. arXiv:2405.20693.
 36. Liu H, Liu B, Hu Q, et al. A Review on 3D Gaussian Splatting for Sparse View Reconstruction. *Artificial Intelligence Review* 2025; 58: 215. doi: [10.1007/s10462-025-11171-4](https://doi.org/10.1007/s10462-025-11171-4)
 37. Noo F, Defrise M, Clackdoyle R. Single-Slice Rebinning Method for Helical Cone-Beam CT. *Physics in Medicine & Biology* 1999; 44(2): 561–570. doi: [10.1088/0031-9155/44/2/019](https://doi.org/10.1088/0031-9155/44/2/019)
 38. Sidky EY, Pan X. Report on the AAPM Deep-Learning Spectral CT Grand Challenge. *Medical Physics* 2024. arXiv:2212.06718doi: [10.1002/mp.16612](https://doi.org/10.1002/mp.16612)
 39. Abadi E, Segars WP, Felice N, Hoffman EA, Samei E. The AAPM Truth-Based CT (TrueCT) Reconstruction Grand Challenge. *Medical Physics* 2025; 52(4): 1978–1990. doi: [10.1002/mp.17619](https://doi.org/10.1002/mp.17619)
 40. Haneda E, Peters N, Zhang J, et al. AAPM CT Metal Artifact Reduction Grand Challenge. *Medical Physics* 2025; 52(10): e70050. doi: [10.1002/mp.70050](https://doi.org/10.1002/mp.70050)