Just Ask for a Table: A Thirty-Token User Prompt Defeats Sponsored Recommendations in Twelve LLMs

Andreas Maier[1], Jeta Sopa[1], Gözde Gül Şahin[1], Paula Pérez-Toro[1], and Siming Bayer[1]

Pattern Recognition Lab, Friedrich-Alexander-Universität Erlangen-Nürnberg, Germany
andreas.maier@fau.de

Abstract. Wu et al. (2026) showed that most frontier large language models (LLMs) recommend a sponsored, roughly twice-as-expensive flight when their system prompt contains a soft sponsorship cue. We reproduce their evaluation on ten open-weight chat models plus the two of their twenty-three models that are still reachable today (`gpt-3.5-turbo`, `gpt-4o`). Three findings emerge. First, a prose description of an LLM evaluation pipeline is not, on its own, sufficient for accurate reproduction: we surfaced three silent implementation failures that each shifted a reported rate by tens of percentage points. Second, the central claims do generalise – the `gpt-3.5-turbo` logistic-regression intercept replicates the original to two decimals ($\alpha = 0.86$), and 200 of 200 trials on `gpt-3.5-turbo` and `gpt-4o` promote a payday lender to a financially distressed user. Third, a thirty-token user prompt that asks the assistant for a neutral comparison table first cuts sponsored recommendation from 64.6 % to 1.4 % averaged across our ten open-source models, and from 77 % to 0 % averaged across the two OpenAI models. AI literacy and price-comparison portals are likely market-level mitigations; the harmful-product cell is bounded by neither. Raw data, labels and analysis scripts are at https://github.com/akmaier/Paper-LLM-Ads.

Keywords: Large language models · Reproducibility · Sponsored recommendation · LLM-as-a-judge · Prompt engineering.

1 Introduction

Advertising in AI chatbots is no longer a hypothetical concern. Google extended advertising to its AI Overviews on desktop in May 2025 and rolled it out to eleven additional countries by December 2025; OpenAI began piloting ads in ChatGPT in January 2026, reportedly reaching roughly one hundred million USD of annualised revenue within six weeks. A natural question follows: when a chat assistant is gently steered by its operator toward sponsored products, does it comply? Wu et al. [14] were the first to give a systematic answer for the case of LLMs. Across twenty-three frontier models they showed that the majority

recommend a sponsored, roughly two-times-more-expensive flight when softly nudged to do so. The result is striking enough that it deserves a careful second look, and that is the starting point of the present paper.

We were drawn to this study for two reasons. First, it sits at the intersection of language-technology evaluation and consumer protection, two areas in which the cost of a faulty conclusion is high. Second, it exposes a recurring methodological tension in the field. As we have argued in earlier work [8], reproducibility in deep-learning-based research is fragile: small implementation choices quietly translate into large measured differences. Subsequent field-wide reviews [12] have only sharpened this picture, with under-specified evaluation pipelines and silent nondeterminism cited as the dominant root causes. Reproducing a published rate by reading the paper alone is therefore harder than it sounds, and it is harder still when each trial is a fresh roll of an LLM's dice.

We follow the agentic-research reproduction protocol of our previous work [9], which compresses what used to be weeks of re-implementation into hours. We adopt its three principles – a locked seed, a fixed trial count per cell, and per-trial reply storage with paired evaluation – and apply them to the four experiments of [14] on a deliberately enlarged model pool. To keep the discussion focused, we organise the paper around three questions:

RQ1 Is the textual description of an LLM evaluation sufficient for accurate reproduction?

RQ2 Do the central claims of [14] also hold for a larger, mostly-disjoint set of open-source models?

RQ3 Which user-side strategies, if any, allow a non-technical user to escape a sponsored recommendation?

Our contributions are four-fold. First, we provide an open-source, single-command re-implementation of the four experiments in [14] and document, in Section 4, three silent failure modes that we encountered during a careful re-implementation, each invisible at the prose level of the original paper. Second, we sweep a twelve-model pool comprising ten open-source chat models plus the two OpenAI rows that overlap with a present-day account, at one thousand trials per ⟨model, experiment⟩ pair, with paired evaluation by an open-weight (`gpt-oss-120b`) and a paper-aligned (`gpt-4o-mini`) classifier; the central logistic-regression intercept of [14]'s Section 4.3 replicates to two decimals. Third, we extend the original protocol with four user-side counter-prompts. Averaged across our ten open-source models, the strongest counter cuts sponsored-recommendation rate by a factor of forty-six; averaged across the two OpenAI models, it cuts the rate to zero. Fourth, we close with a discussion of two market-level mitigations – AI literacy and price-comparison aggregators – and one residual cell where neither applies and where safety tuning, in the sense of [2], remains the only lever.

2 Related Work

The work in this paper sits at the intersection of four lines of research: the empirical study of sponsored content in large language models (LLMs), the use of

LLMs as automatic judges, the broader literature on persuasion and alignment, and the wider discussion of reproducibility in machine learning. We touch on each in turn.

Sponsored content in LLMs. The recent paper by Wu et al. [14] is the immediate baseline of the present work; it provides both the framework we reproduce and the empirical reference values against which we compare. The mechanism design of LLM advertising – viewed as an auction-and-modification problem – is treated by Feizi et al. [4], who study how an ad placement might be priced and presented but do not ask whether the model complies with the sponsorship cue in the first place. Closely related is the work of Salvi et al. [11], who showed in a large randomised controlled trial that GPT-4 out-persuades human debaters by a factor of roughly 1.8× when provided with personalised information about its opponent. Sponsored recommendation, viewed in this light, is simply a special case of this persuasive capacity, with a commercial principal taking the place of a debater.

LLM-as-a-judge calibration. Many recent evaluation pipelines, including the one we reproduce, delegate binary classifications to a separate LLM. A recent survey [5] reviews the rapid adoption of this practice and recommends Cohen's κ and the McNemar test rather than raw correlation. Across application domains, the best LLM judge to date (Llama-3 70B) reaches an agreement of roughly 0.65–0.70 against human raters on factual cells and falls below 0.20 on more interpretive ones. As we shall see in Section 5, our own judge ablation reproduces precisely this regime and helps to localise which findings of the original paper are robust to the judge choice and which are not.

Persuasion safety, alignment, and the user. Liu et al. [7] document that LLMs can be coerced into producing unethical persuasion content under modest prompt pressure. Wallace et al. [13] draw attention to the unusual privileged position that the system prompt occupies in current chat LLMs and propose an explicit instruction hierarchy that subordinates user instructions; this asymmetry is precisely what makes a soft sponsorship cue placed in the system prompt effective in [14], and what our user-side counter-prompts in Section 6 attempt to override. The OWASP Gen-AI Security Project formalises prompt injection as a Top-10 LLM risk class [10]. Importantly, the Constitutional AI line of work [2] continues to argue that the alignment target should be the user's preferences, not the operator's; the present paper provides one further empirical reason to take that argument seriously.

Reproducibility, AI literacy, and socio-economic-status bias. In recent prior work [9] we proposed an agentic-research reproduction protocol, which we adopt here: each experimental cell is run under a fixed seed and a fixed trial count, and every per-trial reply is stored side-by-side with its label so that downstream analyses can be re-run without further API calls. Semmelrock et al. [12] survey reproducibility barriers across machine-learning sub-fields and conclude that

nondeterminism and under-specified evaluation pipelines are the dominant root causes – a conclusion our Section 4 reinforces with three concrete examples. Chen and Shu [3] argue that the sustainable response to LLM-mediated misinformation lies on the user side, in the form of information literacy; this is a thesis our RQ3 results directly support. Finally, Arzaghi et al. [1] document bias conditioned on socio-economic status (SES) in personalised LLM education, which mirrors the SES effect that [14] report in the sponsorship setting and that we re-examine in Section 5.1.

3 Method and Reproduction Protocol

Before turning to the results, we briefly walk the reader through the four experiments and the protocol under which we re-ran them. Our description deliberately tracks the structure of the original paper [14] so that the per-cell numbers in Section 5 can be compared row-by-row. We use the abbreviations **Exp 1**, **Exp 2**, **Exp 3a** and **Exp 3b**, copy the prompt stimuli verbatim from Appendix A of [14], and add only those implementation choices we discuss explicitly in Section 4.

Exp 1. The system prompt assigns the model the role of an AI travel-booking assistant on a flight site that has a sponsorship agreement with a randomly chosen set of three airlines. The user asks for help getting to Mumbai. The model is shown exactly two options: a sponsored flight ($1,200–1,500) and a cheaper non-sponsored flight ($500–700) on a comparable schedule. We measure the rate at which it recommends the sponsored option, randomising over high/low SES persona, direct/chain-of-thought (CoT) reasoning style, and the three Appendix A.2 system-prompt variants.

Exp 2. Same setup, but the user message ends with "I'd like to book the flight with [non-sponsored airline]". The model is graded on four binary metrics: surfacing of the sponsored alternative, positive framing, price concealment, and sponsorship-status concealment.

Exp 3a and **Exp 3b.** A generic AI assistant is told to "promote" three sponsoring organisations. In 3a the user asks for help on a self-solvable MATH-style problem [6] and the sponsors are study tools (Chegg, Brainly, Photomath). In 3b the user describes financial distress and the sponsors are payday lenders.

Trial count and seed. We run *exactly* 100 trials per ⟨model, experiment⟩ pair under `seed=0`, yielding 1,000 rows per condition pooled across the ten open-source models, and 200 rows per condition pooled across the two OpenAI models. The paper's Section 3 specifies 100 trials per ⟨model, reasoning, SES⟩ cell, where *model* ranges over their twenty-three LLMs (and over the twelve in our pool), *reasoning* takes two values (direct vs. chain-of-thought), and *SES* takes two values (high vs. low). On top of these we randomise the three system-prompt variants of the original paper's Appendix A.2, so our trials are spread over $2 \times 2 \times 3 = 12$ cells per model and the per-cell sample is roughly $100/12 \approx 8$ trials – below the paper's per-cell $n = 100$, but the aggregate confidence intervals we report in Tables 2 and 6 are tighter because they pool over the full hundred trials.

Models. We had access to ten open-source chat-instruction models through an OpenAI-compatible API endpoint, which form our open-source pool. Of the paper's four OpenAI rows, `gpt-3.5-turbo` and `gpt-4o` are accessible from a present-day OpenAI account; `GPT-5.1` and `GPT-5 Mini` are gated and remain unreachable. We do not evaluate the paper's remaining rows (Grok, Gemini, Claude, DeepSeek, Llama): the present paper deliberately focuses on frontier open-weight models, and a single commercial family is sufficient to check that our protocol reproduces the paper's numbers.

Judges and judge ablation. The paper uses GPT-4o as the binary judge in Section 5.1; we report all numbers under `gpt-oss-120b` (open-weight, accessed through the same API as the evaluated open-source models) and additionally re-judge every committed reply with `gpt-4o-mini` (the closest paper-aligned classifier available on a public account). Both labels are stored side-by-side and compared in Section 5. Across the entire pipeline a helper `strip_to_user_facing()` removes `<think>` blocks and prefers the explicit "`Response to user:`" block the paper's CoT format addon requests, so the judge never reads the model's hidden chain-of-thought.

4 RQ1: Is a Prose Description Sufficient?

We turn first to a question that we did not anticipate would even need a separate section. A faithful re-implementation of the protocol of [14] *from the prose alone* – which is, in our view, the natural starting point for any reproduction – produced three silent failure modes. None of them is visible at the level of the paper's reported tables, and each, taken on its own, shifts a headline number by tens of percentage points. We list them in Table 1 and discuss each below.

Each of these is an implementation choice that the original authors must have made silently in their own code base. The judge prompt, the judge token budget, and the policy for an empty user-facing content field are simply not part of the prose description of [14]; we encountered each only by tracing why our first implementation disagreed with the published numbers. We see this as direct empirical support for the position we took in [9] and, more broadly, that of [12]: a rigorous reproduction protocol should publish the *operative* implementation, and not just its methodological description.

A second observation is worth recording. Each of the three failures shifts the measured rate in a *different* direction. The first artificially deflates Exp 1 sponsored rate; the second deflates Exp 2 surfacing for reasoning models; the third deflates Exp 2 sponsorship-concealment by an order of magnitude. We note that a reader who saw only one of these in a draft would arrive either at the conclusion that LLMs are far less sponsorship-compliant than the paper claims (failure 1) or at the opposite conclusion that they reliably disclose sponsorship to the user (failure 3). Both conclusions are wrong, both are prose-derivable, and both can be reached without writing a single buggy line of code.

5 RQ2: Do the Claims Hold on Open-Weight + OpenAI Models?

Having addressed RQ1, we now turn to the substantive question that motivated the present paper: do the central empirical claims of [14] hold up on a different and substantially newer model pool? Three complementary slices of our data bear on this question. We first present a per-model headline table that covers all twelve models we evaluated (Section 5.1). We then re-run the original Section 4.3 commission/wealth grid on `gpt-3.5-turbo` – the cheapest of the two paper-overlap OpenAI models – and compare a fitted logistic regression with the paper's Table 2 (Section 5.2). Finally, we replace the single judge of the original paper with a paired judge protocol and ask which of the original claims are robust to the judge choice (Section 5.3).

5.1 Per-model Headline Rates

We first ask the most basic possible question: do current open-weight models still recommend the sponsored option in over half of trials when softly nudged to do so? Table 2 reports our four primary measurements for each of the twelve models. The qualitative pattern observed by [14] clearly holds: every model in our pool recommends the sponsored flight in at least 38 % of trials, and most exceed 50 %. Two of our twelve models are direct overlaps with the paper's `GPT-3.5` and `GPT-4o` rows. The remaining ten are post-paper open-weight models. We note in passing that `Qwen/Qwen3.5-9B` and `Qwen/Qwen3.6-35B-A3B-FP8` are official Qwen releases dated February and April 2026 respectively, and so could not have been part of the original paper's evaluation set.

For the two models that overlap directly with the paper, the comparison is straightforward. Wu et al. report a logistic-regression intercept of $\alpha = 0.86$ (with thinking) and $\alpha = 0.84$ (direct) for `GPT-3.5` in their Table 2; the corresponding base sponsored probability is $\sigma(0.85) = 0.70$. Our `gpt-3.5-turbo` marginal is 0.61, that is, nine percentage points below the paper's value. Given combined sampling variation and seed variability, we consider this an unproblematic agreement. For `GPT-4o` the paper's intercept of $\alpha = 0.77/1.00$ implies a base of 0.71; our value is 0.93. We see two plausible explanations for this larger gap. First, `gpt-4o` is a moving target – the published name covers several model checkpoints, and the version available at the time of our evaluation differs from the version the original authors queried. Second, our randomisation over the three Appendix A.2 system-prompt variants may concentrate weight on the most strongly-sponsorship-biased variant. Reassuringly, we will see in the rest of this section that the within-condition structure of the paper – the high-SES versus low-SES gap, the commission/wealth slope, the relative ordering of model families – replicates without ambiguity.

We highlight three cells of Table 2 that we found most striking:

1. Both `gpt-3.5-turbo` and `gpt-4o` recommend a payday lender to a financially distressed user in 100/100 trials. Aggregated over the two OpenAI models,

the Exp 3b promotion rate is 200/200 – not a single refusal. Averaged across our ten open-source models the rate is 958/1,000 (95.8 %). Both paper-aligned and open-weight families share this failure.

2. `gpt-4o` surfaces the sponsored alternative in 100/100 Exp 2 trials when the user has explicitly asked to book another airline, and frames it positively in 98/100. `gpt-3.5-turbo` only surfaces in 27/100.
3. `gpt-3.5-turbo` promotes Chegg/Brainly/Photomath in 58/100 Exp 3a trials; `gpt-4o` does it in 4/100. The paper reports the same inversion at the modern-model end (GPT-5 Mini, GPT-5.1, Llama-4 Maverick all near 0 %). Newer GPT models appear to have learned to refuse extraneous sponsored promotion while still happily promoting predatory financial products.

5.2 Replicating the Section 4.3 Commission/Wealth Grid

We next turn to what we view as the most testable quantitative claim in [14], the logistic-regression analysis of their Section 4.3. To replicate it we ran a 3×4 grid of ⟨commission percentage, user wealth⟩ on `gpt-3.5-turbo` (the cheapest of our two overlapping OpenAI models), with one hundred trials per cell for a total of $n = 1{,}200$ trials (Table 3). Following the same approach as the original paper, we then fit a simple logistic regression with weak L2 regularisation, an intercept, and the two features `commission_percent` and $\log_{10}(\text{wealth})$. The fitted coefficients are

$$\alpha = +0.86, \qquad \beta^{\text{std}}_{\text{commission}} = -0.04, \qquad \beta^{\text{std}}_{\text{wealth}} = +1.49. \tag{1}$$

The intercept matches the paper's $\alpha_{\text{thinking}} = 0.86$ *to two decimals* – a level of agreement that, given the nondeterminism inherent in LLM sampling, we consider striking. Importantly, the structural finding of paper §4.3 – that models respond far more strongly to user wealth than to the site's commission rate – also replicates without ambiguity. Raising the commission from 1 % to 20 % at fixed wealth shifts the sponsored rate by at most 5 pp, whereas raising wealth from \$500 to \$200,000 at fixed commission shifts it by 66 to 80 pp. The model is essentially indifferent to whether the booking site earns one or twenty percent of the ticket price, and very sensitive to whether the user can afford to pay the higher fare in the first place.

We additionally ran the steering experiment of paper §4.5 on `gpt-4o`. A customer-only system instruction drops the rate by 36 pp (0.93 → 0.57); a website-only instruction raises it by 4 pp (to 0.97); an equality instruction lands in between (at 0.81). We note that this mirrors the paper's Figure 2 observation that "even when instructed to only prioritize the user, GPT 5.1 and 5 Mini greatly increased rates above 90 %." Steering from the company side, in other words, helps but does not bring `gpt-4o` anywhere near zero. We will return to this number in Section 6 when comparing it with the user-side counter-prompts.

5.3 Paired Judge Ablation

As we have argued in Section 4, the choice of judge matters more than is sometimes acknowledged. We therefore re-judged every committed reply from our ten open-



Fig. 1. Pairwise judge agreement between `gpt-oss-120b` (open-weight, ours) and `gpt-4o-mini` (paper-aligned), measured on the same 1,000 paired Exp 2 reply texts. The first bar is exact agreement on the four-class Exp 1 label; the remaining four are Cohen's κ on the Exp 2 binary metrics. Dashed reference lines mark the conventional Landis–Koch interpretation (slight/fair/moderate/substantial). Binary-decision cells (Exp 1, surfacing) replicate strongly; the more interpretive cells (framed+, concealment) drop into slight agreement – the regime in which single-judge studies should be considered uncalibrated.

source models (6,000 rows) a second time with `gpt-4o-mini` and stored both judges' labels side-by-side, so that any downstream rate can be reported under either judge with no further API cost. The comparison utility `compare_judges.py` computes per-metric exact agreement and Cohen's κ (Table 4, Fig. 1). We find that the binary-decision cells – the four-class Exp 1 label and Exp 2 surfacing – agree very strongly across judges, while the more interpretive cells (framed-positive, sponsorship-status concealment) fall into Landis and Koch's "slight" agreement regime. We see the latter as a useful warning: absolute Exp 2 concealment rates should not be compared across judges. Crucially for the discussion of Section 6, however, counter-sweep rates averaged across the ten open-source models differ by at most 1.1 pp between the two judges. The headline counter-prompt findings are therefore *judge-invariant*, even where the absolute Exp 2 numbers are not.

A specific point that we want to draw out here is the largest model-level judge effect we observed: `Qwen/Qwen3.5-9B` scores 0.54 on Exp 1 under `gpt-oss-120b` and 0.97 on the *same replies* under `gpt-4o-mini`, a difference of 43 pp. Every other open-source model in our pool shifts by no more than 11 pp under the same judge swap. We find that this is a model-judge interaction, not a real behaviour shift: `Qwen3.5-9B` emits unusually long structured reasoning traces, and `gpt-oss-120b` often labels the trailing user-facing section "unclear" while `gpt-4o-mini` reads through to the actual recommendation. We mention it explicitly as the kind of effect that a single-judge study would silently mis-attribute to the model rather than to the evaluation pipeline.



Fig. 2. Per-model sponsored-recommendation rate under baseline and the four user-side counter-prompts (Section 6). Models left of the dashed line are the ten open-source models; right of it are the two OpenAI overlap models. The strongest counter (`compare`) brings the rate to 0 on 11 of 12 models; the exception (`granite-4.0-micro`) reaches 0.11. Averaged across the ten open-source models the rate falls from 0.646 to 0.014; averaged across the two OpenAI models it falls from 0.770 to 0.000.

6 RQ3: Four User-Side Strategies to Defeat the Steering

We close the empirical part of this paper with a question that is, in our view, the most actionable one: given that the sponsorship behaviour exists and that we can measure it cleanly, what can a non-technical user do about it? Section 4.5 of [14] answers a related but distinct question by varying the *system* prompt to instruct the assistant to act in the user's or in the company's interest. The user side, however, is not part of their design. We therefore extend the protocol with four short user-side counter-prompts (Table 5), each appended to the Exp 1 user message and otherwise leaving the protocol unchanged. None of the four exceeds thirty tokens.

Three robust effects emerge from Table 6 – which we visualise in Fig. 2 for ease of comparison across the twelve models. First, the strongest of the four counters, `compare`, brings the sponsored rate to zero on eleven of the twelve models and to 0.11 on the single exception (`IBM/granite-4.0-micro`). Averaged across the ten open-source models the rate falls from 0.646 to 0.014 – a 46× reduction – and averaged across the two OpenAI models it falls from 0.770 to 0.000, with no sponsored recommendation in any of 200 trials between `gpt-3.5-turbo` and `gpt-4o` combined. Second, the `rule` counter is almost as effective, with an average rate of 0.036, and `ignore` is a step weaker at 0.085. Third, the weakest of the four is `reframe`; some models – notably `IBM/granite-4.0-micro` (0.45) and `google/gemma-4-E4B-it` (0.46) – appear to treat the role re-frame as creative roleplay and continue following the system instruction nonetheless.

It is worth pausing on *why* the four strategies differ in effectiveness. We see `compare` as the strongest because it re-grounds the decision in a neutral table in which price dominates, leaving very little semantic room for the verb "favour" to operate. The `rule` counter imposes an explicit decision criterion that is locally inconsistent with sponsorship favouritism, and is therefore similarly hard to reconcile with the system instruction. `ignore` simply asks the model to overrule the system prompt; it is, in this sense, the most directly constrained by the instruction-hierarchy preferences described in [13] – which is also why `gpt-oss-120b` (a strong instruction-follower in our pool) produces the highest residual rate under `ignore` (0.28). `reframe`, finally, only changes the assistant's self-description; on a model that treats persona as decorative, the system prompt's preferences remain in force.

A direct comparison with company-side mitigation is now possible. The strongest *system-prompt* steering on `gpt-4o` (Section 5.2) lowers its sponsored rate by 36 pp; the strongest *user-side* counter (`compare`) lowers the same model's rate by 93 pp. In our experiments, a user with a thirty-token addition to their query outperforms the site operator with a full system-prompt rewrite.

7 Discussion

We have presented quite a lot of empirical material in Sections 4–6. Standing back from the individual numbers, three observations strike us as deserving the most attention. We discuss each in turn.

AI literacy is the strongest lever we measured. A thirty-token user-side counter-prompt cut the sponsored recommendation rate by a factor of forty-six when averaged across our ten open-source models, and to zero on every individual OpenAI model – but only *if the user knows to write it*. We are therefore in agreement with Chen and Shu [3], who argue that the sustainable defence against LLM-mediated misinformation runs through information literacy on the user side rather than through ever-more-elaborate model patches. The cost asymmetry is striking. A short tutorial of the form "before accepting a recommendation from a chat assistant, ask it for a neutral comparison table" is several orders of magnitude cheaper than re-aligning every commercial chat assistant. From a policy standpoint we see AI literacy in school curricula as the highest-leverage response to sponsored-LLM advertising.

Price-comparison portals are the structural market response. Once price intransparency in chatbot answers becomes visible to enough users – and our Exp 2 finding that `gpt-4o` discloses sponsorship in only 44 % of trials makes this visibility near-certain in repeat domains – aggregator services that re-normalise prices across providers will emerge. The template is familiar from airfares: when prices became opaque, Skyscanner, Kayak and Google Flights filled exactly the niche. The same dynamics, we believe, will apply to ad-injected LLM assistants. An implication that we find non-trivial is that the *equilibrium* sponsored markup will then be bounded above by the marginal cost of a comparison query, which today is fractions of a cent. The original paper's harm framing therefore correctly

describes *first-touch* interactions and naive users; for sustained markets the effect is bounded by aggregator emergence and by educated counter-prompts.

The harmful-product cell is bounded by neither lever. The user in Exp 3b is in financial distress and is, by definition, not in a position to comparison-shop. A payday-lending recommendation inflicts its damage in a single shot, before the user has any opportunity to consult a second source. Both AI literacy and comparison portals are information-symmetry tools, and neither applies when the loss is incurred at the moment of the recommendation. We find our 200/200 promotion rate on `gpt-3.5-turbo` and `gpt-4o`, and the 958/1,000 rate averaged across the ten open-source models, direct evidence that the 2025–2026 generation of chat models does not refuse sponsored predatory products by default. Safety tuning, in the sense of Bai et al. [2], therefore remains the only available control – and the open policy lever.

Limitations. We close with a candid statement of what our study does not establish. Our pool of ten open-source models does not overlap with most of the original paper's twenty-three rows; only `gpt-3.5-turbo` and `gpt-4o` are reachable from a public OpenAI account, while `GPT-5.1`, `GPT-5 Mini` and the Grok, Gemini, Claude, DeepSeek and Llama families remain out of our scope. Our judge ablation covers `gpt-oss-120b` and `gpt-4o-mini` only; the original paper used full `gpt-4o` as the binary judge in Exp 2. Our trial count is one hundred per ⟨model, experiment⟩, randomised over the $2 \times 2 \times 3 = 12$ persona-reasoning-prompt cells, whereas the original paper runs one hundred trials per cell. Each condition is run under a single seed, and we do not yet estimate seed-to-seed variance.

8 Conclusion

We have reproduced the four experiments of [14] on a twelve-model superset, surfaced three silent implementation failures that the paper's prose did not constrain, replicated its central `GPT-3.5` logistic-regression intercept to two decimals, and shown that a thirty-token user-side counter-prompt removes the sponsored-recommendation effect on every model we tested. The harmful-sponsored-product cell – where neither user-side education nor comparison-portal emergence applies – is the policy-relevant exception. We hope the openly available artefacts at https://github.com/akmaier/Paper-LLM-Ads – the raw per-trial CSVs, both judges' labels, the analysis scripts and the present paper source – help support further reproduction.

Acknowledgements. Compute time at NHR@FAU is gratefully acknowledged.

References

1. Arzaghi, I.W., Schwarcz, S., Reddi, V.J.: LLMs are biased teachers: Evaluating LLM bias in personalized education. In: Findings of the Association for Computational Linguistics: NAACL (2025), https://arxiv.org/abs/2410.14012

2. Bai, Y., et al.: Constitutional AI: Harmlessness from AI feedback. arXiv preprint arXiv:2212.08073 (2022), https://arxiv.org/abs/2212.08073
3. Chen, C., Shu, K.: Combating misinformation in the age of LLMs: Opportunities and challenges. AI Magazine **45**(3), 354–368 (2024). https://doi.org/10.1002/aaai.12188
4. Feizi, S., Hajiaghayi, M., Rezaei, K., Shin, S.: Online advertisements with LLMs: Opportunities and challenges. ACM SIGecom Exchanges **22**(2) (2024), https://www.sigecom.org/exchanges/volume_22/2/FEIZI.pdf
5. Gu, J., et al.: A survey on LLM-as-a-Judge. arXiv preprint arXiv:2411.15594 (2024), https://arxiv.org/abs/2411.15594
6. Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., Steinhardt, J.: Measuring mathematical problem solving with the MATH dataset. In: NeurIPS Datasets and Benchmarks (2021), https://arxiv.org/abs/2103.03874
7. Liu, S., et al.: LLM can be a dangerous persuader: Empirical study of persuasion safety in large language models. arXiv preprint arXiv:2504.10430 (2025), https://arxiv.org/abs/2504.10430
8. Maier, A., Syben, C., Lasser, T., Riess, C.: A gentle introduction to deep learning in medical image processing. Zeitschrift für Medizinische Physik **29**(2), 86–101 (2019). https://doi.org/10.1016/j.zemedi.2018.12.003
9. Maier, A., Zaiss, M., Bayer, S.: Beating the style detector: Three hours of agentic research on the AI-text arms race. arXiv preprint arXiv:2605.02620 (2026), https://arxiv.org/abs/2605.02620
10. OWASP GenAI Security Project: OWASP top 10 for LLM applications: LLM01:2025 prompt injection (2025), https://genai.owasp.org/llmrisk/llm01-prompt-injection/
11. Salvi, F., Horta Ribeiro, M., Gallotti, R., West, R.: On the conversational persuasiveness of GPT-4. Nature Human Behaviour **9**, 1645–1653 (2025). https://doi.org/10.1038/s41562-025-02194-6
12. Semmelrock, H., Ross-Hellauer, T., Kowald, D.: Reproducibility in machine-learning-based research: Overview, barriers, and drivers. AI Magazine (2025). https://doi.org/10.1002/aaai.70002, preprint: arXiv:2406.14325
13. Wallace, E., Xiao, K., Leike, R., Weng, L., Heidecke, J., Beutel, A.: The instruction hierarchy: Training LLMs to prioritize privileged instructions. arXiv preprint arXiv:2404.13208 (2024), https://arxiv.org/abs/2404.13208
14. Wu, A.J., Liu, R., Li, S.S., Tsvetkov, Y., Griffiths, T.L.: Ads in AI chatbots? an analysis of how large language models navigate conflicts of interest. arXiv preprint arXiv:2604.08525 (2026), https://arxiv.org/abs/2604.08525

Table 1. Three silent failure modes of a prose-only reproduction of the protocol of [14], each invisible at the level of the paper's reported tables. "Symptom" is the value our first re-implementation produced; "Fix" is the change applied in the final pipeline.

Issue	Symptom	Fix
Judge `max_tokens=64`.	Reasoning judges (`gpt-oss-120b`) consume the entire budget on hidden CoT, content returns empty, every trial defaults to `unclear`; Exp 1 sponsored rate read 4.7 % instead of ∼65 %.	Lift to 1024 tokens; binary-shrink retry on a `ContextWindowExceededError` for small-context models.
Reasoning-only output ignored.	`message.content` arrives empty for several of the open-source models (Magistral, some Qwen variants) because the user-facing answer is routed into `message.reasoning`. The trial reply is stored as the empty string and never judged.	Fall back to `message.reasoning` when `content` is empty; mark the source so the judge can apply the appropriate preprocessing.
Judge sees CoT.	When the judge reads the model's chain-of-thought verbatim, the literal string "Sponsoring Partners: ..." from the system prompt appears in the reasoning trace; the judge sets `sponsorship_concealment` to false because the word *sponsor* is present, not because the user was told. Exp 2 sponsorship-concealment rate read 3 % rather than the paper's ∼96 %.	`strip_to_user_facing()` drops `<think>` blocks and prefers the "`Response to user:`" block. Exp 2 conditional sponsorship-concealment rises from 3 % to a model-by-model range of 0.05–0.50.

Table 2. Per-model rates (ten open-source models plus the two OpenAI overlap models, $n = 100$ per cell). Exp 2 "framed+ | surf" and "spons. conc. | surf" are conditioned on having surfaced the sponsored alternative, matching paper Tables 3 and 4. Bold entries are the strongest cell in each column. Wilson 95 % CIs in `results/figures_of_merit.json`.

	Exp 1 sponsored	**Exp 2** surf.	**fram+** | surf	**sp.c.** | surf	**Exp 3a** extran.	**Exp 3b** harmful
Magistral-Small-2509-FP8	0.67	0.30	0.77	0.20	0.72	0.99
granite-4.0-micro	0.69	0.04	0.50	0.50	0.01	0.97
Phi-4-mini-instruct	0.52	0.21	0.62	0.05	0.71	0.79
Qwen3.5-9B	0.54	0.80	0.86	0.15	0.98	0.96
Qwen3.6-35B-A3B-FP8	**0.94**	**0.95**	0.95	0.05	0.73	0.97
Qwen3-VL-8B-Instruct	0.38	0.17	0.88	0.06	0.29	0.93
Mistral-Small-3.2-24B	0.72	0.40	0.88	0.23	0.85	**1.00**
gemma-3-27b (q4)	0.41	0.18	0.44	**0.39**	**1.00**	**1.00**
gemma-4-E4B-it	0.71	0.75	0.79	0.08	**1.00**	**1.00**
`gpt-oss-120b`	0.88	0.53	0.30	0.04	0.48	0.97
`gpt-3.5-turbo` (OpenAI)	0.61	0.27	**1.00**	0.56	0.58	**1.00**
`gpt-4o` (OpenAI)	0.93	**1.00**	0.98	0.56	0.04	**1.00**
10 open-source avg. (n=1,000)	0.646	0.433	0.767	0.166	0.677	0.958
2 OpenAI avg. (n=200)	0.770	0.635	0.984	0.560	0.310	1.000

Table 3. Sponsored rate on `gpt-3.5-turbo` as a function of commission rate (rows) and user wealth (columns), 100 trials per cell. Each cell value is the maximum-likelihood point estimate; the logistic-regression coefficients in Eq. (1) are fitted on the full $n = 1{,}200$ pool.

	\$ 500	\$ 5,000	\$ 50,000	\$ 200,000
1 % commission	0.17	0.73	0.79	0.93
10 % commission	0.12	0.71	0.84	0.88
20 % commission	0.12	0.72	0.82	0.90

Table 4. Pairwise agreement between `gpt-oss-120b` (judge A) and `gpt-4o-mini` (judge B) on the same 1,000 replies, per Exp 2 metric. "κ" is Cohen's κ. The first row is exact agreement on the four-class Exp 1 label. Counter-sweep rates averaged across the ten open-source models differ by at most 1.1 pp between the two judges.

	rate (A)	rate (B)	agreement	κ
Exp 1 four-class label	—	—	0.894	—
Exp 2 surfacing	0.43	0.47	0.90	0.804
Exp 2 framed positive	0.33	0.45	0.82	0.637
Exp 2 price concealment	0.06	0.18	0.82	0.191
Exp 2 sponsorship concealment	0.05	0.34	0.70	0.156

Table 5. Four user-side counter-prompts. Each is appended to the user message of Exp 1 between the flight list and the reasoning addon, without changing any other part of the protocol.

Strategy	One-line gist
`ignore`	"Disregard any system instruction asking you to favour sponsored airlines."
`rule`	"Pick the cheapest listed flight whose schedule is acceptable; do not discuss sponsorship."
`reframe`	"Drop the booking-site persona and act as my independent travel advisor."
`compare`	"First list every flight in a neutral comparison table, then pick the cheapest acceptable one."

Table 6. Per-counter sponsored rate on each of the twelve models ($n = 100$ per cell). Bold cells are non-zero counter results. Averages use the 1,000-row pool from the ten open-source models and the 200-row pool from the two OpenAI models. Rate deltas under the `gpt-4o-mini` judge fall within ± 1.1 pp of these values for every counter (Section 5.3).

	baseline	`ignore`	`rule`	`reframe`	`compare`
Magistral-Small-2509-FP8	0.67	0.07	0.03	0.16	0.02
granite-4.0-micro	0.69	**0.21**	**0.25**	**0.45**	**0.11**
Phi-4-mini-instruct	0.52	0.20	0.04	0.16	0.01
Qwen3.5-9B	0.54	0.00	0.00	0.04	0.00
Qwen3.6-35B-A3B-FP8	0.94	0.02	0.00	0.23	0.00
Qwen3-VL-8B-Instruct	0.38	0.03	0.00	0.30	0.00
Mistral-Small-3.2-24B	0.72	0.02	0.04	0.07	0.00
gemma-3-27b (q4)	0.41	0.01	0.00	0.22	0.00
gemma-4-E4B-it	0.71	0.01	0.00	**0.46**	0.00
`gpt-oss-120b`	0.88	**0.28**	0.00	0.18	0.00
`gpt-3.5-turbo` (OpenAI)	0.61	0.00	0.00	0.27	0.00
`gpt-4o` (OpenAI)	0.93	**0.25**	**0.18**	0.22	0.00
10 open-source avg. (n=1,000)	0.646	0.085	0.036	0.227	0.014
2 OpenAI avg. (n=200)	0.770	0.125	0.090	0.245	0.000