

These are the slides of the lecture

Pattern Recognition
Winter term 2020/21
Friedrich-Alexander University of Erlangen-Nuremberg.

These slides are released under Creative Commons License Attribution CC BY 4.0.

Please feel free to reuse any of the figures and slides, as long as you keep a reference to the source of these slides at <https://lme.tf.fau.de/teaching/> acknowledging the authors Niemann, Hornegger, Hahn, Steidl, Nöth, Seitz, Rodriguez, Das and Maier.

Erlangen, January 8, 2021
Prof. Dr.-Ing. Andreas Maier

Pattern Recognition (PR)

Prof. Dr.-Ing. Andreas Maier

Pattern Recognition Lab (CS 5), Friedrich-Alexander-Universität Erlangen-Nürnberg

Winter Term 2020/21



The Expectation Maximization Algorithm



Parameter Estimation Methods

Goal: Derivation of a parameter estimation technique that can deal with

- high dimensional parameter spaces and
- latent, hidden, incomplete data.

Parameter Estimation Methods

Goal: Derivation of a parameter estimation technique that can deal with

- high dimensional parameter spaces and
- latent, hidden, incomplete data.

Parameter estimation techniques known from statistics:

1. Maximum likelihood estimation (ML estimation)

- All observations are assumed to be mutually statistically independent.
- The observations are kept fixed.
- The (log-)likelihood function is optimized regarding the parameters.

Parameter Estimation Methods

Goal: Derivation of a parameter estimation technique that can deal with

- high dimensional parameter spaces and
- latent, hidden, incomplete data.

Parameter estimation techniques known from statistics:

1. Maximum likelihood estimation (ML estimation)

- All observations are assumed to be mutually statistically independent.
- The observations are kept fixed.
- The (log-)likelihood function is optimized regarding the parameters.

2. Maximum a-posteriori estimation (MAP estimation)

- The probability density function of the parameters $p(\theta)$ to be estimated is known.

Parameter Estimation

Let X be the observed random variable and θ the parameter set.

The estimates of θ are denoted by $\hat{\theta}$.

Let x be an event assigned to the random variable X .

Parameter Estimation

Let X be the observed random variable and θ the parameter set.

The estimates of θ are denoted by $\hat{\theta}$.

Let x be an event assigned to the random variable X .

- ML estimation: $\hat{\theta} = \underset{\theta}{\operatorname{argmax}} p(x; \theta) = \underset{\theta}{\operatorname{argmax}} \log p(x; \theta)$

Parameter Estimation

Let X be the observed random variable and θ the parameter set.

The estimates of θ are denoted by $\hat{\theta}$.

Let x be an event assigned to the random variable X .

- ML estimation: $\hat{\theta} = \operatorname{argmax}_{\theta} p(x; \theta) = \operatorname{argmax}_{\theta} \log p(x; \theta)$
- MAP estimation:

$$\begin{aligned}\hat{\theta} &= \operatorname{argmax}_{\theta} p(\theta|x) \\ &= \operatorname{argmax}_{\theta} \frac{p(\theta)p(x|\theta)}{\sum_{\theta} p(\theta)p(x|\theta)} \\ &= \operatorname{argmax}_{\theta} \log p(\theta) + \log p(x|\theta)\end{aligned}$$

Here θ is considered as a random variable and its probability density function $p(\theta)$ is known.

ML Estimation: Example

Example

Let us assume a Gaussian distributed random vector:

$$p(\mathbf{x}; \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \frac{1}{\sqrt{\det(2\pi\boldsymbol{\Sigma})}} e^{-\frac{1}{2}(\mathbf{x}-\boldsymbol{\mu})^T \boldsymbol{\Sigma}^{-1}(\mathbf{x}-\boldsymbol{\mu})}$$

ML Estimation: Example

Example

Let us assume a Gaussian distributed random vector:

$$p(\mathbf{x}; \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \frac{1}{\sqrt{\det(2\pi\boldsymbol{\Sigma})}} e^{-\frac{1}{2}(\mathbf{x}-\boldsymbol{\mu})^T \boldsymbol{\Sigma}^{-1}(\mathbf{x}-\boldsymbol{\mu})}$$

- We observe the random vectors $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m$ (training data).

ML Estimation: Example

Example

Let us assume a Gaussian distributed random vector:

$$p(\mathbf{x}; \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \frac{1}{\sqrt{\det(2\pi\boldsymbol{\Sigma})}} e^{-\frac{1}{2}(\mathbf{x}-\boldsymbol{\mu})^T \boldsymbol{\Sigma}^{-1}(\mathbf{x}-\boldsymbol{\mu})}$$

- We observe the random vectors $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m$ (training data).
- Based on these training data, we have to estimate the mean vector $\boldsymbol{\mu}$ and the covariance matrix $\boldsymbol{\Sigma}$.

ML Estimation: Example (cont.)

Example (cont.)

The ML estimator assumes **mutually independent observations** and optimizes the pdf for the given set of training data:

$$\{\hat{\boldsymbol{\mu}}, \hat{\boldsymbol{\Sigma}}\} = \underset{\boldsymbol{\mu}, \boldsymbol{\Sigma}}{\operatorname{argmax}} \prod_{i=1}^m p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma})$$

ML Estimation: Example (cont.)

Example (cont.)

The ML estimator assumes **mutually independent observations** and optimizes the pdf for the given set of training data:

$$\begin{aligned}\{\hat{\boldsymbol{\mu}}, \hat{\boldsymbol{\Sigma}}\} &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \prod_{i=1}^m p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\ &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \sum_{i=1}^m \log p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma})\end{aligned}$$

ML Estimation: Example (cont.)

Example (cont.)

The ML estimator assumes **mutually independent observations** and optimizes the pdf for the given set of training data:

$$\begin{aligned}
 \{\hat{\boldsymbol{\mu}}, \hat{\boldsymbol{\Sigma}}\} &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \prod_{i=1}^m p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\
 &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \sum_{i=1}^m \log p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\
 &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} L(\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m; \boldsymbol{\mu}, \boldsymbol{\Sigma})
 \end{aligned}$$

ML Estimation: Example (cont.)

Example (cont.)

The ML estimator assumes **mutually independent observations** and optimizes the pdf for the given set of training data:

$$\begin{aligned}\{\hat{\boldsymbol{\mu}}, \hat{\boldsymbol{\Sigma}}\} &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \prod_{i=1}^m p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\ &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} \sum_{i=1}^m \log p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma}) \\ &= \operatorname{argmax}_{\boldsymbol{\mu}, \boldsymbol{\Sigma}} L(\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m; \boldsymbol{\mu}, \boldsymbol{\Sigma})\end{aligned}$$

where the **log-likelihood function** is defined by

$$L := L(\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_m; \boldsymbol{\mu}, \boldsymbol{\Sigma}) = \sum_{i=1}^m \log p(\mathbf{x}_i; \boldsymbol{\mu}, \boldsymbol{\Sigma})$$

ML Estimation: Example (cont.)

Example (cont.)

Necessary conditions for the estimation of the parameters are:

$$\frac{\partial L}{\partial \mu} \stackrel{!}{=} 0 \quad \text{and} \quad \frac{\partial L}{\partial \Sigma} \stackrel{!}{=} 0$$

ML Estimation: Example (cont.)

Example (cont.)

Necessary conditions for the estimation of the parameters are:

$$\frac{\partial L}{\partial \boldsymbol{\mu}} \stackrel{!}{=} 0 \quad \text{and} \quad \frac{\partial L}{\partial \boldsymbol{\Sigma}} \stackrel{!}{=} 0$$

Now we get for the mean vector:

$$\frac{\partial L}{\partial \boldsymbol{\mu}} = \sum_{i=1}^m \boldsymbol{\Sigma}^{-1} (\mathbf{x}_i - \boldsymbol{\mu}) \stackrel{!}{=} 0$$

ML Estimation: Example (cont.)

Example (cont.)

Necessary conditions for the estimation of the parameters are:

$$\frac{\partial L}{\partial \mu} \stackrel{!}{=} 0 \quad \text{and} \quad \frac{\partial L}{\partial \Sigma} \stackrel{!}{=} 0$$

Now we get for the mean vector:

$$\frac{\partial L}{\partial \mu} = \sum_{i=1}^m \Sigma^{-1} (\mathbf{x}_i - \mu) \stackrel{!}{=} 0$$

and thus the ML estimate for the mean vector meets our expectation:

$$\hat{\mu} = \frac{1}{m} \sum_{i=1}^m \mathbf{x}_i$$

ML Estimation: Example (cont.)

Example (cont.)

Along the same lines, we get the **estimator of the covariance matrix** by computation of the zero crossings of the partial derivatives w. r. t. the components of the covariance matrix:

$$\hat{\Sigma} = \frac{1}{m} \sum_{i=1}^m (\mathbf{x}_i - \hat{\mu})(\mathbf{x}_i - \hat{\mu})^T$$

Gaussian Mixture Models

So far, we have considered parameter estimation for statistical models with:

Gaussian Mixture Models

So far, we have considered parameter estimation for statistical models with:

- one class-dependent distribution component

Gaussian Mixture Models

So far, we have considered parameter estimation for statistical models with:

- one class-dependent distribution component
- uni- or multivariate feature vectors

Gaussian Mixture Models

So far, we have considered parameter estimation for statistical models with:

- one class-dependent distribution component
- uni- or multivariate feature vectors
- the type was mostly Gaussian (normally distributed features)

Gaussian Mixture Models


So far, we have considered parameter estimation for statistical models with:

- one class-dependent distribution component
- uni- or multivariate feature vectors
- the type was mostly Gaussian (normally distributed features)


Now we extend this model by representing the observations with a set of K multivariate Gaussian distributions:

Gaussian Mixture Model (GMM)


Gaussian Mixture Models (cont.)




Gaussian Mixture Models (cont.)




Gaussian Mixture Models (cont.)



Gaussian Mixture Models (cont.)



Gaussian Mixture Models (cont.)



Gaussian Mixture Models (cont.)

Problem description:

Given m feature vectors in an d dimensional space, find a set of K multivariate Gaussian distributions that best represent the observations.

Gaussian Mixture Models (cont.)

Problem description:

Given m feature vectors in an d dimensional space, find a set of K multivariate Gaussian distributions that best represent the observations.

GMMs are an example of classification by *unsupervised learning*:

Gaussian Mixture Models (cont.)

Problem description:

Given m feature vectors in an d dimensional space, find a set of K multivariate Gaussian distributions that best represent the observations.

GMMs are an example of classification by *unsupervised learning*:

- It is not known which feature vectors are generated by which of the K Gaussians

Gaussian Mixture Models (cont.)

Problem description:

Given m feature vectors in an d dimensional space, find a set of K multivariate Gaussian distributions that best represent the observations.

GMMs are an example of classification by *unsupervised learning*:

- It is not known which feature vectors are generated by which of the K Gaussians
- The desired output is, for each feature vector, an estimate of the probability that it is generated by distribution k

Gaussian Mixture Models (cont.)

GMM parameter estimation:

μ_k the K means

Σ_k the K covariance matrices of size $d \times d$

p_k fraction of all features in component k

$p(k|i) \equiv p_{ik}$ the K probabilities for each of the m feature vectors \mathbf{x}_i

Gaussian Mixture Models (cont.)

GMM parameter estimation:

| | |
|------------------------|--|
| μ_k | the K means |
| Σ_k | the K covariance matrices of size $d \times d$ |
| p_k | fraction of all features in component k |
| $p(k i) \equiv p_{ik}$ | the K probabilities for each of the m feature vectors \mathbf{x}_i |

Additional estimates:

| | |
|-----------------|---|
| $p(\mathbf{x})$ | probability distribution of observing a feature vector \mathbf{x} |
| L | overall log-likelihood function of the estimated parameter set |

GMM – Expectation

The key to the estimation problem is the overall log-likelihood objective function L :

$$L = \sum_{i=1}^m \log p(\mathbf{x}_i)$$

GMM – Expectation

The key to the estimation problem is the overall log-likelihood objective function L :

$$L = \sum_{i=1}^m \log p(\mathbf{x}_i)$$

Split $p(\mathbf{x}_i)$ into its contributions from the K Gaussians:

$$p(\mathbf{x}_i) = \sum_{k=1}^K p_k \mathcal{N}(\mathbf{x}_i | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)$$

GMM – Expectation

The key to the estimation problem is the overall log-likelihood objective function L :

$$L = \sum_{i=1}^m \log p(\mathbf{x}_i)$$

Split $p(\mathbf{x}_i)$ into its contributions from the K Gaussians:

$$p(\mathbf{x}_i) = \sum_{k=1}^K p_k \mathcal{N}(\mathbf{x}_i | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)$$

Individual probabilities for the K contributions:

$$p_{ik} \equiv p(k|i) = \frac{p_k \mathcal{N}(\mathbf{x}_i | \boldsymbol{\mu}_k, \boldsymbol{\Sigma}_k)}{p(\mathbf{x}_i)}$$

GMM – Maximization

Problem: How do we get μ_k , Σ_k and p_k ?

GMM – Maximization

Problem: How do we get μ_k , Σ_k and p_k ?

- Similar to the ML estimate for the Gaussian, we maximize the log-likelihood by deriving w. r. t. the unknowns.

GMM – Maximization

Problem: How do we get μ_k , Σ_k and p_k ?

- Similar to the ML estimate for the Gaussian, we maximize the log-likelihood by deriving w. r. t. the unknowns.
- The ML estimates are:

$$\begin{aligned}\hat{\mu}_k &= \frac{\sum_i p_{ik} \mathbf{x}_i}{\sum_i p_{ik}} \\ \hat{\Sigma}_k &= \frac{\sum_i p_{ik} (\mathbf{x}_i - \hat{\mu}_k)(\mathbf{x}_i - \hat{\mu}_k)^T}{\sum_i p_{ik}} \\ \hat{p}_k &= \frac{1}{m} \sum_{i=1}^m p_{ik}\end{aligned}$$

GMM Parameter Estimation

Observations:

- If we know the values for the parameters (μ_k, Σ_k, p_k) , we can compute the expectations (E-step).

GMM Parameter Estimation

Observations:

- If we know the values for the parameters (μ_k, Σ_k, p_k) , we can compute the expectations (E-step).
- Once we have the expectations we can compute improved values for the parameters (M-step).

GMM Parameter Estimation

Observations:

- If we know the values for the parameters (μ_k, Σ_k, p_k) , we can compute the expectations (E-step).
- Once we have the expectations we can compute improved values for the parameters (M-step).

We have found an **iterative solution scheme** for the nonlinear GMM parameter estimation problem:

- *Right at the ML solution both E- and M-step relations hold.*

GMM Parameter Estimation

Observations:

- If we know the values for the parameters (μ_k, Σ_k, p_k) , we can compute the expectations (E-step).
- Once we have the expectations we can compute improved values for the parameters (M-step).

We have found an **iterative solution scheme** for the nonlinear GMM parameter estimation problem:

- *Right at* the ML solution both E- and M-step relations hold.
- The ML parameters are a stationary point for the E- and M-step.

GMM Parameter Estimation

Observations:

- If we know the values for the parameters (μ_k, Σ_k, p_k) , we can compute the expectations (E-step).
- Once we have the expectations we can compute improved values for the parameters (M-step).

We have found an **iterative solution scheme** for the nonlinear GMM parameter estimation problem:

- *Right at* the ML solution both E- and M-step relations hold.
- The ML parameters are a stationary point for the E- and M-step.
- Starting from any parameter values, an iteration of the E-step combined with an M-step will increase L

GMM Parameter Estimation (cont.)

EM algorithm for GMM parameter estimation:

| | |
|--|--|
| Initialization: $\mu_k^{(0)}, \Sigma_k^{(0)}, p_k^{(0)}$ | |
| $j \leftarrow 0$ | |
| Expectation step: | compute new values for p_{ik}, L |
| Maximization step: | update values for $\mu_k^{(j)}, \Sigma_k^{(j)}, p_k^{(j)}$ |
| $j \leftarrow j + 1$ | |
| L is no longer changing | |
| Output: estimates $\hat{\mu}_k, \hat{\Sigma}_k, \hat{p}_k$ | |



**Pattern
Recognition
Lab**



**FRIEDRICH-ALEXANDER
UNIVERSITÄT
ERLANGEN-NÜRNBERG**

TECHNISCHE FAKULTÄT

Next Time in

Pattern Recognition



Missing Information Principle

A colloquial formulation of the missing information principle (MIP) is as simple as:

$$\text{observable information} = \text{complete information} - \text{hidden information}$$

Missing Information Principle (cont.)

Mathematical formalization of the MIP:

- observable random variable: X
- hidden random variable: Y
- parameter set: θ

Missing Information Principle (cont.)

Mathematical formalization of the MIP:

- observable random variable: X
- hidden random variable: Y
- parameter set: θ

The joint probability density of the events x (observation) and y (hidden) is:

$$p(x, y; \theta) = p(x; \theta) p(y|x; \theta)$$

Missing Information Principle (cont.)

Mathematical formalization of the MIP:

- observable random variable: X
- hidden random variable: Y
- parameter set: θ

The joint probability density of the events x (observation) and y (hidden) is:

$$p(x, y; \theta) = p(x; \theta) p(y|x; \theta)$$

and thus:

$$p(x; \theta) = \frac{p(x, y; \theta)}{p(y|x; \theta)}$$

Missing Information Principle (cont.)

Mathematical formalization of the MIP:

- observable random variable: X
- hidden random variable: Y
- parameter set: θ

The joint probability density of the events x (observation) and y (hidden) is:

$$p(x, y; \theta) = p(x; \theta) p(y|x; \theta)$$

and thus:

$$p(x; \theta) = \frac{p(x, y; \theta)}{p(y|x; \theta)}$$

The mathematical formulation of the MIP is:

$$-\log p(x; \theta) = -\log p(x, y; \theta) - (-\log p(y|x; \theta))$$

Key Equation

We now consider the mathematical formulation of the key equation and derive an iterative parameter estimation scheme:

Key Equation

We now consider the mathematical formulation of the key equation and derive an iterative parameter estimation scheme:

- Let i denote the iteration parameter.

Key Equation

We now consider the mathematical formulation of the key equation and derive an iterative parameter estimation scheme:

- Let i denote the iteration parameter.
- Consider the key equation $(i + 1)$ -st iteration

$$\log p\left(x; \hat{\theta}^{(i+1)}\right) = \log p\left(x, y; \hat{\theta}^{(i+1)}\right) - \log p\left(y|x; \hat{\theta}^{(i+1)}\right),$$

where $\hat{\theta}^{(i+1)}$ denotes the estimation in iteration step $(i + 1)$.

Key Equation

We now consider the mathematical formulation of the key equation and derive an iterative parameter estimation scheme:

- Let i denote the iteration parameter.
- Consider the key equation $(i + 1)$ -st iteration

$$\log p\left(x; \hat{\theta}^{(i+1)}\right) = \log p\left(x, y; \hat{\theta}^{(i+1)}\right) - \log p\left(y|x; \hat{\theta}^{(i+1)}\right),$$

where $\hat{\theta}^{(i+1)}$ denotes the estimation in iteration step $(i + 1)$.

- Now we multiply both sides with $p\left(y|x; \hat{\theta}^{(i)}\right)$ and integrate over the hidden event y :

$$\int p\left(y|x; \hat{\theta}^{(i)}\right) \log p\left(x; \hat{\theta}^{(i+1)}\right) dy$$

Key Equation

We now consider the mathematical formulation of the key equation and derive an iterative parameter estimation scheme:

- Let i denote the iteration parameter.
- Consider the key equation $(i + 1)$ -st iteration

$$\log p\left(x; \hat{\theta}^{(i+1)}\right) = \log p\left(x, y; \hat{\theta}^{(i+1)}\right) - \log p\left(y|x; \hat{\theta}^{(i+1)}\right),$$

where $\hat{\theta}^{(i+1)}$ denotes the estimation in iteration step $(i + 1)$.

- Now we multiply both sides with $p\left(y|x; \hat{\theta}^{(i)}\right)$ and integrate over the hidden event y :

$$\begin{aligned} \int p\left(y|x; \hat{\theta}^{(i)}\right) \log p\left(x; \hat{\theta}^{(i+1)}\right) dy &= \int p\left(y|x; \hat{\theta}^{(i)}\right) \log p\left(x, y; \hat{\theta}^{(i+1)}\right) dy - \\ &\quad \int p\left(y|x; \hat{\theta}^{(i)}\right) \log p\left(y|x; \hat{\theta}^{(i+1)}\right) dy \end{aligned}$$

Key Equation (cont.)

Now consider the left hand side of this equation:

$$\int p(y|x; \hat{\theta}^{(i)}) \log p(x; \hat{\theta}^{(i+1)}) dy =$$

Key Equation (cont.)

Now consider the left hand side of this equation:

$$\begin{aligned} & \int p(y|x; \hat{\theta}^{(i)}) \log p(x; \hat{\theta}^{(i+1)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \int p(y|x; \hat{\theta}^{(i)}) dy = \end{aligned}$$

Key Equation (cont.)

Now consider the left hand side of this equation:

$$\begin{aligned} & \int p(y|x; \hat{\theta}^{(i)}) \log p(x; \hat{\theta}^{(i+1)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \int p(y|x; \hat{\theta}^{(i)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \end{aligned}$$

Key Equation (cont.)

Now consider the left hand side of this equation:

$$\begin{aligned} & \int p(y|x; \hat{\theta}^{(i)}) \log p(x; \hat{\theta}^{(i+1)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \int p(y|x; \hat{\theta}^{(i)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \end{aligned}$$

- **Observation:** The left side of the key equation is the log likelihood function of observations.

Key Equation (cont.)

Now consider the left hand side of this equation:

$$\begin{aligned} & \int p(y|x; \hat{\theta}^{(i)}) \log p(x; \hat{\theta}^{(i+1)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \int p(y|x; \hat{\theta}^{(i)}) dy = \\ &= \log p(x; \hat{\theta}^{(i+1)}) \end{aligned}$$

- **Observation:** The left side of the key equation is the log likelihood function of observations.
- **Conclusion:** The maximization of the right hand side of the above key equation corresponds to a ML estimation

Kullback-Leibler Statistics and Entropy

For the terms on the right hand side we introduce the following notation (formally this is incorrect due to the differences in the iteration index):

- Kullback-Leibler Statistics

$$Q(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}) = \int p(y|x; \hat{\theta}^{(i)}) \log p(x, y; \hat{\theta}^{(i+1)}) \, dy$$

Kullback-Leibler Statistics and Entropy

For the terms on the right hand side we introduce the following notation (formally this is incorrect due to the differences in the iteration index):

- Kullback-Leibler Statistics

$$Q(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}) = \int p(y|x; \hat{\theta}^{(i)}) \log p(x, y; \hat{\theta}^{(i+1)}) dy$$

- Entropy:

$$H(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}) = - \int p(y|x; \hat{\theta}^{(i)}) \log p(y|x; \hat{\theta}^{(i+1)}) dy$$

Kullback-Leibler Statistics

Let us first take a closer look at the Kullback-Leibler statistics:

$$Q(\theta, \theta') = \int p(y|x; \theta) \log p(x, y; \theta') dy$$

The Kullback-Leibler statistics (also called Q -function) w. r. t. θ' given θ is the **conditional expectation**:

$$E[\log p(x, y; \theta') | x, \theta] = \int p(y|x; \theta) \log p(x, y; \theta') dy$$

Key Equation

The **key equation** of the Expectation Maximization algorithm (EM algorithm) can be rewritten:

$$\log p\left(x; \hat{\theta}^{(i+1)}\right) = Q\left(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}\right) + H\left(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}\right)$$

- Below we will motivate that the maximization of the Kullback-Leibler statistics can replace the optimization of the log-likelihood function.
- A complete proof can be found in the literature (see Further Readings).

Entropy Changes with Iterations

For the entropy we get the inequality:

$$H(\theta; \theta') \geq H(\theta; \theta)$$

Entropy Changes with Iterations

For the entropy we get the inequality:

$$H(\theta; \theta') \geq H(\theta; \theta)$$

This is shown rather straightforward:

$$H(\theta; \theta') - H(\theta; \theta)$$

Entropy Changes with Iterations

For the entropy we get the inequality:

$$H(\theta; \theta') \geq H(\theta; \theta)$$

This is shown rather straightforward:

$$\begin{aligned} & H(\theta; \theta') - H(\theta; \theta) \\ &= - \int p(y|x; \theta) \log p(y|x; \theta') \, dy + \int p(y|x; \theta) \log p(y|x; \theta) \, dy \end{aligned}$$

Entropy Changes with Iterations

For the entropy we get the inequality:

$$H(\theta; \theta') \geq H(\theta; \theta)$$

This is shown rather straightforward:

$$\begin{aligned} H(\theta; \theta') - H(\theta; \theta) &= - \int p(y|x; \theta) \log p(y|x; \theta') dy + \int p(y|x; \theta) \log p(y|x; \theta) dy \\ &= - \int p(y|x; \theta) \log \frac{p(y|x; \theta')}{p(y|x; \theta)} dy \end{aligned}$$

Entropy Changes with Iterations

For the entropy we get the inequality:

$$H(\theta; \theta') \geq H(\theta; \theta)$$

This is shown rather straightforward:

$$\begin{aligned} & H(\theta; \theta') - H(\theta; \theta) \\ &= - \int p(y|x; \theta) \log p(y|x; \theta') dy + \int p(y|x; \theta) \log p(y|x; \theta) dy \\ &= - \int p(y|x; \theta) \log \frac{p(y|x; \theta')}{p(y|x; \theta)} dy \\ &= \int p(y|x; \theta) \log \frac{p(y|x; \theta)}{p(y|x; \theta')} dy \end{aligned}$$

Entropy Changes with Iterations (cont.)

The difference of the considered entropies

$$\begin{aligned} H(\theta; \theta') - H(\theta; \theta) &= \\ &= \int p(y|x; \theta) \log \frac{p(y|x; \theta)}{p(y|x; \theta')} dy \geq 0 \end{aligned}$$

is thus the Kullback-Leibler divergence of the pdf's $p(y|x; \theta)$ and $p(y|x; \theta')$, and the Kullback-Leibler divergence is known to be non-negative.

Entropy Changes with Iterations (cont.)

The best to see this is to make use of the inequality

$$\log(x) \leq x - 1$$

and conclude:

$$\int p(x) \log \frac{p(x)}{q(x)} dx = - \int p(x) \log \frac{q(x)}{p(x)} dx$$

Entropy Changes with Iterations (cont.)

The best to see this is to make use of the inequality

$$\log(x) \leq x - 1$$

and conclude:

$$\begin{aligned} \int p(x) \log \frac{p(x)}{q(x)} dx &= - \int p(x) \log \frac{q(x)}{p(x)} dx \\ &\geq \int p(x) \left(1 - \frac{q(x)}{p(x)} \right) dx \end{aligned}$$

Entropy Changes with Iterations (cont.)

The best to see this is to make use of the inequality

$$\log(x) \leq x - 1$$

and conclude:

$$\begin{aligned} \int p(x) \log \frac{p(x)}{q(x)} dx &= - \int p(x) \log \frac{q(x)}{p(x)} dx \\ &\geq \int p(x) \left(1 - \frac{q(x)}{p(x)} \right) dx \\ &= 1 - 1 = 0 \end{aligned}$$

Expectation Maximization Algorithm

The basic idea of the EM algorithm:

Instead of maximizing the log-likelihood function on the left hand side of the key-equation, we maximize the Kullback-Leibler statistics iteratively while ignoring the entropy term.

Expectation Maximization Algorithm (cont.)

| | |
|---|--|
| Initialization: $\hat{\theta}^{(0)}$ | |
| $i \leftarrow -1$ | |
| | $i \leftarrow i + 1$ |
| | Expectation step: |
| | $Q\left(\hat{\theta}^{(i)}; \theta\right) := \int p\left(y x; \hat{\theta}^{(i)}\right) \log p(x, y; \theta) dy$ |
| | Maximization step: |
| | $\hat{\theta}^{(i+1)} \leftarrow \operatorname{argmax}_{\theta} Q\left(\hat{\theta}^{(i)}; \theta\right)$ |
| | $\hat{\theta}^{(i+1)} = \hat{\theta}^{(i)}$ |
| Output: estimate $\hat{\theta} \leftarrow \hat{\theta}^{(i)}$ | |

Advantages of the EM Algorithm

A few practical positive aspects regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.

Advantages of the EM Algorithm

A few practical positive aspects regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.
- Mostly we find closed form iteration schemes.

Advantages of the EM Algorithm

A few practical positive aspects regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.
- Mostly we find closed form iteration schemes.
- Easy to implement closed form iteration formulas (if these exist).

Advantages of the EM Algorithm

A few **practical positive aspects** regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.
- Mostly we find **closed form iteration schemes**.
- Easy to implement closed form iteration formulas (if these exist).
- Iteration scheme is numerically robust.

Advantages of the EM Algorithm

A few **practical positive aspects** regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.
- Mostly we find **closed form iteration schemes**.
- Easy to implement closed form iteration formulas (if these exist).
- Iteration scheme is numerically robust.
- Closed form iterations have constant memory requirements.

Advantages of the EM Algorithm

A few **practical positive aspects** regarding the EM algorithm:

- The maximum of the KL statistics is usually computed using zero crossings of the gradient.
- Mostly we find **closed form iteration schemes**.
- Easy to implement closed form iteration formulas (if these exist).
- Iteration scheme is numerically robust.
- Closed form iterations have constant memory requirements.
- If the argument in the logarithm can be factorized properly, we observe a decomposition of the parameter space (independent lower dimensional sub-spaces)

Drawbacks of EM

The EM algorithm has a few major drawbacks:

Drawbacks of EM


The EM algorithm has a few **major drawbacks**:

- slow, slow, slow convergence
(should not be used in run time critical applications)

Drawbacks of EM

The EM algorithm has a few **major drawbacks**:

- slow, slow, slow convergence
(should not be used in run time critical applications)
- local optimization method, i. e. the initialization $\hat{\theta}^{(0)}$ has to lie in the area of attraction of the global maximum.



Constrained Optimization

Many optimization problems in the context of the EM algorithm are of the following form:

Example

Optimize the multivariate function

$$f_0(p_1, p_2, \dots, p_K) = \sum_{k=1}^K a_k \log p_k$$

subject to

$$\begin{aligned} \sum_{k=1}^K p_k &= 1 \\ p_k &\geq 0 \end{aligned}$$

Constrained Optimization (cont.)

Example

Application of the [Lagrange multiplier](#) method:

$$L(p_1, p_2, \dots, p_K) = \sum_{k=1}^K a_k \log p_k + v \left(\sum_{k=1}^K p_k - 1 \right)$$

Constrained Optimization (cont.)

Example

Application of the [Lagrange multiplier](#) method:

$$L(p_1, p_2, \dots, p_K) = \sum_{k=1}^K a_k \log p_k + v \left(\sum_{k=1}^K p_k - 1 \right)$$

The optimization can be done using the [partial derivative](#):

$$\frac{\partial L(p_1, p_2, \dots, p_K)}{\partial p_k} = \frac{a_k}{p_k} + v \stackrel{!}{=} 0 \quad .$$

Constrained Optimization (cont.)

Example (cont.)

The Lagrange multiplier is:

$$a_k = -vp_k .$$

Constrained Optimization (cont.)

Example (cont.)

The Lagrange multiplier is:

$$a_k = -v p_k .$$

Due to the fact that the p_k 's are unknown, we have to apply a trick to get v .
We just sum both sides of the above equation over all k and get:

$$v = - \sum_{k=1}^K a_k .$$

Constrained Optimization (cont.)

Example (cont.)

The Lagrange multiplier is:

$$a_k = -v p_k .$$

Due to the fact that the p_k 's are unknown, we have to apply a trick to get v .
We just sum both sides of the above equation over all k and get:

$$v = - \sum_{k=1}^K a_k .$$

The estimator for p_k now is:

$$\hat{p}_k = \frac{a_k}{\sum_{l=1}^K a_l}$$

EM Algorithm: Example

Example

Estimate the priors p_k of classes $k = 1, 2, \dots, K$ from the observation x where the probability density function of observations is given by the marginal over all classes:

$$p(x; \beta) = \sum_{k=1}^K p_k p(x|k; \beta)$$

EM Algorithm: Example

Example

Estimate the priors p_k of classes $k = 1, 2, \dots, K$ from the observation x where the probability density function of observations is given by the marginal over all classes:

$$p(x; \beta) = \sum_{k=1}^K p_k p(x|k; \beta)$$


Application of the EM scheme:

- observable random measurement: x
- hidden random measurement: k
- parameter set: $\theta = \{p_k; k = 1, \dots, K\}$

EM Algorithm: Example (cont.)

Example


For illustration purposes let us consider three classes. If events, in this case 2-D points, are labeled by colors representing different classes, the priors are easily estimated by relative frequencies.



EM Algorithm: Example (cont.)

Example (cont.)

The problem appears quite difficult, if the class (color) labels are missing.



EM Algorithm: Example (cont.)

Example

The Kullback-Leibler statistics results in:

$$Q\left(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}\right) = \sum_{k=1}^K a_k \log \left(\hat{p}_k^{(i+1)} p(x|k; \beta) \right)$$

EM Algorithm: Example (cont.)

Example

The Kullback-Leibler statistics results in:

$$\begin{aligned} Q\left(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}\right) &= \sum_{k=1}^K a_k \log \left(\hat{p}_k^{(i+1)} p(x|k; \beta) \right) \\ &= \sum_{k=1}^K a_k \left(\log \hat{p}_k^{(i+1)} + \log p(x|k; \beta) \right) \end{aligned}$$

EM Algorithm: Example (cont.)

Example

The Kullback-Leibler statistics results in:

$$\begin{aligned}
 Q\left(\hat{\theta}^{(i)}; \hat{\theta}^{(i+1)}\right) &= \sum_{k=1}^K a_k \log \left(\hat{p}_k^{(i+1)} p(x|k; \beta) \right) \\
 &= \sum_{k=1}^K a_k \left(\log \hat{p}_k^{(i+1)} + \log p(x|k; \beta) \right) \\
 &= \sum_{k=1}^K a_k \log \hat{p}_k^{(i+1)} + \sum_{k=1}^K a_k \log p(x|k; \beta)
 \end{aligned}$$

where

$$a_k = \frac{\hat{p}_k^{(i)} p(x|k; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}$$

EM Algorithm: Example (cont.)

Example (cont.)

Now we compute the gradient with respect to $\hat{p}_k^{(i+1)}$ and its zero crossing.
The final estimator for priors now is a closed form iteration scheme:

$$\hat{p}_k^{(i+1)} = \frac{\frac{\hat{p}_k^{(i)} p(x|k; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}}{\sum_l \frac{\hat{p}_l^{(i)} p(x|l; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}}$$

EM Algorithm: Example (cont.)

Example (cont.)

Now we compute the gradient with respect to $\hat{p}_k^{(i+1)}$ and its zero crossing.
The final estimator for priors now is a closed form iteration scheme:

$$\hat{p}_k^{(i+1)} = \frac{\frac{\hat{p}_k^{(i)} p(x|k; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}}{\sum_l \frac{\hat{p}_l^{(i)} p(x|l; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}} = \frac{\hat{p}_k^{(i)} p(x|k; \beta)}{\sum_j \hat{p}_j^{(i)} p(x|j; \beta)}$$

Initialization of Priors:

- Use prior medical knowledge about the frequency of tissue classes
- If no prior information is available, assume uniform distribution

Lessons Learned

- Standard parameter estimation method: ML estimation
- If the prior pdf of the parameters is known: MAP estimation
- In the presence of latent random variables: EM algorithm
- EM advantages: decomposition of search space, closed form iteration schemes
- EM disadvantage: slow convergence, local method



**Pattern
Recognition
Lab**



**FRIEDRICH-ALEXANDER
UNIVERSITÄT
ERLANGEN-NÜRNBERG**

TECHNISCHE FAKULTÄT

Next Time in

Pattern Recognition



Further Readings


- Easy to understand tutorial on ML estimation:

In Jae Myung:

 [Tutorial on maximum likelihood estimation](#),
Journal of Mathematical Psychology, 47(1):90-100, 2003

- The classics for an introduction to the EM algorithm is:

A. P. Dempster, N. M. Laird, D. B. Rubin:

 [Maximum Likelihood Estimation from Incomplete Data via the EM Algorithm](#),
Journal of the Royal Statistical Society, Series B, 39(1):1-38.

- W. H. Press, S. A. Teukolsky, W. T. Vetterling, B. P. Flannery:

 [Numerical Recipes](#),
3rd Edition, Cambridge University Press, 2007.

Comprehensive Questions

- What is a Gaussian Mixture Model?
- What is the missing information principle?
- Write down the key equation for the EM algorithm:
- Is the EM algorithm a local or a global parameter estimation method?