OUTPUT L: SPSS

```
Run MATRIX procedure:

*************** PROCESS Procedure for SPSS Version 3.00 *****************

          Written by Andrew F. Hayes, Ph.D.       www.afhayes.com
    Documentation available in Hayes (2018). www.guilford.com/p/hayes3

**************************************************************************
Model  : 7
    Y  : use4
    X  : mbrp
    M  : crave2
    W  : bdi0

Covariates:
 crave0   treathrs

Sample
Size:  168

**************************************************************************
OUTCOME VARIABLE:
 crave2

Model Summary
          R       R-sq        MSE          F        df1        df2          p
      .5140      .2642      .7277    11.6319     5.0000   162.0000      .0000

Model
              coeff         se          t          p       LLCI       ULCI
constant     1.0385      .4701     2.2090      .0286      .1102     1.9668
mbrp          .5872      .5241     1.1204      .2642     -.4478     1.6222
bdi0         1.1221      .2762     4.0625      .0001      .5767     1.6675
Int_1        -.9485      .4235    -2.2398      .0265    -1.7847     -.1122
crave0        .1920      .0735     2.6138      .0098      .0470      .3371
treathrs     -.0177      .0103    -1.7190      .0875     -.0380      .0026

Product terms key:
 Int_1    :        mbrp     x        bdi0

Test(s) of highest order unconditional interaction(s):
       R2-chng          F        df1        df2          p
X*W      .0228     5.0166     1.0000   162.0000      .0265
----------
    Focal predict: mbrp     (X)
          Mod var: bdi0     (W)

Conditional effects of the focal predictor at values of the moderator(s):

       bdi0     Effect         se          t          p       LLCI       ULCI
      .9020     -.2683      .1850    -1.4500      .1490     -.6336      .0971
     1.1900     -.5414      .1375    -3.9384      .0001     -.8129     -.2699
     1.5180     -.8525      .1941    -4.3923      .0000    -1.2358     -.4692

**************************************************************************
```

OUTCOME VARIABLE:
 use4

Model Summary

R	R-sq	MSE	F	df1	df2	p
.7304	.5335	.2105	46.6070	4.0000	163.0000	.0000

Model

	coeff	se	t	p	LLCI	ULCI
constant	1.1298	.2150	5.2545	.0000	.7052	1.5544
mbrp	.0926	.0773	1.1979	.2327	-.0601	.2453
crave2	.4810	.0402	11.9547	.0000	.4015	.5604
crave0	-.0884	.0397	-2.2246	.0275	-.1668	-.0099
treathrs	-.0199	.0056	-3.5720	.0005	-.0309	-.0089

****************** DIRECT AND INDIRECT EFFECTS OF X ON Y *****************

Direct effect of X on Y

Effect	se	t	p	LLCI	ULCI
.0926	.0773	1.1979	.2327	-.0601	.2453

Conditional indirect effects of X on Y:

INDIRECT EFFECT:
 mbrp -> crave2 -> use4

bdi0	Effect	BootSE	BootLLCI	BootULCI
.9020	-.1290	.0770	-.2869	.0183
1.1900	-.2604	.0862	-.4458	-.1090
1.5180	-.4100	.1367	-.7080	-.1767

Index of moderated mediation:

	Index	BootSE	BootLLCI	BootULCI
bdi0	-.4562	.2172	-.9463	-.0934

********************** ANALYSIS NOTES AND ERRORS ************************

Level of confidence for all confidence intervals in output:
  95.0000

Number of bootstrap samples for percentile bootstrap confidence intervals:
  10000

W values in conditional tables are the 16th, 50th, and 84th percentiles.

------ END MATRIX -----