

# PROCESS Documentation Addendum

PROCESS is documented in Appendices A and B of the second edition of *Introduction to Mediation, Moderation, and Conditional Process Analysis*. This addendum to the documentation describes options and features added to PROCESS version 3 since the printing of the book in December 2017. The most recent version of this addendum was produced on July 26, 2018.

## Dichotomous Y

(Version 3.1)

With the release of version 3.1, PROCESS will accept a dichotomous outcome variable  $Y$ . No input is needed from the user to specify that  $Y$  is dichotomous; PROCESS figures this out on its own. When PROCESS sees only two values in the variable specified as  $Y$ , the estimation of  $Y$  is conducted using logistic regression, modeling the probability of the event coded in  $Y$ , with the event being modeled represented in the data with the largest numerical code in the variable specified as  $Y$ . For example, if  $Y$  is coded 0 and 1, the probability of  $Y = 1$  is estimated, and all effects should be interpreted accordingly. All regression coefficients for the model of  $Y$  are logistic regression coefficients and are on a log-odds metric, including confidence intervals for these coefficients. These can be exponentiated to yield effects on an odds ratio metric.

Inferences for each regression coefficient in the model of  $Y$  are based on ratio of the estimate of the coefficient to its standard error.  $P$ -values and confidence intervals are based on the assumption of a normally distributed sampling distribution of the regression coefficient. Hence, the hypothesis test that a regression coefficient is equal to zero is equivalent to a Wald test. Inference for the complete model of  $Y$  is based a likelihood ratio test with degrees of freedom equal to the number of predictors in the model of  $Y$ .

When the model of  $Y$  includes a moderation component, the section of output for the model of  $Y$  labelled “test for highest-order unconditional interaction(s)” is based on a likelihood ratio test, comparing the fit of the model of  $Y$  that includes the interaction compared to a model that excludes it. For single-degree-of-freedom tests of interactions, this test can produce a  $p$ -value for the interaction that is different than the  $p$ -value produced for the ratio of the regression coefficient to its standard error, as likelihood ratio and Wald tests are equivalent only asymptotically and can produce different results in finite samples.

Although likelihood ratio tests are used for tests of unconditional interactions, tests of conditional interactions as well as tests of conditional effects of  $X$  when  $X$  is specified as multicategorical are Wald tests.

When the **plot** option is used with a dichotomous  $Y$ , estimates of  $Y$  for combinations of focal predictor and moderator(s) are estimated log odds of the event for those combinations. PROCESS also produces the estimated probability of the event under the label “prob.”

Indirect effects of  $X$  when  $Y$  is dichotomous are calculated as always as the product of the effect of  $X$  on the mediator  $M$  and the effect of mediator  $M$  on  $Y$  controlling for  $X$ . The indirect effect (and direct effect of  $X$ ) is on a log-odds metric given that the effect of the mediator on  $Y$  is a logistic regression coefficient. Because the regression coefficient for  $X$  in a model of  $Y$  without the mediators included is not equal to the sum of the direct and indirect effects of  $X$ , the **total** option is not available with a dichotomous  $Y$ . The **effsize** option is also disabled for models with a dichotomous  $Y$ .

Logistic regression is computationally more intensive than ordinary least squares regression analysis. When combined with repeated model estimation using bootstrapping for inference about indirect effects, time to produce output can be considerable even in modest sample sizes. Expect PROCESS to take longer to show results than when  $Y$  is not dichotomous. A good strategy when estimating a model with indirect effects is to first set the number of bootstrap samples to a smaller number than the default of 5000 (e.g., **boot=1000**), even zero, to make sure the model will estimate and PROCESS will produce output. Once you are satisfied, increase the number of bootstrap samples to generate the final result that you interpret.

In addition, the logistic regression estimation module programmed in PROCESS is more susceptible to matrix inversion errors and also errors produced by “perfect separation” (as it is called in the logistic regression literature). These errors are more likely to occur when  $X$  and/or moderators  $W$  or  $Z$  are multicategorical or when the event is rare or very frequent in the data. If you see INV, EXP, or other errors in the SPSS output or SAS log file, do not interpret the output.

The user has control over the maximum number of iterations before PROCESS provides a solution as well as the convergence criterion. The convergence criterion is met when changes to the logistic regression coefficients result in a change in the likelihood of less than the specified criterion. At that point, the iteration stops and the solution is provided. A failure to converge can sometimes be rectified by increasing the number of iterations or increasing the convergence criterion. However, doing so will increase computational time, perhaps dramatically. This can be done with the **iterate** and **converge** options. The defaults are 100 and .0001, respectively (i.e., **iterate=100** and **converge=.0001**).