

Module - I

Introduction To Android (An)

- * Android is a sw package & linux based os for mob devices such as tablet comp & Smart Phns.
- * Developed by Google & later the OHA. (Open Handset Alliance).
- * Java lang is mainly used to write the android code even though other langs can be used.
- * open source (source code is visible to public & can be edit)
- * Anyone can customize the (An) system.
- * There are a lot of mob appli~ that can be chosen by the consumer.
- * It provides many interesting features like weathr details, opening screen, etc.
- * categories of (An) appli~ :
 - Entertainment → netflix, Amazon prime
 - Commun → whatsapp, telegram
 - Productivity → google drive, proot hub
 - Personalization → wallpapers, Launchers
 - Music & Audio → MX player, Youtube music
 - Social media & video → FB, Instagram.

⇒ Android history:

- * Initially Andy Rubin founded (An) in corporation in 2003.
- * In 2005, google acquired (An) in corporation.
- * The key employees of (An) in corporation are Andy Rubin, Rich Miner, Chris White, Eric Rickerson.
- * In 2007, google announces the development of android OS.
- * In 2008, HTC launched the 1st (An) mob.
- * (An) is the nick name of Andy Rubin given by reporters bcz of his love to robots.

Version	codename	Features
1.5	Cupcake	<ul style="list-style-type: none"> • Soft Keyboard • Advanced media recording (img, video) • widget, live folders
1.6	Donut	<ul style="list-style-type: none"> • Advanced search capability • Text to speech
2.0.1	Eclair	<ul style="list-style-type: none"> • Improved google maps
2.2	Froyo	<ul style="list-style-type: none"> • USB tethering • wifi hotspot

2.3

gingerbread

installation of apps from SD card.

4.0

icecream sandwich

HD screen, unlock screen in different ways

4.4

kitkat

more sensors, GPS support.

10


space for foldable phone.

11

new Permission control.

⇒ (An) Architecture / (An) s/w stack:

It is categorized into 5 parts -






Fig: Android Architecture

1) Linux kernel:

It is the heart of Android architecture that exists at the root of Android architecture. Responsible for device drivers, power management, memory management, device management & resource access.

2) Native Libraries:

On the top of Linux kernel, there are native libraries like C++ (responsible for browser, SQLite (for DB), FreeType (for font), Media (for playing & recording audio & video).

3) Android Runtime:

- * Here, there are core libraries & JVM (Dalvik virtual machine) which is responsible to run Android application.
- * JVM is like JVM but it is optimized for mobile devices.
- * It consumes less memory & provides fast performance.
- * Dalvik VM takes the generated Java class files & combines them into 1 or more Dalvik executable (dex) files.

4) Android Framework:

- * It includes Android APIs like UI, telephony, resources, loc, content providers, & package manager.
- * Provides a lot of classes & interfaces for Android application development.

5) APPLI :

- * on the top of (An) framework, there are appli.
- * All appli. like home, contact, settings, games, browsers are using (An) framework that uses (An) runtime & libraries.
- * (An) runtime & native libraries are using Linux kernel.

=> (An) Java packages :

- * android.app → implements appli. model for (An).
- * android.app.admin → provides device administration features at the system level
- * android.accounts → provides class to manage accounts like google, fb.
- * android.database → contains class to explore data returned through a content provider.
- * android.animation → to apply animation for diff obj, animation class & methods are included.
- * android.content → manages access to central ~~repository~~ repository of data.
- * android.text → provides text processing class.

→ (An) Studio =

It is the official integrated development envrmt (IDE) for (An) app development. Based on IntelliJ IDE, a Java IDE for s/w.

=> Components of (An) / Fundamental components :

There are some necessary building blocks that an (An) appli. consist of.

1) Activity :

- represents a single screen with a user interface & generally contains 1 more view
- implemented as a subclass of `Activity` class
- UI of our appli. is built around 1 more : extensions of `Activity` class.
- public class MainActivity extends Activity {
 - - -
}
- user signature → eg.

2) Service :

- background process that can run for a long time.
- 2 types → local & remote
- local Service is accessed from within the appli. whereas remote Service is

accessed remotely from other app running on same device
eg → music
↳ public class ServiceName extends Service { }

3) view:

↳ UI element like btn, label, textfield, etc
↳ Anything that you see is a view.
↳ public class ViewName extends View { }

4) Intent:

↳ used to invoke components
↳ used to start the service, launch an activity, display a web page.
↳ passed int-obj → msg → passing framework.

5) Content providers:

↳ used to manage & persist the app's data. also typically interacts with SQL DB.
↳ should be a sub-cls of cls Content providers
↳ public cls CupName extends Cup { }
↳ public void onCreate() { }

6) Fragment:

↳ have like parts of activity
↳ an activity can display 1 or more fragments on the screen at same time.

1) AndroidManifest.xml:

↳ contains info about activities, content providers, permissions, etc
↳ It is like web.xml file in Java EE

=> (An) virtual device (AVD):

- * It is an emulator configuration that allows developers to test the app by simulating the real device capabilities.
 - * we can configure the AVD by specifying the hardware & I/O options.
 - * AVD manager enables an easy way of creating & managing the AVD with its graphical interface.
 - * Steps to create an AVD from AVD manager graphical interface —
 - Go to window → AVD manager & select virtual devices.
 - Click on New to create a virtual device
 - Give it some name & select target ~~an~~ platform from the dropdown list
 - Click on 'create AVD' & we are done.
- (Grab mob resources & components from manifest & use them in manifest).

→ Stx of (An) Applic :

(An) applic in eclipse / in any development tool has a pre-defined Stx with code & resource organized into a hierarchy.

Source components -

- 1) src - Stands for source code, contains Java source files
- 2) gen - Stands for generated Java library, This library is for (An) internal use only
- 3) assets - used to store raw asset files
- 4) android 4.2.2 - (An) framework library is stored here.
- 5) libs - contains private libraries.
- 6) res - Stands for resource files.
- 7) AndroidManifest.xml - (An) definition file.
- 8) project.properties.
- 9) MainLayout.xml, etc.
- 10) Proguard-project.txt.

⇒ Applic Life cycle :

* It is controlled by 7 methods of android.app.Activity class. (An) activity is the Rules of Context Thewrapper class.

obj
↑
Context
↑
Context wrapper
↑
Context wrapper
↑
Activity.

* 7 lifecycle methods -

- 1) onCreate - called when activity (A) is first created.
- 2) onStart - called when (A) is becoming visible to the user.
- 3) onPause - called when (A) is not visible to the user.
- 4) onResume - called when (A) will start interacting with the user.
- 5) onStop - called when (A) is no longer visible to the user.
- 6) onDestroy - called after (A) is stopped, prior (An) attempt to start
- 7) onDestory - called b4 the (A) is destroyed.

