

Literature Review: CSE 6730 Project 1

Chris Dunlap, Allen Koh, Matt May

February 2016

A variety of techniques have been used to model pedestrian movement. Cellular automata, lattice gas, social force, fluid-dynamic, agent-based, game-theoretic, and animal experimentation-based approaches have been used [10]. As noted by Zheng, Zhong, and Liu [10], models often encounter or attempt to model several common phenomena: clogging, side-stepping, lane formation, and herding behavior, among them.

These phenomena manifest themselves in different ways and at different magnitudes depending on the system being modeled. In one of the early explorations of 2D cellular automata to simulating vehicular traffic flow, Biham and Middleton [1] note the presence of a sharp *jamming transition* in which all cars in the simulation transition from moving at maximal speed to being stuck. Similar effects were noted in simulations of bi-directional pedestrian movement, with Weifeng, Lizhong, and Weicheng [9] finding that as total pedestrian density increases, a critical value is reached at which the system transitions into a jammed state where only a few pedestrians are able to proceed.

In a slightly different take on the problem, Okazaki and Matsushita [8] modeled pedestrian evacuation using Coulomb’s Law, with actors magnetically moving toward their goals and away from obstacles that would lead to collisions. In another application of equations of natural phenomena, Helbing [4] derived fluid dynamic equations for explaining the movement of pedestrian crowds, observing phenomena such as the development of lanes, jamming, and crossing. Helbing [6] further notes an explicit “faster-is-slower” effect, in which attempting to move faster results in a smaller average speed of leaving at high pedestrian density in evacuation scenarios.

In a more recent study, Helbing et al. [5] uses a “social force” model, which states that pedestrians operate in some sense automatically when reacting to obstacles and other pedestrians, applying strategies that have been learned to be most effective over time. Several suggestions are made to alleviate the three most common problems in pedestrian crowds: counterflows, bottlenecks, and intersecting flows. The presence of strategically placed obstacles are found to actually reduce these negative phenomena, leading to improved flow.

Building on previous cellular automata-based models, Burstedde et al. [2] introduce a *floor field*, a secondary grid of cells which underlies the main grid and acts as a substitute for pedestrian intelligence. These fields can be either static or dynamic, and are capable of promoting the avoidance of jams, as well as simulating attractive effects, in which pedestrians are more likely to

follow in the paths of pedestrians ahead of them.

Taking a more algorithmic approach, Fang et al. [3] have designed a modified ant colony optimization (ACO) algorithm for optimizing pedestrian evacuation, seeking to minimize evacuation time, evacuation distance, and congestion. Kemloh Wagoum, Seyfried, and Holl [7] utilize an observation principle approach in modeling pedestrian evacuation, in which pedestrians first observe their environment and then make a final decision on strategy based on obtained data.

References

- [1] Ofer Biham, Alan Middleton, and Dov Levine. Self-organization and a dynamical transition in traffic-flow models. *Physical Review A*, 46(10):R6124, 1992.
- [2] Carsten Burstedde, Kai Klauck, Andreas Schadschneider, and Johannes Zittartz. Simulation of pedestrian dynamics using a two-dimensional cellular automaton. *Physica A: Statistical Mechanics and its Applications*, 295(3):507–525, 2001.
- [3] Zhixiang Fang, Xinlu Zong, Qingquan Li, Qiuping Li, and Shengwu Xiong. Hierarchical multi-objective evacuation routing in stadium using ant colony optimization approach. *Journal of Transport Geography*, 19(3):443–451, 2011.
- [4] Dirk Helbing. A fluid dynamic model for the movement of pedestrians. *arXiv preprint cond-mat/9805213*, 1998.
- [5] Dirk Helbing, Lubos Buzna, Anders Johansson, and Torsten Werner. Self-organized pedestrian crowd dynamics: Experiments, simulations, and design solutions. *Transportation science*, 39(1):1–24, 2005.
- [6] Dirk Helbing, Illés Farkas, and Tamas Vicsek. Simulating dynamical features of escape panic. *Nature*, 407(6803):487–490, 2000.
- [7] Armel Ulrich Kemloh Wagoum, Armin Seyfried, and Stefan Holl. Modeling the dynamic route choice of pedestrians to assess the criticality of building evacuation. *Advances in Complex Systems*, 15(07):1250029, 2012.

- [8] Shigeyuki Okazaki and Satoshi Matsushita. A study of simulation model for pedestrian movement with evacuation and queuing. In *International Conference on Engineering for Crowd Safety*, pages 271–280, 1993.
- [9] Fang Weifeng, Yang Lizhong, and Fan Weicheng. Simulation of bi-direction pedestrian movement using a cellular automata model. *Physica A: Statistical Mechanics and its Applications*, 321(3):633–640, 2003.
- [10] Xiaoping Zheng, Tingkuan Zhong, and Mengting Liu. Modeling crowd evacuation of a building based on seven methodological approaches. *Building and Environment*, 44(3):437–445, 2009.