

# Certification of Arctic Termination

Adam Koprowski

Eindhoven University of Technology  
Department of Mathematics and Computer Science

(joint work with Frédéric Blanqui and Johannes Waldmann)

7 March 2008  
TCS seminar, VU

## 1 CoLoR

- Background: termination of rewriting
- Why?... motivation
- How?... CoLoR's approach to certification
- When?... history of the project
- What?... overview of the content
- Related work
- Certified competition

## 2 Arctic Termination

- Monotone Algebras
- Polynomial Interpretations
- Matrix Interpretations
- Arctic Interpretations
- Arctic Below Zero Interpretations
- Performance & Summary

## 1 CoLoR

- Background: termination of rewriting
- Why?... motivation
- How?... CoLoR's approach to certification
- When?... history of the project
- What?... overview of the content
- Related work
- Certified competition

## 2 Arctic Termination

- Monotone Algebras
- Polynomial Interpretations
- Matrix Interpretations
- Arctic Interpretations
- Arctic Below Zero Interpretations
- Performance & Summary

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned}0 + y &= y \\ s(x) + y &= s(x + y)\end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned}0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y)\end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned} 0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y) \end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned} s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ s(s(0 + s(s(0)))) &\rightarrow s(s(s(s(0)))) \end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned} 0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y) \end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned} s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ &s(s(0 + s(s(0)))) \rightarrow s(s(s(s(0)))) \end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned}0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y)\end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned}s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ &s(s(0 + s(s(0)))) \rightarrow s(s(s(s(0))))\end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.



# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned}0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y)\end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned}s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ s(s(0 + s(s(0)))) &\rightarrow s(s(s(s(0))))\end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned} 0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y) \end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned} s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ &s(s(0 + s(s(0)))) \rightarrow s(s(s(s(0)))) \end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Introduction to term rewriting

## Example (Plus)

Let's define plus in Peano arithmetic.

$$\begin{aligned}0 + y &\rightarrow y \\ s(x) + y &\rightarrow s(x + y)\end{aligned}$$

## Example (Computing with plus)

Now let us do some some maths... how about  $2 + 2$ ?

$$\begin{aligned}s(s(0)) + s(s(0)) &\rightarrow s(s(0) + s(s(0))) \rightarrow \\ &s(s(0 + s(s(0)))) \rightarrow s(s(s(s(0))))\end{aligned}$$

## Definition

A TRS is **terminating** iff it does not admit infinite reductions.

# Termination of rewriting

## Termination of rewriting:

- **Is undecidable.**
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- There exists a number of tools for proving termination.
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- **Is an important topic in term rewriting.**
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- There exists a number of tools for proving termination.
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- There exists a number of tools for proving termination.
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- **Recently the emphasis is on automation.**
- There exists a number of tools for proving termination.
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- **There exists a number of tools for proving termination.**
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.



# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- There exists a number of tools for proving termination.
- **Stimulated by an annual termination competition.**
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

# Termination of rewriting

## Termination of rewriting:

- Is undecidable.
- Is an important topic in term rewriting.
- Many methods exist and new ones are constantly being developed.
- Recently the emphasis is on automation.
- There exists a number of tools for proving termination.
- Stimulated by an annual termination competition.
- Tools (and proofs that they produce) are getting more and more complex, so reliability is an issue.

- Certification of results of termination provers.
- Common proof format for termination provers:
  - common tools (proof presentation, manipulation, ...),
  - control language for provers (integration of tools)
- Extension of proof assistance kernels.

- Certification of results of termination provers.
- **Common proof format for termination provers:**
  - common tools (proof presentation, manipulation, ...),
  - control language for provers (integration of tools)
- Extension of proof assistance kernels.

- Certification of results of termination provers.
- Common proof format for termination provers:
  - common tools (proof presentation, manipulation, ...),
    - control language for provers (integration of tools)
- Extension of proof assistance kernels.

- Certification of results of termination provers.
- Common proof format for termination provers:
  - common tools (proof presentation, manipulation, ...),
  - **control language for provers (integration of tools)**
- Extension of proof assistance kernels.

- Certification of results of termination provers.
- Common proof format for termination provers:
  - common tools (proof presentation, manipulation, ...),
  - control language for provers (integration of tools)
- Extension of proof assistance kernels.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

## How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.



# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`

CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.

How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's approach to certification

CoLoR

`http://color.loria.fr`


CoLoR: Coq Library on Rewriting and Termination.

Goal: certification of termination proofs produced by various termination provers.



How to certify termination results?

- Possibility: certification of tools source code.  
⇒ difficult, tool dependent, extra work with every change, ...
- CoLoR's approach:
  - TPG: common format for termination proofs.
  - Tools output proofs in TPG format.
  - CoLoR: a Coq library of results on termination.
  - Rainbow: a tool for translation from proofs in TPG format to Coq proofs, using results from CoLoR.

# CoLoR's architecture overview




# CoLoR's architecture overview





# CoLoR's architecture overview



- Project started (Blanqui) March 2004
- First release March 2005
- First certified proofs July 2006
- First certification workshop May 2007
- First certified competition June 2007

# History

- Project started (Blanqui) March 2004
- **First release** March 2005
- First certified proofs July 2006
- First certification workshop May 2007
- First certified competition June 2007

# History

- Project started (Blanqui) March 2004
- First release March 2005
- **First certified proofs** **July 2006**
- First certification workshop May 2007
- First certified competition June 2007

# History

- Project started (Blanqui) March 2004
- First release March 2005
- First certified proofs July 2006
- **First certification workshop** **May 2007**
- First certified competition June 2007

# History

- Project started (Blanqui) March 2004
- First release March 2005
- First certified proofs July 2006
- First certification workshop May 2007
- First certified competition June 2007

- Termination criteria:

- polynomial interpretations [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- matrix interpretations [Koprowski, Zantema]
- arctic interpretations [Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs [Blanqui]
- rule elimination [Blanqui]
- arguments filtering [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]

- Termination criteria:

- polynomial interpretations**

- multiset ordering
  - recursive path ordering
  - higher-order recursive path ordering
  - dependency graph cycles
  - matrix interpretations**
  - arctic interpretations**

[Hinderer]

[Koprowski]

[Coupet-Grimal, Delobel]

[Koprowski]

[Blanqui]

[Koprowski, Zantema]

[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
  - rule elimination
  - arguments filtering
  - conversion from algebraic to varyadic terms

[Blanqui]

[Blanqui]

[Blanqui]

[Blanqui]



- Termination criteria:

- polynomial interpretations**

[Hinderer]

- multiset ordering**

[Koprowski]

- recursive path ordering

[Coupet-Grimal, Delobel]

- higher-order recursive path ordering

[Koprowski]

- dependency graph cycles

[Blanqui]

- matrix interpretations**

[Koprowski, Zantema]

- arctic interpretations**

[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs

[Blanqui]

- rule elimination

[Blanqui]

- arguments filtering

[Blanqui]

- conversion from algebraic to varyadic terms

[Blanqui]

- Termination criteria:

- **polynomial interpretations**
- multiset ordering
- **recursive path ordering**
- higher-order recursive path ordering
- dependency graph cycles
- **matrix interpretations**
- **arctic interpretations**

[Hinderer]

[Koprowski]

[Coupet-Grimal, Delobel]

[Koprowski]

[Blanqui]

[Koprowski, Zantema]

[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
- rule elimination
- arguments filtering
- conversion from algebraic to varyadic terms

[Blanqui]

[Blanqui]

[Blanqui]

[Blanqui]

- Termination criteria:

- **polynomial interpretations**
- multiset ordering
- recursive path ordering
- **higher-order recursive path ordering**
- dependency graph cycles
- **matrix interpretations**
- **arctic interpretations**

[Hinderer]  
[Koprowski]  
[Coupet-Grimal, Delobel]  
**[Koprowski]**  
[Blanqui]  
[Koprowski, Zantema]  
[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
- rule elimination
- arguments filtering
- conversion from algebraic to varyadic terms

[Blanqui]  
[Blanqui]  
[Blanqui]  
[Blanqui]

- Termination criteria:

- polynomial interpretations
- multiset ordering
- recursive path ordering
- higher-order recursive path ordering
- dependency graph cycles
- matrix interpretations
- arctic interpretations

[Hinderer]  
[Koprowski]  
[Coupet-Grimal, Delobel]  
[Koprowski]  
[Blanqui]  
[Koprowski, Zantema]  
[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
- rule elimination
- arguments filtering
- conversion from algebraic to varyadic terms

[Blanqui]  
[Blanqui]  
[Blanqui]  
[Blanqui]

- Termination criteria:

- **polynomial interpretations**
- multiset ordering
- recursive path ordering
- higher-order recursive path ordering
- dependency graph cycles
- **matrix interpretations**
- arctic interpretations

[Hinderer]  
[Koprowski]  
[Coupet-Grimal, Delobel]  
[Koprowski]  
[Blanqui]  
[Koprowski, Zantema]  
[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
- rule elimination
- arguments filtering
- conversion from algebraic to varyadic terms

[Blanqui]  
[Blanqui]  
[Blanqui]  
[Blanqui]

- Termination criteria:

- **polynomial interpretations**
- multiset ordering
- recursive path ordering
- higher-order recursive path ordering
- dependency graph cycles
- **matrix interpretations**
- **arctic interpretations**

[Hinderer]  
[Koprowski]  
[Coupet-Grimal, Delobel]  
[Koprowski]  
[Blanqui]  
[Koprowski, Zantema]  
[Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs
- rule elimination
- arguments filtering
- conversion from algebraic to varyadic terms

[Blanqui]  
[Blanqui]  
[Blanqui]  
[Blanqui]

- Termination criteria:

- **polynomial interpretations** [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- **matrix interpretations** [Koprowski, Zantema]
- **arctic interpretations** [Koprowski, Waldmann]

- Transformation techniques:

- dependency pairs [Blanqui]
- rule elimination [Blanqui]
- arguments filtering [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]

- Termination criteria:

- **polynomial interpretations** [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- **matrix interpretations** [Koprowski, Zantema]
- **arctic interpretations** [Koprowski, Waldmann]

- Transformation techniques:

- **dependency pairs** [Blanqui]
- **rule elimination** [Blanqui]
- arguments filtering [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]



- Termination criteria:

- **polynomial interpretations** [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- **matrix interpretations** [Koprowski, Zantema]
- **arctic interpretations** [Koprowski, Waldmann]

- Transformation techniques:

- **dependency pairs** [Blanqui]
- **rule elimination** [Blanqui]
- arguments filtering [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]

- Termination criteria:

- **polynomial interpretations** [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- **matrix interpretations** [Koprowski, Zantema]
- **arctic interpretations** [Koprowski, Waldmann]

- Transformation techniques:

- **dependency pairs** [Blanqui]
- **rule elimination** [Blanqui]
- **arguments filtering** [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]

- Termination criteria:

- **polynomial interpretations** [Hinderer]
- multiset ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- higher-order recursive path ordering [Koprowski]
- dependency graph cycles [Blanqui]
- **matrix interpretations** [Koprowski, Zantema]
- **arctic interpretations** [Koprowski, Waldmann]

- Transformation techniques:

- **dependency pairs** [Blanqui]
- **rule elimination** [Blanqui]
- arguments filtering [Blanqui]
- **conversion from algebraic to varyadic terms** [Blanqui]

- General libraries:

- matrices [Koprowski]
- semi-rings [Koprowski,Zantema]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- lists, vectors, relations, etc.

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- **matrices**

[Koprowski]

- semi-rings

[Koprowski,Zantema]

- simply typed lambda-terms

[Koprowski]

- finite multisets

[Koprowski]

- varyadic terms

[Blanqui]

- algebraic terms with symbols of fixed arity

[Hinderer, Blanqui]

- integer polynomials with multiple variables

[Hinderer]

- lists, vectors, relations, etc.

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.

- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices
- **semi-rings**
- simply typed lambda-terms
- finite multisets
- varyadic terms
- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
[Koprowski]  
[Koprowski]  
[Blanqui]  
[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices
- semi-rings
- **simply typed lambda-terms**
- finite multisets
- varyadic terms
- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
**[Koprowski]**  
[Koprowski]  
[Blanqui]  
[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices
- semi-rings
- simply typed lambda-terms
- **finite multisets**
- varyadic terms
- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
[Koprowski]  
**[Koprowski]**  
[Blanqui]  
[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.



- General libraries:

- matrices
- semi-rings
- simply typed lambda-terms
- finite multisets
- **varyadic terms**

- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
[Koprowski]  
[Koprowski]  
[Blanqui]

[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices
- semi-rings
- simply typed lambda-terms
- finite multisets
- varyadic terms
- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
[Koprowski]  
[Koprowski]  
[Blanqui]  
[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices
- semi-rings
- simply typed lambda-terms
- finite multisets
- varyadic terms
- algebraic terms with symbols of fixed arity
- integer polynomials with multiple variables
- lists, vectors, relations, etc.

[Koprowski]  
[Koprowski,Zantema]  
[Koprowski]  
[Koprowski]  
[Blanqui]  
[Hinderer, Blanqui]  
[Hinderer]

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices [Koprowski]
- semi-rings [Koprowski,Zantema]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- **lists, vectors, relations, etc.**

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices [Koprowski]
- semi-rings [Koprowski,Zantema]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- lists, vectors, relations, etc.

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library.
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- General libraries:

- matrices [Koprowski]
- semi-rings [Koprowski,Zantema]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- lists, vectors, relations, etc.

- In total:

- **≈ 50.000 lines of code (more than half the size of the standard library.**
- ≈ 1.000 definitions and ≈ 2.500 lemmas.

- General libraries:

- matrices [Koprowski]
- semi-rings [Koprowski,Zantema]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- lists, vectors, relations, etc.

- In total:

- $\approx 50.000$  lines of code (more than half the size of the standard library).
- $\approx 1.000$  definitions and  $\approx 2.500$  lemmas.

- CoLoR project

Authors: Blanqui, ...

Tool: T-TPA, ...

Proof assistant: Coq

- A3PAT project

Authors: Contejean, ...

Tool: CiME, ...

Proof assistant: Coq

- Isabelle/HOL termination checker

Authors: Bulwahn, Krauss, Nipkow, ...

Tool: T<sub>T</sub>T

Proof assistant: Isabelle/HOL



- CoLoR project

Authors: Blanqui, ...

Tool: T-TPA, ...

Proof assistant: Coq

- A3PAT project

Authors: Contejean, ...

Tool: CiME, ...

Proof assistant: Coq

- Isabelle/HOL termination checker

Authors: Bulwahn, Krauss, Nipkow, ...

Tool: T<sub>T</sub>T

Proof assistant: Isabelle/HOL

- CoLoR project

Authors: Blanqui, ...

Tool: T-TPA, ...

Proof assistant: Coq

- A3PAT project

Authors: Contejean, ...

Tool: CiME, ...

Proof assistant: Coq

- Isabelle/HOL termination checker

Authors: Bulwahn, Krauss, Nipkow, ...

Tool: T<sub>T</sub>T

Proof assistant: Isabelle/HOL

- In the termination competition in 2007 a new “certified” category was introduced.
- Participants:
  - CIME + A3PAT
  - TPA + CoLoR
  - $T_T T_2$  + CoLoR

- In the termination competition in 2007 a new “certified” category was introduced.
- Participants:
  - CiME + A3PAT
  - TPA + CoLoR
  - TT<sub>2</sub> + CoLoR

- In the termination competition in 2007 a new “certified” category was introduced.
- Participants:

• CiME + A3PAT	317
• TPA + CoLoR	354
• TT <sub>2</sub> + CoLoR	289



## 1 CoLoR

- Background: termination of rewriting
- Why?... motivation
- How?... CoLoR's approach to certification
- When?... history of the project
- What?... overview of the content
- Related work
- Certified competition

## 2 Arctic Termination

- Monotone Algebras
- Polynomial Interpretations
- Matrix Interpretations
- Arctic Interpretations
- Arctic Below Zero Interpretations
- Performance & Summary

# Monotone algebras

## Definition (Monotonicity)

An operation  $[f] : A \times \dots \times A \rightarrow A$  is *monotone* with respect to a binary relation  $\triangleright$  on  $A$  if

$$a_i \triangleright a'_i \implies [f](a_1, \dots, a_i, \dots, a_n) \triangleright [f](a_1, \dots, a'_i, \dots, a_n).$$

## Definition (Monotone $\Sigma$ -algebras)

A *weakly monotone  $\Sigma$ -algebra*  $(A, [\cdot], >, \gtrsim)$  is a  $\Sigma$ -algebra  $(A, [\cdot])$  equipped with two binary relations  $>, \gtrsim$  on  $A$  such that

- $>$  is well-founded;
- $> \cdot \gtrsim \subseteq >$ ;
- for every  $f \in \Sigma$  the operation  $[f]$  is monotone with respect to  $\gtrsim$ .

An *extended monotone  $\Sigma$ -algebra*  $(A, [\cdot], >, \gtrsim)$  is a weakly monotone  $\Sigma$ -algebra  $(A, [\cdot], >, \gtrsim)$  in which moreover for every  $f \in \Sigma$  the operation  $[f]$  is monotone with respect to  $>$ .



# Monotone algebras

## Definition (Monotonicity)

An operation  $[f] : A \times \dots \times A \rightarrow A$  is *monotone* with respect to a binary relation  $\triangleright$  on  $A$  if

$$a_i \triangleright a'_i \implies [f](a_1, \dots, a_i, \dots, a_n) \triangleright [f](a_1, \dots, a'_i, \dots, a_n).$$

## Definition (Monotone $\Sigma$ -algebras)

A *weakly monotone  $\Sigma$ -algebra*  $(A, [\cdot], >, \gtrsim)$  is a  $\Sigma$ -algebra  $(A, [\cdot])$  equipped with two binary relations  $>, \gtrsim$  on  $A$  such that

- $>$  is well-founded;
- $> \cdot \gtrsim \subseteq >$ ;
- for every  $f \in \Sigma$  the operation  $[f]$  is monotone with respect to  $\gtrsim$ .

An *extended monotone  $\Sigma$ -algebra*  $(A, [\cdot], >, \gtrsim)$  is a weakly monotone  $\Sigma$ -algebra  $(A, [\cdot], >, \gtrsim)$  in which moreover for every  $f \in \Sigma$  the operation  $[f]$  is monotone with respect to  $>$ .

## Theorem

Let  $R, R', S, S'$  be TRSs over a signature  $\Sigma$ ,  $(A, [\cdot], >, \gtrsim)$  be an extended monotone  $\Sigma$ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R \cup S$  and
- $\ell >_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R' \cup S'$

Then  $\text{SN}(R/S)$  implies  $\text{SN}(R \cup R' / S \cup S')$ .

## Theorem

Let  $R, R', S, S'$  be TRSs over a signature  $\Sigma$ , let  $(A, [\cdot], >, \gtrsim)$  be a weakly monotone  $\Sigma$ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R \cup S$  and
- $\ell >_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R'$ ,

Then  $\text{SN}(R_{\text{top}}/S)$  implies  $\text{SN}((R \cup R')_{\text{top}}/S)$ .

## Theorem

Let  $R, R', S, S'$  be TRSs over a signature  $\Sigma$ ,  $(A, [\cdot], >, \gtrsim)$  be an extended monotone  $\Sigma$ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R \cup S$  and
- $\ell >_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R' \cup S'$

Then  $\text{SN}(R/S)$  implies  $\text{SN}(R \cup R' / S \cup S')$ .

## Theorem

Let  $R, R', S, S'$  be TRSs over a signature  $\Sigma$ , let  $(A, [\cdot], >, \gtrsim)$  be a weakly monotone  $\Sigma$ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R \cup S$  and
- $\ell >_{\mathcal{T}} r$  for every rule  $\ell \rightarrow r$  in  $R'$ ,

Then  $\text{SN}(R_{\text{top}}/S)$  implies  $\text{SN}((R \cup R')_{\text{top}}/S)$ .

# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).

# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).

# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).

# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).

# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).



# Basic definitions

Given TRSs  $\mathcal{R}$  and  $\mathcal{S}$  define:

- *top rewrite relation*:  $t \xrightarrow{\text{top}}_{\mathcal{R}} u$  if and only if there is a rewrite rule  $\ell \rightarrow r \in \mathcal{R}$  and a substitution  $\sigma : \mathcal{V} \rightarrow \mathcal{T}(\Sigma, \mathcal{V})$  such that  $t = \ell\sigma$  and  $u = r\sigma$ .
- *rewrite relation*:  $\rightarrow_{\mathcal{R}}$  is the smallest relation such that  $\xrightarrow{\text{top}}_{\mathcal{R}} \subseteq \rightarrow_{\mathcal{R}}$  and  $\rightarrow_{\mathcal{R}}$  is context-closed.
- *relation modulo*:  $\rightarrow_1 / \rightarrow_2 \equiv \rightarrow_2^* \cdot \rightarrow_1$ .
- *termination*:  $\text{SN}(\rightarrow_{\mathcal{R}})$ .
- *relative termination*:  $\text{SN}(\rightarrow_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$ .
- *relative top termination*:  $\text{SN}(\xrightarrow{\text{top}}_{\mathcal{R}} / \rightarrow_{\mathcal{S}})$  (important in the dependency pairs setting).

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2(y + z + 2) + 2x(y + z + 2) + 1$$

$$[x * y + x * z] = (2x + 2y + 2xy + 1) + (2x + 2z + 2xz + 1) + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- **Semi-ring computation structure:**  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2(y + z + 2) + 2x(y + z + 2) + 1$$

$$[x * y + x * z] = (2x + 2y + 2xy + 1) + (2x + 2z + 2xz + 1) + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2(y + z + 2) + 2x(y + z + 2) + 1$$

$$[x * y + x * z] = (2x + 2y + 2xy + 1) + (2x + 2z + 2xz + 1) + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2(y + z + 2) + 2x(y + z + 2) + 1$$

$$[x * y + x * z] = (2x + 2y + 2xy + 1) + (2x + 2z + 2xz + 1) + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2(y + z + 2) + 2x(y + z + 2) + 1$$

$$[x * y + x * z] = (2x + 2y + 2xy + 1) + (2x + 2z + 2xz + 1) + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 2x + 2y + 2z + 4 + 2xy + 2xz + 4x + 1$$

$$[x * y + x * z] = 2x + 2y + 2xy + 1 + 2x + 2z + 2xz + 1 + 2$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 6x + 2y + 2z + 2xy + 2xz + 5$$

$$[x * y + x * z] = 4x + 2y + 2z + 2xy + 2xz + 4$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .



# Polynomial interpretations

- Interpretation domain:  $\mathbb{N}$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .

## Example

$$x * (y + z) \rightarrow x * y + x * z$$

$$[x + y] = x + y + 2, \quad [x * y] = 2x + 2y + 2xy + 1$$

$$[x * (y + z)] = 6x + 2y + 2z + 2xy + 2xz + 5$$

$$[x * y + x * z] = 4x + 2y + 2z + 2xy + 2xz + 4$$

- To obtain strict monotonicity we require that for every interpretation  $[f(x_1, \dots, x_n)]$ ,  $\forall i, \exists c > 0, c * x_i \in [f(x_1, \dots, x_n)]$ .

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$$[f(x_1 \dots x_n)] = F_f x_1 + \dots + F_f x_n + \vec{r}$$



# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- **Semi-ring computation structure:**  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$$[f(x_1 \dots x_n)] = F_f x_1 + \dots + F_f x_n + \vec{t} \text{ we have}$$

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$$[f(x_1 \dots x_n)] = F_f x_1 + \dots + F_f x_n + \vec{t} \text{ we have}$$

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$$[f(x_1 \dots x_n)] = F_f x_1 + \dots + F_f x_n + \vec{t} \text{ we have}$$

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$[f(x_1 \dots x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{r}$  we have

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$[f(x_1 \dots x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{r}$  we have

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \left( \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 0 \end{pmatrix} \right) + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation

$[f(x_1 \dots x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{r}$  we have



# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, u_i \geq v_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 1 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- Strict monotonicity ensured if for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{f}$  we have  $\forall i, (F_i)_{1,1} > 0$ .

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, u_i \geq v_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 1 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- **Now we need to restrict to linear interpretations.**
- Strict monotonicity ensured if for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{f}$  we have  $\forall i, (F_i)_{1,1} > 0$ .

# Matrix interpretations

- Interpretation domain:  $\mathbb{N}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{N}, +, * \rangle$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\vec{u} \geq \vec{v} \wedge \vec{u}_1 > \vec{v}_1$ .

## Example

$$a(a(x)) \rightarrow a(b(a(x))).$$

$$[a(x)] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad [b(x)] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 0 \end{pmatrix}$$

$$[a(a(x))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 1 \\ 1 \end{pmatrix}$$

$$[a(b(a(x)))] = \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} x + \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- Now we need to restrict to linear interpretations.
- **Strict monotonicity ensured if for every interpretation**  
 $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  **we have  $\forall i, (F_i)_{1,1} > 0$ .**

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- **We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .**
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- Problem: arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- Problem: well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- Problem: we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- **Semi-ring computation structure:**  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .



# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  **full termination only for SRSs.**
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{A}_{\mathbb{N}}^d$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots + F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{N}}^{d-1}$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not> 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{N}}^{d-1}$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .



# Arctic interpretations

- $\mathbb{A}_{\mathbb{N}} \equiv \{-\infty\} \cup \mathbb{N}$ .
- We say that  $a \in \mathbb{A}_{\mathbb{N}}$  is *finite* iff  $a \neq -\infty$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{N}}^{d-1}$ , for some fixed  $d$ .
- Semi-ring computation structure:  $\langle \mathbb{A}_{\mathbb{N}}, \max, + \rangle$ .
- $a \gg b \equiv a > b \vee (a = b = -\infty)$ .
- $\vec{u} \geq \vec{v}$  iff  $\forall i, \vec{u}_i \geq \vec{v}_i$ .
- $\vec{u} > \vec{v}$  iff  $\forall i, \vec{u}_i \gg \vec{v}_i$ .
- **Problem:** arctic addition is not strictly monotonic in single arguments, ie.  $5 > 3$  but  $5 \oplus 6 = 6 \not\gg 6 = 3 \oplus 6$ . We cannot get strict monotonicity for symbols of arity  $> 1$ .
- $\Rightarrow$  full termination only for SRSs.
- $\Rightarrow$  for TRSs we can “only” prove top-termination.
- **Problem:** well-foundedness of  $>$  (as  $-\infty \gg -\infty$ )
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\exists i, \text{finite}((F_i)_{1,1})$  or  $\text{finite}(\vec{f}_1)$ .

## Example

$$\{cac \rightarrow \epsilon, aca \rightarrow a^4 \mid \epsilon \rightarrow c^4\}.$$

$$[a](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix} \quad [c](x) = \begin{pmatrix} 0 & -\infty & -\infty \\ -\infty & -\infty & 0 \\ -\infty & 0 & -\infty \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix}$$

- $[c]$  is a permutation (it swaps the second and third component), so  $[c]^2 = [c]^4 = [\epsilon]$ .
- $[a]$  is idempotent, so  $[a] = [a^4]$ .

$$[cac](x) = \begin{pmatrix} 0 & -\infty & 0 \\ 1 & 0 & 1 \\ 0 & -\infty & 0 \end{pmatrix} x \quad [aca](x) = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 2 & 2 & 1 \end{pmatrix} x \quad [a^4](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x$$

## Example

$$\{cac \rightarrow \epsilon, aca \rightarrow a^4 \mid \epsilon \rightarrow c^4\}.$$

$$[a](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix} \quad [c](x) = \begin{pmatrix} 0 & -\infty & -\infty \\ -\infty & -\infty & 0 \\ -\infty & 0 & -\infty \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix}$$

- $[c]$  is a permutation (it swaps the second and third component), so  $[c]^2 = [c]^4 = [\epsilon]$ .
- $[a]$  is idempotent, so  $[a] = [a^4]$ .

$$[cac](x) = \begin{pmatrix} 0 & -\infty & 0 \\ 1 & 0 & 1 \\ 0 & -\infty & 0 \end{pmatrix} x \quad [aca](x) = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 2 & 2 & 1 \end{pmatrix} x \quad [a^4](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x$$

## Example

$$\{cac \rightarrow \epsilon, aca \rightarrow a^4 \mid \epsilon \rightarrow c^4\}.$$

$$[a](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix} \quad [c](x) = \begin{pmatrix} 0 & -\infty & -\infty \\ -\infty & -\infty & 0 \\ -\infty & 0 & -\infty \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix}$$

- $[c]$  is a permutation (it swaps the second and third component), so  $[c]^2 = [c]^4 = [\epsilon]$ .
- $[a]$  is idempotent, so  $[a] = [a^4]$ .

$$[cac](x) = \begin{pmatrix} 0 & -\infty & 0 \\ 1 & 0 & 1 \\ 0 & -\infty & 0 \end{pmatrix} x \quad [aca](x) = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 2 & 2 & 1 \end{pmatrix} x \quad [a^4](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x$$

## Example

$$\{cac \rightarrow \epsilon, aca \rightarrow a^4 \mid \epsilon \rightarrow c^4\}.$$

$$[a](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix} \quad [c](x) = \begin{pmatrix} 0 & -\infty & -\infty \\ -\infty & -\infty & 0 \\ -\infty & 0 & -\infty \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix}$$

- $[c]$  is a permutation (it swaps the second and third component), so  $[c]^2 = [c]^4 = [\epsilon]$ .
- $[a]$  is idempotent, so  $[a] = [a^4]$ .

$$[cac](x) = \begin{pmatrix} 0 & -\infty & 0 \\ 1 & 0 & 1 \\ 0 & -\infty & 0 \end{pmatrix} x \quad [aca](x) = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 2 & 2 & 1 \end{pmatrix} x \quad [a^4](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x$$

## Example

$$\{\mathbf{c} \mathbf{a} \mathbf{c} \rightarrow \epsilon, \mathbf{a} \mathbf{c} \mathbf{a} \rightarrow \mathbf{a}^4 / \epsilon \rightarrow \mathbf{c}^4\}.$$

$$[\mathbf{a}](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix} \quad [\mathbf{c}](x) = \begin{pmatrix} 0 & -\infty & -\infty \\ -\infty & -\infty & 0 \\ -\infty & 0 & -\infty \end{pmatrix} x + \begin{pmatrix} -\infty \\ -\infty \\ -\infty \end{pmatrix}$$

- $[\mathbf{c}]$  is a permutation (it swaps the second and third component), so  $[\mathbf{c}]^2 = [\mathbf{c}]^4 = [\epsilon]$ .
- $[\mathbf{a}]$  is idempotent, so  $[\mathbf{a}] = [\mathbf{a}^4]$ .

$$[\mathbf{c} \mathbf{a} \mathbf{c}](x) = \begin{pmatrix} 0 & -\infty & 0 \\ 1 & 0 & 1 \\ 0 & -\infty & 0 \end{pmatrix} x \quad [\mathbf{a} \mathbf{c} \mathbf{a}](x) = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 2 & 2 & 1 \end{pmatrix} x \quad [\mathbf{a}^4](x) = \begin{pmatrix} 0 & 0 & -\infty \\ 0 & 0 & -\infty \\ 1 & 1 & 0 \end{pmatrix} x$$

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- Problem: we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .



# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- **Semi-ring structure:**  $\langle \mathbb{A}_{\mathbb{Z}}, \text{max}, + \rangle$ .
- $\geq, >$  as before.
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- **Problem: we need to ensure that we stay within the domain.**
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Arctic below zero interpretations

- $\mathbb{A}_{\mathbb{Z}} \equiv \{-\infty\} \cup \mathbb{Z}$ .
- Interpretation domain:  $\mathbb{N} \times \mathbb{A}_{\mathbb{Z}}^{d-1}$ , for some fixed  $d$ .
- $\Rightarrow$  we restrict first component to  $\mathbb{N}$  to get well-foundedness.
- Semi-ring structure:  $\langle \mathbb{A}_{\mathbb{Z}}, \max, + \rangle$ .
- $\geq, >$  as before.
- **Problem:** we need to ensure that we stay within the domain.
- $\Rightarrow$  for every interpretation  $[f(x_1, \dots, x_n)] = F_1 x_1 + \dots F_n x_n + \vec{f}$  we require  $\vec{f}_1 \geq 0$ .

# Example arctic below zero proof

## Example

while  $x > y$  do  $x := x - 1$ ;

$\text{cond}(\text{true}, x, y) \rightarrow \text{cond}(\text{gr}(x, y), p(x), y), \quad \text{gr}(s(x), s(y)) \rightarrow \text{gr}(x, y),$   
 $\text{gr}(0, x) \rightarrow \text{false}, \quad \text{gr}(s(x), 0) \rightarrow \text{true},$   
 $p(0) \rightarrow 0, \quad p(s(x)) \rightarrow x$

$\text{cond}^\#(\text{true}, x, y) \rightarrow \text{cond}^\#(\text{gr}(x, y), p(x), y)$

$[\text{cond}^\#(x, y, z)] = (0)x + (0)y + (-\infty)z + (0), \quad [0] = (0),$   
 $[\text{cond}(x, y, z)] = (0)x + (2)y + (-\infty)z + (0), \quad [\text{false}] = (0),$   
 $[\text{gr}(x, y)] = (-1)x + (-\infty)y + (0), \quad [\text{true}] = (2),$   
 $[p(x)] = (-1)x + (0), \quad [s(x)] = (2)x + (3).$

$[\text{cond}^\#(\text{true}, x, y)] = (0)x + (-\infty)y + (2)$

$[\text{cond}^\#(\text{gr}(x, y), p(x), y)] = (-1)x + (-\infty)y + (0)$

# Example arctic below zero proof

## Example

while  $x > y$  do  $x := x - 1$ ;

$\text{cond}(\text{true}, x, y) \rightarrow \text{cond}(\text{gr}(x, y), p(x), y), \quad \text{gr}(s(x), s(y)) \rightarrow \text{gr}(x, y),$   
 $\text{gr}(0, x) \rightarrow \text{false}, \quad \text{gr}(s(x), 0) \rightarrow \text{true},$   
 $p(0) \rightarrow 0, \quad p(s(x)) \rightarrow x$

$\text{cond}^\sharp(\text{true}, x, y) \rightarrow \text{cond}^\sharp(\text{gr}(x, y), p(x), y)$

$[\text{cond}^\sharp(x, y, z)] = (0)x + (0)y + (-\infty)z + (0), \quad [0] = (0),$   
 $[\text{cond}(x, y, z)] = (0)x + (2)y + (-\infty)z + (0), \quad [\text{false}] = (0),$   
 $[\text{gr}(x, y)] = (-1)x + (-\infty)y + (0), \quad [\text{true}] = (2),$   
 $[p(x)] = (-1)x + (0), \quad [s(x)] = (2)x + (3).$

$[\text{cond}^\sharp(\text{true}, x, y)] = (0)x + (-\infty)y + (2)$

$[\text{cond}^\sharp(\text{gr}(x, y), p(x), y)] = (-1)x + (-\infty)y + (0)$

# Example arctic below zero proof

## Example

while  $x > y$  do  $x := x - 1$ ;

$\text{cond}(\text{true}, x, y) \rightarrow \text{cond}(\text{gr}(x, y), p(x), y), \quad \text{gr}(s(x), s(y)) \rightarrow \text{gr}(x, y),$   
 $\text{gr}(0, x) \rightarrow \text{false}, \quad \text{gr}(s(x), 0) \rightarrow \text{true},$   
 $p(0) \rightarrow 0, \quad p(s(x)) \rightarrow x$

$\text{cond}^\#(\text{true}, x, y) \rightarrow \text{cond}^\#(\text{gr}(x, y), p(x), y)$

$[\text{cond}^\#(x, y, z)] = (0)x + (0)y + (-\infty)z + (0), \quad [0] = (0),$   
 $[\text{cond}(x, y, z)] = (0)x + (2)y + (-\infty)z + (0), \quad [\text{false}] = (0),$   
 $[\text{gr}(x, y)] = (-1)x + (-\infty)y + (0), \quad [\text{true}] = (2),$   
 $[p(x)] = (-1)x + (0), \quad [s(x)] = (2)x + (3).$

$[\text{cond}^\#(\text{true}, x, y)] = (0)x + (-\infty)y + (2)$

$[\text{cond}^\#(\text{gr}(x, y), p(x), y)] = (-1)x + (-\infty)y + (0)$



# Example arctic below zero proof

## Example

while  $x > y$  do  $x := x - 1$ ;

$$\begin{aligned} \text{cond}(\text{true}, x, y) &\rightarrow \text{cond}(\text{gr}(x, y), p(x), y), & \text{gr}(s(x), s(y)) &\rightarrow \text{gr}(x, y), \\ \text{gr}(0, x) &\rightarrow \text{false}, & \text{gr}(s(x), 0) &\rightarrow \text{true}, \\ p(0) &\rightarrow 0, & p(s(x)) &\rightarrow x \end{aligned}$$

$$\text{cond}^\#(\text{true}, x, y) \rightarrow \text{cond}^\#(\text{gr}(x, y), p(x), y)$$

$$\begin{aligned} [\text{cond}^\#(x, y, z)] &= (0)x + (0)y + (-\infty)z + (0), & [0] &= (0), \\ [\text{cond}(x, y, z)] &= (0)x + (2)y + (-\infty)z + (0), & [\text{false}] &= (0), \\ [\text{gr}(x, y)] &= (-1)x + (-\infty)y + (0), & [\text{true}] &= (2), \\ [p(x)] &= (-1)x + (0), & [s(x)] &= (2)x + (3). \end{aligned}$$

$$[\text{cond}^\#(\text{true}, x, y)] = (0)x + (-\infty)y + (2)$$

$$[\text{cond}^\#(\text{gr}(x, y), p(x), y)] = (-1)x + (-\infty)y + (0)$$

# Example arctic below zero proof

## Example

while  $x > y$  do  $x := x - 1$ ;

$$\begin{aligned} \text{cond}(\text{true}, x, y) &\rightarrow \text{cond}(\text{gr}(x, y), p(x), y), & \text{gr}(s(x), s(y)) &\rightarrow \text{gr}(x, y), \\ \text{gr}(0, x) &\rightarrow \text{false}, & \text{gr}(s(x), 0) &\rightarrow \text{true}, \\ p(0) &\rightarrow 0, & p(s(x)) &\rightarrow x \end{aligned}$$

$$\text{cond}^\#(\text{true}, x, y) \rightarrow \text{cond}^\#(\text{gr}(x, y), p(x), y)$$

$$\begin{aligned} [\text{cond}^\#(x, y, z)] &= (0)x + (0)y + (-\infty)z + (0), & [0] &= (0), \\ [\text{cond}(x, y, z)] &= (0)x + (2)y + (-\infty)z + (0), & [\text{false}] &= (0), \\ [\text{gr}(x, y)] &= (-1)x + (-\infty)y + (0), & [\text{true}] &= (2), \\ [p(x)] &= (-1)x + (0), & [s(x)] &= (2)x + (3). \end{aligned}$$

$$[\text{cond}^\#(\text{true}, x, y)] = (0)x + (-\infty)y + (2)$$

$$[\text{cond}^\#(\text{gr}(x, y), p(x), y)] = (-1)x + (-\infty)y + (0)$$

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	

# Performance & Summary

- We presented an extension of matrix interpretations method by replacing the usual semi-ring structure with the arctic semi-ring.
- The method can prove full termination for SRSs and (relative) top termination for TRSs.
- We extended this from naturals to integers, resulting in arctic below zero interpretations.
- The whole method has been formalized in Coq within the CoLoR project.
- It has also been implemented in Matchbox, by transforming the constraints to propositional satisfiability problem and running Minisat.

problem set	time	s	sa	sz	saz	2007 winner
975 TRS	1 min	361	376	388	389	TPA: 354
	10 min	365	381	393	394	
517 SRS	1 min	178	312	298	320	Matchbox: 337
	10 min	185	349	323	354	



`http://color.loria.fr`



Thank you for your attention.