

Predictive Labeling with Dependency Pairs using SAT

Adam Koprowski¹ Aart Middeldorp²

¹Eindhoven University of Technology

²University of Innsbruck

20 July 2007

CADE

Bremen

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4)$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow \gcd(\max(5, 3) - \min(5, 3), s(\min(5, 3)))$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow^+ \gcd(s(\max(4, 2)) - \min(5, 3), s(\min(5, 3)))$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$x - 0 \rightarrow x$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(6, 4) \rightarrow^+ \gcd(s(s(\max(3, 1))) - \min(5, 3), s(\min(5, 3)))$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$x - 0 \rightarrow x$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(6, 4) \rightarrow^+ \gcd(s(s(s(\max(2, 0)))) - \min(5, 3), s(\min(5, 3)))$$

Termination of Rewriting

Example

$$\text{min}(x, 0) \rightarrow 0$$

$$\text{min}(0, y) \rightarrow 0$$

$$\text{min}(s(x), s(y)) \rightarrow s(\text{min}(x, y))$$

$$\text{gcd}(0, s(x)) \rightarrow s(x)$$

$$\text{gcd}(s(x), 0) \rightarrow s(x)$$

$$\text{gcd}(s(x), s(y)) \rightarrow \text{gcd}(\text{max}(x, y) - \text{min}(x, y), s(\text{min}(x, y)))$$

$$\text{max}(x, 0) \rightarrow x$$

$$\text{max}(0, y) \rightarrow y$$

$$\text{max}(s(x), s(y)) \rightarrow s(\text{max}(x, y))$$

$$x - 0 \rightarrow x$$

$$s(x) - s(y) \rightarrow x - y$$

$$\text{gcd}(6, 4) \rightarrow^+ \text{gcd}(s(s(s(2))) - \text{min}(5, 3), s(\text{min}(5, 3)))$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow^+ \gcd(5 - 3, 4)$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow^+ \gcd(2, 4)$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow^+ \gcd(2, 2)$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\text{gcd}(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\text{gcd}(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\text{gcd}(s(x), s(y)) \rightarrow \text{gcd}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\text{gcd}(6, 4) \rightarrow^+ \text{gcd}(0, 2)$$

Termination of Rewriting

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd(6, 4) \rightarrow^+ 2$$

Definition

A TRS is **terminating** if it does not admit an infinite rewrite sequence.

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, **semantic labeling**, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, **predictive labeling**, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, **polynomial interpretations**, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, **matrix interpretations**, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, **dependency pair method**, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, **lexicographic path order**, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, TPA, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, polynomial interpretations, lexicographic path order, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, semantic labeling, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, predictive labeling, uncurrying, matrix interpretations, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, **TPA**, TTT, TTTbox, ...

Definition

A TRS is terminating if it does not admit an infinite rewrite sequence.

Termination methods

Knuth-Bendix order, **polynomial interpretations**, **lexicographic path order**, multiset order, multiset path order, recursive path order, semantic path order, recursive decomposition order, transformation order, elementary interpretations, well-founded monotone algebra, general path order, **semantic labeling**, type introduction, freezing, top-down labeling, dependency pair method, matchbounds, size-change principle, **predictive labeling**, uncurrying, **matrix interpretations**, quasi-periodic interpretations, bounded increase ...

Termination tools

AProVE, Cariboo, Cime, JamBox, MatchBox, MultumNonMultum, MuTerm, Teparla, Torpa, **TPA**, TTT, TTTbox, ...

1 Theory

- Semantic Labeling (SL)
- Predictive Labeling (PL)
- Dependency Pairs (DP)

2 Practice

- SAT encoding
- Experimental results

3 Conclusions

1 Theory

- Semantic Labeling (SL)
- Predictive Labeling (PL)
- Dependency Pairs (DP)

2 Practice

- SAT encoding
- Experimental results

3 Conclusions

Example

Is this TRS terminating?

$$f(s(x), s(y)) \rightarrow s(f(x, y))$$

$$f(x, c) \rightarrow c$$

$$f(c, y) \rightarrow c$$

$$g(x, c) \rightarrow x$$

$$g(s(x), s(y)) \rightarrow s(g(x, y))$$

$$g(c, y) \rightarrow y$$

$$h(s(x), s(y)) \rightarrow h(x, y)$$

$$h(x, c) \rightarrow x$$

$$l(s(x), s(y)) \rightarrow l(h(g(x, y), f(x, y)), s(f(x, y)))$$

Example

How about this one?

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$s(x) - s(y) \rightarrow x - y$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Semantic Labeling (SL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$s(x) - s(y) \rightarrow x - y$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

Semantic Labeling (SL)

Example

$$\min(x, 0) \rightarrow 0$$

$$x \geq 0$$

$$\min(0, y) \rightarrow 0$$

$$0 \geq 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$2x + 1 \geq 2x + 1$$

$$\max(x, 0) \rightarrow x$$

$$x \geq x$$

$$\max(0, y) \rightarrow y$$

$$y \geq y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$2x + 2y + 2 > 2x + 2y + 1$$

$$s(x) - s(y) \rightarrow x - y$$

$$2x + 1 > x$$

$$x - 0 \rightarrow x$$

$$x \geq x$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$0 \geq 0$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

Semantic Labeling (SL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$s(x) - s(y) \rightarrow x - y$$

$$x - 0 \rightarrow x \quad i, j \in \mathbb{N}$$

$$\gcd_{4i+2j+3}(s(x), s(y)) \rightarrow \gcd_{4i+2j+1}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd_i(x, y) \rightarrow \gcd_j(x, y) \quad i > j$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

$$\ell_{\gcd}(x, y) = 2x + y$$

Semantic Labeling (SL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(x, 0) \rightarrow x$$

\Rightarrow LPO applicable

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$s(x) - s(y) \rightarrow x - y$$

$$x - 0 \rightarrow x$$

$$\gcd_{4i+2j+3}(s(x), s(y)) \rightarrow \gcd_{4i+2j+1}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\gcd_i(x, y) \rightarrow \gcd_j(x, y)$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

$$\ell_{\gcd}(x, y) = 2x + y$$

Semantic Labeling (SL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(x, 0) \rightarrow x$$

\Rightarrow LPO applicable

$$\max(0, y) \rightarrow y$$

$\dots > \text{gcd}_1 > \text{gcd}_0 > \{\min, \max, -\} > s$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$s(x) - s(y) \rightarrow x - y$$

$$x - 0 \rightarrow x$$

$$\text{gcd}_{4i+2j+3}(s(x), s(y)) \rightarrow \text{gcd}_{4i+2j+1}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\text{gcd}_i(x, y) \rightarrow \text{gcd}_j(x, y)$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \text{gcd}_{\mathbb{N}}(x, y) = 0$$

$$\ell_{\text{gcd}}(x, y) = 2x + y$$

Definition (Semantic labeling)

- Semantics:
 - \mathcal{F} -algebra $\mathcal{A} = (A, \{f_A\}_{f \in \mathcal{F}}, >_{\mathcal{A}}, \succsim_{\mathcal{A}})$

Definition (Semantic labeling)

- Semantics:
 - \mathcal{F} -algebra $\mathcal{A} = (A, \{f_A\}_{f \in \mathcal{F}}, >_{\mathcal{A}}, \succsim_{\mathcal{A}})$
- Labeling:
 - for every $f \in \mathcal{F}$ a set of labels $L_f \subseteq A$
 - labeling functions $\ell_f : A^n \rightarrow L_f$ for every n -ary $f \in \mathcal{F}$ with $L_f \neq \emptyset$

Definition (Semantic labeling)

- Semantics:
 - \mathcal{F} -algebra $\mathcal{A} = (A, \{f_A\}_{f \in \mathcal{F}}, >_{\mathcal{A}}, \succsim_{\mathcal{A}})$
- Labeling:
 - for every $f \in \mathcal{F}$ a set of labels $L_f \subseteq A$
 - labeling functions $\ell_f : A^n \rightarrow L_f$ for every n -ary $f \in \mathcal{F}$ with $L_f \neq \emptyset$
- Labeling of terms (for a variable assignment $\alpha : \mathcal{V} \rightarrow A$).

$$\text{lab}_{\alpha}(t) = \begin{cases} t & \text{if } t \text{ is a variable,} \\ f(\text{lab}_{\alpha}(t_1), \dots, \text{lab}_{\alpha}(t_n)) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f = \emptyset, \\ f_a(\text{lab}_{\alpha}(t_1), \dots, \text{lab}_{\alpha}(t_n)) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f \neq \emptyset \end{cases}$$

with $a = \ell_f([\alpha]_{\mathcal{A}}(t_1), \dots, [\alpha]_{\mathcal{A}}(t_n))$

Definition (Semantic labeling)

- Semantics:
 - \mathcal{F} -algebra $\mathcal{A} = (A, \{f_A\}_{f \in \mathcal{F}}, >_{\mathcal{A}}, \succsim_{\mathcal{A}})$
- Labeling:
 - for every $f \in \mathcal{F}$ a set of labels $L_f \subseteq A$
 - labeling functions $\ell_f : A^n \rightarrow L_f$ for every n -ary $f \in \mathcal{F}$ with $L_f \neq \emptyset$
- Labeling of terms (for a variable assignment $\alpha : \mathcal{V} \rightarrow A$).

$$\text{lab}_{\alpha}(t) = \begin{cases} t & \text{if } t \text{ is a variable,} \\ f(\text{lab}_{\alpha}(t_1), \dots, \text{lab}_{\alpha}(t_n)) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f = \emptyset, \\ f_a(\text{lab}_{\alpha}(t_1), \dots, \text{lab}_{\alpha}(t_n)) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f \neq \emptyset \end{cases}$$

with $a = \ell_f([\alpha]_{\mathcal{A}}(t_1), \dots, [\alpha]_{\mathcal{A}}(t_n))$

- **Labeled TRS:**
 - $\mathcal{R}_{\text{lab}} = \{\text{lab}_{\alpha}(l) \rightarrow \text{lab}_{\alpha}(r) \mid l \rightarrow r \in \mathcal{R}, \alpha : \mathcal{V} \rightarrow A\}$
 - $\text{Decr} = \{f_a(x_1, \dots, x_n) \rightarrow f_b(x_1, \dots, x_n) \mid f \in \mathcal{F}, L_f \neq \emptyset; a, b \in L_f, a > b\}$

Theorem (Zantema, 1995)

A TRS \mathcal{R} is terminating if there exists:

- a *weakly-monotone* \mathcal{F} -algebra and
- a *weakly-monotone* labeling ℓ

such that:

- $\mathcal{R} \subseteq \succsim_{\mathcal{A}}$ and
- $\mathcal{R}_{\text{lab}} \cup \text{Decr}$ is terminating

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\text{gcd}(0, s(x)) \rightarrow s(x)$$

$$\text{gcd}(s(x), 0) \rightarrow s(x)$$

$$\text{gcd}(s(x), s(y)) \rightarrow \text{gcd}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$x - 0 \rightarrow x$$

$$s(x) - s(y) \rightarrow x - y$$

Predictive Labeling (PL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\text{gcd}(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\text{gcd}(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\text{gcd}(s(x), s(y)) \rightarrow \text{gcd}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \text{gcd}_{\mathbb{N}}(x, y) = 0$$

Problem: how to obtain a quasi-model?

Predictive Labeling (PL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y \\ -_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

Problem: how to obtain a quasi-model?

⇒ use predictive labeling (quasi-model constraints only for usable rules)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\text{gcd}(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\text{gcd}(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\text{gcd}(s(x), s(y)) \rightarrow \text{gcd}(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- 1 Look at symbols that will get labels.

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- 1 Look at symbols that will get labels.
- 2 Look at their subterms.

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- ② Look at their subterms.
- ③ All function symbols occurring there are usable.

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- ③ All function symbols occurring there are usable.
- ④ Also the symbols that depend on them.

Predictive Labeling (PL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$0_{\mathbb{N}} = 0 \quad s_{\mathbb{N}}(x) = 2x + 1 \quad \min_{\mathbb{N}}(x, y) = x \quad \max_{\mathbb{N}}(x, y) = x + y$$

$$-_{\mathbb{N}}(x, y) = x \quad \gcd_{\mathbb{N}}(x, y) = 0$$

Computation of usable rules:

- 4 Also the symbols that depend on them.
- 5 Semantics needed only for usable symbols.

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- ⑤ Semantics needed only for usable symbols.
- ⑥ Quasi-model constraints only required for usable rules.

Predictive Labeling (PL)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Computation of usable rules:

- 1 Look at symbols that will get labels.
- 2 Look at their subterms.
- 3 All function symbols occurring there are usable.
- 4 Also the symbols that depend on them.
- 5 Semantics needed only for usable symbols.
- 6 Quasi-model constraints only required for usable rules.

Definition (Usable rules)

- $f \triangleright_d g \equiv \exists f(\dots) \rightarrow r \in \mathcal{R}, g(\dots) \trianglelefteq r$

Definition (Usable rules)

- $f \triangleright_d g \equiv \exists f(\dots) \rightarrow r \in \mathcal{R}, g(\dots) \trianglelefteq r$
- $F^* \equiv \{g \mid f \triangleright_d^* g \text{ for some } f \in \mathcal{F}\}.$

Definition (Usable rules)

- $f \triangleright_d g \equiv \exists f(\dots) \rightarrow r \in \mathcal{R}, g(\dots) \trianglelefteq r$
- $F^* \equiv \{g \mid f \triangleright_d^* g \text{ for some } f \in \mathcal{F}\}.$
- $\mathcal{G}_\ell(t) = \begin{cases} \emptyset & \text{if } t \text{ is a variable,} \\ \mathcal{F}(t_1)^* \cup \dots \cup \mathcal{F}(t_n)^* & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f \neq \emptyset, \\ \mathcal{G}_\ell(t_1) \cup \dots \cup \mathcal{G}_\ell(t_n) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f = \emptyset \end{cases}$

Definition (Usable rules)

- $f \triangleright_d g \equiv \exists f(\dots) \rightarrow r \in \mathcal{R}, g(\dots) \trianglelefteq r$
- $F^* \equiv \{g \mid f \triangleright_d^* g \text{ for some } f \in \mathcal{F}\}.$
- $$\mathcal{G}_\ell(t) = \begin{cases} \emptyset & \text{if } t \text{ is a variable,} \\ \mathcal{F}(t_1)^* \cup \dots \cup \mathcal{F}(t_n)^* & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f \neq \emptyset, \\ \mathcal{G}_\ell(t_1) \cup \dots \cup \mathcal{G}_\ell(t_n) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f = \emptyset \end{cases}$$
- $\mathcal{G}_\ell(\mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{R}} \mathcal{G}_\ell(l) \cup \mathcal{G}_\ell(r)$

Definition (Usable rules)

- $f \triangleright_d g \equiv \exists f(\dots) \rightarrow r \in \mathcal{R}, g(\dots) \trianglelefteq r$
- $F^* \equiv \{g \mid f \triangleright_d^* g \text{ for some } f \in \mathcal{F}\}.$
- $$\mathcal{G}_\ell(t) = \begin{cases} \emptyset & \text{if } t \text{ is a variable,} \\ \mathcal{F}(t_1)^* \cup \dots \cup \mathcal{F}(t_n)^* & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f \neq \emptyset, \\ \mathcal{G}_\ell(t_1) \cup \dots \cup \mathcal{G}_\ell(t_n) & \text{if } t = f(t_1, \dots, t_n) \text{ and } L_f = \emptyset \end{cases}$$
- $\mathcal{G}_\ell(\mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{R}} \mathcal{G}_\ell(l) \cup \mathcal{G}_\ell(r)$
- $\mathcal{U}(\mathcal{R}, \ell) = \{l \rightarrow r \in \mathcal{R} \mid \text{root}(l) \in \mathcal{G}_\ell(\mathcal{R})\}$

Theorem (Hirokawa, Middeldorp, 2006)

A TRS \mathcal{R} is terminating if there exists:

- a weakly-monotone \sqcup -algebra and
- a weakly-monotone labeling ℓ

such that:

- $\mathcal{U}(\mathcal{R}, \ell) \subseteq \succsim_{\mathcal{A}}$ and
- $\mathcal{R}_{\text{lab}} \cup \text{Decr}$ is terminating

Dependency Pairs (DP)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Dependency Pairs (DP)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

⇒ apply dependency pairs

Dependency Pairs (DP)

Example

$$\min(x, 0) \rightarrow 0$$

$$\min(0, y) \rightarrow 0$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$\max(x, 0) \rightarrow x$$

$$\max(0, y) \rightarrow y$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$x - 0 \rightarrow x$$

$$s(x) - s(y) \rightarrow x - y$$

Dependency Pairs (DP)

Example

$$\min(x, 0) \rightarrow 0$$

$$\max(x, 0) \rightarrow x$$

$$\min(0, y) \rightarrow 0$$

$$\max(0, y) \rightarrow y$$

$$\min(s(x), s(y)) \rightarrow s(\min(x, y))$$

$$\max(s(x), s(y)) \rightarrow s(\max(x, y))$$

$$\gcd(0, s(x)) \rightarrow s(x)$$

$$x - 0 \rightarrow x$$

$$\gcd(s(x), 0) \rightarrow s(x)$$

$$s(x) - s(y) \rightarrow x - y$$

$$\gcd(s(x), s(y)) \rightarrow \gcd(\max(x, y) - \min(x, y), s(\min(x, y)))$$

$$(1) \quad \text{minus}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(x, y) \quad (5) \quad \gcd^\#(s(x), s(y)) \rightarrow \min^\#(x, y)$$

$$(2) \quad \min^\#(s(x), s(y)) \rightarrow \min^\#(x, y) \quad (6) \quad \gcd^\#(s(x), s(y)) \rightarrow \max^\#(x, y)$$

$$(3) \quad \max^\#(s(x), s(y)) \rightarrow \max^\#(x, y)$$


$$(4) \quad \gcd^\#(s(x), s(y)) \rightarrow \text{minus}^\#(\max(x, y), \min(x, y))$$

$$(7) \quad \gcd^\#(s(x), s(y)) \rightarrow \gcd^\#(\max(x, y) - \min(x, y), s(\min(x, y)))$$

Dependency Pairs (DP)

Example


- (1) $\text{minus}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(x, y)$ (5) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$
(2) $\text{min}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$ (6) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(3) $\text{max}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(4) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(\text{max}(x, y), \text{min}(x, y))$
(7) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{gcd}^\#(\text{max}(x, y) - \text{min}(x, y), s(\text{min}(x, y)))$



Dependency Pairs (DP)

Example


- (1) $\text{minus}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(x, y)$ (5) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$
(2) $\text{min}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$ (6) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(3) $\text{max}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(4) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(\text{max}(x, y), \text{min}(x, y))$
(7) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{gcd}^\#(\text{max}(x, y) - \text{min}(x, y), s(\text{min}(x, y)))$




Dependency Pairs (DP)

Example


- (1) $\text{minus}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(x, y)$ (5) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$
(2) $\text{min}^\#(s(x), s(y)) \rightarrow \text{min}^\#(x, y)$ (6) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(3) $\text{max}^\#(s(x), s(y)) \rightarrow \text{max}^\#(x, y)$
(4) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{minus}^\#(\text{max}(x, y), \text{min}(x, y))$
(7) $\text{gcd}^\#(s(x), s(y)) \rightarrow \text{gcd}^\#(\text{max}(x, y) - \text{min}(x, y), s(\text{min}(x, y)))$




Proving termination with PL




Proving termination with PL



Proving termination with PL



Proving termination with PL



Theorem

A *DP problem* $(\mathcal{P}, \mathcal{R})$ is finite if there exists:

- a weakly-monotone \sqcup -algebra and
- a weakly-monotone labeling ℓ

such that:

- $\mathcal{P} \subseteq \text{DP}(\mathcal{R})$
- \mathcal{R} is finitely branching,
- $\mathcal{U}(\mathcal{R}, \ell) \subseteq \succeq_{\mathcal{A}}$ and
- $(\mathcal{P}_{\text{lab}}, \mathcal{R}_{\text{lab}} \cup \text{Decr})$ is finite.

1 Theory

- Semantic Labeling (SL)
- Predictive Labeling (PL)
- Dependency Pairs (DP)

2 Practice

- SAT encoding
- Experimental results

3 Conclusions

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),
- search for LPO proof over infinite signature (\mathcal{R}_{lab}),

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),



J. Endrullis, J. Waldmann, and H. Zantema.

Matrix interpretations for proving termination of term rewriting.

In *Proc. 3rd IJCAR 2006*.

- search for LPO proof over infinite signature (\mathcal{R}_{lab}),

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),



J. Endrullis, J. Waldmann, and H. Zantema.

Matrix interpretations for proving termination of term rewriting.

In *Proc. 3rd IJCAR 2006*.

- search for LPO proof over infinite signature (\mathcal{R}_{lab}),



P. Schneider-Kamp, R. Thiemann, E. Annov, M. Codish and J. Giesl.

Implementing RPO using SAT.

WST 2007.

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),



J. Endrullis, J. Waldmann, and H. Zantema.

Matrix interpretations for proving termination of term rewriting.

In *Proc. 3rd IJCAR 2006*.

- search for LPO proof over infinite signature (\mathcal{R}_{lab}),



P. Schneider-Kamp, R. Thiemann, E. Annov, M. Codish and J. Giesl.

Implementing RPO using SAT.

WST 2007.



A. Koprowski and H. Zantema.

Automation of recursive path ordering for infinite labelled rewrite systems.

In *Proc. 3rd IJCAR 2006*.

How to search for termination proofs using PL + DP?

How to:

- choose which function symbols to label (L_f),
- search for quasi-model (f_A) and labeling functions (ℓ_f),



J. Endrullis, J. Waldmann, and H. Zantema.

Matrix interpretations for proving termination of term rewriting.

In *Proc. 3rd IJCAR 2006*.

- search for LPO proof over infinite signature (\mathcal{R}_{lab}),



P. Schneider-Kamp, R. Thiemann, E. Annov, M. Codish and J. Giesl.

Implementing RPO using SAT.

WST 2007.




A. Koprowski and H. Zantema.

Automation of recursive path ordering for infinite labelled rewrite systems.

In *Proc. 3rd IJCAR 2006*.

⇒ Idea: use SAT

Proving termination with PL



- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

Quasi-model constraints

- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

- We introduce:

- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

- We introduce:

- L_f to indicate whether f is labeled ($L_f \neq \emptyset$) and

Quasi-model constraints

- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

- We introduce:
 - L_f to indicate whether f is labeled ($L_f \neq \emptyset$) and
 - U_f variables to indicate whether f is usable for labeling.

Quasi-model constraints

- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

- We introduce:
 - L_f to indicate whether f is labeled ($L_f \neq \emptyset$) and
 - U_f variables to indicate whether f is usable for labeling.

- Usable rules:

$$\omega_{\text{UR}}(\mathcal{P}, \mathcal{R}) = \bigwedge_{f \in \mathcal{F}^\#} \left(L_f \implies \bigwedge_{g \in \Delta_f(\mathcal{P}, \mathcal{R})^*} U_g \right)$$

Quasi-model constraints

- Symbol dependencies:

$$\Delta_f(\mathcal{P}, \mathcal{R}) = \bigcup_{l \rightarrow r \in \mathcal{P} \cup \mathcal{R}} \{g \in \mathcal{F}(t) \mid \text{root}(t) = f \text{ and } t \sqsubseteq l \text{ or } t \sqsubseteq r\}.$$

- We introduce:

- L_f to indicate whether f is labeled ($L_f \neq \emptyset$) and
- U_f variables to indicate whether f is usable for labeling.

- Usable rules:

$$\omega_{\text{UR}}(\mathcal{P}, \mathcal{R}) = \bigwedge_{f \in \mathcal{F}^\#} \left(L_f \implies \bigwedge_{g \in \Delta_f(\mathcal{P}, \mathcal{R})^*} U_g \right)$$

- Quasi-model constraints:

$$\omega_{\text{QM}}(\mathcal{R}) = \bigwedge_{f \in \mathcal{D}_{\mathcal{R}}} \left(U_f \implies \bigwedge_{l \rightarrow r \in \mathcal{R}_f} \lceil [l]_{\mathcal{A}} \succeq_{\mathcal{A}} [r]_{\mathcal{A}} \rceil \right).$$

- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.

Encoding LPO

- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.
- Use the standard encoding of LPO only differently encoding precedence comparisons.

Encoding LPO

- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.
- Use the standard encoding of LPO only differently encoding precedence comparisons.
- Coding a precedence: for every $f \in \mathcal{F}$ introduce its level: $f_L \in \mathbb{N}$.

- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.
- Use the standard encoding of LPO only differently encoding precedence comparisons.
- Coding a precedence: for every $f \in \mathcal{F}$ introduce its level: $f_L \in \mathbb{N}$.
- This induces the precedence:
 - $f_o \succ g_o$ if $f_L >_{\mathbb{N}} g_L$
 - $f_i \succ g_j$ if $f_L =_{\mathbb{N}} g_L$ and $i >_{\mathcal{A}} j$.

Encoding LPO


- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.
- Use the standard encoding of LPO only differently encoding precedence comparisons.
- Coding a precedence: for every $f \in \mathcal{F}$ introduce its level: $f_L \in \mathbb{N}$ and sublevel: $f_{SL} \in \mathbb{N}$.
- This induces the precedence:
 - $f_o \succ g_o$ if $f_L >_{\mathbb{N}} g_L$
 - $f_i \succ g_j$ if $f_L =_{\mathbb{N}} g_L$ and $i >_{\mathcal{A}} j$ or $(i \succeq_{\mathcal{A}} j \text{ and } f_{SL} >_{\mathbb{N}} g_{SL})$.

Encoding LPO

- LPO lifts a well-founded (quasi)-ordering of function symbols to a well-founded (quasi)-ordering of terms.
- Use the standard encoding of LPO only differently encoding precedence comparisons.
- Coding a precedence: for every $f \in \mathcal{F}$ introduce its level: $f_L \in \mathbb{N}$ and sublevel: $f_{SL} \in \mathbb{N}$.
- This induces the precedence:
 - $f \circ g$ if $f_L >_{\mathbb{N}} g_L$
 - $f_i \succ g_j$ if $f_L =_{\mathbb{N}} g_L$ and $i >_{\mathcal{A}} j$ or $(i \gtrsim_{\mathcal{A}} j$ and $f_{SL} >_{\mathbb{N}} g_{SL})$.
- SAT encoding:

$$\begin{aligned}\lceil f_i \succ g_j \rceil &= \lceil f_L >_{\mathbb{N}} g_L \rceil \vee \left(\lceil f_L =_{\mathbb{N}} g_L \rceil \wedge L_f \wedge L_g \wedge (\lceil i >_{\mathcal{A}} j \rceil \vee \right. \\ &\quad \left. (\lceil i \gtrsim_{\mathcal{A}} j \rceil \wedge \lceil f_{SL} >_{\mathbb{N}} g_{SL} \rceil) \right) \\ \lceil f_i \succ f_j \rceil &= L_f \wedge \lceil i >_{\mathcal{A}} j \rceil\end{aligned}$$

Proving termination with PL



Finite branching condition

- Forbid rules of the shape:

$$\dots f_{0x+\dots} \dots \rightarrow \dots f_{cx+\dots} \quad c > 0$$

Finite branching condition

- Forbid rules of the shape:

$$\dots f_{0x+\dots} \dots \rightarrow \dots f_{cx+\dots} \quad c > 0$$

- by means of the following formula:

$$\omega_{\text{FB}}(\mathcal{R}) = \bigwedge_{l \mapsto r \in \mathcal{R}} \bigwedge_{x \in \mathcal{V}(r)} (\Phi_x(r) \implies \Phi_x(l))$$

with

$$\Phi_x(t) = \bigvee_{f(t_1, \dots, t_n) \leq t} L_f \wedge a > 0$$

where a is the coefficient of x when (symbolically) computing the label of f in $f(t_1, \dots, t_n)$.

Finite branching condition

- Forbid rules of the shape:

$$\dots f_{0x+\dots} \dots \rightarrow \dots f_{cx+\dots} \quad c > 0$$

- by means of the following formula:

$$\omega_{\text{FB}}(\mathcal{R}) = \bigwedge_{l \rightarrow r \in \mathcal{R}} \bigwedge_{x \in \mathcal{V}(r)} (\Phi_x(r) \implies \Phi_x(l))$$

with

$$\Phi_x(t) = \bigvee_{f(t_1, \dots, t_n) \leq t} L_f \wedge a > 0$$

where a is the coefficient of x when (symbolically) computing the label of f in $f(t_1, \dots, t_n)$.

Finite branching condition

- Forbid rules of the shape:

$$\dots f_{0x+\dots} \dots \rightarrow \dots f_{cx+\dots} \quad c > 0$$

- by means of the following formula:

$$\omega_{\text{FB}}(\mathcal{R}) = \bigwedge_{l \rightarrow r \in \mathcal{R}} \bigwedge_{x \in \mathcal{V}(r)} (\Phi_x(r) \implies \Phi_x(l))$$

with

$$\Phi_x(t) = \bigvee_{f(t_1, \dots, t_n) \leq t} L_f \wedge a > 0$$

where a is the coefficient of x when (symbolically) computing the label of f in $f(t_1, \dots, t_n)$.

Table: Experiments with TPA on 864 TRSs from the TPDB version 3.2.

		60 seconds timeout			10 minutes timeout		
	technique	yes	time	timeout	yes	time	timeout
1×1	SL	440	1178	2	440	1351	0
	PL	456	1193	2	456	1316	0
	PL'	426	752	1	426	893	0

Table: Experiments with TPA on 864 TRSs from the TPDB version 3.2.

		60 seconds timeout			10 minutes timeout		
	technique	yes	time	timeout	yes	time	timeout
1×1	SL	440	1178	2	440	1351	0
	PL	456	1193	2	456	1316	0
	PL'	426	752	1	426	893	0
2×2	SL	503	6905	51	506	24577	30
	PL	527	6906	53	532	25582	32
	PL'	522	5211	33	524	11328	8

1 Theory

- Semantic Labeling (SL)
- Predictive Labeling (PL)
- Dependency Pairs (DP)

2 Practice

- SAT encoding
- Experimental results

3 Conclusions

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Future work:

- extending interpretations to handle min and max functions.

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Future work:

- extending interpretations to handle min and max functions.
- experimenting with different base orders (RPO, KBO, ...),

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Future work:

- extending interpretations to handle min and max functions.
- experimenting with different base orders (RPO, KBO, ...),
- getting rid of the restriction to finitely branching systems (Ohlebusch),

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Future work:

- extending interpretations to handle min and max functions.
- experimenting with different base orders (RPO, KBO, ...),
- getting rid of the restriction to finitely branching systems (Ohlebusch),

Improvements and innermost termination:

Conclusions

We presented:

- an extension of the theory of PL to the DP setting,
- a way to effectively search for PL proofs using LPO by encoding the problem into SAT.

Future work:

- extending interpretations to handle min and max functions.
- experimenting with different base orders (RPO, KBO, ...),
- getting rid of the restriction to finitely branching systems (Ohlebusch),

Improvements and innermost termination:



R. Thiemann, A. Middeldorp.

Innermost Termination of Rewrite Systems by Labeling.

WRS 2007.

The end



Thank you for your attention.