

Certification of Matrix Interpretations in Coq

Adam Koprowski
(joint work with Hans Zantema)

Eindhoven University of Technology
Department of Mathematics and Computer Science

11 May 2007
CoLoR workshop

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR
 - Overview
 - Proof format

Outline

- 1 CoLoR
 - Motivation
- 2 Formalization of matrix interpretations
- 3 CoLoR

Motivation:

- **Enhanced trust in tools' results.**
- Common proof format – all tools speaking the same language!
 - common tools (proof presentation, manipulation, ...),
 - easier integration of the tools [Waldmann],
 - categories for single technique in the competition [Middeldorp],

Motivation:

- Enhanced trust in tools' results.
- **Common proof format – all tools speaking the same language!**
 - common tools (proof presentation, manipulation, ...),
 - easier integration of the tools [Waldmann],
 - categories for single technique in the competition [Middeldorp],

Motivation:

- Enhanced trust in tools' results.
- Common proof format – all tools speaking the same language!
 - common tools (proof presentation, manipulation, ...),
 - easier integration of the tools [Waldmann],
 - categories for single technique in the competition [Middeldorp],

Motivation:

- Enhanced trust in tools' results.
- Common proof format – all tools speaking the same language!
 - common tools (proof presentation, manipulation, ...),
 - **easier integration of the tools [Waldmann],**
 - categories for single technique in the competition [Middeldorp],

Motivation:

- Enhanced trust in tools' results.
- Common proof format – all tools speaking the same language!
 - common tools (proof presentation, manipulation, ...),
 - easier integration of the tools [Waldmann],
 - **categories for single technique in the competition [Middeldorp],**

Outline

- 1 CoLoR
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR

z086.trs

$$a(a(x)) \rightarrow c(b(x)), \quad b(b(x)) \rightarrow c(a(x)), \quad c(c(x)) \rightarrow b(a(x))$$

Matrix interpretation for z086.trs

$$a(x) = \begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix}$$

$$b(x) = \begin{bmatrix} 1 & 1 & 0 & 0 \\ 0 & 2 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$$

$$c(x) = \begin{bmatrix} 1 & 0 & 0 & 2 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$

z086.trs

$$a(a(x)) \rightarrow c(b(x)), \quad b(b(x)) \rightarrow c(a(x)), \quad c(c(x)) \rightarrow b(a(x))$$

Matrix interpretation for z086.trs

$$a(x) = \begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix}$$

$$b(x) = \begin{bmatrix} 1 & 1 & 0 & 0 \\ 0 & 2 & 0 & 1 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$$

$$c(x) = \begin{bmatrix} 1 & 0 & 0 & 2 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$

Termination proof for z086.trs

$$a(a(x)) = \begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} \left(\begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix} \right) + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix}$$

$$c(b(x)) = \begin{bmatrix} 1 & 0 & 0 & 2 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 0 & 0 & 0 \end{bmatrix} \left(\begin{bmatrix} 1 & 1 & 0 & 0 \\ 0 & 2 & 0 & 1 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} \right) + \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$

Termination proof for z086.trs

$$\begin{aligned}
 a(a(x)) &= \begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} \left(\begin{bmatrix} 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 1 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix} \right) + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix} \\
 &= \begin{bmatrix} 1 & 1 & 0 & 1 \\ 0 & 1 & 0 & 1 \\ 0 & 2 & 0 & 1 \\ 0 & 0 & 0 & 1 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix} \\
 c(b(x)) &= \begin{bmatrix} 1 & 0 & 0 & 2 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 0 & 2 \\ 0 & 0 & 0 & 0 \end{bmatrix} \left(\begin{bmatrix} 1 & 1 & 0 & 0 \\ 0 & 2 & 0 & 1 \\ 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix} \right) + \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix} \\
 &= \begin{bmatrix} 1 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 2 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{bmatrix} x + \begin{bmatrix} 0 \\ 0 \\ 2 \\ 0 \end{bmatrix}
 \end{aligned}$$

Outline

- 1 CoLoR
- 2 **Formalization of matrix interpretations**
 - Introduction to matrix interpretations
 - **Monotone algebras**
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR

Definition (Monotonicity)

An operation $[f] : A \times \dots \times A \rightarrow A$ is *monotone* with respect to a binary relation \triangleright on A if

$$a_i \triangleright a'_i \implies [f](a_1, \dots, a_i, \dots, a_n) \triangleright [f](a_1, \dots, a'_i, \dots, a_n).$$

Definition

Given a relation \triangleright on A we define its extension to a relation on terms as:

$$s \triangleright_{\mathcal{T}} t \equiv \forall \alpha : \mathcal{X} \rightarrow A, [s, \alpha] \triangleright [t, \alpha]$$

Definition (Monotonicity)

An operation $[f] : A \times \dots \times A \rightarrow A$ is *monotone* with respect to a binary relation \triangleright on A if

$$a_i \triangleright a'_i \implies [f](a_1, \dots, a_i, \dots, a_n) \triangleright [f](a_1, \dots, a'_i, \dots, a_n).$$

Definition

Given a relation \triangleright on A we define its extension to a relation on terms as:

$$s \triangleright_{\mathcal{T}} t \equiv \forall \alpha : \mathcal{X} \rightarrow A, [s, \alpha] \triangleright [t, \alpha]$$

Definition (A weakly monotone Σ -algebra)

A *weakly monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a Σ -algebra $(A, [\cdot])$ equipped with two binary relations $>, \gtrsim$ on A such that

- $>$ is well-founded;
- $> \cdot \gtrsim \subseteq >$;
- for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to \gtrsim .

Definition (An extended monotone Σ -algebra)

An *extended monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a weakly monotone Σ -algebra $(A, [\cdot], >, \gtrsim)$ in which moreover for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to $>$.

Definition (A weakly monotone Σ -algebra)

A *weakly monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a Σ -algebra $(A, [\cdot])$ equipped with two binary relations $>, \gtrsim$ on A such that

- $>$ is well-founded;
- $> \cdot \gtrsim \subseteq >$;
- for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to \gtrsim .

Definition (An extended monotone Σ -algebra)

An *extended monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a weakly monotone Σ -algebra $(A, [\cdot], >, \gtrsim)$ in which moreover for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to $>$.

Definition (A weakly monotone Σ -algebra)

A *weakly monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a Σ -algebra $(A, [\cdot])$ equipped with two binary relations $>, \gtrsim$ on A such that

- $>$ is well-founded;
- $> \cdot \gtrsim \subseteq >$;
- for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to \gtrsim .

Definition (An extended monotone Σ -algebra)

An *extended monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a weakly monotone Σ -algebra $(A, [\cdot], >, \gtrsim)$ in which moreover for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to $>$.

Definition (A weakly monotone Σ -algebra)

A *weakly monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a Σ -algebra $(A, [\cdot])$ equipped with two binary relations $>, \gtrsim$ on A such that

- $>$ is well-founded;
- $> \cdot \gtrsim \subseteq >$;
- for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to \gtrsim .

Definition (An extended monotone Σ -algebra)

An *extended monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a weakly monotone Σ -algebra $(A, [\cdot], >, \gtrsim)$ in which moreover for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to $>$.

Definition (A weakly monotone Σ -algebra)

A *weakly monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a Σ -algebra $(A, [\cdot])$ equipped with two binary relations $>, \gtrsim$ on A such that

- $>$ is well-founded;
- $> \cdot \gtrsim \subseteq >$;
- for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to \gtrsim .

Definition (An *extended monotone Σ -algebra*)

An *extended monotone Σ -algebra* $(A, [\cdot], >, \gtrsim)$ is a weakly monotone Σ -algebra $(A, [\cdot], >, \gtrsim)$ in which moreover for every $f \in \Sigma$ the operation $[f]$ is monotone with respect to $>$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , $(A, [\cdot], >, \gtrsim)$ be an extended monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R' \cup S'$

Then $\text{SN}(R/S)$ implies $\text{SN}(R \cup R' / S \cup S')$.

Theorem

Let R, R', S, S' be TRSs over a signature Σ , let $(A, [\cdot], >, \gtrsim)$ be a weakly monotone Σ -algebra such that:

- $\ell \gtrsim_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in $R \cup S$ and
- $\ell >_{\mathcal{T}} r$ for every rule $\ell \rightarrow r$ in R' ,

Then $\text{SN}(R_{\text{top}}/S)$ implies $\text{SN}((R \cup R')_{\text{top}}/S)$.

- **Monotone algebras are formalized as a functor.**
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_T$ and \gtrsim_T must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_T$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - **similarly for \gtrsim .**
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

- Monotone algebras are formalized as a functor.
- Apart for the aforementioned requirements there is one additional required to deal with concrete examples: $>_{\mathcal{T}}$ and $\gtrsim_{\mathcal{T}}$ must be decidable.
- More precisely the requirement is to provide a relation \gg , such that
 - $\gg \subseteq >_{\mathcal{T}}$ and
 - \gg is decidable
 - similarly for \gtrsim .
- The structure returned by the functor contains all the machinery required to prove (relative)-(top)-termination in Coq.

Outline

- 1 CoLoR
- 2 **Formalization of matrix interpretations**
 - Introduction to matrix interpretations
 - Monotone algebras
 - **Matrices**
 - Matrix interpretations
 - Practicalities
- 3 CoLoR

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - monotonicity of $*$
 - ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - monotonicity of $*$
 - ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:

- $M + N = N + M,$
- $M * (N * P) = (M * N) * P$
- monotonicity of $*$
- ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - monotonicity of $*$
 - ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - monotonicity of $*$
 - ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - **monotonicity of $*$**
 - ...

- Matrices are formalized as a functor taking as an argument the semi-ring of coefficients \mathcal{R} and providing a structure of matrices of arbitrary sizes with coefficients in \mathcal{R} and
- a number of basic operations over matrices such as:

$$[\cdot], \quad M_{i,j}, \quad M + N, \quad M * N, \quad M^T, \dots$$

- and a number of basic properties such as:
 - $M + N = N + M$,
 - $M * (N * P) = (M * N) * P$
 - monotonicity of $*$
 - ...

Outline

- 1 CoLoR
- 2 Formalization of matrix interpretations**
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations**
 - Practicalities
- 3 CoLoR

Polynomial interpretations in the setting of monotone algebras:

- $A = \mathbb{Z}$,
- $> = >_{\mathbb{Z}}, \gtrsim = \geq_{\mathbb{Z}}$,
- interpretations represented by polynomials
 $[f(x_1, \dots, x_n)] = P_{\mathbb{Z}}(x_1, \dots, x_n)$,
- $>_{\mathcal{T}}$ not decidable (positiveness of polynomial) — heuristics required.

Polynomial interpretations in the setting of monotone algebras:

- $A = \mathbb{Z}$,
- $> = >_{\mathbb{Z}}, \gtrsim = \geq_{\mathbb{Z}}$,
- interpretations represented by polynomials
 $[f(x_1, \dots, x_n)] = P_{\mathbb{Z}}(x_1, \dots, x_n)$,
- $>_{\mathcal{T}}$ not decidable (positiveness of polynomial) — heuristics required.

Polynomial interpretations in the setting of monotone algebras:

- $A = \mathbb{Z}$,
- $> = >_{\mathbb{Z}}, \gtrsim = \geq_{\mathbb{Z}}$,
- **interpretations represented by polynomials**
 $[f(x_1, \dots, x_n)] = P_{\mathbb{Z}}(x_1, \dots, x_n)$,
- $>_{\mathcal{T}}$ not decidable (positiveness of polynomial) — heuristics required.

Polynomial interpretations in the setting of monotone algebras:

- $A = \mathbb{Z}$,
- $> = >_{\mathbb{Z}}, \gtrsim = \geq_{\mathbb{Z}}$,
- interpretations represented by polynomials
 $[f(x_1, \dots, x_n)] = P_{\mathbb{Z}}(x_1, \dots, x_n)$,
- $>_{\mathcal{T}}$ not decidable (positiveness of polynomial) — heuristics required.

Matrix interpretations in the setting of monotone algebras:

- fix a dimension d ,
- $A = \mathbb{N}^d$,
- $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d)$ iff $\forall i, u_i \geq_{\mathbb{N}} v_i$,
- $(u_1, \dots, u_d) > (v_1, \dots, v_d)$ iff
 $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d) \wedge u_1 >_{\mathbb{N}} v_1$,
- interpretations represented as:
 $[f(x_1, \dots, x_n)] = M_1 x_1 + \dots + M_n x_n + v$
where $M_i \in \mathbb{N}^{d \times d}$, $v \in \mathbb{N}^d$,
- $>_{\mathcal{T}}$ and $\succeq_{\mathcal{T}}$ are decidable in this case but thanks to
introducing \gg we do not need to prove completeness of
their characterization.

- fix a dimension d ,

- fix a dimension d ,

- $A = \mathbb{N}^d$,

- $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d)$ iff $\forall i, u_i \geq_{\mathbb{N}} v_i$,

- interpretations represented as:

Matrix interpretations in the setting of monotone algebras:

- fix a dimension d ,
- $A = \mathbb{N}^d$,
- $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d)$ iff $\forall i, u_i \geq_{\mathbb{N}} v_i$,
- $(u_1, \dots, u_d) > (v_1, \dots, v_d)$ iff
 $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d) \wedge u_1 >_{\mathbb{N}} v_1$,
- interpretations represented as:
 $[f(x_1, \dots, x_n)] = M_1 x_1 + \dots + M_n x_n + v$
 where $M_i \in \mathbb{N}^{d \times d}$, $v \in \mathbb{N}^d$,
- $>_{\mathcal{T}}$ and $\succeq_{\mathcal{T}}$ are decidable in this case but thanks to introducing \gg we do not need to prove completeness of their characterization.

Matrix interpretations in the setting of monotone algebras:

- fix a dimension d ,
- $A = \mathbb{N}^d$,
- $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d)$ iff $\forall i, u_i \geq_{\mathbb{N}} v_i$,
- $(u_1, \dots, u_d) > (v_1, \dots, v_d)$ iff
 $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d) \wedge u_1 >_{\mathbb{N}} v_1$,
- **interpretations represented as:**
 $[f(x_1, \dots, x_n)] = M_1 x_1 + \dots + M_n x_n + v$
where $M_i \in \mathbb{N}^{d \times d}$, $v \in \mathbb{N}^d$,
- $>_{\mathcal{T}}$ and $\succeq_{\mathcal{T}}$ are decidable in this case but thanks to introducing \gg we do not need to prove completeness of their characterization.

Matrix interpretations in the setting of monotone algebras:

- fix a dimension d ,
- $A = \mathbb{N}^d$,
- $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d)$ iff $\forall i, u_i \geq_{\mathbb{N}} v_i$,
- $(u_1, \dots, u_d) > (v_1, \dots, v_d)$ iff
 $(u_1, \dots, u_d) \succeq (v_1, \dots, v_d) \wedge u_1 >_{\mathbb{N}} v_1$,
- interpretations represented as:
 $[f(x_1, \dots, x_n)] = M_1 x_1 + \dots + M_n x_n + v$
 where $M_i \in \mathbb{N}^{d \times d}$, $v \in \mathbb{N}^d$,
- $>_{\mathcal{T}}$ and $\succeq_{\mathcal{T}}$ are decidable in this case but thanks to introducing \gg we do not need to prove completeness of their characterization.

Outline

- 1 CoLoR
- 2 Formalization of matrix interpretations
 - Introduction to matrix interpretations
 - Monotone algebras
 - Matrices
 - Matrix interpretations
 - Practicalities
- 3 CoLoR

Formalization size (LOC):

- **Monotone algebras:** 351
- Matrices: 642
- Matrix interpretations: 673
- Polynomial interpretations in MA setting: 116

Formalization size (LOC):

- Monotone algebras: 351
- **Matrices:** 642
- Matrix interpretations: 673
- Polynomial interpretations in MA setting: 116

Formalization size (LOC):

- Monotone algebras: 351
- Matrices: 642
- **Matrix interpretations: 673**
- Polynomial interpretations in MA setting: 116

Formalization size (LOC):

- Monotone algebras: 351
- Matrices: 642
- Matrix interpretations: 673
- Polynomial interpretations in MA setting: 116

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- **polynomial interpretations:** 167
- matrix interpretations: 237
- polynomial and matrix interpretations: 275
 - Verification time: AVG: 5sec. MAX: 75sec.
 - Certificate size: AVG: 25kB. MAX: 437kB
 - Proof steps: AVG: 5 MAX: 29

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- **matrix interpretations:** **237**
- polynomial and matrix interpretations: 275
 - Verification time: AVG: 5sec. MAX: 75sec.
 - Certificate size: AVG: 25kB. MAX: 437kB
 - Proof steps: AVG: 5 MAX: 29

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- matrix interpretations: 237
- **polynomial and matrix interpretations: 275**
 - Verification time: AVG: 5sec. MAX: 75sec.
 - Certificate size: AVG: 25kB. MAX: 437kB
 - Proof steps: AVG: 5 MAX: 29

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- matrix interpretations: 237
- polynomial and matrix interpretations: 275
 - **Verification time:** **AVG: 5sec.** **MAX: 75sec.**
 - Certificate size: AVG: 25kB. MAX: 437kB
 - Proof steps: AVG: 5 MAX: 29

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- matrix interpretations: 237
- polynomial and matrix interpretations: 275
 - Verification time: AVG: 5sec. MAX: 75sec.
 - **Certificate size:** **AVG: 25kB.** **MAX: 437kB**
 - Proof steps: AVG: 5 MAX: 29

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- matrix interpretations: 237
- polynomial and matrix interpretations: 275
 - Verification time: AVG: 5sec. MAX: 75sec.
 - Certificate size: AVG: 25kB. MAX: 437kB
 - **Proof steps: AVG: 5 MAX: 29**

Evaluation of **TPA + Rainbow** on **TPDB 3.2** (864 TRSs):

- polynomial interpretations: 167
- matrix interpretations: 237
- polynomial and matrix interpretations: 275
 - Verification time: AVG: 5sec. MAX: 75sec.
 - Certificate size: AVG: 25kB. MAX: 437kB
 - Proof steps: AVG: 5 MAX: 29

“demo”

Outline

- 1 CoLoR
- 2 Formalization of matrix interpretations
- 3 CoLoR
 - Overview
 - Proof format

Content of CoLoR.

- **Termination criteria:**

- **matrix interpretations** [Koprowski, Zantema]
- dependency graph cycles [Blanqui]
- higher-order recursive path ordering [Koprowski]
- recursive path ordering [Coupet-Grimal, Delobel]
- multiset ordering [Koprowski]
- **polynomial interpretations** [Hinderer]

- Transformation techniques:

- dependency pairs [Blanqui]
- rule elimination [Blanqui]
- arguments filtering [Blanqui]
- conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - **dependency graph cycles** [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - **higher-order recursive path ordering** [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - **recursive path ordering** [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - **multiset ordering** [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - **dependency pairs** [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - **rule elimination** [Blanqui]
 - arguments filtering [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - **arguments filtering** [Blanqui]
 - conversion from algebraic to varyadic terms [Blanqui]

Content of CoLoR.

- Termination criteria:
 - **matrix interpretations** [Koprowski, Zantema]
 - dependency graph cycles [Blanqui]
 - higher-order recursive path ordering [Koprowski]
 - recursive path ordering [Coupet-Grimal, Delobel]
 - multiset ordering [Koprowski]
 - **polynomial interpretations** [Hinderer]
- Transformation techniques:
 - dependency pairs [Blanqui]
 - rule elimination [Blanqui]
 - arguments filtering [Blanqui]
 - **conversion from algebraic to varyadic terms** [Blanqui]

Content of CoLoR (ctd.)

- **General libraries:**

- matrices [Koprowski]
- simply typed lambda-terms [Koprowski]
- finite multisets [Koprowski]
- varyadic terms [Blanqui]
- algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
- integer polynomials with multiple variables [Hinderer]
- vectors [Hinderer, Blanqui]
- lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:

- **matrices [Koprowski]**
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - **simply typed lambda-terms [Koprowski]**
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - **finite multisets [Koprowski]**
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - **varyadic terms [Blanqui]**
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - **integer polynomials with multiple variables [Hinderer]**
 - vectors [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - **vectors** [Hinderer, Blanqui]
 - lists, relations, etc.

Content of CoLoR (ctd.)

- General libraries:
 - matrices [Koprowski]
 - simply typed lambda-terms [Koprowski]
 - finite multisets [Koprowski]
 - varyadic terms [Blanqui]
 - algebraic terms with symbols of fixed arity [Hinderer, Blanqui]
 - integer polynomials with multiple variables [Hinderer]
 - vectors [Hinderer, Blanqui]
 - **lists, relations, etc.**

- Lines of code

Data-types	11.990	28.69%
Terms	18.474	44.21%
Math	4.007	9.59%
Term. techniques	7.312	17.49%
Total	41.783	100.00%

- Coq constructs

Inductive definitions	38
Fixpoint definitions	115
Definitions	554
Lemmas	2.160

- Lines of code

Data-types	11.990	28.69%
Terms	18.474	44.21%
Math	4.007	9.59%
Term. techniques	7.312	17.49%
Total	41.783	100.00%

- Coq constructs

Inductive definitions	38
Fixpoint definitions	115
Definitions	554
Lemmas	2.160

Outline

- 1 CoLoR
- 2 Formalization of matrix interpretations
- 3 CoLoR
 - Overview
 - Proof format

```
type vector = int list
type matrix = vector list
type monom = int list
type polynom = (int * monom) list
type poly_int = polynom FMap.t
type mi_fun = { mi_const: vector; mi_args: matrix list }
type matrix_int = { mi_dim: int; mi_int: mi_fun FMap.t }
type red_ord =
  | PolyInt of poly_int
  | MatrixInt of matrix_int
type proof =
  | MannaNess of red_ord * proof
  | Trivial
```