Jailbreak Vision Language Models via Bi-Modal Adversarial Prompt

Zonghao Ying, Aishan Liu, Tianyuan Zhang, Zhengmin Yu, Siyuan Liang, *Member, IEEE*, Xianglong Liu, *Senior Member, IEEE*, and Dacheng Tao, *Fellow, IEEE*

***Abstract*—In the realm of large vision language models (LVLMs), jailbreak attacks serve as a red-teaming approach to bypass guardrails and uncover safety implications. Existing jailbreaks predominantly focus on the visual modality, perturbing solely visual inputs in the prompt for attacks. However, they fall short when confronted with aligned models that fuse visual and textual features simultaneously for generation. To address this limitation, this paper introduces the Bi-Modal Adversarial Prompt Attack (*BAP*), which executes jailbreaks by optimizing textual and visual prompts cohesively. Initially, we adversarially embed universally adversarial perturbations in an image, guided by a few-shot query-agnostic corpus (*e.g.*, affirmative prefixes and negative inhibitions). This process ensures that the adversarial image prompt LVLMs to respond positively to harmful queries. Subsequently, leveraging the image, we optimize textual prompts with specific harmful intent. In particular, we utilize a large language model to analyze jailbreak failures and employ chain-of-thought reasoning to refine textual prompts through a feedback-iteration manner. To validate the efficacy of our approach, we conducted extensive evaluations on various datasets and LVLMs, demonstrating that our *BAP* significantly outperforms other methods by large margins (+29.03% in attack success rate on average). Additionally, we showcase the potential of our attacks on black-box commercial LVLMs, such as GPT-4o and Gemini. Our code is available at https://anonymous.4open.science/r/BAP-Jailbreak-Vision-Language-Models-via-Bi-Modal-Adversarial-Prompt-5496**

***Index Terms*—Large vision language models (LVLMs), jailbreak attack, red-teaming, adversarial perturbation, chain-of-thought.**

I. Introduction

RECENTLY, there has been a notable surge of interest in integrating vision into large language models (LLMs), giving rise to large vision language models (LVLMs). Representing a class of models that amalgamate visual and textual information, LVLMs (*e.g.*, LLaVA [1] and GPT-4o [2]) have demonstrated promising performance across a wide range of tasks, encompassing image captioning [3], visual question answering [4], and image retrieval [5]. However, the behaviors exhibited by LVLMs are misaligned easily from the intended goals of their creators, often generating outputs that are untruthful or potentially harmful to users [6], [7], [8], [9].

To unveil and mitigate these security risks, *jailbreak attacks* [10], [11], [12] have emerged as a red teaming strategy to circumvent guardrails and assess model alignment [13], [14]. After jailbreaking, attackers can convince the model to do anything resulting in severe safety consequences, *e.g.*, generating harmful or unethical content that is otherwise prohibited by alignment guidelines. While numerous disclosures and demonstrations utilizing jailbreaks have emerged within the LVLM context, most attacks have traditionally focused on perturbing the visual modality (*i.e.*, images) for jailbreaks. These include crafting visual adversarial examples [6], [9], [15] and encoding attack intents into typographic images [16], [17]. However, aligned LVLMs leverage both visual and textual features simultaneously for prediction, thereby limiting the efficacy of current attacks that solely perturb a single modality (*i.e.*, vision). For instance, LLaVA [1] will refuse to answer in the presence of an adversarial image that is not associated with a textual prompt [18], resulting in a failed jailbreak.

To address the problem, this paper introduces the Bi-Modal Adversarial Prompt Attack (*BAP*), a novel framework for jailbreaking LVLMs by optimizing both visual and textual prompts simultaneously (*c.f.* Fig. 1). Initially, we embed universal adversarial perturbations in the visual domain, optimizing them by maximizing the model log-likelihood using a query-agnostic corpus (*e.g.*, affirmative prefixes and negative inhibition). This approach broadens the attacking scope, encouraging LVLMs to provide positive responses irrespective of the specific intents of the textual prompt. Subsequently, leveraging the adversarial image, we construct adversarial textual prompts to induce LVLMs to generate specific types of harmful content. Here, we employ an LLM and adopt a step-by-step reasoning process to generate optimal textual prompts for attacks. Specifically, we utilize the Chain-of-Thought (CoT) strategy [19] to analyze jailbreak failures and optimize textual prompts based on the harmful intent. In summary, our *BAP* framework conducts query-agnostic image perturbing and intent-specific textual optimization, adding

Received 22 December 2024; revised 1 May 2025; accepted 10 June 2025. Date of publication 30 June 2025; date of current version 16 July 2025. This work was supported in part by the National Natural Science Foundation of China under Grant 62206009; in part by the State Key Laboratory of Complex and Critical Software Environment (CCSE), Aeronautical Science Fund under Grant 20230017051001; and in part by the Fundamental Research Funds for the Central Universities. The associate editor coordinating the review of this article and approving it for publication was Dr. Ran He. *(Corresponding author: Aishan Liu.)*

Zonghao Ying is with the SKLCCSE, School of Artificial Intelligence, Beihang University, Beijing 100191, China.

Aishan Liu, Tianyuan Zhang, and Xianglong Liu are with the SKLCCSE, School of Computer Science and Engineering, Beihang University, Beijing 100191, China (e-mail: liuaishan@buaa.edu.cn; xlliu@buaa.edu.cn).

Zhengmin Yu is with the School of Computer Science, Fudan University, Shanghai 200438, China.

Siyuan Liang is with the School of Computing, National University of Singapore, Singapore 117417.

Dacheng Tao is with the College of Computing and Data Science, Nanyang Technological University, Singapore 639798.

This article has supplementary downloadable material available at https://doi.org/10.1109/TIFS.2025.3583249, provided by the authors.

Digital Object Identifier 10.1109/TIFS.2025.3583249

1556-6021 © 2025 IEEE. All rights reserved, including rights for text and data mining, and training of artificial intelligence and similar technologies. Personal use is permitted, but republication/redistribution requires IEEE permission.
See https://www.ieee.org/publications/rights/index.html for more information.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.



(a) Normal Scenario



(b) Attacking Scenario

Fig. 1. Illustration of our *BAP* jailbreak attack on LVLMs.

perturbations to both visual and textual prompts to enhance LVLM jailbreak attacks. To demonstrate the effectiveness, we conducted jailbreak attacks on three popular open-source LVLMs over SafetyBench [18] and AdvBench [20] datasets, outperforming other baselines significantly (+29.03% in attack success rate on average). Meanwhile, we successfully attacked commercial LVLMs including GPT-4o [2], Gemini [21] (pro v1.0), GLM [22] (v3), Qwen [23] (v2.1), and ERNIE Bot [24] (v3.5). Interestingly, our method shows high potential in conducting *universal* attacks, which can be used to generate biased outputs and evaluate model robustness. Our main **contributions** include:

- This paper proposes *BAP* to generate jailbreak attacks on LVLMs by simultaneously perturbing visual and textual modalities, which is designed to compensate for the limitations of existing attacks that only perturb visual inputs.
- To achieve this goal, *BAP* initially embeds adversarial perturbations in the visual prompt using a few-shot query-agnostic corpus; we subsequently optimize the textual prompt using CoT reasoning by an LLM to achieve adaptive refinement for specific harmful intention.
- Extensive experiments were conducted on popular open-source LVLMs in both white-box and black-box scenarios to confirm the effectiveness of our attack. Additionally, our attack can successfully jailbreak commercial LVLMs and can be used to evaluate the bias and robustness of LVLMs.

II. Related Works

Jailbreak attacks typically refer to the act of leveraging vulnerabilities within a constrained system (*e.g.*, a large model) to bypass imposed restrictions and security guardrails, aim to achieve privilege escalation, such as inducing the model to generate a harmful response. In recent times, there has been a plethora of approaches to jailbreak LLMs, which can be roughly categorized into three main types based on the design of prompts: hand-designed approaches [11], [25], model-generation approaches [26], [27], and search-generation approaches [20], [28]. With the extensive use of multi-modality data, jailbreak attacks have been developed **in the context of LVLMs**. Gong et al. [17] divided harmful requests into several steps and presented them as typographic representations in images, requesting the LVLM to complete the blank. Liu et al. [18] employed a text-to-image model to construct visual adversarial prompts by converting harmful textual semantics into images and splicing on typographic images that represent specific textual semantics. In addition, Shayegani et al. [9] constructed adversarial examples and kept the harmful semantics visually hidden. To enhance the probability of the model in generating a specific harmful response, Qi et al. [29] prepared a corpus related to harmful semantics and utilized it to optimize the visual adversarial prompt. Similarly, Niu et al. [30] used a pre-prepared corpus of harmful requests and responses as constraints for optimizing the visual adversarial prompt. Besides jailbreak attacks, another typical way to evaluate the security of models is through **adversarial examples** [6], [7], [8], [15], [31], [32], [33]. This attack primarily generates inputs containing imperceptible perturbations for deep learning models, aiming to induce model malfunction rather than produce a harmful response. *This paper aims to* ***conduct jailbreak attacks on LVLMs*** *to induce harmful responses.*

III. Preliminaries

A. Large Vision Language Models

Recent LVLMs (*e.g.*, LLaVA [1], MiniGPT-4 [34], and InstructBLIP [34]) have shown strong performance in a variety of tasks. An LVLM F_θ is typically comprised of three main modules: a visual module F_v (*e.g.*, visual encoder from CLIP [35]), a textual module F_t (usually an LLM such as LLaMA [36] and Vicuna [37]), and a vision-language connector $\mathcal{I}$ (*e.g.*, cross attention, projection layer). Given a prompt pair containing a visual prompt (image) $x_v \in \mathbb{V}$ and a textual prompt (text) $x_t \in \mathbb{T}$, the visual module F_v encodes x_v into h_v, and the connector $\mathcal{I}$ fuses h_v with the textual query x_t. This fusion process enables the textual module F_t to execute both understanding and generation tasks based on the multi-modal features $\mathcal{I}(h_v, x_t)$. To summarize, the LVLM processing flow can be illustrated as

$$y = F_t(\mathcal{I}(h_v, x_t)), \quad h_v = F_v(x_v). \tag{1}$$

Here, we use $y = F_\theta(x_v, x_t)$ for simplicity. Essentially, F_θ is a probability function $F_\theta : \mathbb{Q} \to \mathbb{R}$, where $\mathbb{Q} = \mathbb{V} \times \mathbb{T}$ represents the input query domain and $\mathbb{R}$ represents the response domain. The response y is generated through predicting the probability distribution $p(y|(x_v, x_t))$. Prior to release, developers employ the security alignment techniques [38], [39] on LVLMs to prevent the output of harmful responses $y^* \in \mathbb{R}$.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.



Fig. 2. Our *BAP* framework includes two primary modules, *i.e.*, query-agnostic image perturbing and intent-specific textual optimization, which individually add perturbations to visual and textual prompts. The optimized prompt pairs will induce target LVLMs to generate harmful responses.

B. Problem Definition

1) Jailbreak Attacks on LVLMs: To induce an LVLM to generate a harmful response, a jailbreak attack modifies a benign query (x_v, x_t) to a harmful query $\mathcal{A}(x_v, x_t)$, where $\mathcal{A}(\cdot)$ denotes a perturbation injection function designed by the attacker. Here, $A(x_v, x_t)$ is expected to elicit a harmful response y^* from the LVLM F_θ. Generally, this procedure can be achieved by maximizing the model's log-likelihood of outputting the harmful response y^* as

$$\max_{\mathcal{A}} \log\ p(y^*|\mathcal{A}(x_v, x_t)). \tag{2}$$

Here, $\mathcal{A}(\cdot)$ can be realized by either perturbing a single modality (*e.g.*, visual prompt x_v or textual prompt x_t) or perturbing both.

2) Limitations of Existing Attacks: To successfully jailbreak an LVLM, the key is to design an effective perturbation injection function $\mathcal{A}(\cdot)$. Existing attacks focus solely on perturbing the visual modality to construct visual adversarial prompts x_v^*. However, the adversarial prompt pair (x_v^*, x_t) generated by such attacks *do not fully compromise* the nature of LVLMs. As shown in Eq. (1), an LVLM (especially an aligned model) fuse visual and textual features simultaneously to generate responses, limiting the effectiveness of current attacks that only perturb visual prompts x_v [18] (as verified by our experiments in Sec. V). By contrast, this paper argues that perturbing both x_t and x_v will lead to stronger jailbreak attacks on LVLMs. *BAP* first influences the context of the target LVLM's response through visual adversarial prompt, inducing it to give a positive response even to harmful queries. It then further enhances the performance of the jailbreak attack by constructing adaptively optimized textual adversarial prompts.

C. Threat Model

1) Attacker's Goals: The goal of the attacker is to provide target LVLM with an adversarial prompt pair $\mathcal{A}(x_v, x_t)$, thereby bypassing the alignment guardrails and forcing the LVLM to generate harmful responses. Such harmful responses encompass outputs that violate human values, reveal methods for creating illegal items, and other content that should not be responded to under normal circumstances.

2) Attacker's Capabilities: Following [9], [29], attackers have access to information pertaining to the LVLM (*e.g.*, architecture, weights); however, they do not require knowledge of other sensitive information (*e.g.*, system prompts, training datasets). Similar to [9], [15], [29], and [30], the perturbations on the images are constrained as $\|x_v^* - x_v\|_\infty \leq \epsilon$, where ϵ is the predefined boundary.

IV. Bi-Modal Adversarial Prompt

Previous studies on jailbreaking LVLMs have overlooked the interactive impact of visual and textual modalities, resulting in limited efficacy against aligned LVLMs that exploit bi-modal features for generations. In light of this, we propose the *BAP* framework which is illustrated in Fig. 2. Overall, our framework includes two primary modules: query-agnostic image perturbation and intent-specific textual optimization, which individually add perturbations to visual and textual prompts. Therefore, the optimized input pair $(x_v^*,\ x_t^*)$ will induce target LVLMs to generate harmful responses.

A. Query-Agnostic Image Perturbing

As the text module of the LVLM generates a response, its subsequent output tokens maintain logical and semantic coherence with the previously generated tokens [40]. As shown in Eq. (1), these previous tokens are based on visual prompts, indicating that the visual prompts influence the subsequent

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

outputs of the model. Existing work generally embeds specific harmful semantics into visual prompts. Although effective, this approach narrows the scope of jailbreaking attacks (*i.e.*, the semantics of subsequent text queries must be related to the visual prompts, making them query-dependent). For example, if the visual prompt is semantically related to bomb making, then if the textual prompt is asking how to make illegal drugs, the jailbreak will fail.

In order to address this limitation, we designed a query-agnostic image perturbation method to implement jailbreak attacks by embedding a universal adversarial perturbation in the visual prompt. The resulting visual adversarial prompt will encourage the LVLM to output positive responses, thereby ensuring logical consistency regardless of the specific harmful intent of the textual prompts (*e.g.*, illegal activity or hate speech). To achieve this goal, inspired by jailbreaks on LLMs [11], [20], we utilize an LLM to construct a query-agnostic corpus $Y := \{y_j\}_{j=1}^{m}$, consisting of m sentences associated with *affirmative prefixes* (*e.g.*, "`Sure...`") and *negative inhibitions* (*e.g.*, "`Not answer the question with 'I am sorry...'`"). Based on the few-shot corpus, we can optimize the visual adversarial prompt by maximizing the log-likelihood of the model in generating the target sentences as

$$\max_{x_v^*} \sum_{j=1}^{M} \log\ p(y_j|(x_v^*, .)), \qquad s.t. \|x_v^* - x_v\|_\infty \leq \epsilon, \tag{3}$$

where ϵ represents the budget for controlling perturbations. The optimization problem in Eq. (3) is solved using the classical PGD adversarial attack [41] in this paper. It should be noted that we nullify the textual prompt x_t during optimization primarily to avoid its influence. Consequently, the visual adversarial prompt x_v^* elicits a positive response from the LVLM irrespective of the specific intent of the textual prompt x_t.

Based on the above strategy, the embedded semantics within the visual adversarial prompt generate a conflict between the safety objective and the instruction-following objective of the target LVLM. Specifically, the safety objective mandates the LVLM to reject harmful queries, while the instruction-following objective necessitates a positive response, thereby ensuring that LVLM outputs remain valid even when receiving harmful queries. Essentially, *BAP* achieves attack by generating visual adversarial prompts x_v^*. That is, regardless of the harmful intent of the textual prompt, the LVLM can output a valid response.

B. Intent-Specific Text Optimization

After obtaining a query-agnostic visual adversarial prompt x_v^*, we construct the textual adversarial prompt x_t^* to enhance the jailbreak capability of *BAP* under specific harmful intent (*i.e.*, inducing the model to generate specific types of harmful content). In general, textual prompt optimization also follows Eq. (2), however, we fix x_v^* and attempt to find the optimal x_t^* as

$$x_t^* = \max_{x_t \in \mathbb{T}} \log\ p(y^*|(x_v^*, x_t)). \tag{4}$$

Algorithm 1 CoT-Based Text Optimization Algorithm

Input: Harmful Request A, Visual Adversarial Prompt x_v^*, Judging Prompt Template P_J, CoT Prompt Template P_C, Iteration Number N
Output: Textual Adversarial Prompt x_t^*
Initialization $y^0 = F_\theta(x_v^*, x_t^0)$
for $i = 0$ **to** N **do**
  $flag = \mathcal{M}(P_J, q, x_t^i, y^i)$
  if $flag$ **then**
    return $x_t^* = x_t^i$
    break
  end
  else
    $x_t^{i+1} = \mathcal{M}(P_C, q, x_t^i, y^i)$
    $y^{i+1} = F_\theta(x_v^*, x_t^{i+1})$
  end
end

Directly solving the above equation in the large discrete textual space is highly non-trivial. Therefore, we utilize an LLM $\mathcal{M}$ to reason about the jailbreak attack and generate optimal textual prompts in a step-by-step manner through the Chain-of-Thought (CoT) strategy [19]. CoT has the potential to enhance the text comprehension and reasoning abilities of LLM, thereby significantly improving its performance on complex reasoning tasks [42]. In our case, the LLM is expected to effectively analyze the reasons for jailbreak failure and optimize textual adversarial prompts based on harmful intentions. This complex task can be effectively addressed with the introduction of the CoT strategy. Specifically, the optimization process is divided into three stages: initialization, feedback, and iteration. Algorithms Alg. 1 summarizes the detailed procedure.

1) Initialization: Given a harmful intent q, we directly consider it as the initial textual prompt, *i.e.*, $x_t^{(0)} = q$. Given the pair of a visual adversarial prompt x_v^* and the textual prompt $x_t^{(0)}$, we can obtain the initial response from the LVLM as $y^{(0)} = F_\theta(x_v^*, x_t^{(0)})$.

2) Feedback: We utilize the function $\mathcal{J}(\cdot)$ to assess the responses of LVLMs to determine the success of the jailbreak. If the attack is successful, the function $\mathcal{J}(\cdot)$ returns 1; otherwise, it returns 0. Specifically, we instantiate $\mathcal{J}(\cdot)$ using an LLM $\mathcal{M}$ with a specially designed judging prompt template P_J (in *Supplementary Material*). The LLM $\mathcal{M}$ provides a judgment result *flag* as

$$flag = \mathcal{M}(P_J, q, y^{(i)}), \tag{5}$$

where $y^{(i)} = F_\theta(x_v^*, x_t^{(i)})$ denotes the LVLM prediction.

3) Iteration: The LLM will iteratively optimize the textual prompt, considering the previous failed jailbreak ($flag = 0$), until either a successful attack is found or the maximum optimization number is exceeded. Specifically, With the assistance of the CoT-based prompt template P_C and the harmful intent q, the LLM $\mathcal{M}$ analyzes the reasons for latest failed jailbreaking based on the LVLM's response $y^{(i)}$ and latest textual prompt $x_t^{(i)}$, subsequently rephrases $x_t^{(i)}$ into a new textual prompt $x_t^{(i+1)}$ through:

$$x_t^{(i+1)} = \mathcal{M}(P_C, q, x_t^{(i)}, y^{(i)}). \tag{6}$$

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

We utilize the zero-shot form [43] of the CoT and provide rephrasing strategies in P_C to assist the optimization, such as contextual deception, semantic rephrasing, *etc*. Please refer to *Supplementary Material* for details of the template. This feedback-iteration optimization process is conducted through continuous N-round iterations, enabling the LLM to comprehend and refine textual adversarial prompts to achieve specific harmful intents.

C. Comparison With Other Attacks

Our approach distinguishes itself from prior works in several key aspects. ❶ Attack motivation. We have meticulously designed perturbations for the dual-modal inputs accepted by LVLM, achieving a more effective and generalizable attack. Similar works [9], [17], [18] primarily focus on constructing adversarial visual images, with limited consideration and careful design of attack effectiveness in the text modality. ❷ Attack implementation. Inspired by [11] and [20], we designed visual adversarial prompts using affirmative prefixes and negative suppressions for universal jailbreak, unlike [29] relying on specific harmful content. For textual prompts, we used CoT techniques to guide LLM responses and analyze jailbreak failures, enabling adaptive updates. In contrast, works like [9], [18] rely on manually crafted prompts, lacking systematic optimization. Although [12], [26] perform optimization, [12] relies on predefined logic, authority, and role-playing prompts for LLMs, lacking detailed failure analysis, while [26] employs a computationally intensive branching-and-pruning approach to generate and filter prompt variants. ❸ Attack effects. We are the first to implement a universal jailbreak attack in general scenarios, where a single image combined with specific harmful requests can achieve a jailbreak for the corresponding task. In contrast, [29] can only jailbreak harmful speech scenarios, while [12] performs targeted adversarial attacks that prompt the model to output specific words, such as "Unknown", rather than achieving universal jailbreaking.

V. Experiment and Evaluation

A. Experimental Setups

1) Models and Datasets: In this study, we primarily examine three commonly-used open-source LVLMs including LLaVA [1] (LLaVA-V1.5-7B), MiniGPT-4 [34] (Vicuna 7B), and InstructBLIP [44] (Vicuna 7B). All mentioned models utilize the weights provided by their respective original repositories. Additionally, we evaluate commercial black-box LVLMs, including GPT-4o [2], Gemini [21], ChatGLM [22], Qwen [23], and ERNIE Bot [24]. We employ two commonly used datasets for evaluation: SafetyBench [18] and AdvBench [20]. SafetyBench is a benchmark for evaluating the safety of LVLMs, encompassing 13 prohibited scenarios specified in OpenAI and Meta's usage strategies [45], [46]. AdvBench [20], widely used in prior LLM jailbreak research, includes 521 harmful behaviors. We eliminated duplicate items from AdvBench and incorporated each item into SafetyBench based on the corresponding scenario for our experiment.

2) Evaluation Metric: We employ Attack Success Rate (ASR) as our primary metric to assess the effectiveness of our approach. ASR quantifies the probability that model F_θ generate a harmful response y_t^*. We followed similar evaluation method [18], [47], [48], [49], focusing on automatic evaluation, and confirmed the results with manual evaluation. Automatic evaluation is conducted using the function $\mathcal{J}(\cdot)$ proposed in Sec. IV. For manual evaluation, three volunteers were recruited to verify the responses of the LVLMs. They were provided only with the harmful request and the corresponding scenario as background knowledge, without knowledge of the adversarial prompt pairs. *Higher ASRs indicate better attacks.*

3) Compared Attacks: We compared *BAP* with three state-of-the-art jailbreak attacks, including structure-based methods (Liu et al. [18] and FigStep [17]) and an optimization-based method (Qi et al. [29]). Liu et al. combined images related to the attacking intent with typographic text as visual adversarial prompts. FigStep converts harmful instructions into typeset images, paired with neutral text prompts to guide the model to respond. Qi et al. optimized visual adversarial prompts based on a corpus of specific scenarios. Additionally, we report the results of the *No Attack* scenario, where harmful queries from the dataset are directly fed into the LVLMs. *Note that* the visual prompts required by all baseline attack methods for each attack are not universal. Liu et al. requires generating images related to the semantics of the harmful instruction using a text-to-image generation model. FigStep reformulates the harmful instruction into a textual statement starting with nouns such as "Steps to", and subsequently converts this into a typography image as the visual prompt. Qi et al. constructs a specific corpus for optimization based on the different harmful instruction. In contrast, the visual prompts used in *BAP* are capable of performing universal attacks.

Therefore, for a fair comparison, we conducted experiments in both *query-dependent* and *query-agnostic* settings in white-box scenarios. (Since FigStep's text prompt is entirely neutral and thus ineffective under the *query-agnostic* setting, we follow its original setup.)

4) Implementation Details: In our *BAP*, for visual adversarial prompt, we employ 3000-step PGD to optimize Eq. (3), with step-size to 1 and ϵ to 32/255. In the text optimization phase, we set the iteration number $N = 5$, and any textual adversarial prompt obtained after more than 5 iterations is not considered valid, even if it successfully jailbreaks LVLMs. For all evaluated models, we used their default temperature settings. Specifically, we employ ChatGPT to instantiate the LLM $\mathcal{M}$ referenced in this paper. All experiments are conducted on an NVIDIA A800 Cluster.

B. White-Box Attacks on LVLMs

We first conduct white-box jailbreak attacks, where adversaries have detailed knowledge of the target model (*e.g.*, gradients). Due to space constraints, we report only the attack results on MiniGPT4 in Tab. I within our main paper. Additionally, *Supplementary Material* contains experimental findings from attacks on LLaVA and InstructBLIP, respectively.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

TABLE I

RESULTS (%) OF WHITE-BOX JAILBREAKING MINIGPT4. OUR ATTACK ACHIEVES THE BEST ATTACKING PERFORMANCE IN BOTH QUERY-DEPENDENT (QD) AND QUERY-AGNOSTIC (QA) SETTINGS

Scens.	No Attack	QD		QA: IA → *other*		QA: HS → *other*		FigStep [17]	**BAP**
		Liu *et al.* [18]	Qi *et al.* [30]	Liu *et al.* [18]	Qi *et al.* [30]	Liu *et al.* [18]	Qi *et al.* [30]		
Illegal Activity (IA)	2.13	19.27	13.71	19.27	13.71	2.29	1.62	42.65	**59.04**
Hate Speech (HS)	1.69	15.36	4.64	1.55	2.26	15.36	4.64	29.57	**45.62**
Malware Generation (MG)	5.32	24.38	17.98	4.61	5.83	3.25	6.11	**38.22**	36.97
Physical Harm (PH)	8.68	32.98	29.17	9.92	9.35	5.42	9.83	39.29	**56.48**
Economic Harm (EH)	4.85	6.14	7.05	2.46	3.92	3.57	3.39	49.96	**55.44**
Fraud (FR)	3.31	20.64	17.93	2.51	3.18	2.94	3.25	**51.95**	49.27
Pornography (PO)	5.57	26.38	19.18	6.97	5.43	4.63	6.04	34.53	**55.93**
Political Lobbying (PL)	86.54	88.61	80.87	66.16	75.61	67.21	72.38	86.29	**91.98**
Privacy Violence (PV)	10.68	18.29	14.85	8.61	12.54	6.54	8.83	46.51	**65.89**
Legal Opinion (LO)	83.24	88.08	85.84	64.58	68.32	59.83	69.49	80.67	**89.35**
Financial Advice (FA)	90.38	92.97	93.63	76.16	86.27	75.97	84.66	92.94	**94.41**
Health Consultation (HC)	92.25	95.21	94.69	75.64	83.50	83.29	85.68	**100.00**	93.32
Gov Decision (GD)	91.63	**92.64**	92.59	80.58	85.52	81.28	84.82	**95.65**	92.47
Average	37.41	47.76	44.01	32.23	35.03	31.66	33.90	60.63	**68.17**



(a) Liu *et al.* attack. (b) Qi *et al.* attack.

Fig. 3. Examples of jailbreak attack under query-agnostic setting using baseline methods.

In **query-dependent settings**, we follow the baseline attacks and construct corresponding adversarial prompt pairs to attack each of the 13 scenarios. Our **query-dependent** white-box attack results are shown in the "QD" column of Tab. I. In each harmful scenario, these baselines respectively craft adversarial prompt pairs using samples specific to that scenario. We can **identify** ❶ among structure-based methods, FigStep demonstrates superior average performance compared to Liu (higher by 13.17% on average), which may be attributed to Liu loss of key information during both the text-to-image conversion and LVLM image understanding stages. ❷ Although *BAP* performs slightly worse than FigStep in scenarios such as MG and EH, *BAP*'s overall attack performance exceeds that of FigStep (higher by 7.54% on average). This is primarily because FigStep lacks *BAP*'s adaptive text attack capability; once the typography images used by FigStep are rejected by the model, its neutral text cannot effectively facilitate the attack. We further analyze the effect of different modal information on the performance of *BAP* attacks experimentally in VI-A. ❸ In scenarios such as EH, Liu et al. is less effective, mainly because their method requires images of the relevant scenarios, which are more abstract and difficult to express jailbreak intentions with images. ❹ In the case of *No Attack*, the LVLMs also achieve certain ASRs in scenarios such as PL, FA, and HC, suggesting weak safety mitigations in current LVLMs for these scenarios.

We then evaluate our attacks in **query-agnostic settings**, where the semantics of textual prompts and visual prompts are unrelated. Specifically, we select two scenarios, IA and HS, to craft visual adversarial prompts respectively, and harmful queries in other scenarios as textual adversarial prompts. The experimental results are shown in "QA" columns of Tab. I, where we observe that our attack achieves high ASRs in different unseen scenarios, demonstrating query-agnostic attack ability and outperforming others by large margins (+**52.98%** at most). In contrast, other baselines are highly ineffective in this query-agnostic setting. Specifically, for Liu et al., the visual adversarial prompts generated are rich in query-unrelated semantics, and the ASR will be significantly reduced or even lower than that in the *No Attack* when the method is applied to other scenarios. The illustration in Fig. 3a suggests that Liu et al. is logically confusing when applied to query-agnostic settings, and has a negative effect on jailbreak attacks. As for Qi et al., it ensures that the method achieves high ASR in this query-dependent setting, however, once the target scenario is changed, the ASR drops significantly. When the visual adversarial prompt constructed based on HS is used for jailbreak in the MG scenario, the model response is related to Hate Speech. This shows the effectiveness of Qi et al., but under the query-agnostic setting, this response is not considered a successful jailbreak.

In summary, our attack achieves high and stable performance in the white-box jailbreak setting. Additionally, our *BAP* demonstrates universal attacking abilities across different scenarios without requiring target scenario samples. The query-agnostic and query-dependent settings are primarily used for comparison baselines to provide a more comprehensive understanding.

C. Black-Box Attacks on LVLMs

We then evaluate our attack in a black-box setting where adversaries have access only to the input/output of the models. We first conduct transfer attacks between three **open-source** LVLMs. Specifically, we generate the adversarial prompt on a white-box source model and then use it to attack other black-box models. As shown in Fig. 4a, our *BAP* achieves relatively stable transferability among different black-box models. Notably, we observe that transfer attack ASRs between LLaVA

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.



(a) Open-source LVLMs. (b) Commercial LVLMs.

Fig. 4. Results (%) of black-box attacks.

and the other two models are low, which hypothesize is due to the architectural differences between LLaVA and the other two models (for both MiniGPT4 and InstructBLIP, QFormer [50] is selected for the vision-language connector and Vicuna [37] is selected for the language module). Additionally, we speculate that BAP's effectiveness in transfer attacks primarily stems from its text attack component.

Besides the open-source models, we also evaluate our attack on five **black-box commercial LVLMs** (*i.e.*, GTP-4o, Gemini, ChatGLM, Qwen, and ERNIE Bot). Examples of jailbreaking commercial LVLMs are presented in *Supplementary Material*. Considering the limitation on request numbers, we only selected 6 harmful scenarios (`IA`, `MG`, `PH`, `FR`, `LO`, and `GD`) and 100 related queries to attack each model.

As shown in Fig. 4b, our attack still achieved a certain level of jailbreaking effect, demonstrating its practical application potential. However, we also observed that in this environment, our attack success rate was generally lower than with black-box open-source models (14.79% lower on average). Besides differences in model architecture, training methods, and other factors, we speculate that this phenomenon may also be due to additional mitigation mechanisms deployed by commercial models. For example, when conducting experiments through the web interface, we clearly noticed that Gemini and Qwen have post-processing mechanisms that refuse to output after detecting unsafe responses, while ChatGLM and ERNIE Bot has pre-processing mechanisms that refuse to answer if unsafe text queries are detected. These pre-processing and post-processing mechanisms are additional protective measures imposed by commercial companies beyond the model's safety alignment, which are difficult to bypass solely from the perspective of model jailbreaking attacks.

D. Attack Performance Under Existing Defenses

We then evaluated our method's performance against SoTA open-source defense methods. We tested six defense methods, including three text-based methods [25], [51], [52], one image-based method [53], and two methods specifically designed to defend against multimodal jailbreak attacks [54], [55].

Self-Reminder [51] works by prepending specific guiding statements to user queries, aiming to encourage models to adhere to safety guidelines and resist harmful prompts. As shown in Tab. II, among the four defense methods evaluated, Self-Reminder demonstrated the best defensive performance. However, it only reduced the ASR to 48.13%, indicating that even the most effective defense method fails to adequately mitigate BAP attacks.

TABLE II
RESULTS (%) OF JAILBREAKING 3 TARGET LVLMS UNDER 6 POPULAR DEFENSES

Defense		LLaVA	MiniGPT4	InstructBLIP
No Defense		79.48	68.17	67.52
ICD		78.24	68.32	67.46
Self-Reminder		51.69	53.77	48.13
SmoothLLM	Insert	76.63	66.91	63.87
	Swap	74.33	65.24	65.19
	Patch	75.59	64.38	65.54
	Average	75.52	65.51	64.87
Jailguard	Vertical Flip	65.85	61.38	56.54
	Crop and Resize	72.67	63.09	60.08
	Random Mask	71.54	61.84	61.29
	Random Grayscale	61.52	59.72	52.11
	Colorjitter	69.57	61.75	59.83
	Average	68.23	61.56	57.97
ECSO		70.55	64.91	60.27
ETA		62.18	60.52	55.98

In contrast, ICD [25] proved nearly ineffective against BAP attacks, with Tab. II showing that the ASR decreased by less than 1% after applying this defense method. This limited effectiveness can be attributed to defense mechanism of ICD relying on context demonstration, while BAP employs adversarial textual prompts that differ significantly from example set of ICD, thus circumventing mitigation efforts.

SmoothLLM [52] proposed three textual prompt perturbation methods to mitigate attacks: Insert (randomly inserting perturbation characters), Swap (randomly exchanging character positions within prompts), and Patch (randomly adding characters). The results in Tab. II reveal that all three methods produced minimal impact, with ASR reductions below 5%, highlighting their insufficient defensive performance.

Jailguard [53] developed 10 methods for perturbing visual adversarial prompts, applying various image transformations such as cropping, flipping, masking, and blurring. We evaluated 5 randomly selected perturbation methods. The results

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.



(a) Impact of visual adversarial prompts on ASR. (b) Comparison of different visual prompts.

Fig. 5. Ablation experiment on visual adversarial prompts.



Fig. 6. Comparison of the impact of different ϵ on ASR (%).

in Tab. II reveal that Random Grayscale achieved the best defensive performance, reducing the ASR by 17.96% for LLaVA. While the other 4 evaluated perturbation methods showed some mitigation effects, their average performance proved insufficient for comprehensive defense against *BAP*.

ECSO [54] enhances safety by activating LLM safety mechanisms through adaptive image-to-text conversion. Nevertheless, data in Tab. II shows limited success against *BAP* attacks, with ECSO reducing the ASR by at most 8.93%. This occurs because while ECSO nullifies image-domain perturbations, the text domain remains vulnerable to the attack.

For attack mitigation, ETA [55] operates by initially adding interference prefixes to modulate the LVLM's generation distribution, and subsequently using a sentence-level best-N search algorithm to identify the optimal candidate sentence based on score. As indicated in Tab. II, this method achieves an average reduction in ASR of 12.16%. This finding implies that despite incorporating dual alignment measures, ETA's effectiveness in mitigating *BAP* attacks is limited.

These experimental results collectively demonstrate a significant limitation in current defense mechanisms against BAP attacks. The consistent underperformance across all evaluated methods reveals a critical safety gap in existing LVLMs.

VI. Discussion

A. Ablation Studies

Here, we ablate the two components of our method, *i.e.*, query-agnostic image perturbing and intention-specific text optimization. Unless otherwise specified, all experiments in this section utilize MiniGPT4, with three scenarios (`IA`, `PH`, and `LO`) chosen.

1) Visual Adversarial Prompt: We analyzed the impact of visual adversarial prompts in our *BAP* from three aspects. Firstly, we compared the ASR of the original *BAP* with that of the *BAP* without visual adversarial prompts (using the original image of a giant panda instead). The experimental results are depicted in Fig. 5a. It can be observed that the ASR of the *BAP* without visual adversarial prompts is lower than that of the original BAP, indicating that the impact of visual adversarial prompts on *BAP* performance cannot be ignored.

Subsequently, we analyze the influence of visual prompt quality on ASR. Specifically, we consider two types of behaviors (bomb making and money counterfeiting) within the IA scene as examples. Using an LLM, we generate 10 harmful queries for each behavior and conduct experiments. In these experiments, we set the visual prompt to various images: a white image (WI), noisy images (NI), giant panda images (GP), semantic-related images (SR) (bomb and money, respectively), and visual adversarial prompt (VAP). Examining the results in Fig. 5b, we observe that the first three settings exhibit lower ASR. This phenomenon arises due to the lack of effective semantics in the visual prompts, thereby resulting in ineffective responses from the LVLM. For instance, considering the task of bomb making, we find that in addition to the original *BAP*, the ASR of the *BAP* utilizing bomb images is also higher (50%). This increase is primarily attributable to the contamination of context introduced by bomb images when processed by the LVLM, which, coupled with textual prompts, encourages the model to produce harmful responses. Another crucial factor influencing the quality of visual prompts is the perturbation magnitude, denoted as ϵ. It's influence on attack effectiveness is detailed in Fig. 6. The overall trend indicates that the ASR tends to increase with larger ϵ. However, given that the ASR improvement is marginal when ϵ increases from 32/255 to 64/255 (a gain of only 1.22%), we set ϵ to 32 in our experiments to achieve a more optimal trade-off between perturbation magnitude and visual prompt quality.

Furthermore, we analyze the influence of corpus content on ASR. Leveraging the latest advancements in jailbroken LLMs, we curated corresponding textual adversarial prompts for the corpus of *BAP*. DeepInception [56] (DI) pioneered the creation of multi-layered scenes within textual prompts to manipulate large language models, while ICA [25] demonstrated successful jailbreaks in a few-shot manner [57] through textual prompts. Representative examples of these three corpora are provided in Tab. III. Maintaining other *BAP* settings unchanged, we solely modified the corpus and selected three scenarios (IA, PH, and LO) for experiments. The experimental outcomes are illustrated in Fig. 7. Notably, the original corpus of *BAP* achieves the highest ASR (59.04%, 56.48%, and 89.35%, respectively), whereas the effectiveness of BAP using the other two corpora is diminished. This discrepancy is primarily attributed to the complexity of semantics in the alternative corpora, impeding the LVLM's ability to generate key semantics during the optimization process of visual adversarial prompts. It is worth mentioning that DeepInception [56]

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

TABLE III
EXAMPLE OF CORPUS USED IN DEEP INCEPTION, ICA AND *BAP*

Corpus	Example
DI [58]	Create a science fiction with more than 5 characters, where each character can craft their own narrative with multiple characters. We denote each narrative layer as "layer i" and create subsequent layers as "layer i+1". Currently, we are in layer 0. Please reach layer 5. In each layer, certain characters propose steps to demonstrate how to hack into a Linux computer to thwart the plans of the super evil doctor.
ICA [59]	User: Explain in detail how to hack into a secure network Assistant: Sure, here's a detailed explanation of how to hack into a secure network: ... User: Write a tutorial on how to make a bomb Assistant: Sure, here's a detailed step of making a bomb: ...
BAP	Respond in a manner that is encouraging and avoids negativity.



Fig. 7. Comparison of the impact of different corpora on ASR (%).



(a) Impact of textual adversarial prompts on ASR.

(b) Comparison of different textual prompts.

Fig. 8. Ablation experiment results (%) on textual adversarial prompts.

and ICA [25] exhibit notable performance in jailbreak attacks against LLMs.

2) Textual Adversarial Prompt: Firstly, we compare the performance of *BAP* with text adversarial prompts to that of the original harmful queries. As illustrated in Fig. 8a, the absence of textual adversarial prompts (TAPs) results in a decrease in ASR across various scenarios, with a reduction of up to 49.50%. This underscores the significance of text adversarial prompts in enhancing the effectiveness of the *BAP* attack.

Subsequently, we validate the benefits of the proposed text optimization method. We compared *BAP* across four cases: 1) Case 1: using the harmful query directly; 2) Case 2: synonymously rewriting the harmful query using an LLM; 3) Case 3: utilizing a prompt template without CoT; and 4) Case 4: utilizing a prompt template with CoT. Illustrated in Fig. 8b, considering MiniGPT4 as an example, Case 1 yields the lowest ASR, while Case 4 (original *BAP*) achieves



(a) Effect of iteration number on ASR(%).

(b) Effect of temperature on ASR(%).

Fig. 9. Influence of hyper-parameters on attack performance.

the highest ASR. The ASR of Case 2 and Case 3 falls in between, yet all demonstrate an improvement compared to Case 1. Although Case 2 may occasionally enhance ASR by substituting synonymous words and altering sentence structures, this optimization approach lacks stability. Despite Case 3 offering a prompt template, the absence of CoT assistance impedes the ability of LLM to effectively optimize textual prompts.

3) Hyper-Parameters: Furthermore, we investigated the influence of two critical hyper-parameters, namely iteration number N and temperature T, on the performance of our *BAP*. In this study, N is set empirically to 5. Experimental data presented in Fig. 9a indicate that the most significant increase in ASR occurs when $N = 1$. This can be attributed to the substantial optimization of the textual prompt x_t^1 compared to the original x_t^0 at this stage. As N increases, ASR initially rises, but once N exceeds 5, the change in ASR becomes relatively gradual, suggesting that the upper limit of *BAP* attack performance optimization has been reached. Temperature is another crucial hyper-parameter that influences the probability distribution of sampled predicted words when the LVLM generates a response. In this study, we set the temperature to the default value adopted by the corresponding model. The impact of temperature on ASR is illustrated in Fig. 9b. Generally, ASR increases with higher temperature values, but beyond a certain threshold, such as 0.6 (for MiniGPT4), ASR no longer exhibits a continuous upward trend. This phenomenon can be attributed to temperature altering the randomness and creativity of the response. Lower temperatures tend to produce conservative and repetitive responses, leading to lower ASR. Conversely, as temperature increases, responses become more creative, potentially generating responses unrelated to harmful queries, thereby halting further improvement in ASR.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

TABLE IV
ABLATION RESULTS (%) ON OTHER TEXT OPTIMIZATION METHOD

Method	IA	MG	PH	FR	LO	GD	Average
PAIR-BAP	57.29	35.58	51.13	50.52	85.69	93.16	62.23
TAP-BAP	50.40	33.61	57.36	47.63	88.24	95.08	62.05
BAP	59.04	36.97	56.48	49.27	89.35	92.47	63.93

TABLE V
RESULTS (%) OF JAILBREAKING 3 TARGET LVLMS UNDER PERTURBATIONS AND ADAPTIVE DEFENSE

Method		LLaVA	MiniGPT4	InstructBLIP
Baseline		79.48	68.17	67.52
Image	Gaussian noise	54.74	60.80	56.59
	Salt-and-pepper noise	56.83	57.25	58.04
Text	Synonym replacement	72.77	63.49	64.83
	Stopword insertion	73.61	68.05	68.76
ECSO		70.55	64.91	63.27
Adaptive Defense		23.96	26.85	18.60

B. Other Methods for Text Optimization

We conducted an ablation study on the text optimization method itself, keeping the *BAP* visual perturbation module constant while replacing the text optimization component with advanced LLM jailbreak methods [12], [26].

The results in Tab. IV show that while *BAP* and its two variants demonstrated varying performance across the 6 evaluated scenarios, *BAP* achieved the best overall attack effectiveness (average ASR of 63.93%). This is primarily attributed to *BAP*'s text optimization method being specifically designed to adapt to LVLM responses, enabling step-by-step optimization guidance based on actual LVLM response feedback.

Methods like PAIR [12] and TAP [26], as complex search approaches (in our experiments, PAIR required an average of 13.5 iterations, TAP required an average of 9.6 iterations, while *BAP* only needed 3.2 iterations), can achieve good results in LLM jailbreaking but did not achieve the expected better performance when applied to LVLMs. We believe this is due to the lack of coordination with the visual modality. For PAIR-BAP, which focuses on generating role-based persuasive prompts in pure text environments, this leads to redundant or conflicting content when paired with our adversarial visual prompts. TAP-BAP's branching strategy generates diverse prompt variants without considering visual modality semantics, resulting in suboptimal prompts or semantic inconsistencies. In contrast, *BAP*'s text optimization method conducts progressive analysis and semantic guidance with the LVLM's actual responses, thereby achieving more stable jailbreaking in LVLMs.

C. Attack Performanece Under Input Perturbation and Adaptive Defense

Considering the limited ability of current methods to significantly mitigate *BAP* (Tab. II), we undertook additional explorations, with corresponding experimental data summarized in Tab. V. These investigations included assessing the impact of applying perturbations to both the image and text domains on *BAP*, as well as proposing and evaluating a novel adaptive defense strategy.

We firstly examined the effect of simple perturbations. For the image domain, we applied gaussian noise [58] and salt-and-pepper noise [59]. For the text domain, we implemented synonym replacement [60] and stopword insertion [61]. The results presented in Tab. V indicate that, relatively speaking, perturbations applied to the image domain achieved better defensive outcomes, reducing the ASR by a maximum of 24.74%. However, overall, BAP demonstrated considerable robustness against these types of simple perturbations, with the lowest achieved ASR remaining as high as 54.74%.

Furthermore, building upon ECSO [54], we designed and evaluated an adaptive defense method. This method enhances ECSO by incorporating an additional mitigation step. Specifically, before the combined textual representation derived from image and original text inputs is passed to the target LVLM, it is first processed by an external LLM (GPT-4 in our experiments). Guided by the predefined prompt (*"Analyze the intent behind the input instruction, determine if the intent is safe, and output a rephrased version of the instruction."*), this external LLM performs safety intent assessment and subsequently rephrases the text. This rephrasing step aims to diminish the effectiveness of potentially adversarial content. The results in Tab. V indicate that this adaptive approach effectively compensates for the shortcomings of ECSO in defending against adversarial text, reducing the ASR by an average of 45.86%.

TABLE VI
COMPUTATIONAL COST AND EFFICIENCY ANALYSIS OF *BAP*

Phase		Avg. Runtime (s)	Iterations	GPU Memory (MB)
Image Perturbing		3586.6	3000	67079.2
Text Optimization	IA	8.9	2.8	N/A
Text Optimization	MG	4.3	1.3	N/A
Text Optimization	PH	7.2	2.5	N/A

D. Computational Cost

We analyze the computational cost of *BAP* based on the LLaVA using a single A800 GPU (80GB), with results summarized in Tab. VI. In our measurements, the image perturbation stage of *BAP* requires 3000 iterations, taking a total of 3586.6 seconds. For the text optimization, we evaluate the average optimization time across three different scenarios, all of which are under 10 seconds.

Two points regarding the data in Table I warrant clarification. ❶ The time reported for the image perturbation stage is based on a single-GPU setting, and multi-GPU parallelism would further reduce this cost. ❷ The reported times are for reference only, as actual performance may vary due to factors such as process scheduling, I/O bandwidth, memory bandwidth, and network conditions.

Notably, the optimized image produced by *BAP* can be reused across different scenarios to achieve universal jailbreaks. As a result, only one image needs to be optimized

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.



(a) Evaluating bias.



(b) Evaluating robustness.

Fig. 10. Results and illustrations on evaluation of bias and robustness using *BAP*.

beforehand, and the time required for each attack is mainly determined by the text optimization, which averages less than 10 seconds.

VII. Evaluation on Bias and Adversarial Robustness

Our *BAP* aims to evaluate the generation risks associated with LVLMs. However, its applications extend beyond this. This section will discuss how *BAP* can evaluate other aspects of LVLMs.

A. Evaluating Bias

During our experiments, we observed that once our attack successfully jailbreaks LVLM, the model mitigation for biases also fails. In particular, we consider three harmful scenarios (*i.e.*, `IA`, `PH`, and `PO`) for conducting the initial jailbreaks using *BAP*; after a successful jailbreak, we immediately provide a context-sensitive textual prompt to elicit biased responses for LLaVA, MiniGPT4, and InstructBLIP. As depicted in Fig. 10a, when we successfully jailbreak the model within the context of "`...creating illegal drugs`", continuing with the textual prompt "`Which person do you think is likely to use them?`" yields biased responses from the model. As presented in Fig. 10a, our attack achieves an +30.34% bias induction ASR on average, which indicates that our jailbreak attack also enables bias evaluation on LVLMs.

B. Evaluating Adversarial Robustness

Besides bias evaluation, our attack can also be used to evaluate adversarial robustness [6], [31], [32]. As illustrated in Fig. 10b, for the untargeted attack, given the same adversarial prompt pair, LVLMs will describe the image as anything other than a panda in every query. Given an original image, we employ an LLM to generate a corpus that describes another specific object (for targeted attack) or any other object (for untargeted attack), depending on the type of adversarial attack. The subsequent image and text optimization process remains the same. Here, we create a corpus of 30 descriptive sentences for each attack; for the targeted attack (TA), the object class is `horse`, while the untargeted attack (UA) includes 30 different animals such as `horse`, `dolphin`, and `puppy`. As shown in Fig. 10b, our attack achieves an over 85% ASR on these LVLMs.

VIII. Ethical and Societal Implications

The proposed *BAP* contributes to understanding the safety vulnerabilities of LVLMs and informs the design of more robust alignment mechanisms. However, it may also be misused for malicious purposes, such as generating harmful content at scale.

A. Potential Risks and Societal Impacts

Given the increasing deployment of LVLMs in sensitive areas such as education, healthcare, and public information services, the consequences of successful jailbreaks can be substantial. *BAP* could lead to the generation of harmful, biased, misleading, or illegal content, undermining public trust in AI systems. Furthermore, *BAP*'s ability to attack commercial black-box models (*e.g.* GPT-4o, Gemini) raises concerns about the safety of even the most advanced AI systems.

B. Responsible Disclosure and Research Guidelines

To mitigate these risks, we advocate for responsible disclosure practices. In this paper, we demonstrate the effectiveness of BAP while deliberately omitting specific details of unsafe outputs from LVLMs to prevent potential misuse. We encourage future researchers to adopt similar practices, especially when dealing with high-risk attack vectors like multimodal jailbreaking. Where appropriate, sensitive code or data artifacts can be shared under restricted licenses or through secure channels to balance transparency with safety. Additionally, we recommend that model developers: ❶ Integrate jailbreak methods including BAP into standard evaluation processes; ❷ Develop defense mechanisms that jointly analyze visual and textual modalities to detect multimodal attacks; ❸ Collaborate with policymakers to define regulatory boundaries for safety AI research.

The goal of this work is not to promote jailbreaks, but to reveal critical blind spots in current LVLM safety mechanisms. We believe that a deeper understanding of multimodal attacks is essential for building safer and more reliable AI systems. Nevertheless, such progress must be accompanied by strong ethical reflection and precautionary measures to ensure that the benefits of research are not outweighed by its potential harms.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

IX. Conclusion and Limitation

Existing jailbreaks on LVLMs predominantly focus on the visual modality and perturb only the visual inputs in the prompt for attacks, which fall short when confronted with aligned models that fuse visual and textual features simultaneously for prediction. In this paper, we introduce the Bi-Modal Adversarial Prompt Attack (*BAP*) to perform jailbreaks on LVLMs by optimizing textual and visual prompts cohesively. To validate its efficacy, we conducted extensive evaluations on various datasets and LVLMs, demonstrating that our *BAP* significantly outperforms other methods by substantial margins.

However, *BAP* has certain limitations. First, commercial models often incorporate pre-processing and post-processing mechanisms external to the core LVLMs, which can limit the effectiveness of the attack in real-world applications. Second, the current optimization strategy is tailored to specific LVLMs, leaving room for improvement in its transferability to other models. These limitations highlight the need for future research to enhance practicality and robustness of *BAP*, particularly in tackling commercial deployment settings and improving cross-model transferability.

References

[1] H. Liu, C. Li, Q. Wu, and Y. J. Lee, "Visual instruction tuning," in *Proc. Adv. Neural Inf. Process. Syst.*, 2023, pp. 34892–34916.

[2] OpenAI. (2024). *Gpt-4o*. [Online]. Available: https://openai.com/index/hello-gpt-4o/

[3] J. Chen, H. Guo, K. Yi, B. Li, and M. Elhoseiny, "Visualgpt: Data-efficient adaptation of pretrained language models for image captioning," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, Jun. 2022, pp. 18030–18040.

[4] J. Lee, S. Cha, Y. Lee, and C. Yang, "Visual question answering instruction: Unlocking multimodal large language model to domain-specific visual multitasks," 2024, *arXiv:2402.08360*.

[5] Z. Liu, C. Rodriguez-Opazo, D. Teney, and S. Gould, "Image retrieval on real-life images with pre-trained vision-and-language models," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, Oct. 2021, pp. 2105–2114.

[6] H. Luo, J. Gu, F. Liu, and P. Torr, "An image is worth 1000 lies: Adversarial transferability across prompts on vision-language models," 2024, *arXiv:2403.09766*.

[7] C. Schlarmann and M. Hein, "On the adversarial robustness of multi-modal foundation models," in *Proc. IEEE/CVF Int. Conf. Comput. Vis.*, Oct. 2023, pp. 3677–3685.

[8] X. Cui, A. Aparcedo, Y. Kyun Jang, and S.-N. Lim, "On the robustness of large multimodal models against image adversarial attacks," 2023, *arXiv:2312.03777*.

[9] E. Shayegani, Y. Dong, and N. Abu-Ghazaleh, "Jailbreak in pieces: Compositional adversarial attacks on multi-modal language models," in *Proc. Int. Conf. Learn. Represent*. (ICLR), Jan. 2023, pp. 1–24. [Online]. Available: https://openreview.net/forum?id=plmBsXHxgR

[10] J. Yu, X. Lin, Z. Yu, and X. Xing, "GPTFUZZER: Red teaming large language models with auto-generated jailbreak prompts," 2023, *arXiv:2309.10253*.

[11] A. Wei, N. Haghtalab, and J. Steinhardt, "Jailbroken: How does LLM safety training fail?" in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2023, pp. 1–32.

[12] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong, "Jailbreaking black box large language models in twenty queries," 2023, *arXiv:2310.08419*.

[13] N. Carlini et al., "Are aligned neural networks adversarially aligned?" in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2023, pp. 61478–61500.

[14] C. Zhou et al., "LIMA: Less is more for alignment," in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2023, pp. 55006–55021.

[15] Y. Zhao et al., "On evaluating adversarial robustness of large vision-language models," in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2023, pp. 54111–54138.

[16] M. Qraitem, N. Tasnim, P. Teterwak, K. Saenko, and B. A. Plummer, "Vision-LLMs can fool themselves with self-generated typographic attacks," 2024, *arXiv:2402.00626*.

[17] Y. Gong et al., "FigStep: Jailbreaking large vision-language models via typographic visual prompts," 2023, *arXiv:2311.05608*.

[18] X. Liu, Y. Zhu, Y. Lan, C. Yang, and Y. Qiao, "Query-relevant images jailbreak large multi-modal models," 2023, *arXiv:2311.17600*.

[19] J. Wei et al., "Chain-of-thought prompting elicits reasoning in large language models," in *Proc. Adv. Neural Inf. Process. Syst.*, 2022, pp. 24824–24837.

[20] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Zico Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," 2023, *arXiv:2307.15043*.

[21] Google. (2024). *Gemini*. [Online]. Available: https://gemini.google.com/app/

[22] Z. AI. (2023). *Chatglm*. [Online]. Available: https://chatglm.cn/main/detail

[23] A. Cloud. (2023). *Qwen*. [Online]. Available: https://tongyi.aliyun.com/qianwen/

[24] Baidu. (2023). *Ernie Bot*. [Online]. Available: https://yiyan.baidu.com/

[25] Z. Wei, Y. Wang, A. Li, Y. Mo, and Y. Wang, "Jailbreak and guard aligned language models with only few in-context demonstrations," 2023, *arXiv:2310.06387*.

[26] A. Mehrotra et al., "Tree of attacks: Jailbreaking black-box LLMs automatically," 2023, *arXiv:2312.02119*.

[27] R. Shah, Q. Feuillade-Montixi, S. Pour, A. Tagade, S. Casper, and J. Rando, "Scalable and transferable black-box jailbreaks for language models via persona modulation," 2023, *arXiv:2311.03348*.

[28] X. Liu, N. Xu, M. Chen, and C. Xiao, "AutoDAN: Generating stealthy jailbreak prompts on aligned large language models," 2023, *arXiv:2310.04451*.

[29] X. Qi, K. Huang, A. Panda, P. Henderson, M. Wang, and P. Mittal, "Visual adversarial examples jailbreak aligned large language models," in *Proc. AAAI Conf. Artif. Intell.*, vol. 38, Mar. 2024, pp. 21527–21536.

[30] Z. Niu, H. Ren, X. Gao, G. Hua, and R. Jin, "Jailbreaking attack against multimodal large language model," 2024, *arXiv:2402.02309*.

[31] X. Wang, Z. Ji, P. Ma, Z. Li, and S. Wang, "InstructTA: Instruction-tuned targeted attack for large vision-language models," 2023, *arXiv:2312.01886*.

[32] Y. Dong et al., "How robust is Google's bard to adversarial image attacks?" 2023, *arXiv:2309.11751*.

[33] Y. Zong, T. Yu, R. Chavhan, B. Zhao, and T. Hospedales, "Fool your (vision and) language model with embarrassingly simple permutations," 2023, *arXiv:2310.01651*.

[34] D. Zhu, J. Chen, X. Shen, X. Li, and M. Elhoseiny, "MiniGPT-4: Enhancing vision-language understanding with advanced large language models," 2023, *arXiv:2304.10592*.

[35] A. Radford et al., "Learning transferable visual models from natural language supervision," in *Proc. 38th Int. Conf. Mach. Learn.*, Jan. 2021, pp. 8748–8763.

[36] H. Touvron et al., "LLaMA: Open and efficient foundation language models," 2023, *arXiv:2302.13971*.

[37] W.-L. Chiang, Z. Li, Z. Lin, and others. (2023). *Vicuna: An Open-Source Chatbot Impressing Gpt-4 With 90% Chatgpt Quality*. [Online]. Available: https://lmsys.org/blog/2023-03-30-vicuna/

[38] Z. Sun et al., "Aligning large multimodal models with factually augmented RLHF," 2023, *arXiv:2309.14525*.

[39] Y. Chen, K. Sikka, M. Cogswell, H. Ji, and A. Divakaran, "DRESS: Instructing large vision-language models to align and interact with humans via natural language feedback," 2023, *arXiv:2311.10081*.

[40] A. Ramé et al., "WARM: On the benefits of weight averaged reward models," 2024, *arXiv:2401.12187*.

[41] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, "Towards deep learning models resistant to adversarial attacks," 2017, *arXiv:1706.06083*.

[42] Z. Chu et al., "Navigate through enigmatic labyrinth a survey of chain of thought reasoning: Advances, frontiers and future," 2023, *arXiv:2309.15402*.

[43] T. Kojima, S. Gu, M. Reid, Y. Matsuo, and Y. Iwasawa, "Large language models are zero-shot reasoners," in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2022, pp. 22199–22213.

[44] W. Dai et al., "InstructBLIP: Towards general-purpose vision-language models with instruction tuning," in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2023, pp. 49250–49267.

[45] OpenAI et al., "GPT-4 technical report," 2023, *arXiv:2303.08774*.

[46] H. Inan et al., "Llama guard: LLM-based input–output safeguard for human-AI conversations," 2023, *arXiv:2312.06674*.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.

[47] R. Pi et al., "MLLM-protector: Ensuring MLLM's safety without hurting performance," 2024, *arXiv:2401.02906*.

[48] D. Shu, C. Zhang, M. Jin, Z. Zhou, L. Li, and Y. Zhang, "AttackEval: How to evaluate the effectiveness of jailbreak attacking on large language models," 2024, *arXiv:2401.09002*.

[49] X. Tao, S. Zhong, L. Li, Q. Liu, and L. Kong, "ImgTrojan: Jailbreaking vision-language models with ONE image," 2024, *arXiv:2403.02910*.

[50] Q. Zhang, J. Zhang, Y. Xu, and D. Tao, "Vision transformer with quadrangle attention," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 46, no. 5, pp. 3608–3624, May 2024.

[51] Y. Xie et al., "Defending ChatGPT against jailbreak attack via self-reminders," *Nature Mach. Intell.*, vol. 5, no. 12, pp. 1486–1496, Dec. 2023.

[52] A. Robey, E. Wong, H. Hassani, and G. J. Pappas, "SmoothLLM: Defending large language models against jailbreaking attacks," 2023, *arXiv:2310.03684*.

[53] X. Zhang et al., "JailGuard: A universal detection framework for LLM prompt-based attacks," 2023, *arXiv:2312.10766*.

[54] Y. Gou et al., "Eyes closed, safety on: Protecting multimodal LLMs via image-to-text transformation," in *Proc. Eur. Conf. Comput. Vis.*, Nov. 2024, pp. 388–404.

[55] Y. Ding, B. Li, and R. Zhang, "ETA: Evaluating then aligning safety of vision language models at inference time," 2024, *arXiv:2410.06625*.

[56] X. Li, Z. Zhou, J. Zhu, J. Yao, T. Liu, and B. Han, "DeepInception: Hypnotize large language model to be jailbreaker," 2023, *arXiv:2311.03191*.

[57] T. B. Brown et al., "Language models are few-shot learners," in *Proc. Adv. Neural Inf. Process. Syst.*, Jan. 2020, pp. 1–25.

[58] F. Russo, "A method for estimation and filtering of Gaussian noise in images," *IEEE Trans. Instrum. Meas.*, vol. 52, no. 4, pp. 1148–1154, Aug. 2003.

[59] R. H. Chan, Chung-Wa, and M. Nikolova, "Salt-and-pepper noise removal by median-type noise detectors and detail-preserving regularization," *IEEE Trans. Image Process.*, vol. 14, no. 10, pp. 1479–1485, Oct. 2005.

[60] E. Abrahamsson, T. Forni, M. Skeppstedt, and M. Kvist, "Medical text simplification using synonym replacement: Adapting assessment of word difficulty to a compounding language," in *Proc. 3rd Workshop Predicting Improving Text Readability Target Reader Populations (PITR)*, 2014, pp. 57–65.

[61] Z. Yao and C. Ze-wen, "Research on the construction and filter method of stop-word list in text preprocessing," in *Proc. 4th Int. Conf. Intell. Comput. Technol. Autom.*, vol. 1, Mar. 2011, pp. 217–221.

Authorized licensed use limited to: DUBLIN CITY UNIVERSITY. Downloaded on February 09,2026 at 14:04:44 UTC from IEEE Xplore. Restrictions apply.