The Mammoth Python Workbook: 600 Practice MCQs

Fixed HTML Encoding Edition

1. What is the output?

```
x = [1, 2, 3]
y = x
y.append(8)
print(x)
```

A. [1, 2, 3, 8]
B. Error
C. [8]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 8]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

2. What is the output of print(3 ** 2 ** 2)?

A. 81
B. Error
C. 78
D. 12

Correct Answer: 81
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

3. What will bool('') evaluate to?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

4. How do you start a 'for' loop that iterates from 0 to 5?

A. loop(6):
B. for i in range(0, 5):
C. for i in range(6):
D. for i in range(5):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

5. What is the result of 'moon' + 'shine'?

A. 'moonshine'
B. ['moon', 'shine']
C. Error
D. 'moon shine'

Correct Answer: 'moonshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

6. Which keyword is used to create a function in Python?

A. def
B. define
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

7. What is the output of type(4.4)?

A. Error
B. <class 'double'>
C. <class 'int'>
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

8. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

9. Which of the following creates a dictionary?

A. {'a': 1}
B. ['a': 1]
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

10. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. 6
C. 3
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

11. What will bool(()) evaluate to?

A. None
B. True
C. False
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

12. What is the output of type(5.3)?

A. Error
B. <class 'int'>
C. <class 'float'>
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

13. If lst = [1, 5, 3, 1, 7], what is lst[-4]?

A. 1
B. Error
C. 5
D. 7

Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

14. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 6
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

15. Which keyword is used to create a function in Python?

A. def
B. function
C. func
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

16. Which keyword is used to create a function in Python?

A. function
B. func
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

17. What is the output of print(3 ** 3 ** 2)?

A. 729
B. 19683
C. 18
D. Error

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

18. Which keyword is used to create a function in Python?

A. def
B. define
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

19. What is the result of 'apple' + 'script'?

A. 'applescript'
B. Error
C. 'apple script'
D. ['apple', 'script']

Correct Answer: 'applescript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

20. What will bool([]) evaluate to?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

21. What is the output of type(3.2)?

A. Error
B. <class 'int'>
C. <class 'float'>
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

22. What is the result of 'sun' + 'light'?

A. ['sun', 'light']
B. 'sunlight'
C. Error
D. 'sun light'

Correct Answer: 'sunlight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

23. What is the output of 18 % 2?

A. 9
B. 0
C. Error
D. 18

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

24. What is the output?

```
x = [1, 2, 3]
y = x
y.append(4)
print(x)
```

A. [1, 2, 3, 4]
B. [1, 2, 3]
C. [4]
D. Error

Correct Answer: [1, 2, 3, 4]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

25. What is the output of print(3 ** 2 ** 3)?

A. 729
B. 6561
C. 18
D. Error

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

26. What is the output of 20 % 2?

A. 0
B. 20
C. Error
D. 10

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

27. If lst = [7, 7, 1, 4, 9], what is lst[-5]?

A. 28
B. 7
C. Error
D. 9

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

28. What is the result of 'sun' + 'pie'?

A. Error
B. 'sun pie'
C. 'sunpie'
D. ['sun', 'pie']

Correct Answer: 'sunpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

29. What is the output of type(6.4)?

A. <class 'int'>
B. <class 'float'>
C. Error
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

30. What is the result of 'moon' + 'shine'?

A. 'moonshine'
B. 'moon shine'
C. Error
D. ['moon', 'shine']

Correct Answer: 'moonshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

31. Which of the following creates a dictionary?

A. ('a', 1)
B. {'a': 1}
C. <'a': 1>
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

32. What is 'Coding'.upper()?

A. Error
B. None
C. 'CODING'
D. 'Coding'

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

33. What is 'Coding'.upper()?

A. 'Coding'
B. 'CODING'
C. None
D. Error

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

34. What is the output of print(3 ** 2 ** 2)?

A. 81
B. 12
C. Error
D. 53

Correct Answer: 81
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

35. What is the result of 'moon' + 'pie'?

A. Error
B. 'moon pie'
C. ['moon', 'pie']
D. 'moonpie'

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

36. How do you start a 'for' loop that iterates from 0 to 8?

A. loop(9):
B. for i in range(8):
C. for i in range(0, 8):
D. for i in range(9):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

37. What is the output of 23 % 2?

A. 1
B. 23
C. Error
D. 11

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

38. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(0, 5):
B. for i in range(5):
C. loop(6):
D. for i in range(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

39. What is the output of type(6.2)?

A. <class 'int'>
B. <class 'double'>
C. Error
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

40. Which keyword is used to create a function in Python?

A. define
B. def
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

41. What is 'Python'.upper()?

A. None
B. 'PYTHON'
C. Error
D. 'Python'

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

42. How do you start a 'for' loop that iterates from 0 to 7?

A. for i in range(0, 7):
B. loop(8):
C. for i in range(7):
D. for i in range(8):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

43. What is 2 > 1?

A. None
B. Error
C. False
D. True

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

44. Which of the following creates a dictionary?

A. ['a': 1]
B. ('a', 1)
C. {'a': 1}
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

45. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(0, 5):
B. for i in range(5):
C. loop(6):
D. for i in range(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

46. What is the output of 18 // 3?

A. 6
B. 6.0
C. 7
D. Error

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

47. What is the result of 'sun' + 'pie'?

A. 'sunpie'
B. ['sun', 'pie']
C. Error
D. 'sun pie'

Correct Answer: 'sunpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

48. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

49. What is the output of: True or True?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

50. Which of the following creates a dictionary?

A. ('a', 1)
B. ['a': 1]
C. <'a': 1>
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

51. What is the output of print(2 ** 3 ** 3)?

A. 18
B. Error
C. 512
D. 134217728

Correct Answer: 134217728
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

52. Which of the following creates a dictionary?

A. {'a': 1}
B. <'a': 1>
C. ['a': 1]
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

53. What is the output of print(3 ** 3 ** 2)?

A. Error
B. 19683
C. 18
D. 729

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

54. If lst = [8, 1, 7, 1, 6], what is lst[-5]?

A. Error
B. 30
C. 6
D. 8

Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

55. What is 4 < 1?

A. False
B. True
C. None
D. Error

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

56. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

57. What is the output of 21 // 3?

A. 7
B. Error
C. 8
D. 7.0

Correct Answer: 7
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

58. What is the output of 18 // 5?

A. 3.6
B. 4
C. Error
D. 3

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

59. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. [1, 2, 3, 9]
B. [9]
C. [1, 2, 3]
D. Error

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

60. If lst = [5, 3, 6, 8, 4], what is lst[-4]?

A. 5
B. 3
C. 4
D. Error

Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

61. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 6
C. 1
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

62. How do you start a 'for' loop that iterates from 0 to 7?

A. loop(8):
B. for i in range(7):
C. for i in range(0, 7):
D. for i in range(8):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

63. Which of the following creates a dictionary?

A. <'a': 1>
B. {'a': 1}
C. ['a': 1]
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

64. What will bool('') evaluate to?

A. False
B. True
C. None
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

65. Which keyword is used to create a function in Python?

A. func
B. define
C. function
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

66. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [1, 2, 3]
B. [1, 2, 3, 5]
C. Error
D. [5]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

67. What is the result of 'sun' + 'script'?

A. 'sun script'
B. ['sun', 'script']
C. Error
D. 'sunscript'

Correct Answer: 'sunscript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

68. What is the output of print(2 ** 3 ** 2)?

A. 512
B. 12
C. Error
D. 64

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

69. What is the output of 17 // 3?

A. 6
B. Error
C. 5
D. 5.666666666666667

Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

70. What is the output of: False and True?

A. Error
B. True
C. False
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

71. Which keyword is used to create a function in Python?

A. func
B. function
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

72. What is the output of print(2 ** 3 ** 2)?

A. 512
B. Error
C. 12
D. 64

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

73. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Exits the loop entirely
C. Restarts the loop
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

74. What is the output of 20 % 5?

A. Error
B. 4
C. 0
D. 20

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

75. What is the output of 19 // 6?

A. 3.1666666666666665
B. 4
C. 3
D. Error

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

76. What is the output?

```
x = [1, 2, 3]
y = x
y.append(7)
print(x)
```

A. Error
B. [1, 2, 3]
C. [7]
D. [1, 2, 3, 7]

Correct Answer: [1, 2, 3, 7]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

77. Which keyword is used to create a function in Python?

A. define
B. function
C. def
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

78. What is 5 < 2?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

79. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. Error
C. 6
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

80. What is the result of 'moon' + 'pie'?

A. 'moon pie'
B. 'moonpie'
C. Error
D. ['moon', 'pie']

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

81. Which keyword is used to create a function in Python?

A. def
B. define
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

82. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. Error
B. [5]
C. [1, 2, 3]
D. [1, 2, 3, 5]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

83. What is the output of type(7.4)?

A. <class 'int'>
B. <class 'float'>
C. <class 'double'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

84. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

85. What is 4 == 2?

A. None
B. False
C. True
D. Error

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

86. What is the output of: False and False?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

87. What will bool({}) evaluate to?

A. False
B. True
C. Error
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

88. What will bool([]) evaluate to?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

89. What is the output of 18 // 4?

A. Error
B. 5
C. 4
D. 4.5

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

90. What is the result of 'sun' + 'shine'?

A. 'sun shine'
B. Error
C. ['sun', 'shine']
D. 'sunshine'

Correct Answer: 'sunshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

91. If lst = [1, 3, 7, 6, 5], what is lst[-3]?

A. 1
B. 7
C. Error
D. 5

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

92. What is the output of: True and False?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

93. What is the output of type(2.9)?

A. <class 'int'>
B. Error
C. <class 'float'>
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

94. What is the output of 16 // 4?

A. Error
B. 4.0
C. 4
D. 5

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

95. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. Error
B. [9]
C. [1, 2, 3, 9]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

96. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [6]
B. [1, 2, 3]
C. [1, 2, 3, 6]
D. Error

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

97. What is the output of 16 % 5?

A. 1
B. 16
C. 3
D. Error

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

98. What is the output of: True or True?

A. True
B. False
C. Error
D. None

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

99. What will bool(()) evaluate to?

A. Error
B. None
C. False
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

100. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

101. What will bool('') evaluate to?

A. Error
B. True
C. False
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

102. What is 'Python'.upper()?

A. None
B. 'PYTHON'
C. 'Python'
D. Error

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

103. What will bool('') evaluate to?

A. True
B. Error
C. False
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

104. If lst = [1, 7, 1, 3, 7], what is lst[-1]?

A. 1
B. 93
C. Error
D. 7

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

105. What is the result of 'java' + 'light'?

A. Error
B. 'java light'
C. ['java', 'light']
D. 'javalight'

Correct Answer: 'javalight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

106. What is the result of 'moon' + 'script'?

A. 'moonscript'
B. 'moon script'
C. ['moon', 'script']
D. Error

Correct Answer: 'moonscript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

107. What will bool([]) evaluate to?

A. None
B. Error
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

108. What is 'Data'.upper()?

A. 'DATA'
B. 'Data'
C. None
D. Error

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

---

109. How do you start a 'for' loop that iterates from 0 to 4?

A. loop(5):
B. for i in range(4):
C. for i in range(0, 4):
D. for i in range(5):

Correct Answer: for i in range(5):
Reasoning: range(5) generates numbers from 0 up to, but not including, 5.

---

110. Which keyword is used to create a function in Python?

A. define
B. def
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

111. What is the output of print(2 ** 2 ** 3)?

A. 12
B. 256
C. Error
D. 64

Correct Answer: 256
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

112. What is 1 > 1?

A. Error
B. False
C. None
D. True

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

113. What is 5 > 4?

A. False
B. Error
C. True
D. None

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

114. What is the output of 19 % 3?

A. Error
B. 6
C. 19
D. 1

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

115. Which keyword is used to create a function in Python?

A. function
B. def
C. define
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

116. What is the output?

```
x = [1, 2, 3]
y = x
y.append(4)
print(x)
```

A. [1, 2, 3]
B. Error
C. [4]
D. [1, 2, 3, 4]

Correct Answer: [1, 2, 3, 4]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

117. What will bool('') evaluate to?

A. None
B. False
C. True
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

118. What is the output of print(2 ** 2 ** 3)?

A. 256
B. 64
C. 12
D. Error

Correct Answer: 256
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

119. How do you start a 'for' loop that iterates from 0 to 9?

A. for i in range(0, 9):
B. for i in range(10):
C. for i in range(9):
D. loop(10):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

120. What is the output of 22 % 6?

A. 22
B. 4
C. Error
D. 3

Correct Answer: 4
Reasoning: The modulo operator (%) returns the remainder of the division.

---

121. Which keyword is used to create a function in Python?

A. def
B. func
C. function
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

122. What is the output of print(2 ** 2 ** 2)?

A. 16
B. Error
C. 8
D. 24

Correct Answer: 16
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

123. What is the output of 16 // 5?

A. 3
B. Error
C. 3.2
D. 4

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

124. Which of the following creates a dictionary?

A. ('a', 1)
B. ['a': 1]
C. {'a': 1}
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

125. What is the output of 18 % 6?

A. 3
B. Error
C. 0
D. 18

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

126. What is the output of 18 % 2?

A. 0
B. 9
C. 18
D. Error

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

127. Which keyword is used to create a function in Python?

A. define
B. def
C. function
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

128. What is the output of print(2 ** 3 ** 2)?

A. 64
B. 512
C. 12
D. Error

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

129. Which of the following creates a dictionary?

A. ('a', 1)
B. {'a': 1}
C. <'a': 1>
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

130. Which of the following creates a dictionary?

A. {'a': 1}
B. <'a': 1>
C. ('a', 1)
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

131. What is the output of 23 // 2?

A. 12
B. Error
C. 11.5
D. 11

Correct Answer: 11
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

132. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [1, 2, 3]
B. [5]
C. [1, 2, 3, 5]
D. Error

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

133. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [1, 2, 3, 6]
B. Error
C. [1, 2, 3]
D. [6]

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

134. What will bool('') evaluate to?

A. False
B. None
C. True
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

135. What is the result of 'java' + 'shine'?

A. 'javashine'
B. 'java shine'
C. ['java', 'shine']
D. Error

Correct Answer: 'javashine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

136. Which keyword is used to create a function in Python?

A. func
B. def
C. function
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

137. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Restarts the loop
C. Skips the current iteration
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

138. How do you start a 'for' loop that iterates from 0 to 3?

A. for i in range(4):
B. loop(4):
C. for i in range(3):
D. for i in range(0, 3):

Correct Answer: for i in range(4):
Reasoning: range(4) generates numbers from 0 up to, but not including, 4.

---

139. What is the output of 20 % 6?

A. 3
B. 2
C. 20
D. Error

Correct Answer: 2
Reasoning: The modulo operator (%) returns the remainder of the division.

---

140. What is the output of 17 % 6?

A. 17
B. Error
C. 2
D. 5

Correct Answer: 5
Reasoning: The modulo operator (%) returns the remainder of the division.

---

141. What is the output of: False or False?

A. True
B. Error
C. None
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

---

142. What is 1 == 2?

A. True
B. False
C. Error
D. None

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

143. What is 'Coding'.lower()?

A. 'coding'
B. None
C. 'Coding'
D. Error

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

---

144. What is 'Python'.lower()?

A. 'Python'
B. 'python'
C. Error
D. None

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

145. What is the output of: False and False?

A. False
B. None
C. True
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

146. What is 5 != 5?

A. True
B. Error
C. None
D. False

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

147. What is the output?

```
x = [1, 2, 3]
y = x
y.append(4)
print(x)
```

A. [4]
B. [1, 2, 3]
C. Error
D. [1, 2, 3, 4]

Correct Answer: [1, 2, 3, 4]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

148. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

149. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. Error
B. [9]
C. [1, 2, 3, 9]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

150. Which of the following creates a dictionary?

A. {'a': 1}
B. ('a', 1)
C. ['a': 1]
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

151. What is 'Python'.lower()?

A. 'Python'
B. Error
C. None
D. 'python'

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

152. What is 2 != 1?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

153. What is the output of print(2 ** 2 ** 2)?

A. 16
B. 90
C. Error
D. 8

Correct Answer: 16
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

154. What is the output of type(7.7)?

A. Error
B. <class 'float'>
C. <class 'int'>
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

155. Which keyword is used to create a function in Python?

A. func
B. define
C. function
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

156. What is 5 != 2?

A. True
B. None
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

157. What is the output of 23 // 3?

A. 7
B. Error
C. 7.666666666666667
D. 8

Correct Answer: 7
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

158. What is 5 < 3?

A. None
B. True
C. False
D. Error

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

159. What is the output of print(3 ** 2 ** 3)?

A. 18
B. 729
C. Error
D. 6561

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

160. What is 'Coding'.lower()?

A. Error
B. 'coding'
C. None
D. 'Coding'

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

---

161. What is the output of 18 // 2?

A. 9.0
B. Error
C. 9
D. 10

Correct Answer: 9
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

162. What is 5 < 5?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

163. What is 2 < 5?

A. Error
B. None
C. True
D. False

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

164. If lst = [1, 9, 6, 6, 6], what is lst[-5]?

A. Error
B. 1
C. 13
D. 6

Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

165. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Pauses the execution
C. Restarts the loop
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

166. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. [9]
B. Error
C. [1, 2, 3]
D. [1, 2, 3, 9]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

167. What is the output of 20 // 5?

A. 5
B. 4
C. 4.0
D. Error

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

168. What is 'Data'.lower()?

A. 'Data'
B. Error
C. None
D. 'data'

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

169. What is 'Data'.lower()?

A. Error
B. 'Data'
C. None
D. 'data'

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

170. How do you start a 'for' loop that iterates from 0 to 6?

A. for i in range(0, 6):
B. for i in range(7):
C. for i in range(6):
D. loop(7):

Correct Answer: for i in range(7):
Reasoning: range(7) generates numbers from 0 up to, but not including, 7.

---

171. What is the output of print(2 ** 2 ** 2)?

A. 8
B. 16
C. Error
D. 53

Correct Answer: 16
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

172. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Pauses the execution
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

173. If lst = [4, 7, 2, 2, 6], what is lst[-1]?

A. 6
B. 4
C. 92
D. Error

Correct Answer: 6
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

174. Which keyword is used to create a function in Python?

A. function
B. func
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

175. What is the output?

```
x = [1, 2, 3]
y = x
y.append(8)
print(x)
```

A. [8]
B. [1, 2, 3, 8]
C. Error
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 8]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

176. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Restarts the loop
C. Skips the current iteration
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

177. How do you start a 'for' loop that iterates from 0 to 9?

A. loop(10):
B. for i in range(10):
C. for i in range(0, 9):
D. for i in range(9):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

178. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. 6
C. 3
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

179. Which of the following creates a dictionary?

A. <'a': 1>
B. ('a', 1)
C. {'a': 1}
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

180. What will bool(()) evaluate to?

A. Error
B. True
C. None
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

181. How do you start a 'for' loop that iterates from 0 to 8?

A. loop(9):
B. for i in range(8):
C. for i in range(9):
D. for i in range(0, 8):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

182. What will bool(()) evaluate to?

A. False
B. Error
C. True
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

183. Which of the following creates a dictionary?

A. {'a': 1}
B. ['a': 1]
C. ('a', 1)
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

184. If lst = [9, 8, 1, 8, 2], what is lst[-2]?

A. Error
B. 2
C. 8
D. 9

Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

185. What is the output of 19 % 4?

A. 19
B. 3
C. Error
D. 4

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

186. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 1
C. 6
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

187. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [1, 2, 3]
B. [1, 2, 3, 6]
C. [6]
D. Error

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

188. What is the output of 20 % 2?

A. 0
B. 10
C. Error
D. 20

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

189. What is 'Data'.upper()?

A. None
B. Error
C. 'Data'
D. 'DATA'

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

---

190. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 6
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

191. What is the result of 'moon' + 'pie'?

A. 'moon pie'
B. ['moon', 'pie']
C. 'moonpie'
D. Error

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

192. What will bool([]) evaluate to?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

193. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

194. What is the result of 'apple' + 'light'?

A. ['apple', 'light']
B. 'applelight'
C. Error
D. 'apple light'

Correct Answer: 'applelight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

195. How do you start a 'for' loop that iterates from 0 to 8?

A. loop(9):
B. for i in range(0, 8):
C. for i in range(8):
D. for i in range(9):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

196. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Restarts the loop
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

197. What is the output of 24 // 4?

A. 6.0
B. 6
C. 7
D. Error

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

198. What is the output of print(2 ** 3 ** 3)?

A. 18
B. 512
C. 134217728
D. Error

Correct Answer: 134217728
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

199. Which keyword is used to create a function in Python?

A. def
B. func
C. function
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

200. What is 'Data'.upper()?

A. 'Data'
B. None
C. 'DATA'
D. Error

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

---

201. How do you start a 'for' loop that iterates from 0 to 4?

A. for i in range(5):
B. for i in range(0, 4):
C. for i in range(4):
D. loop(5):

Correct Answer: for i in range(5):
Reasoning: range(5) generates numbers from 0 up to, but not including, 5.

---

202. What is the output of: False or False?

A. True
B. False
C. None
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

---

203. If lst = [4, 7, 8, 1, 8], what is lst[-4]?

A. 7
B. 8
C. Error
D. 4

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

204. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(0, 5):
B. for i in range(5):
C. loop(6):
D. for i in range(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

205. Which keyword is used to create a function in Python?

A. define
B. function
C. func
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

206. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. 6
C. Error
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

207. What is the result of 'apple' + 'script'?

A. 'apple script'
B. ['apple', 'script']
C. 'applescript'
D. Error

Correct Answer: 'applescript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

208. What is the output of type(6.1)?

A. <class 'int'>
B. <class 'float'>
C. <class 'double'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

209. What is the output of 15 % 4?

A. 3
B. 15
C. Error
D. 57

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

210. What will bool(()) evaluate to?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

211. If lst = [3, 3, 2, 7, 1], what is lst[-5]?

A. 1
B. 3
C. Error
D. 77

Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

212. What is the output of type(5.4)?

A. <class 'double'>
B. <class 'int'>
C. Error
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

213. What is 'Coding'.upper()?

A. 'CODING'
B. None
C. Error
D. 'Coding'

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

214. What is the output of 15 % 5?

A. 15
B. Error
C. 3
D. 0

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

215. What is the output of: False and False?

A. False
B. Error
C. None
D. True

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

216. What is the output of 20 // 5?

A. 4.0
B. 4
C. Error
D. 5

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

217. How do you start a 'for' loop that iterates from 0 to 8?

A. loop(9):
B. for i in range(8):
C. for i in range(9):
D. for i in range(0, 8):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

218. What is the output of 17 // 3?

A. Error
B. 5
C. 5.666666666666667
D. 6

Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

219. What is the output of 15 % 5?

A. 0
B. 3
C. 15
D. Error

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

220. Which keyword is used to create a function in Python?

A. function
B. define
C. def
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

221. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. Error
C. 6
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

222. What is the output of print(2 ** 3 ** 2)?

A. 12
B. 64
C. 512
D. Error

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

223. What is 2 == 2?

A. None
B. False
C. True
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

224. Which of the following creates a dictionary?

A. <'a': 1>
B. ['a': 1]
C. ('a', 1)
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

225. What is the output of type(2.6)?

A. <class 'int'>
B. <class 'double'>
C. <class 'float'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

226. What is the output of 18 % 4?

A. 4
B. Error
C. 18
D. 2

Correct Answer: 2
Reasoning: The modulo operator (%) returns the remainder of the division.

---

227. If lst = [5, 9, 1, 3, 1], what is lst[-2]?

A. 3
B. 5
C. 1
D. Error

Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

228. Which of the following creates a dictionary?

A. ('a', 1)
B. <'a': 1>
C. ['a': 1]
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

229. What does the 'break' statement do in a loop?

A. Restarts the loop
B. Skips the current iteration
C. Pauses the execution
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

230. What is 'Coding'.upper()?

A. None
B. 'Coding'
C. 'CODING'
D. Error

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

231. What is 'Coding'.lower()?

A. 'coding'
B. 'Coding'
C. Error
D. None

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

---

232. What is the output of print(3 ** 2 ** 3)?

A. Error
B. 18
C. 729
D. 6561

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

233. How do you start a 'for' loop that iterates from 0 to 6?

A. loop(7):
B. for i in range(6):
C. for i in range(7):
D. for i in range(0, 6):

Correct Answer: for i in range(7):
Reasoning: range(7) generates numbers from 0 up to, but not including, 7.

---

234. What is the output of: False and True?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

235. What is the output of 20 % 2?

A. 0
B. 20
C. 10
D. Error

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

236. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Restarts the loop
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

237. What is the result of 'apple' + 'light'?

A. Error
B. 'applelight'
C. 'apple light'
D. ['apple', 'light']

Correct Answer: 'applelight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

238. What is the output of: False and False?

A. Error
B. True
C. False
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

239. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

240. If lst = [5, 5, 6, 1, 7], what is lst[-5]?

A. 10
B. 5
C. Error
D. 7

Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

241. What is the output of print(3 ** 3 ** 2)?

A. 18
B. 729
C. Error
D. 19683

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

242. Which keyword is used to create a function in Python?

A. function
B. def
C. func
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

243. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

244. What is the output of 20 // 2?

A. 11
B. 10.0
C. 10
D. Error

Correct Answer: 10
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

245. What is the output of: True and False?

A. None
B. False
C. True
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

246. If lst = [7, 6, 5, 2, 7], what is lst[-3]?

A. Error
B. 5
C. 7
D. 23

Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

247. How do you start a 'for' loop that iterates from 0 to 6?

A. for i in range(7):
B. for i in range(0, 6):
C. loop(7):
D. for i in range(6):

Correct Answer: for i in range(7):
Reasoning: range(7) generates numbers from 0 up to, but not including, 7.

---

248. What will bool({}) evaluate to?

A. None
B. Error
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

249. How do you start a 'for' loop that iterates from 0 to 4?

A. for i in range(5):
B. for i in range(0, 4):
C. loop(5):
D. for i in range(4):

Correct Answer: for i in range(5):
Reasoning: range(5) generates numbers from 0 up to, but not including, 5.

---

250. What is the output of print(2 ** 3 ** 2)?

A. 12
B. 512
C. 64
D. Error

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

251. What is the output of: True or False?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

252. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 6
C. 1
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

253. What is 'Python'.lower()?

A. Error
B. 'python'
C. 'Python'
D. None

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

254. What is the result of 'java' + 'script'?

A. 'java script'
B. ['java', 'script']
C. Error
D. 'javascript'

Correct Answer: 'javascript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

255. How do you start a 'for' loop that iterates from 0 to 8?

A. for i in range(9):
B. loop(9):
C. for i in range(8):
D. for i in range(0, 8):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

256. What is the result of 'apple' + 'shine'?

A. 'appleshine'
B. ['apple', 'shine']
C. Error
D. 'apple shine'

Correct Answer: 'appleshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

257. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

258. What is the output of 18 % 5?

A. Error
B. 3
C. 38
D. 18

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

259. What is the output of: False and False?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

260. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Exits the loop entirely
C. Restarts the loop
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

261. If lst = [3, 6, 5, 2, 4], what is lst[-1]?

A. Error
B. 48
C. 3
D. 4

Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

262. What does the 'break' statement do in a loop?

A. Restarts the loop
B. Skips the current iteration
C. Pauses the execution
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

263. If lst = [8, 4, 5, 7, 6], what is lst[-4]?

A. 6
B. 4
C. Error
D. 8

Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

264. What is 'Python'.upper()?

A. None
B. 'Python'
C. 'PYTHON'
D. Error

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

265. What is the output of: True or False?

A. None
B. Error
C. True
D. False

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

266. What will bool(()) evaluate to?

A. True
B. Error
C. False
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

267. Which of the following creates a dictionary?

A. <'a': 1>
B. ('a', 1)
C. {'a': 1}
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

268. What will bool(()) evaluate to?

A. None
B. Error
C. False
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

269. What is 'Coding'.upper()?

A. Error
B. 'Coding'
C. 'CODING'
D. None

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

270. If lst = [1, 9, 8, 8, 5], what is lst[-2]?

A. 5
B. 8
C. Error
D. 1

Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

271. What will bool('') evaluate to?

A. True
B. None
C. Error
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

272. How do you start a 'for' loop that iterates from 0 to 9?

A. for i in range(0, 9):
B. for i in range(10):
C. for i in range(9):
D. loop(10):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

273. What is the result of 'sun' + 'light'?

A. Error
B. ['sun', 'light']
C. 'sunlight'
D. 'sun light'

Correct Answer: 'sunlight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

274. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Pauses the execution
C. Skips the current iteration
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

275. If lst = [3, 7, 6, 9, 4], what is lst[-1]?

A. 4
B. 3
C. Error
D. 93

Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

276. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 6
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

277. What will bool([]) evaluate to?

A. Error
B. None
C. False
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

278. What is 2 == 4?

A. True
B. None
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

279. What is the output of print(3 ** 3 ** 3)?

A. Error
B. 27
C. 7625597484987
D. 19683

Correct Answer: 7625597484987
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

280. How do you start a 'for' loop that iterates from 0 to 9?

A. for i in range(10):
B. for i in range(9):
C. for i in range(0, 9):
D. loop(10):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

281. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 6
C. 1
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

282. Which of the following creates a dictionary?

A. ['a': 1]
B. ('a', 1)
C. <'a': 1>
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

283. What is the output of: False or False?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

---

284. Which keyword is used to create a function in Python?

A. def
B. func
C. function
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

285. If lst = [8, 7, 7, 9, 4], what is lst[-3]?

A. 4
B. Error
C. 7
D. 8

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

286. What will bool({}) evaluate to?

A. Error
B. None
C. False
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

287. If lst = [5, 6, 9, 4, 5], what is lst[-5]?

A. 14
B. Error
C. 5
D. 89

Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

288. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. Error
C. 3
D. 6

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

289. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. Error
B. [1, 2, 3]
C. [9]
D. [1, 2, 3, 9]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

290. What is the result of 'apple' + 'script'?

A. ['apple', 'script']
B. 'applescript'
C. Error
D. 'apple script'

Correct Answer: 'applescript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

291. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. Error
B. [9]
C. [1, 2, 3, 9]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

292. What will bool(()) evaluate to?

A. True
B. None
C. Error
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

293. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6
B. 3
C. 1
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

294. What is 2 != 1?

A. False
B. Error
C. True
D. None

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

295. What is 'Python'.lower()?

A. 'python'
B. Error
C. None
D. 'Python'

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

296. Which keyword is used to create a function in Python?

A. func
B. function
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

297. What is the output of 17 % 4?

A. 1
B. 17
C. Error
D. 4

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

298. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. Error
B. [1, 2, 3, 5]
C. [5]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

299. What will bool('') evaluate to?

A. None
B. True
C. False
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

300. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 1
C. 3
D. 6

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

301. What is the output of print(3 ** 2 ** 2)?

A. 83
B. 12
C. Error
D. 81

Correct Answer: 81
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

302. What is 5 != 3?

A. Error
B. False
C. None
D. True

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

303. What is the output?

```
x = [1, 2, 3]
y = x
y.append(7)
print(x)
```

A. [7]
B. [1, 2, 3, 7]
C. [1, 2, 3]
D. Error

Correct Answer: [1, 2, 3, 7]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

304. What is the output of: True or True?

A. True
B. None
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

305. What is the output of: False and True?

A. False
B. None
C. True
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

306. What is the output?

```
x = [1, 2, 3]
y = x
y.append(4)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 4]
D. [4]

Correct Answer: [1, 2, 3, 4]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

307. What is the output of 18 // 3?

A. 7
B. 6.0
C. 6
D. Error

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

308. What is the output of print(3 ** 3 ** 2)?

A. 19683
B. 18
C. Error
D. 729

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

309. What is the output of 25 // 4?

A. 7
B. 6
C. 6.25
D. Error

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

310. What is the result of 'apple' + 'script'?

A. 'applescript'
B. 'apple script'
C. ['apple', 'script']
D. Error

Correct Answer: 'applescript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

311. What is the output of 19 % 6?

A. 19
B. Error
C. 3
D. 1

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

312. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 1
C. 6
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

313. What does the 'break' statement do in a loop?

A. Restarts the loop
B. Exits the loop entirely
C. Pauses the execution
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

314. What is the output of 15 % 4?

A. 78
B. 3
C. 15
D. Error

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

315. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 1
C. Error
D. 6

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

316. What is 3 == 4?

A. False
B. None
C. Error
D. True

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

317. Which of the following creates a dictionary?

A. <'a': 1>
B. ('a', 1)
C. ['a': 1]
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

318. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [1, 2, 3, 5]
B. [5]
C. Error
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

319. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 5]
D. [5]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

320. Which keyword is used to create a function in Python?

A. function
B. func
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

321. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 1
C. 6
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

322. What is the output of 21 // 6?

A. 4
B. 3.5
C. 3
D. Error

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

323. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [5]
B. [1, 2, 3]
C. [1, 2, 3, 5]
D. Error

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

324. Which of the following creates a dictionary?

A. ['a': 1]
B. <'a': 1>
C. ('a', 1)
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

325. What is the output of print(2 ** 2 ** 3)?

A. 256
B. 64
C. 12
D. Error

Correct Answer: 256
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

326. What is 'Data'.lower()?

A. None
B. 'data'
C. Error
D. 'Data'

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

327. What does the 'break' statement do in a loop?

A. Restarts the loop
B. Skips the current iteration
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

328. What is the output of 23 % 4?

A. 3
B. Error
C. 23
D. 5

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

329. What is the output of 18 // 5?

A. 3
B. 3.6
C. 4
D. Error

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

330. What is the output of: False and True?

A. True
B. None
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

331. What is 1 != 4?

A. True
B. None
C. Error
D. False

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

332. What is the output of: True or True?

A. False
B. None
C. Error
D. True

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

333. How do you start a 'for' loop that iterates from 0 to 8?

A. for i in range(9):
B. for i in range(8):
C. for i in range(0, 8):
D. loop(9):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

334. What is the output of: True and False?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

335. What is the output of: True or False?

A. True
B. False
C. Error
D. None

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

336. What is the output of: False or True?

A. Error
B. None
C. False
D. True

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

337. What is 4 == 2?

A. False
B. Error
C. None
D. True

Correct Answer: False
Reasoning: Evaluates the comparison operator.

338. What is the output of 23 // 3?

A. Error
B. 8
C. 7
D. 7.666666666666667

Correct Answer: 7
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

339. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 9]
D. [9]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

340. Which of the following creates a dictionary?

A. ('a', 1)
B. ['a': 1]
C. <'a': 1>
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

341. What is the output of: True and True?

A. False
B. Error
C. True
D. None

Correct Answer: True
Reasoning: Evaluates standard logical 'and' operation.

---

342. What is the output of type(2.3)?

A. <class 'double'>
B. Error
C. <class 'int'>
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

343. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [6]
B. [1, 2, 3]
C. [1, 2, 3, 6]
D. Error

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

344. What is the output?

```
x = [1, 2, 3]
y = x
y.append(8)
print(x)
```

A. [1, 2, 3, 8]
B. Error
C. [1, 2, 3]
D. [8]

Correct Answer: [1, 2, 3, 8]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

345. Which of the following creates a dictionary?

A. {'a': 1}
B. ['a': 1]
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

346. What is the output of 18 // 6?

A. Error
B. 3
C. 4
D. 3.0

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

347. What is the output of type(5.8)?

A. <class 'float'>
B. <class 'int'>
C. <class 'double'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

348. What is the output of 21 // 6?

A. Error
B. 4
C. 3
D. 3.5

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

349. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Restarts the loop
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

350. What is the output of 24 // 2?

A. 12.0
B. 13
C. Error
D. 12

Correct Answer: 12
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

351. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 3
C. 1
D. 6

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

352. What is the output of 24 % 5?

A. 4
B. Error
C. 93
D. 24

Correct Answer: 4
Reasoning: The modulo operator (%) returns the remainder of the division.

---

353. What is the output of print(3 ** 3 ** 2)?

A. 19683
B. 729
C. 18
D. Error

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

354. What is 'Python'.lower()?

A. Error
B. 'Python'
C. 'python'
D. None

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

355. What will bool([]) evaluate to?

A. Error
B. True
C. False
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

356. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(0, 5):
B. for i in range(5):
C. for i in range(6):
D. loop(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

357. Which keyword is used to create a function in Python?

A. function
B. define
C. func
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

358. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

359. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Restarts the loop
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

360. What is 1 > 1?

A. False
B. Error
C. None
D. True

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

361. What will bool('') evaluate to?

A. True
B. False
C. None
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

362. How do you start a 'for' loop that iterates from 0 to 4?

A. for i in range(4):
B. for i in range(0, 4):
C. for i in range(5):
D. loop(5):

Correct Answer: for i in range(5):
Reasoning: range(5) generates numbers from 0 up to, but not including, 5.

---

363. What will bool('') evaluate to?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

364. What is the output of 19 // 3?

A. 6
B. 6.333333333333333
C. Error
D. 7

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

365. What is the output of type(5.2)?

A. <class 'float'>
B. <class 'double'>
C. <class 'int'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

366. Which of the following creates a dictionary?

A. ('a', 1)
B. ['a': 1]
C. {'a': 1}
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

367. What is the output of print(3 ** 3 ** 2)?

A. 729
B. 19683
C. Error
D. 18

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

368. What is the output of 20 % 3?

A. 20
B. 2
C. Error
D. 6

Correct Answer: 2
Reasoning: The modulo operator (%) returns the remainder of the division.

---

369. What is the output of print(2 ** 2 ** 2)?

A. Error
B. 54
C. 16
D. 8

Correct Answer: 16
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

370. What is the output?

```
x = [1, 2, 3]
y = x
y.append(7)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 7]
D. [7]

Correct Answer: [1, 2, 3, 7]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

371. How do you start a 'for' loop that iterates from 0 to 7?

A. for i in range(7):
B. loop(8):
C. for i in range(0, 7):
D. for i in range(8):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

372. What is the output of 15 // 6?

A. 2.5
B. Error
C. 3
D. 2

Correct Answer: 2
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

373. What is the output of: False and True?

A. Error
B. True
C. False
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

374. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. Error
C. 6
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

375. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 1
C. 6
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

376. What is the output of 15 // 4?

A. 3
B. Error
C. 4
D. 3.75

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

377. What is the output of print(2 ** 3 ** 3)?

A. 512
B. Error
C. 134217728
D. 18

Correct Answer: 134217728
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

378. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [6]
B. [1, 2, 3]
C. [1, 2, 3, 6]
D. Error

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

379. Which keyword is used to create a function in Python?

A. def
B. func
C. define
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

380. How do you start a 'for' loop that iterates from 0 to 7?

A. for i in range(0, 7):
B. for i in range(7):
C. loop(8):
D. for i in range(8):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

381. What is the output of 24 % 3?

A. 24
B. 0
C. Error
D. 8

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

382. What is the output of 17 // 2?

A. Error
B. 9
C. 8.5
D. 8

Correct Answer: 8
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

383. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

384. If lst = [3, 6, 7, 6, 1], what is lst[-1]?

A. Error
B. 1
C. 30
D. 3

Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

385. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6
B. 1
C. 3
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

386. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(5):
B. for i in range(0, 5):
C. for i in range(6):
D. loop(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

387. What is the result of 'sun' + 'shine'?

A. Error
B. ['sun', 'shine']
C. 'sun shine'
D. 'sunshine'

Correct Answer: 'sunshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

388. What is the result of 'apple' + 'pie'?

A. 'applepie'
B. ['apple', 'pie']
C. Error
D. 'apple pie'

Correct Answer: 'applepie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

389. What is the output of print(2 ** 2 ** 2)?

A. 48
B. 16
C. 8
D. Error

Correct Answer: 16
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

390. What is the output of: True or False?

A. True
B. None
C. Error
D. False

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

391. What is 4 > 4?

A. None
B. Error
C. False
D. True

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

392. What is the output of type(6.3)?

A. <class 'float'>
B. <class 'double'>
C. Error
D. <class 'int'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

393. What is 'Data'.lower()?

A. 'Data'
B. None
C. 'data'
D. Error

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

394. What is the result of 'apple' + 'shine'?

A. ['apple', 'shine']
B. Error
C. 'apple shine'
D. 'appleshine'

Correct Answer: 'appleshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

395. What is 'Data'.lower()?

A. 'Data'
B. Error
C. 'data'
D. None

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

396. What is the output of 20 // 6?

A. 3
B. Error
C. 4
D. 3.3333333333333335

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

397. What is the output of: True and False?

A. True
B. False
C. None
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

398. What is the output of print(3 ** 3 ** 2)?

A. Error
B. 19683
C. 18
D. 729

Correct Answer: 19683
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

399. What is the output of 16 % 4?

A. 16
B. 0
C. 4
D. Error

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

400. Which of the following creates a dictionary?

A. ('a', 1)
B. ['a': 1]
C. <'a': 1>
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

401. What is the output of 18 // 2?

A. 9
B. 9.0
C. Error
D. 10

Correct Answer: 9
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

402. What is the output of 22 // 5?

A. 4
B. 4.4
C. 5
D. Error

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

403. What is the output of type(2.9)?

A. <class 'float'>
B. <class 'int'>
C. Error
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

404. Which keyword is used to create a function in Python?

A. function
B. define
C. func
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

405. What is 2 == 3?

A. True
B. Error
C. False
D. None

Correct Answer: False
Reasoning: Evaluates the comparison operator.

---

406. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6
B. 3
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

407. What is the output of print(3 ** 3 ** 3)?

A. Error
B. 19683
C. 7625597484987
D. 27

Correct Answer: 7625597484987
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

408. What is the output of type(3.4)?

A. <class 'double'>
B. <class 'float'>
C. <class 'int'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

409. What is the result of 'moon' + 'shine'?

A. 'moon shine'
B. Error
C. ['moon', 'shine']
D. 'moonshine'

Correct Answer: 'moonshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

410. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Exits the loop entirely
C. Restarts the loop
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

411. What is 5 > 2?

A. True
B. False
C. Error
D. None

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

412. What is the output of 19 % 5?

A. 3
B. Error
C. 19
D. 4

Correct Answer: 4
Reasoning: The modulo operator (%) returns the remainder of the division.

---

413. Which keyword is used to create a function in Python?

A. def
B. define
C. function
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

414. What is the output of: True and True?

A. True
B. Error
C. False
D. None

Correct Answer: True
Reasoning: Evaluates standard logical 'and' operation.

---

415. Which of the following creates a dictionary?

A. <'a': 1>
B. ('a', 1)
C. {'a': 1}
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

416. What is the output of 22 // 4?

A. 6
B. 5
C. 5.5
D. Error

Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

417. What is 4 < 5?

A. True
B. None
C. Error
D. False

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

418. Which keyword is used to create a function in Python?

A. def
B. define
C. func
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

419. What is the result of 'java' + 'pie'?

A. Error
B. 'java pie'
C. 'javapie'
D. ['java', 'pie']

Correct Answer: 'javapie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

420. What is the output of 15 % 6?

A. 2
B. 15
C. Error
D. 3

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

421. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. [1, 2, 3]
B. [1, 2, 3, 9]
C. [9]
D. Error

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

422. What is the output of 16 // 3?

A. 6
B. Error
C. 5.333333333333333
D. 5

Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

423. Which keyword is used to create a function in Python?

A. define
B. func
C. function
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

424. What is 4 != 1?

A. True
B. Error
C. None
D. False

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

425. Which keyword is used to create a function in Python?

A. define
B. function
C. func
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

426. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1
B. 6
C. Error
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

427. What is the output of 21 // 3?

A. 7
B. 7.0
C. Error
D. 8

Correct Answer: 7
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

428. How do you start a 'for' loop that iterates from 0 to 8?

A. for i in range(0, 8):
B. for i in range(9):
C. for i in range(8):
D. loop(9):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

429. What is the result of 'moon' + 'light'?

A. 'moon light'
B. Error
C. 'moonlight'
D. ['moon', 'light']

Correct Answer: 'moonlight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

430. If lst = [3, 2, 5, 4, 8], what is lst[-5]?

A. 88
B. 3
C. Error
D. 8

Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

431. What is 'Python'.upper()?

A. 'PYTHON'
B. 'Python'
C. Error
D. None

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

432. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 3
C. 6
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

433. What is 5 != 3?

A. None
B. False
C. Error
D. True

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

434. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

435. What is the output of 24 // 5?

A. Error
B. 4.8
C. 5
D. 4

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

436. If lst = [6, 8, 6, 3, 4], what is lst[-4]?

A. Error
B. 6
C. 4
D. 8

Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

437. What is the output of: False and False?

A. False
B. True
C. None
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

438. Which keyword is used to create a function in Python?

A. def
B. func
C. function
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

439. What is 2 != 3?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

440. What is the output of type(6.7)?

A. <class 'float'>
B. Error
C. <class 'int'>
D. <class 'double'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

441. What is the output of print(3 ** 2 ** 3)?

A. 6561
B. 729
C. Error
D. 18

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

442. How do you start a 'for' loop that iterates from 0 to 7?

A. for i in range(7):
B. loop(8):
C. for i in range(8):
D. for i in range(0, 7):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

443. If lst = [2, 6, 9, 8, 3], what is lst[-5]?

A. 2
B. 94
C. Error
D. 3

Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

444. What is the result of 'apple' + 'pie'?

A. 'apple pie'
B. 'applepie'
C. Error
D. ['apple', 'pie']

Correct Answer: 'applepie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

445. What will bool(()) evaluate to?

A. None
B. False
C. Error
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

446. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Exits the loop entirely
C. Skips the current iteration
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

447. What is the result of 'java' + 'light'?

A. Error
B. 'java light'
C. 'javalight'
D. ['java', 'light']

Correct Answer: 'javalight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

448. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error
B. 6
C. 3
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

449. What is the result of 'moon' + 'script'?

A. Error
B. 'moon script'
C. ['moon', 'script']
D. 'moonscript'

Correct Answer: 'moonscript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

450. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [6]
B. Error
C. [1, 2, 3, 6]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

451. What is 'Data'.lower()?

A. Error
B. 'data'
C. 'Data'
D. None

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

452. What does the 'break' statement do in a loop?

A. Restarts the loop
B. Exits the loop entirely
C. Skips the current iteration
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

453. What is the output?

```
x = [1, 2, 3]
y = x
y.append(4)
print(x)
```

A. [1, 2, 3]
B. [4]
C. [1, 2, 3, 4]
D. Error

Correct Answer: [1, 2, 3, 4]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

454. What will bool({}) evaluate to?

A. None
B. Error
C. False
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

455. What is 'Coding'.upper()?

A. 'Coding'
B. 'CODING'
C. Error
D. None

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

456. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Exits the loop entirely
C. Restarts the loop
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

457. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Restarts the loop
C. Pauses the execution
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

458. What is the output of: True or True?

A. True
B. False
C. Error
D. None

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

459. How do you start a 'for' loop that iterates from 0 to 8?

A. loop(9):
B. for i in range(0, 8):
C. for i in range(8):
D. for i in range(9):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

460. Which keyword is used to create a function in Python?

A. define
B. function
C. func
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

461. If lst = [9, 3, 6, 5, 9], what is lst[-3]?

A. 22
B. Error
C. 6
D. 9

Correct Answer: 6
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

462. Which of the following creates a dictionary?

A. ['a': 1]
B. <'a': 1>
C. ('a', 1)
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

463. Which of the following creates a dictionary?

A. ['a': 1]
B. ('a', 1)
C. {'a': 1}
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

464. What is the output of: False or False?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

465. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(6):
B. loop(6):
C. for i in range(5):
D. for i in range(0, 5):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

466. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 6]
D. [6]

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

467. What is 'Data'.lower()?

A. Error
B. None
C. 'Data'
D. 'data'

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

468. What is the output of 15 // 6?

A. Error
B. 2
C. 2.5
D. 3

Correct Answer: 2
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

469. What will bool(()) evaluate to?

A. Error
B. None
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

470. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6
B. 1
C. 3
D. Error

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

471. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Pauses the execution
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

472. What is the output of 21 % 6?

A. 97
B. Error
C. 21
D. 3

Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

---

473. What is 'Python'.upper()?

A. Error
B. 'PYTHON'
C. None
D. 'Python'

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

474. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

475. What is the output of 19 // 6?

A. 3
B. Error
C. 4
D. 3.1666666666666665

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

476. What is 'Python'.upper()?

A. None
B. 'PYTHON'
C. 'Python'
D. Error

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

477. What is the result of 'moon' + 'shine'?

A. 'moonshine'
B. 'moon shine'
C. Error
D. ['moon', 'shine']

Correct Answer: 'moonshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

478. What is the output of type(8.3)?

A. Error
B. <class 'double'>
C. <class 'float'>
D. <class 'int'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

479. What is the output of print(3 ** 2 ** 3)?

A. 729
B. Error
C. 6561
D. 18

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

480. Which keyword is used to create a function in Python?

A. def
B. func
C. define
D. function

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

481. What is the output of 19 // 3?

A. 6
B. Error
C. 6.333333333333333
D. 7

Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

482. What is 2 > 1?

A. False
B. True
C. None
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

---

483. What is the output of type(1.9)?

A. <class 'double'>
B. <class 'int'>
C. <class 'float'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

484. What is the output of: False or True?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

485. How do you start a 'for' loop that iterates from 0 to 6?

A. for i in range(0, 6):
B. for i in range(6):
C. loop(7):
D. for i in range(7):

Correct Answer: for i in range(7):
Reasoning: range(7) generates numbers from 0 up to, but not including, 7.

---

486. How do you start a 'for' loop that iterates from 0 to 9?

A. loop(10):
B. for i in range(10):
C. for i in range(0, 9):
D. for i in range(9):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

487. What is the output of: False and False?

A. False
B. None
C. Error
D. True

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

488. If lst = [1, 7, 1, 6, 8], what is lst[-3]?

A. 1
B. 8
C. 2
D. Error

Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

489. How do you start a 'for' loop that iterates from 0 to 7?

A. loop(8):
B. for i in range(7):
C. for i in range(0, 7):
D. for i in range(8):

Correct Answer: for i in range(8):
Reasoning: range(8) generates numbers from 0 up to, but not including, 8.

---

490. What is the output of type(7.3)?

A. <class 'double'>
B. Error
C. <class 'int'>
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

491. What is the output of print(2 ** 2 ** 3)?

A. 256
B. 64
C. Error
D. 12

Correct Answer: 256
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

492. What is 'Python'.lower()?

A. 'Python'
B. Error
C. None
D. 'python'

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

493. If lst = [3, 8, 7, 4, 2], what is lst[-3]?

A. Error
B. 3
C. 7
D. 2

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

494. What is the output of 24 // 2?

A. 12.0
B. Error
C. 12
D. 13

Correct Answer: 12
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

495. What is the output of print(2 ** 3 ** 2)?

A. 512
B. Error
C. 12
D. 64

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

496. What is the output of type(2.3)?

A. <class 'int'>
B. <class 'double'>
C. Error
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

497. What is 'Coding'.lower()?

A. Error
B. None
C. 'Coding'
D. 'coding'

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

---

498. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6
B. Error
C. 1
D. 3

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

499. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. ('a', 1)
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

500. What is the result of 'moon' + 'light'?

A. ['moon', 'light']
B. 'moonlight'
C. 'moon light'
D. Error

Correct Answer: 'moonlight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

501. What will bool([]) evaluate to?

A. None
B. Error
C. True
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

502. What is the result of 'moon' + 'pie'?

A. 'moonpie'
B. Error
C. ['moon', 'pie']
D. 'moon pie'

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

503. What is the output of: False or True?

A. None
B. Error
C. True
D. False

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

504. What will bool(()) evaluate to?

A. None
B. True
C. Error
D. False

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

505. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. [6]
B. [1, 2, 3, 6]
C. Error
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

506. Which keyword is used to create a function in Python?

A. func
B. function
C. def
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

507. What is the output of: True or True?

A. Error
B. None
C. False
D. True

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

508. What is 'Coding'.lower()?

A. 'coding'
B. None
C. 'Coding'
D. Error

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

---

509. What is the output of type(8.2)?

A. <class 'double'>
B. Error
C. <class 'int'>
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

510. What is the output of 17 // 6?

A. 2.8333333333333335
B. 2
C. Error
D. 3

Correct Answer: 2
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

511. What will bool(()) evaluate to?

A. False
B. True
C. Error
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

512. How do you start a 'for' loop that iterates from 0 to 3?

A. for i in range(4):
B. for i in range(3):
C. loop(4):
D. for i in range(0, 3):

Correct Answer: for i in range(4):
Reasoning: range(4) generates numbers from 0 up to, but not including, 4.

---

513. What is the result of 'moon' + 'pie'?

A. 'moonpie'
B. 'moon pie'
C. Error
D. ['moon', 'pie']

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

514. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

515. Which of the following creates a dictionary?

A. <'a': 1>
B. {'a': 1}
C. ['a': 1]
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

516. Which keyword is used to create a function in Python?

A. def
B. function
C. define
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

517. If lst = [6, 2, 1, 1, 9], what is lst[-2]?

A. Error
B. 1
C. 6
D. 9

Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

518. What is the output of type(5.5)?

A. <class 'double'>
B. <class 'float'>
C. <class 'int'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

519. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Pauses the execution
C. Restarts the loop
D. Exits the loop entirely

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

520. What will bool('') evaluate to?

A. True
B. False
C. Error
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

521. What is the result of 'apple' + 'pie'?

A. 'applepie'
B. ['apple', 'pie']
C. Error
D. 'apple pie'

Correct Answer: 'applepie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

522. Which keyword is used to create a function in Python?

A. function
B. func
C. def
D. define

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

523. What does the 'break' statement do in a loop?

A. Skips the current iteration
B. Restarts the loop
C. Exits the loop entirely
D. Pauses the execution

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

524. What is the output of type(5.0)?

A. <class 'int'>
B. <class 'double'>
C. Error
D. <class 'float'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

525. How do you start a 'for' loop that iterates from 0 to 5?

A. for i in range(6):
B. for i in range(5):
C. for i in range(0, 5):
D. loop(6):

Correct Answer: for i in range(6):
Reasoning: range(6) generates numbers from 0 up to, but not including, 6.

---

526. What is the result of 'java' + 'light'?

A. 'javalight'
B. 'java light'
C. Error
D. ['java', 'light']

Correct Answer: 'javalight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

527. What is the output of: False and False?

A. None
B. Error
C. True
D. False

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

528. What is the result of 'java' + 'light'?

A. 'javalight'
B. Error
C. 'java light'
D. ['java', 'light']

Correct Answer: 'javalight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

529. How do you start a 'for' loop that iterates from 0 to 8?

A. for i in range(0, 8):
B. loop(9):
C. for i in range(9):
D. for i in range(8):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

530. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Pauses the execution
C. Restarts the loop
D. Skips the current iteration

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

531. How do you start a 'for' loop that iterates from 0 to 8?

A. for i in range(9):
B. loop(9):
C. for i in range(8):
D. for i in range(0, 8):

Correct Answer: for i in range(9):
Reasoning: range(9) generates numbers from 0 up to, but not including, 9.

---

532. What is the result of 'java' + 'shine'?

A. 'java shine'
B. ['java', 'shine']
C. Error
D. 'javashine'

Correct Answer: 'javashine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

533. How do you start a 'for' loop that iterates from 0 to 6?

A. loop(7):
B. for i in range(0, 6):
C. for i in range(7):
D. for i in range(6):

Correct Answer: for i in range(7):
Reasoning: range(7) generates numbers from 0 up to, but not including, 7.

---

534. If lst = [3, 7, 7, 3, 9], what is lst[-3]?

A. 9
B. Error
C. 3
D. 7

Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

535. What is the output?

```
x = [1, 2, 3]
y = x
y.append(9)
print(x)
```

A. Error
B. [9]
C. [1, 2, 3, 9]
D. [1, 2, 3]

Correct Answer: [1, 2, 3, 9]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

536. What is the output of 23 // 6?

A. Error
B. 3.8333333333333335
C. 3
D. 4

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

537. What is the output of print(2 ** 2 ** 3)?

A. 12
B. 256
C. Error
D. 64

Correct Answer: 256
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

538. Which keyword is used to create a function in Python?

A. function
B. func
C. define
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

539. What is the output of print(3 ** 2 ** 3)?

A. Error
B. 6561
C. 729
D. 18

Correct Answer: 6561
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

540. What is the output of 18 % 4?

A. 18
B. 4
C. 2
D. Error

Correct Answer: 2
Reasoning: The modulo operator (%) returns the remainder of the division.

---

541. What is the output of: False and False?

A. False
B. True
C. Error
D. None

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

542. What is 'Python'.lower()?

A. Error
B. 'python'
C. None
D. 'Python'

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

543. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 1
C. Error
D. 6

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

544. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. <'a': 1>
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

545. Which of the following creates a dictionary?

A. <'a': 1>
B. ['a': 1]
C. {'a': 1}
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

546. What is the result of 'moon' + 'light'?

A. 'moon light'
B. 'moonlight'
C. Error
D. ['moon', 'light']

Correct Answer: 'moonlight'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

547. What is the output of: False and False?

A. None
B. False
C. True
D. Error

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

548. What is the output of 22 // 5?

A. 4.4
B. 4
C. 5
D. Error

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

549. What will bool('') evaluate to?

A. False
B. Error
C. True
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

550. What is the output of: True and False?

A. None
B. Error
C. False
D. True

Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

---

551. Which of the following creates a dictionary?

A. ('a', 1)
B. <'a': 1>
C. ['a': 1]
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

552. What is 'Data'.lower()?

A. None
B. 'data'
C. Error
D. 'Data'

Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

---

553. How do you start a 'for' loop that iterates from 0 to 4?

A. for i in range(4):
B. loop(5):
C. for i in range(5):
D. for i in range(0, 4):

Correct Answer: for i in range(5):
Reasoning: range(5) generates numbers from 0 up to, but not including, 5.

---

554. What is the output of: False or False?

A. False
B. Error
C. None
D. True

Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

---

555. What is the output?

```
x = [1, 2, 3]
y = x
y.append(6)
print(x)
```

A. Error
B. [6]
C. [1, 2, 3]
D. [1, 2, 3, 6]

Correct Answer: [1, 2, 3, 6]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

556. What does the 'break' statement do in a loop?

A. Pauses the execution
B. Skips the current iteration
C. Exits the loop entirely
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

557. Which of the following creates a dictionary?

A. ['a': 1]
B. {'a': 1}
C. ('a', 1)
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

558. What is 'Data'.upper()?

A. Error
B. 'Data'
C. None
D. 'DATA'

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

---

559. What will bool({}) evaluate to?

A. False
B. None
C. Error
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

560. What is the output of type(3.4)?

A. <class 'float'>
B. Error
C. <class 'double'>
D. <class 'int'>

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

561. How do you start a 'for' loop that iterates from 0 to 9?

A. for i in range(9):
B. loop(10):
C. for i in range(0, 9):
D. for i in range(10):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

562. What is the result of 'apple' + 'shine'?

A. Error
B. 'apple shine'
C. 'appleshine'
D. ['apple', 'shine']

Correct Answer: 'appleshine'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

563. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. [1, 2, 3]
B. Error
C. [1, 2, 3, 5]
D. [5]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

564. What is 'Coding'.upper()?

A. 'Coding'
B. 'CODING'
C. None
D. Error

Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

---

565. What is the output of 22 % 3?

A. Error
B. 1
C. 7
D. 22

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

566. Which of the following creates a dictionary?

A. ('a', 1)
B. {'a': 1}
C. ['a': 1]
D. <'a': 1>

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

567. How do you start a 'for' loop that iterates from 0 to 9?

A. for i in range(9):
B. loop(10):
C. for i in range(0, 9):
D. for i in range(10):

Correct Answer: for i in range(10):
Reasoning: range(10) generates numbers from 0 up to, but not including, 10.

---

568. What is the result of 'moon' + 'script'?

A. ['moon', 'script']
B. Error
C. 'moonscript'
D. 'moon script'

Correct Answer: 'moonscript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

569. What does the 'break' statement do in a loop?

A. Exits the loop entirely
B. Pauses the execution
C. Skips the current iteration
D. Restarts the loop

Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

---

570. If lst = [5, 8, 4, 8, 4], what is lst[-2]?

A. 8
B. Error
C. 4
D. 5

Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

571. What is the output of type(6.4)?

A. <class 'int'>
B. <class 'double'>
C. <class 'float'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

572. What is the output of type(3.6)?

A. <class 'double'>
B. <class 'int'>
C. <class 'float'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

573. What is the output of 23 // 2?

A. Error
B. 12
C. 11
D. 11.5

Correct Answer: 11
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

---

574. What is the output of: False or True?

A. None
B. True
C. False
D. Error

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

575. Which of the following creates a dictionary?

A. ('a', 1)
B. <'a': 1>
C. ['a': 1]
D. {'a': 1}

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

576. Which keyword is used to create a function in Python?

A. func
B. define
C. function
D. def

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

577. What is 'Python'.lower()?

A. None
B. 'Python'
C. Error
D. 'python'

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

578. What is the output?

```
x = [1, 2, 3]
y = x
y.append(5)
print(x)
```

A. Error
B. [1, 2, 3, 5]
C. [1, 2, 3]
D. [5]

Correct Answer: [1, 2, 3, 5]
Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.

---

579. What is the output of print(2 ** 3 ** 2)?

A. Error
B. 64
C. 512
D. 12

Correct Answer: 512
Reasoning: Exponentiation (**) in Python is evaluated from right to left.

---

580. If lst = [5, 2, 7, 5, 6], what is lst[-5]?

A. 34
B. Error
C. 6
D. 5

Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

---

581. What is the output of: True or False?

A. Error
B. None
C. False
D. True

Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

---

582. What will bool({}) evaluate to?

A. None
B. True
C. False
D. Error

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

583. What is the output of type(2.6)?

A. <class 'double'>
B. <class 'int'>
C. <class 'float'>
D. Error

Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

---

584. What is the result of 'sun' + 'script'?

A. 'sun script'
B. 'sunscript'
C. ['sun', 'script']
D. Error

Correct Answer: 'sunscript'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

585. What is 'Python'.upper()?

A. None
B. 'PYTHON'
C. 'Python'
D. Error

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

---

586. Which keyword is used to create a function in Python?

A. define
B. function
C. def
D. func

Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

---

587. What is 'Data'.upper()?

A. 'DATA'
B. None
C. 'Data'
D. Error

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

---

588. What is the output of 25 % 4?

A. 6
B. Error
C. 1
D. 25

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

589. What will bool({}) evaluate to?

A. False
B. Error
C. None
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

590. What is the output of 24 % 5?

A. 4
B. Error
C. 81
D. 24

Correct Answer: 4
Reasoning: The modulo operator (%) returns the remainder of the division.

---

591. What is the output of 17 % 4?

A. 17
B. 1
C. Error
D. 4

Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

---

592. Which of the following creates a dictionary?

A. {'a': 1}
B. <'a': 1>
C. ['a': 1]
D. ('a', 1)

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

593. What is the result of 'moon' + 'pie'?

A. Error
B. 'moon pie'
C. ['moon', 'pie']
D. 'moonpie'

Correct Answer: 'moonpie'
Reasoning: The '+' operator concatenates strings directly without adding spaces.

---

594. Which of the following creates a dictionary?

A. ('a', 1)
B. <'a': 1>
C. {'a': 1}
D. ['a': 1]

Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

---

595. What is the output of 15 % 5?

A. 0
B. 15
C. 3
D. Error

Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

---

596. What will bool(()) evaluate to?

A. None
B. False
C. Error
D. True

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

597. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 3
B. 6
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

---

598. What will bool([]) evaluate to?

A. Error
B. False
C. True
D. None

Correct Answer: False
Reasoning: In Python, all empty sequences and collections evaluate to False.

---

599. What is 'Python'.lower()?

A. None
B. 'python'
C. 'Python'
D. Error

Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

---

600. What is the output of 23 // 6?

A. 3
B. Error
C. 3.8333333333333335
D. 4

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.