1. What is the output?
   x = [1, 2, 3]
   y = x
   y.append(7)
   print(x)
   A. [1, 2, 3, 7]
   B. Error
   C. [1, 2, 3]
   D. [7]
   Correct Answer: [1, 2, 3, 7]
   Reasoning: Assigning y = x creates a reference to the same list in memory. Modifying y modifies x.
2. What is the output of print(3 2 3)?
   A. 87
   B. Error
   C. 6561
   D. 729
   Correct Answer: 6561
   Reasoning: Exponentiation () in Python is evaluated from right to left.
3. What will bool(()) evaluate to?
   A. False
   B. None
   C. Error
   D. True
   Correct Answer: False
   Reasoning: In Python, all empty sequences and collections evaluate to False.
4. How do you start a 'for' loop that iterates from 0 to 4?
   A. for i in range(5):
   B. loop(5):
   C. for i in range(4):
   D. for i in range(0, 4):
   Correct Answer: for i in range(5):
   Reasoning: range(5) generates numbers from 0 up to, but not including, 5.
5. What is the result of 'java' + 'script'?
   A. 'java script'
   B. Error
   C. ['java', 'script']
   D. 'javascript'
   Correct Answer: 'javascript'
   Reasoning: The '+' operator concatenates strings directly without adding spaces.
6. Which keyword is used to create a function in Python?

A. def
B. define
C. func
D. function
Correct Answer: def
Reasoning: 'def' is the standard Python keyword used to define a function.

7. What is the output of type(1.5)?
A. <class 'float'>
B. <class 'double'>
C. Error
D. <class 'int'>
Correct Answer: <class 'float'>
Reasoning: Any number with a decimal point is represented as a floating-point number (float) in Python.

8. What does the 'break' statement do in a loop?
A. Restarts the loop
B. Pauses the execution
C. Exits the loop entirely
D. Skips the current iteration
Correct Answer: Exits the loop entirely
Reasoning: The 'break' statement immediately terminates the innermost enclosing loop.

9. Which of the following creates a dictionary?
A. {'a': 1}
B. <'a': 1>
C. ['a': 1]
D. ('a', 1)
Correct Answer: {'a': 1}
Reasoning: Dictionaries are created using curly braces {} with key-value pairs separated by colons.

10. What is 'Data'.lower()?
A. None
B. Error
C. 'data'
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

11. What is the output of 19 // 3?
A. 6.333333333333333
B. 6
C. 7
D. Error
Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

12. What is 5 == 2?
    A. Error
    B. False
    C. True
    D. None
    Correct Answer: False
    Reasoning: Evaluates the comparison operator.
13. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 3
    B. 6
    C. Error
    D. 1
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
14. What is the output of: True or False?
    A. Error
    B. False
    C. None
    D. True
    Correct Answer: True
    Reasoning: Evaluates standard logical 'or' operation.
15. If lst = [3, 4, 3, 3, 9], what is lst[-1]?
    A. 9
    B. 3
    C. 60
    D. Error
    Correct Answer: 9
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
16. If lst = [3, 2, 7, 7, 7], what is lst[-3]?
    A. 3
    B. Error
    C. 7
    D. 70
    Correct Answer: 7
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
17. What is 'Python'.lower()?
    A. 'python'
    B. None
    C. Error
    D. 'Python'
    Correct Answer: 'python'
    Reasoning: The lower() method changes the casing of the string.
18. What is the output of 24 % 6?

A. 24
B. 0
C. 4
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

19. What is 'Coding'.upper()?
A. 'CODING'
B. None
C. 'Coding'
D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

20. What is 2 == 5?
A. True
B. False
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

21. What is 5 > 4?
A. True
B. None
C. False
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

22. What is 3 < 3?
A. False
B. True
C. None
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

23. What is the output of 15 % 5?
A. Error
B. 3
C. 0
D. 15
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

24. What is the output of 23 // 5?
A. 5

B. 4
C. 4.6
D. Error
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

25. What is the output of 20 % 3?
    A. 2
    B. 6
    C. Error
    D. 20
    Correct Answer: 2
    Reasoning: The modulo operator (%) returns the remainder of the division.
26. What is the output of: False and False?
    A. None
    B. Error
    C. True
    D. False
    Correct Answer: False
    Reasoning: Evaluates standard logical 'and' operation.
27. What is the output of: True and True?
    A. Error
    B. True
    C. None
    D. False
    Correct Answer: True
    Reasoning: Evaluates standard logical 'and' operation.
28. What is 5 > 1?
    A. False
    B. None
    C. True
    D. Error
    Correct Answer: True
    Reasoning: Evaluates the comparison operator.
29. What is 'Python'.lower()?
    A. 'python'
    B. 'Python'
    C. Error
    D. None
    Correct Answer: 'python'
    Reasoning: The lower() method changes the casing of the string.
30. What is 'Python'.lower()?
    A. 'Python'
    B. None

C. Error
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

31. What is the output of 19 // 3?
A. 6
B. 6.333333333333333
C. Error
D. 7
Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

32. What is 'Python'.lower()?
A. Error
B. None
C. 'python'
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

33. What is 2 == 5?
A. False
B. True
C. None
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

34. If lst = [3, 2, 7, 7, 6], what is lst[-3]?
A. 3
B. 7
C. 83
D. Error
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

35. What is 'Coding'.lower()?
A. 'coding'
B. Error
C. None
D. 'Coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

36. What is 'Coding'.lower()?
A. 'coding'
B. None
C. 'Coding'

D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

37. What is 'Data'.lower()?
    A. Error
    B. 'Data'
    C. 'data'
    D. None
    Correct Answer: 'data'
    Reasoning: The lower() method changes the casing of the string.
38. What is the output of 23 % 5?
    A. 23
    B. 4
    C. Error
    D. 3
    Correct Answer: 3
    Reasoning: The modulo operator (%) returns the remainder of the division.
39. If lst = [1, 9, 3, 2, 7], what is lst[-4]?
    A. 1
    B. 7
    C. Error
    D. 9
    Correct Answer: 9
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
40. What is 'Coding'.upper()?
    A. 'CODING'
    B. 'Coding'
    C. None
    D. Error
    Correct Answer: 'CODING'
    Reasoning: The upper() method changes the casing of the string.
41. What is the output of 15 // 5?
    A. 4
    B. Error
    C. 3
    D. 3.0
    Correct Answer: 3
    Reasoning: Floor division (//) divides and rounds down to the nearest integer.
42. If lst = [1, 5, 2, 2, 9], what is lst[-1]?
    A. Error
    B. 1
    C. 9
    D. 68

Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

43. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 1
    B. Error
    C. 6
    D. 3
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
44. If lst = [1, 8, 4, 3, 9], what is lst[-3]?
    A. Error
    B. 9
    C. 1
    D. 4
    Correct Answer: 4
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
45. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 6
    B. 1
    C. Error
    D. 3
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
46. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. Error
    B. 1
    C. 3
    D. 6
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
47. What is 'Coding'.lower()?
    A. None
    B. 'coding'
    C. Error
    D. 'Coding'
    Correct Answer: 'coding'
    Reasoning: The lower() method changes the casing of the string.
48. What is 'Python'.lower()?
    A. 'python'
    B. 'Python'
    C. Error
    D. None
    Correct Answer: 'python'

Reasoning: The lower() method changes the casing of the string.

49. If lst = [3, 2, 2, 3, 1], what is lst[-2]?
    A. 67
    B. Error
    C. 3
    D. 1
    Correct Answer: 3
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
50. What is 5 != 2?
    A. False
    B. None
    C. Error
    D. True
    Correct Answer: True
    Reasoning: Evaluates the comparison operator.
51. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. Error
    B. 1
    C. 3
    D. 6
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
52. What is 2 == 4?
    A. True
    B. False
    C. Error
    D. None
    Correct Answer: False
    Reasoning: Evaluates the comparison operator.
53. What is 4 == 4?
    A. Error
    B. True
    C. False
    D. None
    Correct Answer: True
    Reasoning: Evaluates the comparison operator.
54. What is the output of 15 % 5?
    A. 3
    B. 15
    C. 0
    D. Error
    Correct Answer: 0
    Reasoning: The modulo operator (%) returns the remainder of the division.

55. What is 'Python'.lower()?
    A. Error
    B. 'Python'
    C. None
    D. 'python'
    Correct Answer: 'python'
    Reasoning: The lower() method changes the casing of the string.
56. What is the output of 24 // 6?
    A. Error
    B. 4.0
    C. 4
    D. 5
    Correct Answer: 4
    Reasoning: Floor division (//) divides and rounds down to the nearest integer.
57. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 6
    B. Error
    C. 3
    D. 1
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
58. What is the output of: False or False?
    A. None
    B. Error
    C. True
    D. False
    Correct Answer: False
    Reasoning: Evaluates standard logical 'or' operation.
59. What is the output of 18 % 3?
    A. 0
    B. 6
    C. Error
    D. 18
    Correct Answer: 0
    Reasoning: The modulo operator (%) returns the remainder of the division.
60. What is 4 < 2?
    A. None
    B. True
    C. False
    D. Error
    Correct Answer: False
    Reasoning: Evaluates the comparison operator.
61. What is 'Data'.lower()?

A. Error
B. 'data'
C. 'Data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

62. If lst = [9, 7, 7, 8, 9], what is lst[-1]?
A. 61
B. 9
C. Error
D. 9
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

63. What is the output of 19 // 2?
A. 9
B. 9.5
C. Error
D. 10
Correct Answer: 9
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

64. What is 'Python'.upper()?
A. None
B. Error
C. 'Python'
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

65. What is the output of: True and False?
A. Error
B. False
C. True
D. None
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

66. What is 'Coding'.upper()?
A. None
B. 'Coding'
C. 'CODING'
D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

67. What is 'Coding'.lower()?
A. Error

B. 'Coding'
C. 'coding'
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

68. If lst = [4, 6, 8, 7, 7], what is lst[-3]?
A. 8
B. 4
C. 28
D. Error
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

69. What is 'Coding'.upper()?
A. Error
B. 'CODING'
C. 'Coding'
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

70. What is the output of: False or True?
A. Error
B. False
C. True
D. None
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

71. What is the output of 24 % 6?
A. 4
B. 0
C. Error
D. 24
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

72. What is 5 < 2?
A. None
B. True
C. False
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

73. What is the output of 18 % 3?
A. 18
B. Error

C. 6
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

74. What is 1 < 3?
A. Error
B. True
C. None
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

75. If lst = [5, 4, 3, 5, 8], what is lst[-4]?
A. Error
B. 5
C. 4
D. 8
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

76. What is 'Coding'.upper()?
A. 'CODING'
B. Error
C. None
D. 'Coding'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

77. What is 5 == 1?
A. Error
B. None
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

78. What is the output of 16 // 5?
A. 4
B. 3.2
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

79. What is 1 < 3?
A. Error
B. False
C. None

D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

80. If lst = [9, 8, 4, 4, 2], what is lst[-4]?
    A. 8
    B. 9
    C. Error
    D. 2
    Correct Answer: 8
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
81. What is the output of 17 % 5?
    A. 3
    B. 2
    C. Error
    D. 17
    Correct Answer: 2
    Reasoning: The modulo operator (%) returns the remainder of the division.
82. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 6
    B. Error
    C. 1
    D. 3
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
83. If lst = [1, 9, 3, 3, 5], what is lst[-1]?
    A. 1
    B. Error
    C. 5
    D. 69
    Correct Answer: 5
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
84. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 6
    B. 1
    C. 3
    D. Error
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
85. What is the output of 15 // 5?
    A. Error
    B. 3.0
    C. 4
    D. 3

Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

86. What is 5 == 5?
    A. False
    B. None
    C. Error
    D. True
    Correct Answer: True
    Reasoning: Evaluates the comparison operator.
87. What is 'Coding'.lower()?
    A. 'coding'
    B. Error
    C. 'Coding'
    D. None
    Correct Answer: 'coding'
    Reasoning: The lower() method changes the casing of the string.
88. What is 'Data'.lower()?
    A. 'Data'
    B. 'data'
    C. Error
    D. None
    Correct Answer: 'data'
    Reasoning: The lower() method changes the casing of the string.
89. What is the output of 15 % 5?
    A. 3
    B. 0
    C. 15
    D. Error
    Correct Answer: 0
    Reasoning: The modulo operator (%) returns the remainder of the division.
90. If lst = [5, 5, 2, 1, 9], what is lst[-1]?
    A. Error
    B. 9
    C. 5
    D. 9
    Correct Answer: 9
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
91. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 6
    B. 3
    C. Error
    D. 1
    Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

92. If lst = [3, 9, 9, 5, 3], what is lst[-4]?
    A. Error
    B. 3
    C. 9
    D. 3
    Correct Answer: 9
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
93. What is 'Data'.upper()?
    A. 'DATA'
    B. None
    C. Error
    D. 'Data'
    Correct Answer: 'DATA'
    Reasoning: The upper() method changes the casing of the string.
94. If lst = [5, 4, 3, 6, 4], what is lst[-3]?
    A. 3
    B. 4
    C. 91
    D. Error
    Correct Answer: 3
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
95. What is 4 < 1?
    A. False
    B. None
    C. True
    D. Error
    Correct Answer: False
    Reasoning: Evaluates the comparison operator.
96. What is 'Coding'.upper()?
    A. 'Coding'
    B. 'CODING'
    C. Error
    D. None
    Correct Answer: 'CODING'
    Reasoning: The upper() method changes the casing of the string.
97. What is the output of 24 % 4?
    A. 24
    B. Error
    C. 0
    D. 6
    Correct Answer: 0
    Reasoning: The modulo operator (%) returns the remainder of the division.

98. What is the output of 24 // 6?
    A. 4.0
    B. 5
    C. Error
    D. 4
    Correct Answer: 4
    Reasoning: Floor division (//) divides and rounds down to the nearest integer.
99. What is 'Coding'.upper()?
    A. 'CODING'
    B. None
    C. 'Coding'
    D. Error
    Correct Answer: 'CODING'
    Reasoning: The upper() method changes the casing of the string.
100. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
    A. 1
    B. Error
    C. 3
    D. 6
    Correct Answer: 3
    Reasoning: Converting a list to a set removes all duplicate elements.
101. What is the output of 15 % 5?
    A. 0
    B. Error
    C. 3
    D. 15
    Correct Answer: 0
    Reasoning: The modulo operator (%) returns the remainder of the division.
102. If lst = [1, 9, 7, 7, 1], what is lst[-3]?
    A. Error
    B. 1
    C. 7
    D. 52
    Correct Answer: 7
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
103. If lst = [3, 2, 2, 2, 7], what is lst[-1]?
    A. 3
    B. 7
    C. Error
    D. 92
    Correct Answer: 7
    Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
104. What is 'Python'.lower()?

A. None
B. 'Python'
C. Error
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

105. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 6
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

106. What is 'Data'.upper()?
A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

107. What is 'Coding'.upper()?
A. 'CODING'
B. 'Coding'
C. None
D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

108. If lst = [2, 1, 9, 5, 2], what is lst[-1]?
A. Error
B. 2
C. 82
D. 2
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

109. What is 5 == 1?
A. None
B. True
C. False
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

110. What is 5 > 2?
A. Error

B. None
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

111. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 6
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

112. What is 1 == 3?
A. Error
B. None
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

113. What is 'Coding'.upper()?
A. None
B. 'Coding'
C. Error
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

114. If lst = [2, 1, 1, 8, 3], what is lst[-5]?
A. Error
B. 3
C. 2
D. 95
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

115. What is the output of 15 // 5?
A. Error
B. 3.0
C. 3
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

116. If lst = [9, 8, 1, 3, 9], what is lst[-4]?
A. Error
B. 8

C. 9
D. 9
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

117. What is the output of 24 // 4?
A. Error
B. 6
C. 7
D. 6.0
Correct Answer: 6
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

118. What is the output of 16 // 5?
A. 3.2
B. 4
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

119. What is 'Coding'.upper()?
A. Error
B. None
C. 'Coding'
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

120. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 6
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

121. What is the output of 22 // 4?
A. Error
B. 5
C. 5.5
D. 6
Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

122. What is 2 == 5?
A. True
B. False
C. Error

D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

123. If lst = [8, 5, 2, 3, 4], what is lst[-4]?
A. 5
B. 8
C. Error
D. 4
Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

124. What is 'Coding'.lower()?
A. Error
B. 'Coding'
C. 'coding'
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

125. What is 5 == 1?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

126. What is 'Data'.upper()?
A. Error
B. 'DATA'
C. None
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

127. If lst = [2, 1, 9, 3, 7], what is lst[-2]?
A. 3
B. 7
C. Error
D. 91
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

128. What is the output of 23 // 5?
A. 4.6
B. 5
C. Error
D. 4

Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

129. What is 'Python'.upper()?
A. 'Python'
B. None
C. Error
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

130. What is 4 == 4?
A. False
B. None
C. True
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

131. If lst = [5, 4, 1, 5, 4], what is lst[-4]?
A. 4
B. 5
C. 4
D. Error
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

132. What is 1 < 4?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

133. If lst = [1, 2, 2, 4, 3], what is lst[-2]?
A. Error
B. 3
C. 65
D. 4
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

134. What is 4 != 2?
A. False
B. True
C. Error
D. None
Correct Answer: True

Reasoning: Evaluates the comparison operator.

135. What is 4 > 3?

A. Error
B. None
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

136. What is the output of 15 % 5?

A. 3
B. 0
C. 15
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

137. What is 'Python'.upper()?

A. 'PYTHON'
B. Error
C. 'Python'
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

138. What is the output of 21 // 5?

A. 4.2
B. Error
C. 4
D. 5
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

139. If lst = [8, 5, 2, 3, 2], what is lst[-2]?

A. Error
B. 2
C. 3
D. 69
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

140. What is 'Coding'.lower()?

A. 'Coding'
B. 'coding'
C. Error
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

141. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
142. What is the output of: True or True?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.
143. What is 5 != 2?
A. True
B. Error
C. None
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.
144. What is the output of 23 // 6?
A. Error
B. 3
C. 3.8333333333333335
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
145. What is 'Data'.lower()?
A. Error
B. None
C. 'Data'
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
146. If lst = [3, 2, 6, 8, 3], what is lst[-3]?
A. 3
B. 6
C. Error
D. 83
Correct Answer: 6
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
147. If lst = [9, 8, 4, 3, 1], what is lst[-1]?

A. 9
B. 1
C. Error
D. 35
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

148. What is 'Python'.upper()?
A. 'Python'
B. Error
C. None
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

149. If lst = [2, 1, 9, 3, 4], what is lst[-1]?
A. Error
B. 4
C. 2
D. 46
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

150. What is 2 == 5?
A. False
B. None
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

151. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. Error
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

152. What is 4 == 4?
A. Error
B. False
C. True
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

153. What is 5 != 2?
A. False

B. Error
C. None
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

154. What is 'Coding'.lower()?
A. Error
B. None
C. 'coding'
D. 'Coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

155. What is 1 == 3?
A. False
B. True
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

156. If lst = [1, 9, 3, 2, 2], what is lst[-5]?
A. Error
B. 2
C. 89
D. 1
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

157. What is 'Python'.upper()?
A. 'PYTHON'
B. Error
C. None
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

158. If lst = [5, 4, 3, 6, 8], what is lst[-3]?
A. 8
B. 5
C. Error
D. 3
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

159. What is 'Python'.lower()?
A. Error
B. 'python'

C. 'Python'
D. None
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

160. What is the output of 23 % 5?
A. 4
B. Error
C. 23
D. 3
Correct Answer: 3
Reasoning: The modulo operator (%) returns the remainder of the division.

161. What is the output of 15 // 5?
A. 4
B. 3.0
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

162. If lst = [9, 8, 4, 3, 1], what is lst[-2]?
A. Error
B. 3
C. 1
D. 83
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

163. If lst = [4, 6, 8, 7, 7], what is lst[-3]?
A. 4
B. Error
C. 8
D. 75
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

164. What is 'Python'.upper()?
A. 'Python'
B. 'PYTHON'
C. Error
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

165. What is the output of: False or False?
A. True
B. False
C. Error

D. None
Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

166. What is the output of: True and False?
A. Error
B. None
C. True
D. False
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

167. What is 'Data'.lower()?
A. None
B. Error
C. 'data'
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

168. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 6
C. 1
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

169. What is the output of: False and False?
A. True
B. False
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

170. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

171. If lst = [3, 2, 7, 7, 6], what is lst[-5]?
A. 3
B. 6
C. Error
D. 92

Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

172. If lst = [1, 5, 2, 2, 8], what is lst[-1]?
A. 1
B. Error
C. 54
D. 8
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

173. What is 'Data'.lower()?
A. 'data'
B. None
C. Error
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

174. What is 5 != 2?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

175. What is the output of 24 // 6?
A. Error
B. 4
C. 4.0
D. 5
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

176. What is 'Coding'.lower()?
A. None
B. Error
C. 'coding'
D. 'Coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

177. If lst = [8, 5, 2, 3, 2], what is lst[-3]?
A. Error
B. 8
C. 2
D. 2
Correct Answer: 2

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

178. What is 'Python'.lower()?

A. Error

B. 'python'

C. 'Python'

D. None

Correct Answer: 'python'

Reasoning: The lower() method changes the casing of the string.

179. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6

B. 3

C. 1

D. Error

Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

180. If lst = [9, 8, 4, 3, 1], what is lst[-3]?

A. 1

B. Error

C. 4

D. 9

Correct Answer: 4

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

181. What is 'Coding'.lower()?

A. 'Coding'

B. Error

C. 'coding'

D. None

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

182. If lst = [1, 9, 7, 7, 1], what is lst[-5]?

A. 1

B. Error

C. 1

D. 70

Correct Answer: 1

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

183. If lst = [3, 2, 2, 2, 7], what is lst[-2]?

A. 7

B. Error

C. 3

D. 2

Correct Answer: 2

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

184. What is 'Data'.lower()?
A. 'Data'
B. None
C. 'data'
D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
185. What is 5 > 2?
A. Error
B. None
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.
186. What is 'Python'.upper()?
A. None
B. 'PYTHON'
C. Error
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.
187. What is 'Coding'.lower()?
A. None
B. 'Coding'
C. 'coding'
D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.
188. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. Error
C. 6
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
189. What is 'Data'.lower()?
A. 'Data'
B. Error
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
190. What is 1 < 3?

A. Error
B. True
C. None
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

191. What is the output of 15 // 5?
A. 3.0
B. 3
C. Error
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

192. What is the output of: True and True?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates standard logical 'and' operation.

193. If lst = [3, 4, 3, 3, 9], what is lst[-4]?
A. 4
B. 3
C. Error
D. 29
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

194. What is 'Python'.lower()?
A. None
B. 'python'
C. Error
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

195. What is the output of: False or True?
A. Error
B. True
C. None
D. False
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

196. What is 'Data'.lower()?
A. 'Data'

B. Error
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

197. What is 1 < 3?
A. None
B. True
C. False
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

198. What is 'Coding'.upper()?
A. 'CODING'
B. None
C. 'Coding'
D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

199. What is 4 == 4?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

200. What is 5 == 5?
A. False
B. None
C. True
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

201. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

202. What is 5 != 2?
A. False
B. None

C. True
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

203. If lst = [1, 9, 3, 3, 5], what is lst[-4]?
A. 1
B. Error
C. 5
D. 9
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

204. If lst = [4, 6, 8, 7, 7], what is lst[-2]?
A. 7
B. Error
C. 4
D. 18
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

205. If lst = [1, 5, 2, 2, 8], what is lst[-5]?
A. Error
B. 8
C. 1
D. 83
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

206. If lst = [5, 4, 3, 5, 8], what is lst[-3]?
A. Error
B. 8
C. 3
D. 5
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

207. What is the output of 15 // 5?
A. 3.0
B. 3
C. Error
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

208. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 6
C. 3

D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

209. What is 'Data'.upper()?
A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

210. What is the output of 15 % 5?
A. 0
B. 15
C. Error
D. 3
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

211. What is the output of: True and False?
A. Error
B. False
C. None
D. True
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

212. What is 5 == 1?
A. False
B. None
C. Error
D. True
Correct Answer: False
Reasoning: Evaluates the comparison operator.

213. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 6
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

214. What is 'Data'.upper()?
A. Error
B. 'Data'
C. None
D. 'DATA'

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

215. What is 1 == 3?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

216. What is 'Python'.upper()?
A. Error
B. 'PYTHON'
C. 'Python'
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

217. If lst = [1, 9, 3, 2, 2], what is lst[-1]?
A. Error
B. 1
C. 2
D. 83
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

218. What is 'Python'.upper()?
A. Error
B. 'Python'
C. 'PYTHON'
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

219. What is the output of: False or True?
A. False
B. None
C. Error
D. True
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

220. What is 'Coding'.lower()?
A. 'Coding'
B. Error
C. None
D. 'coding'
Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

221. What is the output of: False or True?

A. None
B. Error
C. False
D. True

Correct Answer: True

Reasoning: Evaluates standard logical 'or' operation.

222. What is 5 == 5?

A. True
B. False
C. None
D. Error

Correct Answer: True

Reasoning: Evaluates the comparison operator.

223. What is the output of 15 // 5?

A. 3.0
B. 3
C. 4
D. Error

Correct Answer: 3

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

224. If lst = [1, 5, 2, 2, 8], what is lst[-3]?

A. 1
B. 2
C. 8
D. Error

Correct Answer: 2

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

225. What is 'Coding'.lower()?

A. None
B. 'Coding'
C. Error
D. 'coding'

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

226. What is 'Coding'.lower()?

A. Error
B. None
C. 'coding'
D. 'Coding'

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

227. What is 'Data'.lower()?
A. None
B. Error
C. 'Data'
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
228. What is 'Coding'.lower()?
A. 'coding'
B. Error
C. 'Coding'
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.
229. If lst = [1, 8, 4, 3, 9], what is lst[-2]?
A. 1
B. 3
C. Error
D. 9
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
230. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 3
C. Error
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
231. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 6
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
232. What is 2 == 5?
A. Error
B. False
C. None
D. True
Correct Answer: False
Reasoning: Evaluates the comparison operator.
233. What is the output of 15 % 5?

A. 0
B. Error
C. 3
D. 15
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

234. What is 'Data'.lower()?
A. Error
B. 'data'
C. 'Data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

235. What is the output of 24 // 6?
A. 4
B. 5
C. Error
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

236. What is the output of 20 // 4?
A. 5.0
B. 6
C. 5
D. Error
Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

237. What is the output of 21 // 5?
A. 4
B. 5
C. Error
D. 4.2
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

238. If lst = [3, 2, 7, 7, 6], what is lst[-1]?
A. 6
B. 3
C. Error
D. 83
Correct Answer: 6
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

239. What is 'Data'.lower()?
A. 'data'

B. None
C. 'Data'
D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

240. What is 'Coding'.upper()?
A. 'CODING'
B. Error
C. None
D. 'Coding'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

241. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 6
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

242. What is the output of 16 // 5?
A. 3.2
B. 4
C. Error
D. 3
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

243. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 1
C. 3
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

244. If lst = [5, 4, 3, 5, 8], what is lst[-1]?
A. Error
B. 8
C. 5
D. 68
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

245. What is the output of 16 // 5?
A. Error
B. 3

C. 3.2
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

246. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 1
C. 3
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

247. What is 5 == 5?
A. Error
B. True
C. False
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

248. What is 'Python'.lower()?
A. 'python'
B. Error
C. 'Python'
D. None
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

249. If lst = [1, 9, 7, 7, 1], what is lst[-2]?
A. 1
B. Error
C. 7
D. 18
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

250. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 3
C. 1
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

251. What is 'Coding'.lower()?
A. 'coding'
B. Error
C. None

D. 'Coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

252. What is 5 == 5?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

253. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 1
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

254. What is 'Data'.upper()?
A. 'DATA'
B. Error
C. None
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

255. What is 'Data'.lower()?
A. 'data'
B. None
C. Error
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

256. What is 2 == 5?
A. None
B. False
C. Error
D. True
Correct Answer: False
Reasoning: Evaluates the comparison operator.

257. What is 'Coding'.lower()?
A. Error
B. 'coding'
C. 'Coding'
D. None

Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

258. What is 5 == 1?
A. False
B. True
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

259. What is 'Python'.lower()?
A. None
B. 'Python'
C. Error
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

260. What is 2 == 4?
A. False
B. True
C. None
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

261. What is the output of 24 % 4?
A. 6
B. 0
C. 24
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

262. If lst = [3, 2, 7, 7, 7], what is lst[-1]?
A. 3
B. 7
C. Error
D. 44
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

263. What is the output of 15 // 5?
A. 4
B. 3.0
C. Error
D. 3
Correct Answer: 3

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

264. What is 'Python'.lower()?

A. None

B. Error

C. 'python'

D. 'Python'

Correct Answer: 'python'

Reasoning: The lower() method changes the casing of the string.

265. What is 'Data'.upper()?

A. 'DATA'

B. None

C. Error

D. 'Data'

Correct Answer: 'DATA'

Reasoning: The upper() method changes the casing of the string.

266. If lst = [5, 4, 1, 5, 4], what is lst[-5]?

A. Error

B. 5

C. 81

D. 4

Correct Answer: 5

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

267. What is the output of 24 // 6?

A. 5

B. 4

C. Error

D. 4.0

Correct Answer: 4

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

268. If lst = [1, 9, 3, 2, 7], what is lst[-3]?

A. 7

B. Error

C. 1

D. 3

Correct Answer: 3

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

269. What is 'Python'.upper()?

A. 'Python'

B. Error

C. None

D. 'PYTHON'

Correct Answer: 'PYTHON'

Reasoning: The upper() method changes the casing of the string.

270. What is the output of: True or True?
A. False
B. None
C. Error
D. True
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.
271. What is the output of 15 // 5?
A. 4
B. 3.0
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
272. What is the output of 15 // 5?
A. Error
B. 3
C. 4
D. 3.0
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
273. What is 5 != 2?
A. False
B. Error
C. True
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.
274. What is the output of 17 // 3?
A. Error
B. 6
C. 5
D. 5.666666666666667
Correct Answer: 5
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
275. What is 'Python'.upper()?
A. 'PYTHON'
B. None
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.
276. What is 'Data'.upper()?

A. Error
B. None
C. 'DATA'
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

277. What is the output of 15 % 5?
A. 15
B. 3
C. Error
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

278. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. Error
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

279. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 1
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

280. What is 4 == 4?
A. Error
B. True
C. None
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

281. If lst = [9, 8, 4, 3, 1], what is lst[-5]?
A. Error
B. 1
C. 15
D. 9
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

282. What is the output of 16 % 5?
A. 3

B. 16
C. 1
D. Error
Correct Answer: 1
Reasoning: The modulo operator (%) returns the remainder of the division.

283. What is 1 < 4?
A. Error
B. True
C. False
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

284. What is 4 < 1?
A. Error
B. True
C. None
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

285. What is 'Data'.upper()?
A. Error
B. 'DATA'
C. 'Data'
D. None
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

286. What is 4 < 1?
A. False
B. None
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

287. What is 'Python'.lower()?
A. Error
B. None
C. 'Python'
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

288. What is the output of: False or False?
A. None
B. Error

C. True
D. False
Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

289. What is 'Coding'.upper()?
A. Error
B. None
C. 'Coding'
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

290. If lst = [1, 9, 3, 3, 5], what is lst[-2]?
A. 5
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

291. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 6
C. 1
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

292. If lst = [9, 8, 4, 4, 2], what is lst[-1]?
A. 9
B. 2
C. Error
D. 81
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

293. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 1
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

294. What is 'Data'.lower()?
A. 'Data'
B. None
C. 'data'

D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

295. What is 'Python'.lower()?
A. 'python'
B. Error
C. None
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

296. What is the output of: False and False?
A. Error
B. True
C. None
D. False
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

297. If lst = [1, 5, 2, 2, 9], what is lst[-2]?
A. 2
B. 1
C. 9
D. Error
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

298. If lst = [9, 7, 7, 8, 9], what is lst[-5]?
A. 9
B. 10
C. Error
D. 9
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

299. What is 'Python'.lower()?
A. None
B. 'python'
C. Error
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

300. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. Error
D. 1

Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

301. What is the output of: False or False?
A. Error
B. None
C. True
D. False
Correct Answer: False
Reasoning: Evaluates standard logical 'or' operation.

302. What is 5 != 2?
A. True
B. False
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

303. If lst = [3, 9, 9, 5, 3], what is lst[-1]?
A. Error
B. 3
C. 96
D. 3
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

304. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 1
C. 3
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

305. What is the output of: False and False?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.

306. What is 'Data'.lower()?
A. Error
B. 'data'
C. None
D. 'Data'
Correct Answer: 'data'

Reasoning: The lower() method changes the casing of the string.

307. What is 'Python'.lower()?

A. 'Python'

B. Error

C. None

D. 'python'

Correct Answer: 'python'

Reasoning: The lower() method changes the casing of the string.

308. What is the output of 15 // 5?

A. 4

B. 3.0

C. 3

D. Error

Correct Answer: 3

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

309. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. Error

B. 6

C. 1

D. 3

Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

310. What is 5 == 1?

A. True

B. False

C. None

D. Error

Correct Answer: False

Reasoning: Evaluates the comparison operator.

311. What is 5 != 2?

A. True

B. Error

C. False

D. None

Correct Answer: True

Reasoning: Evaluates the comparison operator.

312. If lst = [1, 9, 3, 2, 2], what is lst[-4]?

A. 1

B. 9

C. Error

D. 2

Correct Answer: 9

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

313. What is the output of: False or True?
A. Error
B. True
C. None
D. False
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.
314. What is 'Python'.upper()?
A. 'PYTHON'
B. None
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.
315. What is 5 > 2?
A. True
B. None
C. False
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.
316. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 3
C. 1
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
317. What is 'Coding'.upper()?
A. 'CODING'
B. Error
C. 'Coding'
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.
318. If lst = [1, 8, 4, 3, 9], what is lst[-1]?
A. 9
B. 1
C. Error
D. 92
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
319. What is 'Data'.upper()?

A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

320. What is 2 == 5?
A. None
B. Error
C. False
D. True
Correct Answer: False
Reasoning: Evaluates the comparison operator.

321. What is 5 > 1?
A. False
B. True
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

322. If lst = [3, 2, 7, 7, 6], what is lst[-2]?
A. 6
B. Error
C. 3
D. 7
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

323. What is 4 < 2?
A. None
B. False
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

324. What is 3 < 3?
A. True
B. None
C. Error
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

325. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error

B. 3
C. 6
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

326. What is 'Data'.lower()?
A. Error
B. None
C. 'data'
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

327. If lst = [3, 4, 3, 3, 9], what is lst[-3]?
A. 9
B. 3
C. Error
D. 44
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

328. What is 'Coding'.lower()?
A. Error
B. 'coding'
C. None
D. 'Coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

329. If lst = [5, 4, 1, 5, 4], what is lst[-3]?
A. 5
B. 1
C. Error
D. 4
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

330. What is the output of 15 % 5?
A. Error
B. 3
C. 15
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

331. What is 5 == 1?
A. None
B. True

C. False
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

332. What is 5 == 1?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

333. If lst = [1, 2, 2, 4, 3], what is lst[-4]?
A. Error
B. 2
C. 1
D. 3
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

334. If lst = [9, 8, 4, 4, 2], what is lst[-5]?
A. 84
B. 9
C. Error
D. 2
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

335. What is 5 > 2?
A. None
B. Error
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

336. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 3
C. 6
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

337. What is 'Data'.lower()?
A. Error
B. 'data'
C. None

D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

338. What is the output of 15 // 5?
A. 4
B. 3
C. 3.0
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

339. If lst = [5, 4, 1, 5, 4], what is lst[-2]?
A. 5
B. 4
C. Error
D. 1
Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

340. What is 2 == 5?
A. False
B. None
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

341. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

342. What is the output of 15 // 5?
A. 4
B. Error
C. 3.0
D. 3
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

343. What is 5 > 1?
A. False
B. None
C. True
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

344. If lst = [9, 8, 4, 3, 1], what is lst[-4]?
A. Error
B. 1
C. 9
D. 8
Correct Answer: 8
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

345. What is the output of 24 // 6?
A. 5
B. Error
C. 4
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

346. What is 'Data'.lower()?
A. Error
B. 'Data'
C. None
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

347. If lst = [2, 1, 1, 8, 3], what is lst[-4]?
A. 3
B. 1
C. Error
D. 2
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

348. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 1
C. 3
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

349. If lst = [8, 5, 2, 3, 2], what is lst[-1]?
A. Error
B. 2
C. 8
D. 92
Correct Answer: 2

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

350. What is 4 == 4?

A. Error
B. None
C. False
D. True

Correct Answer: True

Reasoning: Evaluates the comparison operator.

351. What is the output of: True and False?

A. False
B. None
C. Error
D. True

Correct Answer: False

Reasoning: Evaluates standard logical 'and' operation.

352. What is 5 != 2?

A. False
B. True
C. Error
D. None

Correct Answer: True

Reasoning: Evaluates the comparison operator.

353. What is 'Data'.upper()?

A. Error
B. None
C. 'DATA'
D. 'Data'

Correct Answer: 'DATA'

Reasoning: The upper() method changes the casing of the string.

354. What is 'Coding'.lower()?

A. 'coding'
B. Error
C. 'Coding'
D. None

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

355. What is the output of 15 % 5?

A. 3
B. 0
C. 15
D. Error

Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

356. What is 'Python'.lower()?
A. Error
B. 'Python'
C. 'python'
D. None
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.
357. What is 'Python'.upper()?
A. None
B. 'PYTHON'
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.
358. What is the output of 15 // 5?
A. 3
B. 4
C. 3.0
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
359. What is 'Data'.upper()?
A. Error
B. 'Data'
C. None
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.
360. What is the output of 15 % 5?
A. 3
B. Error
C. 0
D. 15
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.
361. What is 4 == 4?
A. False
B. True
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.
362. If lst = [3, 2, 7, 7, 7], what is lst[-1]?

A. 7
B. Error
C. 42
D. 3
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

363. What is 'Data'.lower()?
A. Error
B. 'Data'
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

364. What is the output of 24 // 6?
A. 5
B. 4
C. Error
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

365. If lst = [9, 8, 4, 3, 1], what is lst[-2]?
A. 1
B. Error
C. 3
D. 9
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

366. What is 5 != 2?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

367. What is 'Coding'.lower()?
A. Error
B. 'Coding'
C. 'coding'
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

368. What is 'Coding'.upper()?
A. Error

B. 'CODING'
C. 'Coding'
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

369. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 3
C. 1
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

370. What is 5 == 5?
A. None
B. Error
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.

371. What is 'Data'.upper()?
A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

372. What is 5 > 2?
A. True
B. False
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

373. What is 4 == 4?
A. False
B. True
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

374. What is 'Coding'.upper()?
A. 'CODING'
B. 'Coding'

C. None
D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

375. If lst = [1, 9, 3, 2, 7], what is lst[-2]?
A. Error
B. 2
C. 7
D. 1
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

376. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. Error
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

377. If lst = [1, 9, 7, 7, 1], what is lst[-1]?
A. 1
B. 7
C. Error
D. 52
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

378. What is 'Python'.lower()?
A. 'Python'
B. Error
C. None
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

379. What is 'Python'.upper()?
A. 'Python'
B. 'PYTHON'
C. Error
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

380. What is 'Python'.lower()?
A. 'python'
B. None
C. 'Python'

D. Error
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

381. What is 'Data'.lower()?
A. 'Data'
B. None
C. Error
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

382. What is 'Python'.upper()?
A. None
B. 'PYTHON'
C. Error
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

383. What is the output of 15 // 5?
A. Error
B. 3.0
C. 3
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

384. What is 'Data'.upper()?
A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

385. If lst = [2, 1, 1, 8, 3], what is lst[-3]?
A. Error
B. 1
C. 2
D. 3
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

386. What is 5 == 5?
A. True
B. False
C. None
D. Error

Correct Answer: True
Reasoning: Evaluates the comparison operator.

387. If lst = [3, 4, 3, 3, 9], what is lst[-5]?
A. Error
B. 9
C. 3
D. 40
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

388. What is 'Data'.upper()?
A. None
B. Error
C. 'Data'
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

389. What is 'Data'.lower()?
A. None
B. 'Data'
C. Error
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

390. What is 'Python'.upper()?
A. 'PYTHON'
B. None
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

391. What is 'Coding'.lower()?
A. 'coding'
B. None
C. 'Coding'
D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

392. What is the output of: False or True?
A. True
B. False
C. None
D. Error
Correct Answer: True

Reasoning: Evaluates standard logical 'or' operation.

393. What is 'Python'.upper()?

A. Error

B. None

C. 'Python'

D. 'PYTHON'

Correct Answer: 'PYTHON'

Reasoning: The upper() method changes the casing of the string.

394. If lst = [5, 4, 3, 6, 4], what is lst[-1]?

A. 4

B. 5

C. Error

D. 18

Correct Answer: 4

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

395. What is the output of: False and False?

A. Error

B. True

C. None

D. False

Correct Answer: False

Reasoning: Evaluates standard logical 'and' operation.

396. What is the output of 24 // 6?

A. 4.0

B. 5

C. 4

D. Error

Correct Answer: 4

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

397. If lst = [1, 9, 3, 2, 7], what is lst[-5]?

A. 7

B. Error

C. 1

D. 14

Correct Answer: 1

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

398. What is 'Data'.upper()?

A. Error

B. 'DATA'

C. None

D. 'Data'

Correct Answer: 'DATA'

Reasoning: The upper() method changes the casing of the string.

399. What is 'Data'.upper()?
A. Error
B. None
C. 'Data'
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.
400. What is 5 == 1?
A. True
B. False
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.
401. What is the output of 15 % 5?
A. 0
B. 3
C. 15
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.
402. What is 5 != 2?
A. None
B. Error
C. True
D. False
Correct Answer: True
Reasoning: Evaluates the comparison operator.
403. What is 'Data'.lower()?
A. 'data'
B. None
C. Error
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
404. What is 'Coding'.lower()?
A. None
B. 'coding'
C. 'Coding'
D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.
405. What is 5 == 5?

A. True
B. None
C. False
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

406. What is 'Data'.lower()?
A. 'Data'
B. Error
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

407. What is 'Coding'.upper()?
A. Error
B. 'Coding'
C. None
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

408. What is the output of 15 // 5?
A. 3.0
B. 4
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

409. What is 'Python'.lower()?
A. 'python'
B. 'Python'
C. Error
D. None
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

410. What is 5 == 5?
A. Error
B. False
C. None
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

411. What is the output of 24 // 6?
A. Error

B. 5
C. 4
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

412. What is 'Python'.upper()?
A. 'Python'
B. 'PYTHON'
C. Error
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

413. What is the output of 15 // 5?
A. 3
B. 3.0
C. 4
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

414. What is 'Coding'.upper()?
A. 'CODING'
B. 'Coding'
C. Error
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

415. What is the output of 24 % 6?
A. Error
B. 0
C. 4
D. 24
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

416. What is 1 < 3?
A. False
B. True
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

417. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 6

C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

418. If lst = [1, 9, 3, 2, 7], what is lst[-1]?
A. 1
B. 7
C. Error
D. 20
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

419. What is 'Python'.upper()?
A. 'PYTHON'
B. None
C. Error
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

420. What is 5 == 1?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

421. What is the output of 15 // 5?
A. 4
B. Error
C. 3
D. 3.0
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

422. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

423. What is 'Coding'.lower()?
A. 'coding'
B. Error
C. 'Coding'

D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

424. What is the output of 15 // 5?
A. 3
B. Error
C. 4
D. 3.0
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

425. What is 5 == 1?
A. Error
B. True
C. False
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

426. What is 'Python'.upper()?
A. Error
B. None
C. 'PYTHON'
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

427. What is 'Python'.lower()?
A. 'python'
B. Error
C. None
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

428. What is the output of: False or True?
A. Error
B. None
C. True
D. False
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

429. What is 4 < 2?
A. False
B. True
C. Error
D. None

Correct Answer: False
Reasoning: Evaluates the comparison operator.

430. What is 4 < 2?
A. False
B. True
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

431. What is the output of 15 % 5?
A. Error
B. 15
C. 0
D. 3
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

432. What is 'Data'.lower()?
A. 'Data'
B. None
C. 'data'
D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

433. If lst = [3, 2, 7, 7, 7], what is lst[-5]?
A. 7
B. Error
C. 3
D. 83
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

434. What is 'Python'.upper()?
A. 'Python'
B. Error
C. 'PYTHON'
D. None
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

435. What is the output of 24 % 6?
A. Error
B. 4
C. 24
D. 0
Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

436. What is 'Coding'.lower()?

A. 'Coding'

B. Error

C. 'coding'

D. None

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

437. What is 5 == 1?

A. False

B. True

C. None

D. Error

Correct Answer: False

Reasoning: Evaluates the comparison operator.

438. If lst = [3, 9, 9, 5, 3], what is lst[-5]?

A. 3

B. 82

C. Error

D. 9

Correct Answer: 3

Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

439. What is the output of 15 % 5?

A. 3

B. 0

C. 15

D. Error

Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

440. What is 'Python'.upper()?

A. None

B. Error

C. 'Python'

D. 'PYTHON'

Correct Answer: 'PYTHON'

Reasoning: The upper() method changes the casing of the string.

441. What is 'Coding'.lower()?

A. 'Coding'

B. None

C. 'coding'

D. Error

Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

442. What is 1 == 3?
A. False
B. Error
C. True
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.
443. What is 5 > 2?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.
444. What is the output of 24 // 6?
A. 4.0
B. 5
C. Error
D. 4
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.
445. What is the output of: True or True?
A. Error
B. None
C. True
D. False
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.
446. What is 2 == 4?
A. False
B. True
C. None
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.
447. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
448. What is 5 == 1?

A. None
B. Error
C. False
D. True
Correct Answer: False
Reasoning: Evaluates the comparison operator.

449. If lst = [3, 2, 7, 7, 7], what is lst[-4]?
A. 3
B. 7
C. 2
D. Error
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

450. What is 'Python'.upper()?
A. 'PYTHON'
B. None
C. Error
D. 'Python'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

451. If lst = [4, 6, 8, 7, 7], what is lst[-5]?
A. Error
B. 7
C. 4
D. 45
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

452. What is 4 == 4?
A. Error
B. None
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

453. If lst = [3, 2, 7, 7, 6], what is lst[-2]?
A. 7
B. 3
C. Error
D. 6
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

454. What is 'Coding'.upper()?
A. 'CODING'

B. Error
C. 'Coding'
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

455. What is 1 < 3?
A. None
B. False
C. Error
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

456. What is the output of 15 % 5?
A. 15
B. 0
C. 3
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

457. What is 'Data'.lower()?
A. Error
B. None
C. 'Data'
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

458. What is the output of 15 // 5?
A. 3
B. 4
C. Error
D. 3.0
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

459. What is 'Data'.lower()?
A. None
B. Error
C. 'Data'
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

460. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 1

C. Error
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

461. If lst = [3, 2, 7, 7, 7], what is lst[-2]?
A. 7
B. Error
C. 3
D. 66
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

462. What is the output of 15 // 5?
A. Error
B. 3
C. 3.0
D. 4
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

463. What is the output of 15 % 5?
A. 0
B. Error
C. 3
D. 15
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

464. If lst = [1, 5, 2, 2, 9], what is lst[-5]?
A. Error
B. 1
C. 9
D. 56
Correct Answer: 1
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

465. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. Error
C. 6
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

466. What is 'Data'.lower()?
A. 'Data'
B. None
C. 'data'

D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

467. What is 'Python'.lower()?
A. 'python'
B. 'Python'
C. Error
D. None
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

468. If lst = [1, 9, 7, 7, 1], what is lst[-4]?
A. Error
B. 1
C. 9
D. 15
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

469. What is 'Data'.lower()?
A. 'data'
B. Error
C. 'Data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

470. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. Error
C. 3
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

471. What is 'Data'.upper()?
A. 'Data'
B. 'DATA'
C. None
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

472. What is 5 != 2?
A. True
B. False
C. Error
D. None

Correct Answer: True
Reasoning: Evaluates the comparison operator.

473. If lst = [1, 9, 3, 2, 7], what is lst[-1]?
A. Error
B. 1
C. 7
D. 19
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

474. What is 'Data'.upper()?
A. Error
B. 'Data'
C. None
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

475. If lst = [8, 5, 2, 3, 4], what is lst[-1]?
A. 4
B. Error
C. 8
D. 76
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

476. What is 'Coding'.upper()?
A. None
B. Error
C. 'CODING'
D. 'Coding'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

477. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 3
C. 1
D. Error
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

478. What is the output of 15 % 5?
A. Error
B. 3
C. 15
D. 0
Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

479. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6

B. 3

C. 1

D. Error

Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

480. What is the output of 15 // 5?

A. Error

B. 3.0

C. 4

D. 3

Correct Answer: 3

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

481. What is the output of 24 % 6?

A. 0

B. 24

C. Error

D. 4

Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

482. What is 5 != 2?

A. True

B. False

C. Error

D. None

Correct Answer: True

Reasoning: Evaluates the comparison operator.

483. What is 5 == 1?

A. Error

B. False

C. True

D. None

Correct Answer: False

Reasoning: Evaluates the comparison operator.

484. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 1

B. Error

C. 3

D. 6

Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

485. If lst = [3, 4, 3, 3, 9], what is lst[-2]?
A. Error
B. 3
C. 9
D. 44
Correct Answer: 3
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
486. What is 'Data'.upper()?
A. Error
B. 'DATA'
C. None
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.
487. What is 'Coding'.lower()?
A. 'Coding'
B. None
C. Error
D. 'coding'
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.
488. If lst = [5, 4, 1, 5, 4], what is lst[-1]?
A. 4
B. Error
C. 5
D. 70
Correct Answer: 4
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
489. What is 'Data'.lower()?
A. Error
B. 'Data'
C. None
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.
490. What is 5 > 2?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.
491. What is the output of 24 // 6?

A. 4.0
B. Error
C. 5
D. 4
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

492. What is 'Data'.lower()?
A. 'data'
B. None
C. 'Data'
D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

493. What is 4 == 4?
A. False
B. Error
C. None
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

494. If lst = [3, 2, 2, 2, 7], what is lst[-4]?
A. 7
B. 3
C. 2
D. Error
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

495. What is the output of 15 // 5?
A. 3
B. 4
C. Error
D. 3.0
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

496. What is 'Data'.lower()?
A. None
B. 'data'
C. 'Data'
D. Error
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

497. What is the output of: False or True?
A. None

B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

498. What is 'Coding'.upper()?
A. None
B. 'Coding'
C. Error
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

499. What is 'Coding'.upper()?
A. 'Coding'
B. Error
C. 'CODING'
D. None
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

500. What is 'Data'.lower()?
A. Error
B. None
C. 'data'
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

501. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. Error
C. 3
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

502. What is 'Python'.upper()?
A. 'Python'
B. None
C. Error
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

503. What is 5 == 1?
A. Error
B. True

C. False
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

504. What is 'Python'.lower()?
A. 'python'
B. Error
C. None
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

505. What is 4 == 4?
A. False
B. Error
C. True
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

506. If lst = [3, 2, 7, 7, 6], what is lst[-4]?
A. 3
B. 6
C. Error
D. 2
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

507. If lst = [9, 7, 7, 8, 9], what is lst[-4]?
A. Error
B. 7
C. 9
D. 65
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

508. What is 'Python'.upper()?
A. 'Python'
B. None
C. Error
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

509. What is 'Python'.lower()?
A. None
B. Error
C. 'Python'

D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

510. What is 'Coding'.lower()?
A. 'coding'
B. Error
C. 'Coding'
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

511. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. Error
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

512. What is 'Data'.lower()?
A. Error
B. None
C. 'data'
D. 'Data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

513. What is 'Coding'.lower()?
A. 'coding'
B. 'Coding'
C. Error
D. None
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

514. What is 5 == 5?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

515. What is 'Data'.upper()?
A. None
B. 'Data'
C. 'DATA'
D. Error

Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

516. What is 'Python'.upper()?
A. 'Python'
B. 'PYTHON'
C. None
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

517. What is the output of 15 // 5?
A. 4
B. 3.0
C. 3
D. Error
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

518. What is the output of 24 // 6?
A. 4
B. Error
C. 5
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

519. What is 5 == 1?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

520. What is 4 == 4?
A. None
B. False
C. True
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

521. What is the output of: False or True?
A. None
B. False
C. True
D. Error
Correct Answer: True

Reasoning: Evaluates standard logical 'or' operation.

522. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. Error
B. 1
C. 6
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

523. What is 'Data'.upper()?
A. Error
B. None
C. 'Data'
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

524. What is 5 > 2?
A. Error
B. False
C. None
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

525. What is 5 > 2?
A. Error
B. None
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

526. What is 'Data'.upper()?
A. None
B. 'DATA'
C. Error
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

527. What is 'Python'.lower()?
A. Error
B. 'python'
C. None
D. 'Python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

528. What is 'Coding'.lower()?
A. 'coding'
B. None
C. 'Coding'
D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.
529. What is 4 < 1?
A. None
B. Error
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.
530. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 6
C. Error
D. 1
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
531. What is the output of: False and False?
A. None
B. False
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates standard logical 'and' operation.
532. What is 5 != 2?
A. False
B. True
C. Error
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.
533. What is 'Python'.upper()?
A. None
B. 'PYTHON'
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.
534. What is 'Data'.upper()?

A. None
B. 'Data'
C. Error
D. 'DATA'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

535. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 6
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

536. If lst = [1, 5, 2, 2, 8], what is lst[-4]?
A. Error
B. 1
C. 5
D. 8
Correct Answer: 5
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

537. What is 'Data'.upper()?
A. 'DATA'
B. Error
C. 'Data'
D. None
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

538. What is the output of 15 // 5?
A. Error
B. 3.0
C. 4
D. 3
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

539. If lst = [3, 2, 7, 7, 7], what is lst[-3]?
A. 7
B. Error
C. 3
D. 92
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

540. What is 'Data'.lower()?
A. 'Data'

B. Error
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

541. What is 'Data'.upper()?
A. Error
B. None
C. 'DATA'
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

542. What is 4 == 4?
A. False
B. None
C. Error
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

543. What is the output of 24 // 6?
A. 4
B. Error
C. 4.0
D. 5
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

544. What is the output of: False or True?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

545. What is the output of 24 // 6?
A. 5
B. 4
C. Error
D. 4.0
Correct Answer: 4
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

546. What is 'Data'.upper()?
A. Error
B. 'DATA'

C. None
D. 'Data'
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

547. What is 'Python'.lower()?
A. 'Python'
B. Error
C. None
D. 'python'
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.

548. What is 'Python'.upper()?
A. None
B. 'PYTHON'
C. 'Python'
D. Error
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

549. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 6
B. 1
C. Error
D. 3
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

550. If lst = [3, 9, 9, 5, 3], what is lst[-3]?
A. 3
B. 9
C. Error
D. 56
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

551. What is 1 < 3?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

552. What is 'Coding'.upper()?
A. 'CODING'
B. 'Coding'
C. None

D. Error
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

553. What is 5 == 1?
A. False
B. None
C. True
D. Error
Correct Answer: False
Reasoning: Evaluates the comparison operator.

554. What is the output of 15 // 5?
A. 4
B. Error
C. 3.0
D. 3
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

555. What is the output of 24 % 6?
A. 24
B. 4
C. Error
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

556. What is the output of 15 % 5?
A. Error
B. 0
C. 15
D. 3
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

557. What is 5 == 5?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

558. What is 'Python'.upper()?
A. 'Python'
B. Error
C. 'PYTHON'
D. None

Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

559. What is the output of 15 % 5?
A. 15
B. 3
C. Error
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

560. If lst = [1, 5, 2, 2, 8], what is lst[-2]?
A. Error
B. 1
C. 2
D. 8
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

561. What is 4 == 4?
A. False
B. True
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

562. If lst = [9, 7, 7, 8, 9], what is lst[-3]?
A. 7
B. Error
C. 9
D. 24
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

563. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 1
C. Error
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

564. What is 'Coding'.lower()?
A. 'coding'
B. None
C. 'Coding'
D. Error
Correct Answer: 'coding'

Reasoning: The lower() method changes the casing of the string.

565. What is the output of: False or True?

A. False

B. Error

C. None

D. True

Correct Answer: True

Reasoning: Evaluates standard logical 'or' operation.

566. What is the result of len(set([1, 2, 2, 3, 3, 3]))?

A. 6

B. 3

C. Error

D. 1

Correct Answer: 3

Reasoning: Converting a list to a set removes all duplicate elements.

567. What is 'Data'.lower()?

A. None

B. 'Data'

C. Error

D. 'data'

Correct Answer: 'data'

Reasoning: The lower() method changes the casing of the string.

568. What is 'Data'.upper()?

A. Error

B. 'Data'

C. None

D. 'DATA'

Correct Answer: 'DATA'

Reasoning: The upper() method changes the casing of the string.

569. What is the output of 15 % 5?

A. Error

B. 15

C. 0

D. 3

Correct Answer: 0

Reasoning: The modulo operator (%) returns the remainder of the division.

570. What is the output of 15 // 5?

A. 4

B. 3.0

C. 3

D. Error

Correct Answer: 3

Reasoning: Floor division (//) divides and rounds down to the nearest integer.

571. If lst = [1, 5, 2, 2, 9], what is lst[-3]?
A. 2
B. 9
C. Error
D. 1
Correct Answer: 2
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.
572. What is 1 < 3?
A. False
B. Error
C. None
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.
573. What is 'Python'.lower()?
A. 'python'
B. 'Python'
C. None
D. Error
Correct Answer: 'python'
Reasoning: The lower() method changes the casing of the string.
574. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 1
B. 3
C. Error
D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.
575. What is 'Data'.upper()?
A. 'DATA'
B. None
C. 'Data'
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.
576. What is 5 == 1?
A. Error
B. True
C. False
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.
577. If lst = [1, 9, 7, 7, 1], what is lst[-3]?

A. 1
B. Error
C. 7
D. 41
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

578. What is 1 < 3?
A. None
B. Error
C. False
D. True
Correct Answer: True
Reasoning: Evaluates the comparison operator.

579. What is 'Python'.upper()?
A. Error
B. 'Python'
C. None
D. 'PYTHON'
Correct Answer: 'PYTHON'
Reasoning: The upper() method changes the casing of the string.

580. What is 2 == 5?
A. Error
B. None
C. True
D. False
Correct Answer: False
Reasoning: Evaluates the comparison operator.

581. What is 'Coding'.upper()?
A. None
B. 'Coding'
C. Error
D. 'CODING'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

582. What is 4 == 4?
A. False
B. True
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates the comparison operator.

583. What is 5 != 2?
A. Error

B. False
C. True
D. None
Correct Answer: True
Reasoning: Evaluates the comparison operator.

584. What is 'Data'.lower()?
A. 'Data'
B. Error
C. 'data'
D. None
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

585. What is the output of 15 // 5?
A. 4
B. 3.0
C. Error
D. 3
Correct Answer: 3
Reasoning: Floor division (//) divides and rounds down to the nearest integer.

586. What is 'Data'.upper()?
A. 'DATA'
B. Error
C. 'Data'
D. None
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

587. If lst = [3, 2, 7, 7, 6], what is lst[-3]?
A. 6
B. 3
C. Error
D. 7
Correct Answer: 7
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

588. What is 'Coding'.lower()?
A. 'Coding'
B. None
C. 'coding'
D. Error
Correct Answer: 'coding'
Reasoning: The lower() method changes the casing of the string.

589. What is the output of 15 % 5?
A. 15
B. 3

C. 0
D. Error
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

590. What is the output of: False or True?
A. True
B. False
C. None
D. Error
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

591. What is 'Data'.lower()?
A. Error
B. 'Data'
C. None
D. 'data'
Correct Answer: 'data'
Reasoning: The lower() method changes the casing of the string.

592. What is the output of: False or True?
A. Error
B. False
C. True
D. None
Correct Answer: True
Reasoning: Evaluates standard logical 'or' operation.

593. If lst = [9, 8, 4, 3, 1], what is lst[-5]?
A. 1
B. 9
C. 33
D. Error
Correct Answer: 9
Reasoning: Negative indexing starts from the end of the list, where -1 is the last element.

594. What is 5 == 1?
A. False
B. True
C. Error
D. None
Correct Answer: False
Reasoning: Evaluates the comparison operator.

595. What is the result of len(set([1, 2, 2, 3, 3, 3]))?
A. 3
B. 1
C. Error

D. 6
Correct Answer: 3
Reasoning: Converting a list to a set removes all duplicate elements.

596. What is the output of 15 % 5?
A. Error
B. 15
C. 3
D. 0
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.

597. What is 'Data'.upper()?
A. 'DATA'
B. 'Data'
C. None
D. Error
Correct Answer: 'DATA'
Reasoning: The upper() method changes the casing of the string.

598. What is 'Coding'.upper()?
A. 'CODING'
B. Error
C. None
D. 'Coding'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

599. What is 'Coding'.upper()?
A. 'CODING'
B. None
C. Error
D. 'Coding'
Correct Answer: 'CODING'
Reasoning: The upper() method changes the casing of the string.

600. What is the output of 15 % 5?
A. Error
B. 0
C. 3
D. 15
Correct Answer: 0
Reasoning: The modulo operator (%) returns the remainder of the division.