

OBJECTIVES:

Upon completion of these exercises the student will be able to:

- Become familiar with the key features of the Alarm Handling Window and their functionality
- Associate and create Trouble Ticket Reports
- Design and apply a top level filter
- Become familiar with the key features of the Iconic Map and their functionality
- Utilize the on-line documentation

Table of Contents

Topic	Page
INTRODUCTION.....	3
ALARM HANDLING	3-4
ASSOCIATING NS-T TO RESOLUTION	4
TOP LEVEL ALARM FILTERING	4-5
THE ICONIC MAP	5
ON-LINE DOCUMENTATION	5-6
SCENARIO 1	6-7
SCENARIO 2	7-8
SCENARIO 3	8-9

ALARM SURVEILLANCE

These exercises require the student to use the 3 buttons on the mouse, the functionality is as follows:

- MB1 (left button): used to Select and Cut objects
- MB2 (middle button): used to Move and Paste objects
- MB3 (right button): used to open pop-up menus.

Instructions to start TeMIP here...

ALARM HANDLING

1. If the real time Alarm Handling window is not active, click MB1 on the **7th** accelerator icon in the Iconic Map. Alternatively, open the **Applications** menu and select **TeMIP Alarm Handling**

The real time Alarm Handling window is divided into several parts:

- The upper right box lists the OCs that has **Alarm Display** enabled. It also displays a total number of alarms for each OC.
- The upper left box lists the total number of alarms by severity (OC independent).
- The bottom box lists the alarms in real time, color-coded by the severity of the alarm report.

2. List the different alarm states that are visible.
-

3. Select one of the OCs listed in the upper right box and click MB1, then select the **View Alarms** tab. This will enable the display of all alarms, which have been collected since the creation of the OC. You may need to click on **Apply** to activate this function.

4. Select an alarm and click on the **Full Information** button. A window appears displaying all information about the alarm, including status attributes. These attributes store all the management operations performed by the operator.
5. Select an alarm and click on the **Acknowledge button**. The state of the alarm changes to Acknowledge and the outstanding icon (light bulb) changes to an acknowledged icon (rubber stamp) on the alarm line.

Can you describe another possible path to acknowledging an alarm?

6. Select an alarm and click on the **Terminate** button. The state of the alarm changes to Terminated and the alarm disappears from the real time window. The alarm is still stored in TeMIP and can be viewed in the View Alarms window.
7. Sort the alarm columns by clicking on the column heading to display a sort order icon. Click again to toggle between ascending and descending sort order.

ASSOCIATING NS-T TO RESOLUTION

1. Follow the action points 1-4 from the student text (pages 21-22) to create a Trouble Ticket Report.
2. Follow the action points 1-6 from the student text (pages 23-24) to associate a Trouble Ticket Report to an actual alarm.

TOP LEVEL ALARM FILTERING

In the middle part of the real time alarm handling window is the **Filter** button. Click on the **Filter** button and a window appears where you can choose criteria to change the way that alarms are displayed. Your filter mask can be named and saved. Take a look to see if any predefined filters exist.

1. Create a filter of your own. Enter some filter criteria and click on the **Save** button. Enter a filter name and click on **OK**. Now you can re-use your filter.

THE ICONIC MAP

1. Start the Iconic Map by typing the UNIX command `mcc_iconic_map&`
2. Take some time to become familiar with the Iconic Map icons, for more detailed information read the relevant section in the student text book.
3. Navigate through the Domains:

To view a sub-domain, double click on the `xxxx` icon in the Map Window.

To go back to the top domain, click on the **Look Up/Look Back**, or **Go to Top** accelerator icons.

To view the domain tree, click on the **Display Tree View** icon located in the lower left corner of the map. This will display the current domain and all of its nested domains.

4. Click MB1 on an alarming object in the map window. Then click on the 6th accelerator button (**Search**) in the toolbar. This takes you to the Alarm Handling Window and you can see the alarms that are associated with that alarming object.

ON-LINE DOCUMENTATION

1. From the **Help** menu, select **Context-Sensitive Help**. Move the mouse to the map and click somewhere on the map (not over an icon). Notice that the Compaq TeMIP Iconic Map and FCL User's Manual appears open at the Map Window section.
2. Select **Context-Sensitive Help** again, this time move the mouse over an Operation Context icon. Notice that the Compaq TeMIP Alarm Handling User's Manual appears open to the Alarm Handling section.

Using the context sensitive help, it is possible to link to your equipment documentation. When a user clicks on the **Context-Sensitive Help** menu option and clicks on an **Exchange** icon for example, the HTML documentation for that exchange will be displayed.

The **Help** menu also provides access to the **Index**, **Contents** and **Overview** section of the manual.

SCENARIOS

These scenarios let you use the skills you have acquired in the previous exercises.

Your role in all the scenarios is one of several surveillance technicians (first line maintenance).

Scenario 1

Scenario 1 has 4 alarms:

<i>Perceived Severity</i>	<i>Event Type</i>	<i>Probable Cause</i>	<i>Managed Object</i>	<i>Event Time</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>?</i>	<i>x</i>
<i>Major</i>	<i>Equipment Alarm</i>	<i>?</i>	<i>?</i>	<i>y</i>
<i>Major</i>	<i>Equipment Alarm</i>	<i>?</i>	<i>?</i>	<i>z</i>
<i>Warning</i>	<i>Communication Alarm</i>	<i>?</i>	<i>?</i>	<i>X</i>

In this scenario you are to prioritize incoming alarms.

- 1) Ask the instructor to send the scenario 1 alarms to your OC.
- 2) Wait for the set of alarms to appear in the alarm list.
- 3) Prioritize the alarms. If needed using one or more of the methods you have learned: sorting, filtering, alarm details.
- 4) Select the alarm you intend to start working by acknowledging it.
Acknowledged Alarm?
Why?

What you learned: Priority based on perceived severity.

Terminate all alarms in preparation for the next scenario.

Scenario 2

Scenario 2 has 5 alarms:

<i>Perceived Severity</i>	<i>Event Type</i>	<i>Probable Cause</i>	<i>Managed Object</i>	<i>Event Time</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>Small_town_RBS</i>	<i>X</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>Big_City_RBS</i>	<i>Y</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>Medium_town_RBS</i>	<i>X</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>Village_RBS</i>	<i>X</i>
<i>Critical</i>	<i>Communication Alarm</i>	<i>Loss of signal</i>	<i>Farm_RBS</i>	<i>X</i>

In this scenario you are to prioritize incoming alarms.

- 1 Ask the instructor to send the scenario 2 alarms to your OC.
- 2 Wait for the set of alarms to appear in the alarm list.
- 5) Prioritise the alarms. If needed using one or more of the methods you have learned: sorting, filtering, alarm details.
- 6) Select the alarm you intend to start working by acknowledging it.
Acknowledged Alarm?
Why?

What you learned: Priority based on managed object importance.

Terminate all alarms in preparation for the next scenario.

Scenario 3

Scenario 1 has 4 alarms:

Perceived Severity	Event Type	Probable Cause	Managed Object	Event Time
Critical	Communication Alarm	Loss of signal	Big_City_RBS	Y
Major	Equipment Alarm	?	Port1 on Board N	X
Major	Equipment Alarm	?	Board 1	X+1
Minor			Minilink	Z
Minor			Minilink	z
Warning	Communication Alarm	?	Service ? carried by board 1	X+2

In this scenario you are to prioritize incoming alarms. select alarms to escalate, to ignore and to work with..

- 1) Ask the instructor to send the scenario 1 alarms to your OC.
- 2) Wait for the set of alarms to appear in the alarm list.
- 3) Prioritise the alarms. If needed using one or more of the methods you have learned: sorting, filtering, alarm details.
- 4) Select the alarm you intend to start working by acknowledging it.
Acknowledged Alarm?
Why?

- 5) There are some alarms that are caused by to limited radio resources. Escalate them to "Radio Optimising Group"
Which alarms did you select?
- 6) Escalate them to "Radio Optimising Group" in one of 2 ways.
If Resolution is used:
 - A.1 Select the alarms to escalate in the alarm window.
 - A.2 In work space menu, click on "Create TT".
 - A.3 Fill in needed fields.
 - A.4 Assign to "Radio Optimising Group"If no Resolution:
 - B1. Create e-mail.
 - B2. Manually enter enough information to make the alarms identifiable.
 - B3. Find out which radio optimiser is on duty.
 - B4. Send the email to that person.
 - B5. Acknowledge alarms
 - B6 Add operators note to each alarm describing that it has been escalated and to whom.

What you learned: Groping and escalating alarms.

Terminate all alarms in preparation for the next scenario.