AI ADOPTION IN RIDE-HAILING INDUSTRY: EV FLEET OPERATION OPTIMIZATION

An Analytical Study on the Impact of AI Integration on Electric Vehicle Profitability and Total Cost of Ownership



Arab Academy for Science & Technology

Submitted To : Dr. Ahmed Elseddawy
Create By : Mohamed Tarek Ragab
Student ID : 23227320

Executive Summary

Context

The global transition to Electric Vehicle (EV) fleets in ride-hailing requires advanced operational frameworks to manage complex charging and routing constraints.

Problem

Traditional reactive dispatching leads to high Total Cost of Ownership (TCO), excessive 'dead distance,' and sub-optimal energy utilization.

Solution

Integration of Artificial Intelligence of Things (AIoT) utilizing a centralized-decentralized Deep Reinforcement Learning (RL) architecture for dynamic routing.

Impact

Demonstrated reduction in operational expenditure (OPEX) and up to an 18.12% savings in overarching societal costs compared to greedy algorithms.

Artificial Intelligence of Things (AIoT)

IoT Sensor Networks

Embedded devices continuously capture real-time telemetry (battery voltage, thermal fluctuations, spatial coordinates).

AI Computational Models

Advanced machine learning ingests this continuous data stream.

The Result: Shifting from reactive, manual processes to a dynamic, autonomous ecosystem capable of translating raw vehicular data into immediate, profitable action.

Methodology | General Decision-Making Framework

Stage 1: Intelligence

- **Action:** Discover and identify organizational problems.
- **Method:** Data analytics on large EV Fleet datasets to uncover hidden patterns.

Stage 2: Design

- **Action:** Invent and explore potential solutions.
- **Method:** Comprehensive academic and industry literature review on AI adoption in EV fleets.

Stage 3: Choice

- **Action:** Select specific course of action.
- **Method:** Recommend solution maximizing impact while aligning with strategic capabilities.

Stage 4: Implementation

- **Action:** Execute alternative and monitor performance.
- **Method:** Digital transformation and seamless integration with existing ERP platforms.


Reality
Simplification
Assumptions
Intelligence Phase
Organization objectives
Search and scanning procedures
Data collection
Problem identification
Problem ownership
Problem classification
Problem statement
Problem Statement
Design Phase
Formulate a model
Set criteria for choice
Search for alternatives
Predict and measure outcomes
Validation of the model
Alternatives
Choice Phase
Solution to the model
Sensitivity analysis
Selection to best (good)
alternativee(s)
Plan for implementation
Verification, testing of
proposed solution
Solution
Implementation
of solution
SUCCESS
FAILURE

RIDE-HAILING MARKET: ACCELERATING GROWTH & STRATEGIC SHIFTS

2023
Market Size
$158.3 Billion

2032
Projected Market Size
>$480 Billion
(13.2% CAGR)

The 1:1 Swap Fallacy

A direct 1:1 swap of ICE vehicles to EVs only yields a 3% operational savings. However, intelligently replanned, AI-managed EV systems unlock 8%-13% lower Total Cost of Ownership (TCO).

MOBILITY BUSINESS MODEL MATRIX

Hybrid S+A-P model maximizes coverage but amplifies dispatch complexity.

Pure Self-Operated (PSP)	**Self-Operated + Aggregation Platform (S+A-P)**
Pure Aggregation (PAP)	**Super App**



Managing 57 EVs of varying OEMs introduces severe logistical constraints: variable charging downtimes, unpredictable energy management, and chronic range anxiety among dispatchers.

Market Dynamics and Ride-Hailing Business Models

Global Market Expansion: $158.3 Billion (2023) projected to exceed **$480 Billion** (2032).

Business Model	Fleet Ownership	Dispatch Control	Capacity Scaling Mechanism
Pure Self-Operated Platform (PSP)	Independent Drivers	Centralized Platform	Organic driver acquisition
Pure Aggregation Platform (PAP)	No Fleet Owned	Aggregation Layer	Commission from local companies
Self-Operated + Aggregation (S+A-P)	Platform Owned	Hybrid	Own fleet + third-party aggregation
Super App Models	Mixed	Centralized Platform	Integration with cross-vertical services

The subsequent operational analysis targets an S+A-P organization operating a mixed-OEM fleet of 57 Electric Vehicles.

Business Problem Identification | EV Fleet Pain Points

Peak Demand Charging

- Poorly planned charging routes incur peak electricity rates.
- Directly inflates the Total Cost of Ownership (TCO).

Range Anxiety & Refusal

- Limited range compared to gas-powered vehicles.
- Real-time dispatch requests rejected due to insufficient energy for detour + return to charger.

Total Cost of Ownership (TCO)

Dead Distance (Empty Miles)

- Miles driven without a passenger to reach pickup points or charging stations.
- Impacted heavily by traffic, weather, and cargo loads.

Dynamic Vehicle Routing Problem (VRP)

- The operational optimization framework is failing under the complexity of simultaneous routing and dispatch scheduling.

System Design: Traditional Heuristics vs. AIoT Integration

	Traditional Dispatch	AIoT / RL Dispatch
Data Processing	Manual, reactive, historical.	Continuous, real-time telemetry (voltage, thermals, spatial).
Routing Model	Static, model-based optimization.	Dynamic Vehicle Routing Problem (VRP) adaptation; live variable integration.
Energy Management	Unplanned, peak-hour reliance.	Predictive charging schedules maximizing off-peak rates.
Maintenance	Reactive to mechanical failure.	Predictive diagnostics via Random Forest, XGBoost, and LSTM networks.

Quantitative Analytical Methodology

Data Sources: Real-time structured data from a cloud platform integrated with IoT telematics across 57 EVs (augmented by 18-month Kaggle datasets comprising 2,499 rides).



1. Obtain Data

IoT sensors, Telemetry, Cloud APIs

2. Clean and Model

Exploratory Data Analysis (EDA) techniques

3. Visualize and Interpret

Statistical mapping (correlation vs. causation)

4. Insight to Action

Evidence-based operational shifts

5. Iterative Refinement

Continuous model accuracy enhancement

Dataset Overview | Kaggle Data Architecture

Dataset 1: Electric Mobility Ride Transactions

- Duration: 18 Months (Jan 2023 - July 2024).
- Volume: 2,499 real-time completed rides.
- Features: User behavior, driver performance, fare details, and operational metrics.

Dataset 2: EV Analytics (Synthetic)

- Scope: Comprehensive EV performance and battery health.
- Features: Charging behavior, cost analytics across manufacturers, regions, and usage types.

Data Integration: Structured real-time data collected via IoT telematics installed across the 57-vehicle fleet.

Empirical Data: Service Inefficiencies & Driver Proximity

Pickup Responsiveness



Insight: 17.65% of riders experienced waiting times exceeding the industry benchmark of 15 minutes.

Cancellations vs. Distance



Insight: A strong positive correlation exists between maximum ride acceptance distance and trip cancellations, particularly during peak evening hours.

Empirical Data: The Cost of "Dead Distance"



25% Dead Energy

- **Finding:** Approximately 25% of the fleet's total energy consumption is expended on non-revenue-generating operations.
- **Implication:** Nearly a quarter of stored electrical energy is consumed before passenger pickup. This highlights critical inefficiencies in vehicle-to-passenger spatial matching, severely impacting overall TCO and carbon mitigation goals.

AI Methodology: Deep Reinforcement Learning

Core Concept: A computational approach where an 'agent' learns optimal decision-making by interacting with an environment to maximize cumulative rewards.

Algorithm Type: Off-policy learning utilizing neural networks to approximate value functions, overcoming the 'curse of dimensionality' inherent in complex EV routing.

Objective: Formulate dispatching as a linear assignment problem within a Markov Decision Process (MDP) to dynamically map states to optimal actions.



The Centralized-Decentralized RL Architecture

Advantage: Experience replay and target networks ensure training stability while executing highly efficient, real-time fleet coordination.



Reinforcement Learning Engine: Centralized-Decentralized System



Through off-policy reinforcement learning, individual vehicles learn from the environment and feed data to a central brain, which instantly fires back fleet-wide optimized dispatch decisions—all without human intervention.

Implementation Results & Benchmark Performance

18.12%

Reduction in overall societal costs compared to traditional greedy algorithms.

3.20%

Cost savings compared to advanced optimization-based models.

Operational Impact: The RL algorithm efficiently learns optimal EV dispatch strategies, significantly mitigating passenger waiting times and minimizing total operational expenditure (OPEX).

Strategic Implications and Synthesis

Dynamic Adaptability

Unlike static routing, AI-integrated systems seamlessly re-optimize routes in real-time as customer trip requests emerge, effectively solving the dynamic VRP.

Constraint Management

Neural network approximations effectively manage strict EV constraints, enabling intelligent partial recharges rather than binary full-charge/empty operational states.

Sustainability & OPEX

Shifting from a simple 1:1 vehicle replacement to intelligent, data-driven orchestration is mandatory to maximize the Total Cost of Ownership (TCO) advantages of electric mobility.

Electric Vehicles Fleet Management AIOT Platform



References

[1] "IOT-ENABLED FLEET MANAGEMENT AND ITS INFLUENCE ON COST REDUCTION AND PROFITABILITY," Int. J. Progress. Res. Eng. Manag. Sci., Feb. 2026.

[2] M. Bahheti, V. K. Shankarnarayan, S. Durairajan... "AI-Powered Predictive Maintenance for Electric Vehicle Fleets," in 2024 Asian Conference on Intelligent Technologies, 2024.

[5] U. R. F. Averweg, 'Decision-making support systems: Theory & practice'.

[6] J. Shi, Y. Gao, W. Wang, N. Yu, and P. A. Ioannou, 'Operating Electric Vehicle Fleet for Ride-Hailing Services With Reinforcement Learning," IEEE Trans. Intell. Transp. Syst., 2020.

[11] M. Aldossary, 'Enhancing Urban Electric Vehicle (EV) Fleet Management Efficiency in Smart Cities: A Predictive Hybrid Deep Learning Framework," Smart Cities, 2024.

[12] Z. Yi and J. Smart, "A framework for integrated dispatching and charging management of an autonomous electric vehicle ride-hailing fleet," Transp. Res. Part Transp. Environ., 2021.

[13] "Electric Mobility Dataset." Kaggle.