Unit 3 Assignemnt- Interrogating The Data.sql
main

Files

- Unit 3 Assignemnt- Interrogating The Data.sc
- x603-rental-marketplace-database ~/Deskt
  - analysis
    - uni2.md
    - unit1.md
    - unit3-finding.md
  - queries
    - unit3
      - q3_1.sql [ex603_data_rental]
      - q3_2.sql [ex603_data_rental]
      - q3_3.sql [ex603_data_rental]
    - unit4
    - unit5
    - unit6
  - schema

ssignemnt- Interrogating The Data.sql [ex603_data_rental] | q3_2.sql [ex603_data_rental] | unit3-finding.md | q3_3.sql [ex603_data_rental]

Tx: Auto | Playground | ex603_rental.public | ex603_data_rental

```
50  so it returns what you intended.
51   */
52  -- Original query count: 22
53  SELECT COUNT(*) AS not_renter_no_show   370 ms
54  FROM viewings
55  WHERE no_show_reason != 'Renter no show';
56
57  -- Show the Totals: 200
58  SELECT COUNT(*) AS total_viewings   341 ms
59  FROM viewings;
60  -- No Show Reason NULL: 166
61  SELECT COUNT(*)   352 ms
62  FROM viewings
63  WHERE no_show_reason IS NULL;
64
65  -- the problem renter no show + null = 22 + 166 = 188.
```

Services

Database
- ex603_data_rental
  - q3_3.sql 424 ms
  - Unit 3 Assignemnt- Interrogating The D
  - q3_1.sql 350 ms
  - q3_2.sql 352 ms

Output | not_renter_no_show:bigint | Show the Totals: 200 | No Show Reason NULL: 166

CSV

	count
1	166

1 row

x603-rental-marketplace-database > queries > unit3 > q3_2.sql

63:30 (255 chars, 10 line breaks) LF

Files

- Unit 3 Assignemnt- Interrogating The Data.sc
- x603-rental-marketplace-database ~/Deskt
  - analysis
    - uni2.md
    - unit1.md
    - unit3-finding.md
  - queries
    - unit3
      - q3_1.sql [ex603_data_rental]
      - q3_2.sql [ex603_data_rental]
      - q3_3.sql [ex603_data_rental]
    - unit4
    - unit5
    - unit6
  - schema

ssignemnt- Interrogating The Data.sql [ex603_data_rental] | q3_2.sql [ex603_data_rental] | unit3-finding.md | q3_3.sql [ex603_data_rental]

Tx: Auto | Playground | ex603_rental.public | ex603_data_rental

```
50  so it returns what you intended.
51   */
52  -- Original query count: 22
53  SELECT COUNT(*) AS not_renter_no_show   370 ms
54  FROM viewings
55  WHERE no_show_reason != 'Renter no show';
56
57  -- Show the Totals: 200
58  SELECT COUNT(*) AS total_viewings   341 ms
59  FROM viewings;
60  -- No Show Reason NULL: 166
61  SELECT COUNT(*)   352 ms
62  FROM viewings
63  WHERE no_show_reason IS NULL;
64
65  -- the problem renter no show + null = 22 + 166 = 188.
```

Services

- Database
  - ex603_data_rental
    - q3_3.sql 424 ms
    - Unit 3 Assignemnt- Interrogating The D
    - q3_1.sql 350 ms
    - q3_2.sql 352 ms

Output | not_renter_no_show:bigint | Show the Totals: 200 | No Show Reason NULL: 166

CSV

	total_viewings
1	200

1 row

Files
Unit 3 Assignemnt- Interrogating The Data.sc
x603-rental-marketplace-database ~/Deskt
analysis
uni2.md
unit1.md
unit3-finding.md
queries
unit3
q3_1.sql [ex603_data_rental]
q3_2.sql [ex603_data_rental]
q3_3.sql [ex603_data_rental]
unit4
unit5
unit6
schema

ssignemnt- Interrogating The Data.sql [ex603_data_rental]
q3_2.sql [ex603_data_rental]
unit3-finding.md
q3_3.sql [ex603_data_rental]

Tx: Auto | Playground | ex603_rental.public | ex603_data_rental

```
so it returns what you intended.
 */
-- Original query count: 22
SELECT COUNT(*) AS not_renter_no_show   370 ms
FROM viewings
WHERE no_show_reason != 'Renter no show';

-- Show the Totals: 200
SELECT COUNT(*) AS total_viewings   341 ms
FROM viewings;
-- No Show Reason NULL: 166
SELECT COUNT(*)   352 ms
FROM viewings
WHERE no_show_reason IS NULL;

-- the problem renter no show + null = 22 + 166 = 188.
```

Services

Database
ex603_data_rental
q3_3.sql 424 ms
Unit 3 Assignemnt- Interrogating The D
q3_1.sql 350 ms
q3_2.sql 352 ms

Output | not_renter_no_show:bigint | Show the Totals: 200 | No Show Reason NULL: 166

CSV

	not_renter_no_show
1	22

1 row