

Document number: D0032R1
Date: 2015–10-31
Project: Programming Language C++, Library Evolution Working
 Group
Reply-to: Vicente J. Botet Escriba <vicente.botet@wanadoo.fr>

Homogeneous interface for variant, any and optional (Draft Revision 1)

This paper is the 1st revision of [P0032R0] taking in account the feedback from Kona meeting.

This paper identifies some differences in the design of `variant<Ts...>`, `any` and `optional<T>`, diagnoses them as owing to unnecessary asymmetry between those classes, and proposes wording to eliminate the asymmetry.

Contents

History.....	2
Revision 1.....	2
Introduction.....	3
Motivation and Scope.....	3
Proposal.....	4
Design rationale.....	5
in_place constructor.....	5
Differences between the new in_place_t and the old one.....	6
emplace forward member function.....	7
About empty()/explicit operator bool() member functions.....	7
About clear()/reset() member functions.....	8
About a not-a-value any: none.....	8
Do we need an explicit make_any factory?.....	8
About emplace factories.....	9
Which file for in_place_t and in_place?.....	10
Access interface.....	10
Open points.....	10
Technical Specification.....	10
General utilities library	10
Optional objects.....	11
Class any	11
Acknowledgements.....	14
References.....	14
Appendix.....	14

History

Revision 1

The 1st revision of [P0032R0] takes in account the feedback from Kona meeting. Next follow the direction of the committee: globally keep the consensual part and extract the conflicting and less polished part.

- Do we want to adopt the new `in_place` definition?

It is clear that we want a different name for the `emplace` function and the tag, however it is not clear the committee wants the `in_place` function reference. Nevertheless, the author don't know how to have the `in_place` both for optional, any and variant without using function references, so this paper preserve this design.

Leave optional different from variant and any	6
Member function is <code>emplace</code>; tag type is <code>in_place</code>	13
Both are <code>emplace</code>	6

Do we want to adopt the new `in_place` definition?

SF	F	N	A	SA
1	3	8	0	0

- Do we want in place constructor for any? Unanimous Yes.
- Do we want the `clear` and `reset` changes? Yes

How to empty an any or optional?

<code>.reset()</code>	12
<code>.clear()</code>	7
<code>=none</code> (different paper)	7
<code>={} </code>	5
<code>.drain()</code>	1

- Do we want the operator `bool` changes? No, instead a `.something()` member function (e.g. `has_value`) is preferred for the 3 classes. This doesn't mean yet that we replace the existing explicit operator `bool` in optional.

Do we want emptiness checking to be consistent between any/optional?
Unanimous yes

Provide operator <code>bool</code> for both	Y: 6 N: 5
Provide <code>.something()</code>	Y: 17 N: 0
Provide <code>=={}</code>	Y: 0 N: 5
Provide <code>==std::none</code>	Y: 5 N: 2
<code>something(any/optional)</code>	Y: 3 N: 8

- Do we want the *not-a-value* `none`? No, too much unit types. The committee wants a separated paper for a generic `none_t/none`, `none_tc_t<TC>/none<TC>`.

Do we want `none_t` to be a separate paper?

SF	F	N	A	SA
11	1	3	0	0

- Do we want the `make_any` factory? Yes

S F F N A SA
1 9 7 2 0

- Do we want to have a follow up for a concept based on the functions `holds` and `storage_address_of`? Not in this paper.
- Do we want to have a follow up for `select<T>/select<I>?` Not in this paper. Considered as invention
- Do we want to have a follow up for the observers `reference_of`, `value_of` and `address_of`? Not in this paper.

We have improved the wording and in particular added some missing overloads using `initializer_list`.

We have added a comparative table on the appendix also.

Introduction

This paper identifies some differences in the design of `variant<Ts...>`, `any` and `optional<T>`, diagnoses them as owing to unnecessary asymmetry between those classes, and proposes wording to eliminate the asymmetry.

The identified issues are related to the last Fundamental TS proposal [N4480] and the variant proposal [N4542] and concerns mainly:

- coherency of functions that behave the same but that are named differently,
- replace the `in_place` tag by a function with overloads for type and index,
- replacement of `emplace_type<T>/emplace_index<I>` by `in_place<T>/in_place<I>`
- addition of `emplace` factories for `any` and `optional` classes.

Motivation and Scope

Both `optional` and `any` are classes that can store possibly some underlying type. In the case of `optional` the underlying type is known at compile time, for `any` the underlying type is known at run-time.

If the variant proposal ends by having nullable variant, the stored type would be any of the `Ts` or a *not-a-value* type, known at run-time. Let me refer to this possible variant of `nullable_variant<Ts...>`.

The following inconsistencies have been identified:

- `variant<Ts...>` and `optional` provides in place construction with different syntax while `any` requires a specific instance.
- `variant<Ts...>` and `optional` provides `emplace` assignment while `any` requires a specific instance to be assigned.
- The in place tags for `variant<Ts...>` and `optional` are different. However the name

should be the same. Any doesn't provides in place construction and assignment yet.

- `any` provides `any::clear()` to unset the value while `optional` uses assignment from a `nullopt_t` or from `{}`. This paper doesn't contains any proposal to improve this situation. A separated paper would include a generic `none_t/none` proposal.
- `optional` provides a `explicit bool` conversion while `any` provides an `any::empty` member function.
- `optional<T>`, `variant<Ts...>` and `any` provides different interfaces to get the stored value. `optional` uses a `value` member function and pointer-like functions, `variant` uses a tuple like interface, while `any` uses a cast like interface. As all these classes are in someway classes that can possibly store a specific type, the first two limited and know at compile time, the last unlimited, it seems natural that all provide the same kind of interface. This paper doesn't contains any proposal to improve this situation. A separated paper would include a generic `none_t/none` proposal.

The C++ standard should be coherent for features that behave the same way on different types. Instead of creating specific issues, we have preferred to write a specific paper so that we can discuss of the whole view.

Proposal

We propose to:

- Replace `in_place_t/in_place` by an overloaded function (see [eggs-variant]).
- In class `optional<T>`
 - Add a `reset` member function.
 - Add a `has_value` member function.
- Add an additional overload for `make_optional` factory to `emplace` construct.
- In class `any`
 - make the default constructor `constexpr`,
 - add `in_place` forward constructors,
 - add `emplace` forward member functions,
 - rename the `empty` function with `has_value` and make it `constexpr`,
 - rename the `clear` member function to `reset`,
- Add a `make_any` factory to `emplace` construct.
- In class `variant<T>`
 - Replace the uses of `emplace_type_t<T>/emplace_index_t<I>` by `in_place_t<T>/in_place_t<I>`
 - Replace the uses of `emplace_type<T>/emplace_index<I>` by `in_place<T>/in_place<I>`.

Design rationale

in_place constructor

optional<T> in place constructor constructs implicitly a T.

```
template <class... Args>
constexpr explicit optional<T>::optional(in_place_t, Args&&... args);
```

In place construct for any can not have an implicit type T. We need a way to state explicitly which T must be constructed in place.

```
struct in_place_tag {};
template <class T>
using in_place_type_t = in_place_tag(&)(unspecified<T>);
template <class T>
in_place_tag in_place(unspecified<T>) { return {} };
```

The function in_place_tag(&)(unspecified<T>) is used to transport the type T participating in overload resolution.

```
template <class T, class ...Args>
any(in_place_type_t<T>), , Args&& ...);
```

This can be used as

```
any(in_place<X>, v1, ..., vn);
```

Adopting this template class to optional would needs to change the definition of in_place_t/in_place to

```
using in_place_t = in_place_tag(&)(unspecified);
in_place_tag in_place(unspecified) { return {} };
```

The same applies to variant. We need an additional overload for in_place

```
template <int I>
using in_place_index_t = in_place_tag(&)(unspecified<I>);
template <int I>
in_place_tag in_place(unspecified<I>) { return {} };
```

Given

```
struct Foo { Foo(int, double, char); };
```

Before:

```
optional<Foo> of(in_place, 0, 1.5, 'c');
variant<int, Foo> vf(emplace_type<Foo>, 0, 1.5, 'c');
variant<int, Foo> vf(emplace_index<1>, 0, 1.5, 'c');
any af(Foo(0, 1.5, 'c')); // (*)
```

After:

```
optional<Foo> of(in_place, 0, 1.5, 'c');
variant<int, Foo> vf(in_place<Foo>, 0, 1.5, 'c');
variant<int, Foo> vf(in_place<1>, 0, 1.5, 'c');
```

```
any af(in_place<Foo>, 0, 1.5, 'c');
```

Note that before any didn't support non-copyable-non-moveable objects like `std::mutex`. With `in_place` we are able to store a `mutex` in.

Differences between the new `in_place_t` and the old one

Cost of function reference versus tags

The proposed function reference for `in_place_t(&)` (unspecified) takes the size of an address while the previous `in_place_t` struct tag was empty and so its size is 1. We don't think this would reduce significantly the performances and believe that it can even perform better, however some measure would be done if there is an interest.

Possible malicious attacks

Unfortunately using function references would work for any unary function taken the unspecified type and returning `in_place_tag` in addition to `in_place`. Of course defining such a function would imply to hack the unspecified type. This can be seen as a hole on this proposal, but the authors think that it is better to have a uniform interface than protecting from malicious attacks from a hacker.

No default constructible

While adapting `optional<T>` to the new `in_place_t` type we found that we can not anymore use `in_place_t{}`. The authors don't consider this a big limitation as the user can use `in_place` instead.

It needs to be noted that this is in line with the behavior of `nullopt_t` as `nullopt_t{}` fails as no default constructible. However `nullptr_t{}` seems to be well formed.

Not assignable from `{}`

After a deeper analysis we found also that the old `in_place_t` supported

```
in_place_t t = {};
```

The authors don't consider this a big limitation as we don't expect that a lot of users could use this and the user can use `in_place` instead.

```
in_place_t t = in_place;
```

It needs to be noted that this is in line with the behavior of `nullopt_t` as the following compile fails.

```
nullopt_t t = {}; // compile fails
```

However `nullptr_t` seems to be support it.

```
nullptr_t t = {}; // compile pass
```

emplace forward member function

`optional<T>` `emplace` member function emplaces implicitly a `T`.

```
template <class ...Args>
optional<T>::emplace (Args&& ...);
```

`emplace` for `any` can not have an implicit type `T`. We need a way to state explicitly which `T` must be emplaced.

```
template <class T, class ...Args>
any::emplace (Args&& ...);
```

and used as follows

```
any af;
optional<Foo> of;
variant<int, Foo> vf;
af.emplace<Foo>(v1, ..., vn);
of.emplace<Foo>(v1, ..., vn);
vf.emplace<Foo>(v1, ..., vn);
```

About `empty()`/`explicit operator bool()` member functions

`empty` is more associated with containers. We don't see neither `any` nor `optional` as container classes. For probably valued types (as are the smart pointers and `optional`) the standard uses `explicit operator bool` conversion instead.

We consider `any` as a probably valued type. If `nullable_variant` ends modeling a probably valued type both should provide the `explicit operator bool`.

Given

```
struct Foo { Foo(int, double, char); };
unique_ptr<Foo> pf=...
optional<Foo> of=...;
any af=...;
```

Before:

```
if (pf) ...
if (of) ...
if ( ! af.empty()) ...
```

After:

```
if (pf) ...
if (of) ...
if (af) ...
```

A lot of people consider that the `explicit operator bool` conversion is not explicit enough. An alternative to `explicit operator bool()` is to use a member function `has_value` (or `holds`).

After:

```
if (pf.has_value()) ...
if (of.has_value()) ...
if (af.has_value()) ...
```

The `has_value` member function is retained as more explicit and easy to read. As this proposal is not about any change in pointe-like classes we lost uniform syntax respect to pointe-like classes.

After:

```
if (pf) ...
if (of.has_value()) ...
if (af.has_value()) ...
```

Having a uniform interface for pointe-like, type-erased and sum type classes would be the subject of another proposal. This is because this is not the single function for which the interfaces are not uniform.

About `clear()` / `reset()` member functions

`clear()` is more associated to containers. We don't see neither `any` nor `optional` as container classes. For probably valued types (as are the smart pointers) the standard uses `reset` instead.

Given

```
struct Foo { Foo(int, double, char); };
unique_ptr<Foo> pf=...;
optional<Foo> of=...;
any af=...;
```

Before:

```
pf.reset();
of = nullopt;
af.clear();
```

After:

```
pf.reset();
of.reset();
af.reset();
```

About a *not-a-value* any: none

The original proposal contained a `none_t/none` for `any`. It has been considered that we have too much unit types and that another paper should take care of a more generic `none` separately.

Do we need an explicit `make_any` factory?

`any` is not a generic type but a type erased type. `any` play the same role than a possible `make_any`.

This paper however propose a `make_any` factory for the `emplace` case, see below.

Note also that if [N4471] is adopted we wouldn't need any more `make_optional`, as e.g.

`optional(1)` would be deduced as `optional<int>`.

About emplace factories

However, we could consider a `make_xxx` factory that in place constructs a `T`.

`optional<T>` and `any` could be in place constructed as follows:

```
optional<T> opt(in_place, v1, vn);
f(optional<T>(in_place, v1, vn));

any a(in_place<T>, v1, vn);
f(any(in_place<T>, v1, vn));
```

When we use `auto` things change a little bit

```
auto opt = optional<T>(in_place, v1, vn);
auto a = any(in_place<T>, v1, vn);
```

This is almost uniform. However having an `make_xxx` factory function would make the code even more uniform

```
auto opt = make_optional<T>(v1, vn);
f(make_optional<T>(v1, vn));

auto a = make_any<T>(v1, vn);
f(make_any<T>(v1, vn));
```

The implementation of these emplace factories could be:

```
template <class T, class ...Args>
optional<T> make_optional(Args&& ...args) {
    return optional(in_place, std::forward<Args>(args)...);
}

template <class T, class ...Args>
any make_any(Args&& ...args) {
    return any(in_place<T>, std::forward<Args>(args)...);
}
```

Given

```
struct Foo { Foo(int, double, char); };
```

Before:

```
auto up = make_unique<Foo>(v1, ..., vn)
auto sp = make_shared<Foo>(v1, ..., vn)
auto o = optional<Foo>(in_place, v1, ..., vn)
auto a = any(Foo{v1, ..., vn})
```

After:

```
auto up = make_unique<Foo>(v1, ..., vn)
auto sp = make_shared<Foo>(v1, ..., vn)
auto o = make_optional<Foo>(v1, ..., vn)
auto a = make_any<Foo>(v1, ..., vn)
```

Which file for `in_place_t` and `in_place`?

As `in_place_t` and `in_place` are used by `optional` and `any` we need to move its definition to another file. The preference of the authors will be to place them in `<experimental/utility>`.

Note that `in_place` could also be used by `experimental::variant` and that in this case it could also take an index as template parameter.

Access interface

The original paper suggested a possible interface for sum types access. As the subject is quite contentious, another paper could take care of it separately.

Open points

The authors would like to have an answer to the following points if there is yet at all an interest in this proposal:

- Are the differences in behavior of the new `in_place_t` acceptable?
- Where to place `in_place_t/in_place`? `<experimental/utility>`?
- Do we prefer `has_value/holds`?
- Do we want to remove the operator `bool` for `optional`?

Technical Specification

The wording is relative to [N4480].

General utilities library

Add `in` [utility/synop]

```
struct in_place_tag {};
using in_place_t = in_place_tag(&) (unspecified);
template <class T>
using in_place_type_t = in_place_tag(&) (unspecified<T>);
template <int N>
using in_place_index_t = in_place_tag(&) (unspecified<N>);

constexpr in_place_t in_place(unspecified);
template <class ...T>;
constexpr in_place_t in_place(unspecified<T...>);
template <size N>;
constexpr in_place_t in_place(unspecified<N>);
```

Optional objects

Remove `in_place_t/in_place` from [optional/synop] and [optional/inplace]

Update [optional.synopsis] adding after `make_optional`

```
template <class T, class ...Args>
    optional<T> make_optional(Args&& ...args);

template <class T, class U, class ...Args>
    optional<T> make_optional(initializer_list<U> il, Args&& ...args);
```

Add in [optional.object]

```
void reset() noexcept;
```

Add in [optional.specalg]

```
template <class T, class ...Args>
    optional<T> make_optional(Args&& ...args);
```

Returns: `optional<T>(in_place, std::forward(args)...) .`

```
template <class T, class U, class ...Args>
    optional<T> make_optional(initializer_list<U> il, Args&& ...args);
```

Returns: `optional<T>(in_place, il, std::forward(args)...) .`

Class any

Update [any.synopsis] adding

```
template <class T, class ...Args>
    any make_any(Args&& ...args);
template <class U, class T, class ...Args>
    any make_any(initializer_list<U>, Args&& ...args);
```

Add `constexpr` on any default constructor

```
constexpr any() noexcept;
```

Add inside class any

// Constructors

```
template <class T, class ...Args>
    any(in_place_type_t<T>, Args&& ...);
template <class T, class U, class... Args>
    explicit any(in_place_type_t<T>, initializer_list<U>, Args&&...);
```

```
template <class T, class ...Args>
    void emplace(Args&& ...);
template <class T, class U, class... Args>
    void emplace(initializer_list<U>, Args&&...);
```

Replace inside class any

```
void clear() noexcept;
bool empty() const noexcept;
```

by

```
void reset() noexcept;
constexpr bool has_value() const noexcept;
```

and replace any use of `empty()` by `! has_value()`

Add in [any/cons]

```
constexpr any() noexcept;

template <class T, class ...Args>
    any(in_place_type_t<T>, Args&& ...);
```

Requires: `is_constructible_v<T, Args&&...>` is true.

Effects: Initializes the contained value as if direct-non-list-initializing an object of type T with the arguments `std::forward<Args>(args)...`

Postconditions: *this contains a value of type T.*

Throws: Any exception thrown by the selected constructor of T.

```
template <class T, class U, class ...Args>
    any(in_place_type_t<T>, initializer_list<U> il, Args&& ...args);
```

Requires: `is_constructible_v<T, initializer_list<U>&, Args&&...>` is true.

Effects: Initializes the contained value as if direct-non-list-initializing an object of type T with the arguments `il, std::forward<Args>(args)...`

Postconditions: **this contains a value.*

Throws: Any exception thrown by the selected constructor of T.

Remarks: The function shall not participate in overload resolution unless `is_constructible_v<T, initializer_list<U>&, Args&&...>` is true.

Add in [any/modifiers]

```
template <class T, class ...Args>
    void emplace(Args&& ...);
```

Requires: `is_constructible_v<T, Args&&>` is true.

Effects: Calls `this.reset()`. Then initializes the contained value as if direct-non-list-initializing an object of type T with the arguments `std::forward<Args>(args)...`

Postconditions: *this contains a value.*

Throws: Any exception thrown by the selected constructor of T.

Remarks: If an exception is thrown during the call to T's constructor, *this does not contain a value, and the previous (if any) has been destroyed.

Add in [any.assign]

```
template <class T, class U, class ...Args>
void emplace(initializer_list<U> il, Args&& ...args);
```

Requires: `is_constructible<T, initializer_list<U>&, Args&&...>`

Effects: Calls `this->reset()`. Then initializes the contained value as if direct-non-list-initializing an object of type T with the argument `sil, std::forward(args)...`

Postconditions: this contains a value.

Throws: Any exception thrown by the selected constructor of T.

Remarks: If an exception is thrown during the call to T's constructor, *this does not contain a value, and the previous (if any) has been destroyed.

The function shall not participate in overload resolution unless `is_constructible_v<T, initializer_list<U>&, Args&&...>` is true.

Replace in [any/modifier], clear by reset.

Replace in [any/observers], empty by has_value (reversing the meaning).

```
constexpr bool has_value() const noexcept;
```

Returns:

true if *this contains an object, otherwise false.

Add in [any.nonmembers]

```
template <class T, class ...Args>
any make_any(Args&& ...args);
```

Returns: `any(in_place<T>, std::forward<Args>(args)...)...`

```
template <class T, class U, class ...Args>
any make_any(initializer_list<U> il, Args&& ...args);
```

Returns: `any(in_place<T>, il, std::forward<Args>(args)...)...`

Acknowledgements

Thanks to Jeffrey Yasskin to encourage me to report these as possible issues of the TS,

Many thanks to Agustin Bergé K-Balo for the function reference idea to represent `in_place` tags overloads.

Thanks to Tony Van Eerd for championing this proposal during the C++ standard committee meetings and helping me to improve globally the paper. The comparative table in the appendix comes from him.

References

[N4480] N4480 - Working Draft, C++ Extensions for Library Fundamentals

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2015/n4480.html>

[N4542] N4542 - Variant: a type-safe union (v4)

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2015/n4542.pdf>

[eggs-variant] eggs::variant

<https://github.com/eggs-cpp/variant>

[N4471] N4471 - Template parameter deduction for constructors (Rev 2)

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2015/n4471.html>

[P0032R0] Homogeneous interface for variant, any and optional

<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2015/p0032r0.pdf>

Appendix

WITHOUT proposal	WITH proposal
in_place, emplace_type, emplace_index	
<pre>struct Foo { Foo(int, double, char); }; optional<Foo> of(in_place, 0, 1.5); variant<int, Foo> vf(emplace_type<Foo>, 0, 1.5); variant<int, Foo> vf(emplace_index<1>, 0, 1.5); any af(Foo{0, 1.5, 'c'});</pre> <p>NOTE: thus <code>any</code> currently does not support non move/copy-able</p>	<pre>struct Foo { Foo(int, double, char); }; optional<Foo> of(in_place, 0, 1.5); variant<int, Foo> vf(in_place<Foo>, 0, 1.5); variant<int, Foo> vf(in_place<1>, 0, 1.5); any af(in_place<Foo>, 0, 1.5);</pre> <p>Also, now <code>any</code> supports non move/copy-able</p>
any.emplace()	
<pre>of.emplace(0, 1.5, 'c'); vf.emplace<Foo>(0, 1.5, 'c'); vf.emplace<1>(0, 1.5, 'c'); af = Foo{0, 1.5, 'c'};</pre> <p><code>any</code> does not currently <code>emplace</code></p>	<pre>of.emplace(0, 1.5, 'c'); vf.emplace<Foo>(0, 1.5, 'c'); vf.emplace<1>(0, 1.5, 'c'); af.emplace<Foo>(0, 1.5, 'c');</pre> <p>Now <code>any</code> supports non move/copy-able</p>
reset()	
<pre>unique_ptr<Foo> uf = new Foo(0, 1.5, 'c'); uf.reset(); of = nullptr; af.clear();</pre>	<pre>unique_ptr<Foo> uf = new Foo(0, 1.5, 'c'); uf.reset(); of.reset(); af.reset();</pre> <p>variant? No. Does not go empty. Could default-construct, but also doesn't have <code>has_value()</code>. Don't force false consistency.</p>
has_value()	
<pre>if (uf) ... if (of) ... if (! af.empty()) ...</pre>	<pre>if (uf.has_value()) ... if (of.has_value()) ... if (af.has_value()) ...</pre> <p>NOTE: smart-ptrs as well variant? – No. intentionally “<code>corrupted_by_exception</code>”</p>
make_...() factories	
<pre>auto uf = make_unique<Foo>(0, 1.5, 'c'); auto sf = make_shared<Foo>(0, 1.5, 'c'); auto of = make_optional<Foo>(Foo{0, 1.5, 'c'}); auto af = any(Foo{0, 1.5, 'c'});</pre>	<pre>auto uf = make_unique<Foo>(0, 1.5, 'c'); auto sf = make_shared<Foo>(0, 1.5, 'c'); auto of = make_optional<Foo>(0, 1.5, 'c'); auto af = make_any<Foo>(0, 1.5, 'c');</pre> <p>NOTE: EWG has mandated RVO so non move/copy-able also work</p>
constexpr any ctor	
<code>any a;</code>	<code>constexpr any a;</code>