

Document number: DXXXX=yy-nnnn
 Date: 2015-09-13
 Project: Programming Language C++, Library Evolution Working Group
 Reply-to: Vicente J. Botet Escriba <vicente.botet@wanadoo.fr>

C++ generic factory

Experimental generic factories library for C++17.

Contents

Introduction.....	2
Motivation and Scope.....	2
Tutorial.....	4
Type constructor factory.....	4
How to define a class that wouldn't need customization?.....	4
How to customize an existing class.....	5
How to define a type constructor?.....	5
Helper classes.....	6
Design rationale.....	7
Why to have default customization points?.....	7
Customization point.....	7
reference_wrapper<T> overload to deduce T&	8
Product types factories.....	8
High order factory.....	8
Open points.....	9
Technical Specification.....	10
Header <experimental/functional> Synopsis.....	10
DEDUCED_TYPE(T).....	11
Template function make	11
Template function make_custom	12
Example of customizations.....	12
optional	12
expected	13
future/shared_future	13
unique_ptr	14
shared_ptr	14
Implementation.....	14
Acknowledgements.....	14
History.....	15
References.....	15
Appendix - Non Mandatory Helper Classes.....	16

Introduction

This paper presents a proposal for a generic factory make that allows to make generic algorithms that need to create an instance of a wrapped class from its underlying types.

N4471 proposes extending template parameter deduction for functions to constructors of template classes. If N4471 is adopted, it could seem that this proposal will lost most of its added value, but this is not the case.

Motivation and Scope

All these types, `shared_ptr<T>`, `unique_ptr<T,D>`, `optional<T>`, `expected<T,E>` and `future<T>`, have in common that all of them have an underlying type 'T'.

There are two kind of factories:

- type constructor with the underlying types as parameter
 - `back_inserter`
 - `make_optional`
 - `make_ready_future`
 - `make_expected`
- `emplace` construction of the underlying type given the constructor parameters
 - `make_shared`
 - `make_unique`

When writing an application, the user knows if the function to write should return a specific type, as `shared_ptr<T>`, `unique_ptr<T,D>`, `optional<T>`, `expected<T,E>` or `future<T>`. E.g. when the user knows that the function must return a owned smart pointer it would use `unique_ptr<T>`.

```
template <class T>
unique_ptr<T> f() {
    T a,
    ...
    return make_unique(a);
    //return unique_ptr(a); // would this be correct if N4471 is accepted?
}
```

If the user knows that the function must return a shared smart pointer

```
template <class T>
shared_ptr<T> f() {
    T a,
    ...
    return make_shared(a);
    //return shared_ptr(a); // would this be correct if N4471 is accepted?
}
```

However when writing a library, the author doesn't always know which type the user wants as a result. In these cases the function library must take some kind of type constructor to let the user make the choice.

```

template <template <class> class TC, class T>
TC<T> f() {
    T a,
    ...
    return make<TC>(a);
}

```

In addition, we have factories for the product types such as `pair` and `tuple`

- `make_pair`
- `make_tuple`

We can use the class template name as a type constructor

```

vector<int> vi1 = { 0, 1, 1, 2, 3, 5, 8 };
vector<int> vi2;
copy_n(vi1, 3, make<back_insert_iterator>(vi2));

int v=0;
auto x1 = make<shared_ptr>(v);
auto x2 = make<unique_ptr>(v);
auto x3 = make<optional>(v);
auto x4 = make<future>(v);
auto x5 = make<shared_future>(v);
auto x6 = make<expected>(v);
auto x7 = make<pair>(v, v);
auto x8 = make<tuple>(v, v, 1u);

```

or making use of `reference_wrapper` type deduction

```

int v=0;
future<int&> x4 = make<future>(std::ref(v));

```

or use the class name to build to support in place construction

```

auto x1 = make<shared_ptr<A>>(v, v);
auto x2 = make<unique_ptr<A>>(v, v);
auto x3 = make<optional<A>>();
auto x4 = make<future<A>>(v);
auto x5 = make<shared_future<A>>(v, v);
auto x6 = make<expected<A>>(v, v);

```

Note, if N4471 is accepted, the following will be already possible

```

int v=0;
auto x3 = optional(v);
auto x7 = pair(v, v);
auto x8 = tuple(v, v, 1u);

```

However we can not do that for classes having non-member factories as `std::experimental::future`.

It is not clear how N4471 or an evolution of this proposal could be used inside a template. What is the type of the template parameter representing the type constructor? What would be the contents of `?T?` and `?R?` in the following function template.

```

template <?T? TC, class T>

```

```
?R? f() {
    T a,
    ...
    return TC(a);
}
```

Would the following be correct if N4471 is adopted?

```
template <template <class> TC, class T>
TC<T> f() {
    T a,
    ...
    return TC(a);
}
```

We can also make use of the class name to avoid the type deduction

```
int i;
auto x1 = make<future<long>>>(i);
```

Sometimes the user wants that the underlying type be deduced from the parameter, but the type constructor needs more information. A type holder `_t` can be used to mean any type `T`.

```
auto x2 = make<expected<_t, E>>>(v);
auto x2 = make<unique_ptr<_t, MyDeleter>>>(v);
```

Tutorial

Type constructor factory

```
template <class TC>
    apply<TC, int> safe_divide(int i, int j)
{
    if (j == 0)
        return none<TC>();
    else
        return make<TC>(i / j);
}
```

We can use this function with different type constructor as

```
auto x = safe_divide<optional<_t>>>(1, 0);
```

or

```
auto x = safe_divide<expected<_t>>>(1, 0);
```

How to define a class that wouldn't need customization?

For the make default constructor function, the class needs at least to have a default constructor

```
C();
```

For the `make_copy/move` constructor function, the class needs at least to have a constructor from the underlying types.

```
C(Xs&&...);
```

How to customize an existing class

When the existing class doesn't provide the needed constructor as e.g. `future<T>`, the user needs to add the missing overloads for `make_custom` so that they can be found by ADL.

```
namespace boost {
    future<void> make_custom(meta::id<future<void>>)
    {
        return make_ready_future();
    }
    template <class T, class ...Args>
    future<T> make_custom(meta::id<future<T>>, Args&& ...args)
    {
        return make_ready_future<T>(forward<Args>(x)...);
    }
}
```

How to define a type constructor?

The simple case is when the class has a single template parameter as is the case for `future<T>`.

```
namespace boost
{
    struct future_tc {
        template <class T>
        using apply = future<T>;
    };
}
```

When the class has two parameters and the underlying type is the first template parameter, as it is the case for `expected`,

```
namespace boost
{
    template <class E>
    struct expected_tc<E> {
        template <class T>
        using apply = expected<T, E>;
    };
}
```

If the second template depends on the first one as it is the case of `unique_ptr<T, D>`, the rebind of the second parameter must be done explicitly.

```
namespace boost
{
    namespace detail
    {
        template <class D, class T>
        struct rebind;
```

```

template <template <class...> class TC, class ...Ts, class ...Us>
struct rebind<TC<Ts...>, Us...>> {
    using type = TC<Us...>;
};
template <class M, class ...Us>
using rebind_t = typename rebind<M, Us...>>::type;
}

template <>
    struct default_delete<experimental::_t>
    {
        template<class T>
        using apply = default_delete<T>;
    };

template <class D>
    struct unique_ptr<experimental::_t, D>
    {
        template<class T>
        using apply = unique_ptr<T, detail::rebind_t<D, T>>;
    };
}

```

Helper classes

Defining these type constructors is cumbersome. This task can be simplified with some helper classes.

```

// type holder
struct _t {};

namespace meta
{
    // identity meta-function
    template<class T>
    struct id
    {
        using type = T;
    };

    // lift a class template to a type constructor
    template <template <class ...> class TC, class... Args>
    struct lift;

    // reverse lift a class template to a type constructor
    template <template <class ...> class TC, class... Args>
    struct reverse_lift;

    template <class M, class ...U>
    struct rebind : id<typename M::template rebind<U...>> {};

    template <template<class ...> class TC, class ...Ts, class ...Us>
    struct rebind<TC<Ts...>, Us...> : id<TC<Us...>> {};

    template <class M, class ...Us>
    using rebind_t = eval<rebind<M, Us...>>;
}

```

```
}
```

The previous type constructors could be rewritten using these helper classes as follows:

```
namespace boost
{
    template <> struct future<_t> : std::experimental::meta::lift<future>
    {};
}

namespace boost
{
    template <class E> struct expected<_t, E> :
        std::experimental::meta::reverse_lift<expected, E> {};
}

namespace boost
{
    template <>
        struct default_delete<_t> :
            std::experimental::meta::lift<default_delete> {};

    template <class D>
        struct unique_ptr<_t, D>
        {
            template<class T>
                using apply = unique_ptr<T, std::experimental::meta::rebind_t<D, T>>;
        };
}
```

Design rationale

Why to have default customization points?

The first factory `make` uses default constructor to build a `C<void>`.

The second factory `make` uses conversion constructor from the underlying type(s).

The third factory `make` is used to be able to do `emplace` construction given the specific type.

Having a customization point allows to leverage the user of the difficulties to implement these overload. The user customizing this factories has simpler interface to customize, as the type to build is already deduced.

Customization point

This proposal takes advantage of overloading the `make_custom` functions adding the tag `id<T>`.

We have named the customization points `make_custom` to make more evident that these are

customization points.

reference_wrapper<T> overload to deduce T&

As it is the case for `make_pair` when the parameter is `reference_wrapper<T>`, the type deduced for the underlying type is `T&`.

Product types factories

This proposal takes into account also product type factories (as `std::pair` or `std::tuple`).

```
// make product factory overload: Deduce the resulting `Us`
template <template <class...> class T, class ...Ts>
    T<Us...> make(Ts&& ...args);
// make product factory overload: Deduce the resulting `Us`
template <class TC, class ...Ts>
    apply<TC, Us...> make(Ts&& ...args);

auto x = make<pair>(1, 2u);
auto x = make<tuple>(1, 2u, string("a"));
```

High order factory

It is simple to define a high order `maker<TC>` factory of factories that can be used in standard algorithms.

For example

```
std::vector<X> xs;
std::vector<Something<X>> ys;
std::transform(xs.begin(), xs.end(), std::back_inserter(ys),
    maker<Something>{});

template <template <class> class T>
    struct maker {
        template <typename ...X>
            constexpr auto
            operator()(X&& ...x) const
            {
                return make<T>(forward<X>(x) ...);
            }
    };
```

The main problem defining function objects is that we can not have the same class with different template parameters. The `maker` class template has a template class parameter. We need an additional classes that takes a meta-function class and a type.

```
template <template <class...> class T>
    struct maker_tc {
        template <typename ...Xs>
            constexpr auto
            operator()(Xs&& ...xs) const
            {
                return make<T>(forward<Xs>(xs) ...);
            }
    };
```



```

    }
};

template <class MFC> // requires MFC is a type constructor
struct maker_mfc {
    template <class ...Xs>
    constexpr auto
    operator() (Xs&& ...xs)
    {
        return make<MFC>(std::forward<Xs>(xs) ...);
    }
};

template <class M> // requires M is a type
struct maker_t
{
    template <class ...Args>
    constexpr M operator() (Args&& ...args) const
    {
        return make<M>(std::forward<Args>(args) ...);
    }
};

```

Open points

The authors would like to have an answer to the following points if there is at all an interest in this proposal:

- **Is there an interest on the make functions?**
- **Is there an interest on the none functions?**
- **Should the customization be done with overloading or with traits?**

The current proposal uses overloading as customization point. The alternative is to use traits as e.g. the library Hana uses.

If overloading is preferred,

- should the customization function names be suffixed e.g. with `_custom`?
- **Should the namespace `meta` be used for the meta programming utilities `apply` and `id`?**
- **Should the function object factories be part of the proposal?**

The function objects `maker_tc`, `maker_mfc` and `maker_t` could be quite useful.

What should be the default for `maker`?

- **Should the function factories `make` and `none` be function objects?**

N4381 proposes to use function objects as customized points, so that ADL is not involved.

This has the advantages to solve the function and the high order function at once.

The same technique is used a lot in other functional libraries as Range, Fit and Pure.

- **Is there an interest on the helper holder `_t`?**

While not need absolutely, it helps to define friendly type constructors.

- **Is there an interest on the helper meta-functions `types(type_list)`, `lift`, `lift_reverse` and `rebind`?**

If yes, should them be part of a separated proposal?

There is much more on meta-programming utilities as show on the Meta library.

- **Should the customization of the standard classes `pair`, `tuple`, `optional`, `future`, `unique_ptr`, `shared_ptr` be part of this proposal?**

Technical Specification

Header `<experimental/functional>` Synopsis

Add the following declaration in `experimental/functional`.

```
namespace std
{
namespace experimental
{
inline namespace fundamental_v2
{
namespace meta
{
template <class TC, class... Args>
using apply = typename TC::template apply<Args...>;

template<class T>
struct id
{
using type = T;
};
}

template <class TC>
constexpr auto none();

template <template <class ...> class TC>
constexpr auto none();

template <class TC>
meta::apply<TC, void> make();

template <template <class ...> class M>
M<void> make();

template <class TC, class ...Xs>
meta::apply<TC, Ys...> make(Xs&& ...xs);

template <template <class ...> class M, class ...Xs>
M<Ys...> make(Xs&& xs);

template <class M, class ...Xs>
```

```

M make(Xs&& ...xs);

namespace meta
{
    template <class M, class ...Xs>
        M make_custom(meta::id<M>, Xs&& ...xs);
}
}
}
}

```

DEDUCED_TYPE(T)

Let U be `decay_t<T>`. Then V is $X\&$ if U is the same as `reference_wrapper<X>`, otherwise V is U .

Template function make

template + void

```

template <template <class ...> class M>
M<void> make();

```

Effects: Forwards to the customization point `make` with a template constructor `id<M<void>>>`. As if

```

return make_custom(meta::id<M<void>>>{});

```

Remarks: This overload would not participate in overload resolution until `make_custom(meta::id<M<void>>>{})` is well formed.

template + deduced underlying types

```

template <template <class ...> class M, class ...Ts>
M<Vs...> make(Ts&& xs...);

```

where V_s is `DEDUCED_TYPE(Ts)`:

Effects: Forwards to the customization point `make_custom` with a template constructor `meta::id<M<Vs...>>`. As if

```

return make_custom(meta::id<M<Vs...>>{}, std::forward<Ts>(xs)...);

```

Remarks: This overload would not participate in overload resolution until `make_custom(meta::id<M<Vs...>>{}, std::forward<Ts>(xs)...) is well formed.`

type constructor + deduced underlying types

```
template <class TC, class ...Ts>
    meta::apply<TC, Vs...> make(Ts&& xs...);
```

where `V` is `DEDUCED_TYPE(T)`.

Requires: `TC` is a type constructor.

Effects: Forwards to the customization point `make_custom` with a template constructor

`meta::id<meta::apply<TC, Vs...>>`. As if

```
return make_custom(meta::id<meta::apply<TC, V...>>{}, std::forward<Ts>(xs)...);
```

Remarks: This overload would not participate in overload resolution until

`make_custom(meta::id<meta::apply<TC, V...>>{},`

`std::forward<Ts>(xs)...)` is well formed.

type + non deduced underlying type

```
template <class M, class ...Xs>
    M make(Xs&& xs...);
```

Requires: `M` is not a type constructor and the underlying type of `M` is convertible from `Xs...`

Effects: Forwards to the customization point `make_custom` with a template constructor

`meta::id<M>`. As if

```
return make_custom(meta::id<M>{}, std::forward<Xs>(xs)...);
```

Template function `make_custom`

constructor customization point

```
template <class M, class ...Xs>
    M make_custom(meta::id<M>, Xs&& xs...);
```

Returns: A `M` constructed using the constructor `M(std::forward<Xs>(xs)...)`

Throws: Any exception thrown by the constructor.

Remarks: This overload would not participate in overload resolution until

`is_constructible_v<M, Xs&&>`.

Example of customizations

Next follows some examples of customizations that could be included in the standard

optional

```
namespace std {
```

```

namespace experimental {

    // Holder specialization
    template <>
    struct optional<_t>;

}

```

expected

```

namespace std {
namespace experimental {

    // Holder specialization
    template <class E>
    struct expected<_t, E>;

}
}

```

future/shared_future

```

namespace std {

    // customization point for template
    // (needed because std::experimental::future doesn't has a default
    constructor)
    future<void> make_custom(experimental::meta::id<future<void>>);

    // customization point for template
    // (needed because std::experimental::future doesn't has a conversion
    constructor)
    template <class DX, class ...Xs>
    future<DX> make_custom(experimental::meta::id<future<DX>>, Xs&& xs);

    // customization point for template
    // (needed because std::experimental::shared_future doesn't has a default
    constructor)
    shared_future<void> make_custom(experimental::meta::id<shared_future<void>>);

    // customization point for template
    // (needed because std::experimental::shared_future<X> doesn't has a
    constructor from X)
    template <class DX, class ...Xs>
    shared_future<DX> make_custom(experimental::meta::id<shared_future<DX>>,
    Xs&& xs...);

    // Holder specializations
    template <>
    struct future<experimental::_t>;
    template <>
    struct future<experimental::_t&>;
    template <>
    struct shared_future<experimental::_t>;
}

```

```
template <>
    struct shared_future<experimental::_t&>;
}
```

unique_ptr

```
namespace std {

    // customization point for template
    // (needed because std::unique_ptr doesn't has a conversion constructor)
    template <class DX, class ...Xs>
        unique_ptr<DX> make_custom(experimental::meta::id<unique_ptr<DX>>, Xs&& xs);

    // Holder customizations
    template <class D>
        struct unique_ptr<experimental::_t, D>;

    template <>
        struct default_delete<experimental::_t>;

}
```

shared_ptr

```
namespace std {

    // customization point for template
    // (needed because std::shared_ptr doesn't has a conversion constructor)
    template <class DX, class ...Xs>
        shared_ptr<DX> make_custom(experimental::meta::id<shared_ptr<DX>>, Xs&& xs);

    // Holder customization
    template <>
        struct shared_ptr<experimental::_t>;

}
```

Implementation

There is an implementation at <https://github.com/viboes/std-make>.

Acknowledgements

Many thanks to Agustín K-ballo Bergé from which I learn the trick to implement the different overloads. Scott Payer helped me to identify a minimal proposal, making optional the helper classes and of course the addition of high order functional factory and the missing `reference_wrapper` overload.

Thanks to Mike Spertus for its N4471 proposal that would help to avoid the factories in the application code cases.

History

v0.1 Creation

v0.2 Take in account comments from the ML

- Moved `apply` and `type` to `meta` namespace.
- Added `constexpr`.
- Added product type factory overload `make` to support `pair/tuple` types.
- Fix the signature of `make` to support `reference_wrapper` types.
- Added factory function object `maker`.
- Added `none` factory.
- Removed the `emplace make` factory specialization.
- Remove `type_constructor` as out of the scope of the proposal. It was used by `unique_ptr<_t, D>` specialization, but this can be seen as an implementation detail.
- Remove `type_constructor_tag` as this was an implementation detail.
- Refactored `rebind`.
- Moved `rebind`, `lift`, `reverse_lift`, `_t` and `id` to appendix Non Mandatory Helper Classes and to `meta` namespace.

v0.3 Take in account comments from the ML

- Fix some product type and `emplace` factories issues.
- Rename customization point `make` to `make_custom`.
- Reference N4471.
- Replace `meta::type` by `meta::id`

References

- N4471 - Template parameter deduction for constructors (Rev. 2) <http://open-std.org/JTC1/SC22/WG21/docs/papers/2015/n4471.html>
- N4381 - Suggested Design for Customization Points <http://open-std.org/JTC1/SC22/WG21/docs/papers/2015/n4381.html>
- N4480 - Programming Languages — C++ Extensions for Library Fundamentals <http://open-std.org/JTC1/SC22/WG21/docs/papers/2015/n4480.html>
- N4015 - A proposal to add a utility class to represent expected monad <http://www.open-std.org/JTC1/SC22/WG21/docs/papers/2014/n4015.pdf>
- Range-V3 <https://github.com/ericniebler/range-v3>
- Meta <https://github.com/ericniebler/meta>
- Hana <https://github.com/ldionne/hana>
- Pure <https://github.com/splinterofchaos/Pure>
- Fit <https://github.com/pfultz2/Fit>

Appendix - Non Mandatory Helper Classes

In the original proposal there were some helper classes as `lift`, `reverse_lift`, `_t` and `id` that are not mandatory for this proposal. If the committee has interest, a specific proposal can be written.

```
namespace std
{
    namespace experimental
    {
        inline namespace fundamental_v2
        {
            // type holder
            struct _t {};

        namespace meta
        {

            // lift a class template to a type constructor
            template <template <class ...> class TC, class... Args>
                struct lift;

            // reverse lift a class template to a type constructor
            template <template <class ...> class TC, class... Args>
                struct reverse_lift;

            template <class M, class ...U>
                struct rebind : id<typename M::template rebind<U...>> {};

            template <template<class ...> class TC, class ...Ts, class ...Us>
                struct rebind<TC<Ts...>, Us...> : id<TC<Us...>> {};

            template <class M, class ...Us>
                using rebind_t = typename rebind<M, Us...>::type;

        }}}}
```