

Implementácia distribuovaného firewallu založeného na OpenFlow

PODNADPIS

Obsah prezentácie


- Objasnenie témy
- Experiment
- Naša nadstavba na článku

Objasnenie témy

ARCHITEKTÚRA SDN
TOPOLÓGIA SIETE


Architektúra SDN

- Aplikačná vrstva – firewall
- Kontrolná vrstva – POX kontrolér
- Sieťová vrstva – jednotlivé prepínače



Topológia siete

- Stromová topológia
- 7 prepínačov
- 8 hostov
 - IP: 10.0.0.1-8






Experiment

TESTOVANIE FUNKČNOSTI FIREWALLU

Testované scenáre

1. H1 nepingne H2
2. H1 nepigne H7
3. H1 nepristúpi na web server na H4
4. H7 nepristúpi na UDP port 53 na H8



Tabuľka pravidiel blokovania komunikácie

Prepínač	Zdrojová IP	Cieľová IP	Protokol	Port
S3	10.0.0.1	10.0.0.2	1(ICMP)	-
S1	10.0.0.1	10.0.0.7	1(ICMP)	-
S2	10.0.0.1	10.0.0.4	6(TCP)	80
S7	10.0.0.7	10.0.0.8	17(UDP)	53

Nastavenie pravidiel

- ID prepínača
- A, D, S – pridanie, vymazanie, vyhľadanie pravidiel
- Zdrojová a cieľová IP
- Protokol
 - Port

```
Enter the DPID of switch in which you want to insert, delete or show rules: 3
Enter 'A' for adding, 'D' for deleting, 'S' for showing the rules: 'A'
Enter any of the following matching fields
Source IP, Destination IP, Network Protocol, Destination port(UDP or TCP)
Source IP Address(Press Enter for None): 10.0.0.1
Destination IP address(Press Enter for None): 10.0.0.2
Enter Network Protocol(1 for ICMP, 6 for TCP, 17 for UDP): 1
('adding Rule:', (2048, IPAddr('10.0.0.1'), IPAddr('10.0.0.2'), 1))
Enter the DPID of switch in which you want to insert, delete or show rules: 1
Enter 'A' for adding, 'D' for deleting, 'S' for showing the rules: 'A'
Enter any of the following matching fields
Source IP, Destination IP, Network Protocol, Destination port(UDP or TCP)
Source IP Address(Press Enter for None): 10.0.0.1
Destination IP address(Press Enter for None): 10.0.0.7
Enter Network Protocol(1 for ICMP, 6 for TCP, 17 for UDP): 1
('adding Rule:', (2048, IPAddr('10.0.0.1'), IPAddr('10.0.0.7'), 1))

Enter the DPID of switch in which you want to insert, delete or show rules: 2
Enter 'A' for adding, 'D' for deleting, 'S' for showing the rules: 'A'
Enter any of the following matching fields
Source IP, Destination IP, Network Protocol, Destination port(UDP or TCP)
Source IP Address(Press Enter for None): 10.0.0.1
Destination IP address(Press Enter for None): 10.0.0.4
Enter Network Protocol(1 for ICMP, 6 for TCP, 17 for UDP): 6
Enter TCP or UDP destination port: 80
('adding Rule:', (2048, IPAddr('10.0.0.1'), IPAddr('10.0.0.4'), 6, 80))


Enter the DPID of switch in which you want to insert, delete or show rules: 7
Enter 'A' for adding, 'D' for deleting, 'S' for showing the rules: 'A'
Enter any of the following matching fields
Source IP, Destination IP, Network Protocol, Destination port(UDP or TCP)
Source IP Address(Press Enter for None): 10.0.0.7
Destination IP address(Press Enter for None): 10.0.0.8
Enter Network Protocol(1 for ICMP, 6 for TCP, 17 for UDP): 17
Enter TCP or UDP destination port: 53
('adding Rule:', (2048, IPAddr('10.0.0.7'), IPAddr('10.0.0.8'), 17, 53))
```

Testovanie a výsledky

TESTOVACÍ SCENÁR 1,2

```
mininet> pingall
*** Ping: testing ping reachability
h1 -> X h3 h4 h5 h6 X h8
h2 -> X h3 h4 h5 h6 h7 h8
h3 -> h1 h2 h4 h5 h6 h7 h8
h4 -> h1 h2 h3 h5 h6 h7 h8
h5 -> h1 h2 h3 h4 h6 h7 h8
h6 -> h1 h2 h3 h4 h5 h7 h8
h7 -> X h2 h3 h4 h5 h6 h8
h8 -> h1 h2 h3 h4 h5 h6 h7
*** Results: 7% dropped (52/56 received)
```


TESTOVACÍ SCENÁR 3



```
Node: h1 (on mininet-vm)
root@mininet-vm:~# curl 10.0.0.4
curl: (7) Failed to connect to 10.0.0.4 port 80: Connection timed out
root@mininet-vm:~#

Node: h4 (on mininet-vm)
root@mininet-vm:~# python -m SimpleHTTPServer 80 &
[1] 4596
root@mininet-vm:~# Serving HTTP on 0.0.0.0 port 80 ...
```

TESTOVACÍ SCENÁR 4



```
Node: h7 (on mininet-vm)
root@mininet-vm:~# nc -u 10.0.0.8 53
hello

Node: h8 (on mininet-vm)
root@mininet-vm:~# nc -u -l -k 53
```


The image features a dark blue background with several thin, parallel teal lines. On the left side, these lines form a series of nested, slightly offset vertical and horizontal segments. On the bottom right, they form a series of parallel diagonal lines extending towards the corner.

Naša práca

GRAFICKÉ ROZHRANIE

Použitý firewall

- RYU rest firewall
- Black list vs. White list
- Npm
- jQuery – ajax



Aktuálny stav prototypu

The screenshot displays a web application prototype in a browser window. The browser's address bar shows '0.0.0.0'. The application has a header with the 'Admin' logo and a hamburger menu icon. A sidebar on the left contains a menu with four items: 'Dashboard' (home icon), 'Rules' (list icon), 'Logs' (document icon), and 'Network' (globe icon). The main content area is titled 'IP address' and contains a form with the label 'IP address (e.g.: 192.168.56.101:8080):'. Below the label is a text input field with the placeholder 'IP address'. A blue 'Put' button is positioned below the input field. The footer of the application states 'Copyright © 2017 Designed by Colorlib. All rights reserved.'

Admin

- Dashboard
- Rules
- Logs
- Network

IP address

IP address (e.g.: 192.168.56.101:8080):

Put

Copyright © 2017 Designed by Colorlib. All rights reserved.

Aktuálny stav prototypu

Admin

Dashboard

Rules

Logs

Network

0.0.0.0

IP address: 192.168.56.101:8080

Firewall status:

ID	Enabled	
0000000000000001	disabled	enable
0000000000000002	disabled	enable
0000000000000003	disabled	enable
0000000000000004	disabled	enable
0000000000000005	disabled	enable
0000000000000006	disabled	enable
0000000000000007	disabled	enable

Copyright © 2017 Designed by Colorlib. All rights reserved.