TLV2711, TLV2711Y
Advanced LinCMOS™ RAIL-TO-RAIL
## MICROPOWER SINGLE OPERATIONAL AMPLIFIERS

- **Output Swing Includes Both Supply Rails**
- **Low Noise . . . 21 nV/$\sqrt{Hz}$ Typ at f = 1 kHz**
- **Low Input Bias Current . . . 1 pA Typ**
- **Very Low Power . . . 11 μA Per Channel Typ**
- **Common-Mode Input Voltage Range Includes Negative Rail**
- **Wide Supply Voltage Range 2.7 V to 10 V**
- **Available in the SOT-23 Package**
- **Macromodel Included**

DBV PACKAGE
(TOP VIEW)

OUT	1	5	V_{DD}/GND
V_{DD+}	2		
IN+	3	4	IN–

EQUIVALENT INPUT NOISE VOLTAGE†
vs
FREQUENCY

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V.
For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

Figure 1. Equivalent Input Noise Voltage Versus Frequency

description

The TLV2711 is a single low-voltage operational amplifier available in the SOT-23 package. It consumes only 11 μA (typ) of supply current and is ideal for battery-power applications. Looking at Figure 1, the TLV2711 has a 3-V noise level of 21 nV/$\sqrt{Hz}$ at 1 kHz; five times lower than competitive SOT-23 micropower solutions. The device exhibits rail-to-rail output performance for increased dynamic range in single- or split-supply applications. The TLV2711 is fully characterized at 3 V and 5 V and is optimized for low-voltage applications.

The TLV2711, exhibiting high input impedance and low noise, is excellent for small-signal conditioning for high-impedance sources, such as piezoelectric transducers. Because of the micro-power dissipation levels combined with 3-V operation, these devices work well in hand-held monitoring and remote-sensing applications. In addition, the rail-to-rail output feature with single or split supplies makes this family a great choice when interfacing with analog-to-digital converters (ADCs).

With a total area of 5.6mm^2, the SOT-23 package only requires one-third the board space of the standard 8-pin SOIC package. This ultra-small package allows designers to place single amplifiers very close to the signal source, minimizing noise pick-up from long PCB traces.

AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES SOT-23 (DBV)†	SYMBOL	CHIP FORM‡ (Y)
0°C to 70°C	3 mV	TLV2711CDBV	VAJC	TLV2711Y
−40°C to 85°C	3 mV	TLV2711IDBV	VAJI	

† The DBV package available in tape and reel only.
‡ Chip forms are tested at T_A = 25°C only.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Advanced LinCMOS is a trademark of Texas Instruments.

Copyright © 2001, Texas Instruments Incorporated

TEXAS INSTRUMENTS

TLV2711Y chip information

This chip, when properly assembled, displays characteristics similar to the TLV2711C. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. This chip may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS

CHIP THICKNESS: 10 MILS TYPICAL

BONDING PADS: 4 × 4 MILS MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.

ALL DIMENSIONS ARE IN MILS.

PIN (2) IS INTERNALLY CONNECTED TO BACK SIDE OF CHIP.

TEXAS
INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

equivalent schematic

COMPONENT COUNT†	
Transistors	23
Diodes	6
Resistors	11
Capacitors	2

† Includes both amplifiers and all ESD, bias, and trim circuitry

![Texas Instruments logo] **TEXAS INSTRUMENTS**

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

3

TLV2711, TLV2711Y
Advanced LinCMOS™ RAIL-TO-RAIL
MICROPOWER SINGLE OPERATIONAL AMPLIFIERS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{DD} (see Note 1) .... 12 V
Differential input voltage, V_{ID} (see Note 2) .... $\pm V_{DD}$
Input voltage range, V_I (any input, see Note 1) .... -0.3 V to V_{DD}
Input current, I_I (each input) .... ± 5 mA
Output current, I_O .... ± 50 mA
Total current into V_{DD+} .... ± 50 mA
Total current out of V_{DD-} .... ± 50 mA
Duration of short-circuit current (at or below) 25°C (see Note 3) .... unlimited
Continuous total power dissipation .... See Dissipation Rating Table
Operating free-air temperature range, T_A: TLV2711C .... 0°C to 70°C
                                          TLV2711I .... -40°C to 85°C
Storage temperature range, T_{stg} .... -65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: DBV package .... 260°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential voltages, are with respect to V_{DD-}.
2. Differential voltages are at the noninverting input with respect to the inverting input. Excessive current flows when input is brought below $V_{DD-} - 0.3$ V.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \leq 25$°C POWER RATING	DERATING FACTOR ABOVE $T_A = 25$°C	$T_A = 70$°C POWER RATING	$T_A = 85$°C POWER RATING
DBV	150 mW	1.2 mW/°C	96 mW	78 mW

recommended operating conditions

		TLV2711C		TLV2711I		UNIT
		MIN	MAX	MIN	MAX	
Supply voltage, V_{DD} (see Note 1)		2.7	10	2.7	10	V
Input voltage range, V_I		V_{DD-}	$V_{DD+} - 1.3$	V_{DD-}	$V_{DD+} - 1.3$	V
Common-mode input voltage, V_{IC}		V_{DD-}	$V_{DD+} - 1.3$	V_{DD-}	$V_{DD+} - 1.3$	V
Operating free-air temperature, T_A		0	70	-40	85	°C

NOTE 1: All voltage values, except differential voltages, are with respect to V_{DD-}.

TEXAS INSTRUMENTS

electrical characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2711C MIN	TLV2711C TYP	TLV2711C MAX	TLV2711I MIN	TLV2711I TYP	TLV2711I MAX	UNIT
V_{IO}	Input offset voltage					0.4	3		0.4	3	mV
α_{VIO}	Temperature coefficient of input offset voltage	$V_{DD\pm}$ = ±1.5 V, V_O = 0,	V_{IC} = 0, R_S = 50 Ω	Full range		1			1		µV/°C
	Input offset voltage long-term drift (see Note 4)			25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				Full range			150			150	
I_{IB}	Input bias current			25°C			60			60	
				Full range		1	150		1	150	
V_{ICR}	Common-mode input voltage range	$|V_{IO}| \le 5$ mV,	R_S = 50 Ω	25°C	0 to 2	−0.3 to 2.2		0 to 2	−0.3 to 2.2		V
				Full range	0 to 1.7			0 to 1.7			
V_{OH}	High-level output voltage	I_{OH} = −100 µA		25°C		2.94			2.94		V
		I_{OH} = −250 µA		25°C		2.85			2.85		
				Full range	2.6			2.6			
V_{OL}	Low-level output voltage	V_{IC} = 1.5 V,	I_{OL} = 50 µA	25°C		15			15		mV
		V_{IC} = 1.5 V,	I_{OL} = 500 µA	25°C		150			150		
				Full range			500			500	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V, V_O = 1 V to 2 V	R_L = 10 kΩ‡	25°C	3	7		3	7		V/mV
				Full range	1			1			
			R_L = 1 MΩ‡	25°C		600			600		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,		25°C		5			5		pF
z_o	Closed-loop output impedance	f = 7 kHz,	A_V = 1	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V, R_S = 50 Ω	V_O = 1.5 V,	25°C	65	83		65	83		dB
				Full range	60			60			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD} / \Delta V_{IO}$)	V_{DD} = 2.7 V to 8 V, No load	V_{IC} = V_{DD}/2,	25°C	80	95		80	95		dB
				Full range	80			80			
I_{DD}	Supply current	V_O = 1.5 V,	No load	25°C		11	25		11	25	µA
				Full range			30			30	

† Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is − 40°C to 85°C.
‡ Referenced to 1.5 V
NOTE 4: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

operating characteristics at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLV2711C MIN	TLV2711C TYP	TLV2711C MAX	TLV2711I MIN	TLV2711I TYP	TLV2711I MAX	UNIT
SR	Slew rate at unity gain	V_O = 1.1 V to 1.9 V, R_L = 10 kΩ‡, C_L = 100 pF‡	25°C	0.01	0.025		0.01	0.025		V/µs
			Full range	0.005			0.005			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		80			80		nV/√Hz
		f = 1 kHz	25°C		22			22		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		660			660		nV
		f = 0.1 Hz to 10 Hz	25°C		880			880		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ‡, C_L = 100 pF‡	25°C		56			56		kHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 1 V, R_L = 10 kΩ‡, A_V = 1, C_L = 100 pF‡	25°C		7			7		kHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ‡, C_L = 100 pF‡	25°C		56°			56°		
	Gain margin		25°C		20			20		dB

† Full range is –40°C to 85°C.
‡ Referenced to 1.5 V

electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A†	TLV2711C MIN	TLV2711C TYP	TLV2711C MAX	TLV2711I MIN	TLV2711I TYP	TLV2711I MAX	UNIT
V_{IO}	Input offset voltage					0.45	3		0.45	3	mV
α_{VIO}	Temperature coefficient of input offset voltage	$V_{DD\pm}$ = ±2.5 V,	V_{IC} = 0,	Full range		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)	V_O = 0,	R_S = 50 Ω	25°C		0.003			0.003		µV/mo
I_{IO}	Input offset current			25°C		0.5	60		0.5	60	pA
				Full range			150			150	
I_{IB}	Input bias current			25°C		1	60		1	60	pA
				Full range			150			150	
V_{ICR}	Common-mode input voltage range	$\lvert V_{IO} \rvert \le$ 5 mV	R_S = 50 Ω	25°C	0 to 4	−0.3 to 4.2		0 to 4	−0.3 to 4.2		V
				Full range	0 to 3.5			0 to 3.5			
V_{OH}	High-level output voltage	I_{OH} = −100 µA		25°C		4.95			4.95		V
		I_{OH} = −250 µA		25°C		4.875			4.875		
				Full range	4.6			4.6			
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA	25°C		12			12		mV
		V_{IC} = 2.5 V,	I_{OL} = 500 µA	25°C		120			120		
				Full range			500			500	
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, V_O = 1 V to 4 V	R_L = 10 kΩ‡	25°C	6	12		6	12		V/mV
				Full range	3			3			
			R_L = 1 MΩ‡	25°C		800			800		
$r_{i(d)}$	Differential input resistance			25°C		10^{12}			10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance			25°C		10^{12}			10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz,		25°C		5			5		pF
z_o	Closed-loop output impedance	f = 7 kHz,	A_V = 1	25°C		200			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V, R_S = 50 Ω	V_O = 2.5 V,	25°C	70	83		70	83		dB
				Full range	70			70			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V, No load	V_{IC} = V_{DD}/2,	25°C	80	95		80	95		dB
				Full range	80			80			
I_{DD}	Supply current	V_O = 2.5 V,	No load	25°C		13	25		13	25	µA
				Full range			30			30	

† Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is – 40°C to 85°C.
‡ Referenced to 1.5 V
NOTE 5: Typical values are based on the input offset voltage shift observed through 500 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TEXAS INSTRUMENTS

operating characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

	PARAMETER	TEST CONDITIONS	T_A†	TLV2711C MIN	TLV2711C TYP	TLV2711C MAX	TLV2711I MIN	TLV2711I TYP	TLV2711I MAX	UNIT
SR	Slew rate at unity gain	V_O = 1.5 V to 3.5 V, R_L = 10 kΩ‡, C_L = 100 pF‡	25°C	0.01	0.025		0.01	0.025		V/µs
			Full range		0.005			0.005		
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		72			72		nV/√Hz
		f = 1 kHz	25°C		21			21		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		600			600		nV
		f = 0.1 Hz to 10 Hz	25°C		800			800		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ‡, C_L = 100 pF‡	25°C		65			65		kHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 10 kΩ‡, A_V = 1, C_L = 100 pF‡	25°C		7			7		kHz
ϕm	Phase margin at unity gain	R_L = 10 kΩ‡, C_L = 100 pF‡	25°C		60°			60°		
	Gain margin		25°C		22			22		dB

† Full range is −40°C to 85°C.
‡ Referenced to 1.5 V

electrical characteristics at V_{DD} = 3 V, T_A = 25°C (unless otherwise noted)

	PARAMETER	TEST CONDITIONS			TLV2711Y MIN	TLV2711Y TYP	TLV2711Y MAX	UNIT
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±1.5 V, R_S = 50 Ω	V_O = 0,	V_{IC} = 0,		0.47		mV
I_{IO}	Input offset current					0.5		pA
I_{IB}	Input bias current					1		pA
V_{ICR}	Common-mode input voltage range	$\vert V_{IO} \vert \le$ 5 mV,	R_S = 50 Ω			−0.3 to 2.2		V
V_{OH}	High-level output voltage	I_{OH} = −100 µA				2.94		V
		I_{OH} = −200 µA				2.85		
V_{OL}	Low-level output voltage	V_{IC} = 0,	I_{OL} = 50 µA			15		mV
		V_{IC} = 0,	I_{OL} = 500 µA			150		
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 1.5 V,	V_O = 1 V to 2 V	R_L = 10 kΩ†		7		V/mV
				R_L = 1 MΩ†		600		
$r_{i(d)}$	Differential input resistance					10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance					10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz				5		pF
z_o	Closed-loop output impedance	f = 7 kHz,	A_V = 1			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 1.7 V,	V_O = 1.5 V,	R_S = 50 Ω		83		dB
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 2.7 V to 8 V,	V_{IC} = V_{DD}/2,	No load		95		dB
I_{DD}	Supply current	V_O = 1.5 V,	No load			11		µA

† Referenced to 1.5 V

TEXAS INSTRUMENTS

electrical characteristics at V_{DD} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS			TLV2711Y			UNIT
					MIN	TYP	MAX	
V_{IO}	Input offset voltage	$V_{DD\pm}$ = ±2.5 V, R_S = 50 Ω	V_{IC} = 0,	V_O = 0,		0.45		mV
I_{IO}	Input offset current					0.5		pA
I_{IB}	Input bias current					1		pA
V_{ICR}	Common-mode input voltage range	$\lvert V_{IO}\rvert \leq$ 5 mV,	R_S = 50 Ω			−0.3 to 4.2		V
V_{OH}	High-level output voltage	I_{OH} = −100 µA				4.95		V
		I_{OH} = −250 µA				4.875		
V_{OL}	Low-level output voltage	V_{IC} = 2.5 V,	I_{OL} = 50 µA			12		mV
		V_{IC} = 2.5 V,	I_{OL} = 500 µA			120		
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V,	V_O = 1 V to 4 V	R_L = 10 kΩ†		12		V/mV
				R_L = 1 MΩ†		800		
$r_{i(d)}$	Differential input resistance					10^{12}		Ω
$r_{i(c)}$	Common-mode input resistance					10^{12}		Ω
$c_{i(c)}$	Common-mode input capacitance	f = 10 kHz				5		pF
z_O	Closed-loop output impedance	f = 7 kHz,	A_V = 1			200		Ω
CMRR	Common-mode rejection ratio	V_{IC} = 0 to 2.7 V,	V_O = 2.5 V,	R_S = 50 Ω		83		dB
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{DD} = 4.4 V to 8 V,	V_{IC} = V_{DD}/2,	No load		95		dB
I_{DD}	Supply current	V_O = 2.5 V,	No load			13		µA

† Referenced to 1.5 V

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
V_{IO}	Input offset voltage	Distribution	2, 3
		vs Common-mode input voltage	4, 5
α_{VIO}	Input offset voltage temperature coefficient	Distribution	6, 7
I_{IB}/I_{IO}	Input bias and input offset currents	vs Free-air temperature	8
V_I	Input voltage	vs Supply voltage	9
		vs Free-air temperature	10
V_{OH}	High-level output voltage	vs High-level output current	11, 14
V_{OL}	Low-level output voltage	vs Low-level output current	12, 13, 15
$V_{O(PP)}$	Maximum peak-to-peak output voltage	vs Frequency	16
I_{OS}	Short-circuit output current	vs Supply voltage	17
		vs Free-air temperature	18
V_O	Output voltage	vs Differential input voltage	19, 20
A_{VD}	Large-signal differential voltage amplification and phase margin	vs Load resistance	21
		vs Frequency	22, 23
		vs Free-air temperature	24, 25
z_o	Output impedance	vs Frequency	26, 27
CMRR	Common-mode rejection ratio	vs Frequency	28
		vs Free-air temperature	29
k_{SVR}	Supply-voltage rejection ratio	vs Frequency	30, 31
		vs Free-air temperature	32
I_{DD}	Supply current	vs Supply voltage	33
SR	Slew rate	vs Load capacitance	34
		vs Free-air temperature	35
V_O	Large-signal pulse response	vs Time	36, 37, 38, 39
	Inverting small-signal pulse response		40, 41
	Small-signal pulse response		42, 43
V_n	Equivalent input noise voltage	vs Frequency	44, 45
	Noise voltage (referred to input)	Over a 10-second period	46
THD + N	Total harmonic distortion plus noise	vs Frequency	47
	Gain-bandwidth product	vs Free-air temperature	48
		vs Supply voltage	49
ϕ_m	Phase margin	vs Frequency	23, 24
		vs Load capacitance	50
	Gain margin	vs Load capacitance	51
B_1	Unity-gain bandwidth	vs Load capacitance	52

TYPICAL CHARACTERISTICS

**DISTRIBUTION OF TLV2711
INPUT OFFSET VOLTAGE**

546 Amplifiers From 1 Wafer Lot
$V_{DD} = \pm1.5$ V
$T_A = 25°C$

V_{IO} – Input Offset Voltage – mV

Precentage of Amplifiers – %

Figure 2

**DISTRIBUTION OF TLV2711
INPUT OFFSET VOLTAGE**

376 Amplifiers From 1 Wafer Lot
$V_{DD} = \pm2.5$ V
$T_A = 25°C$

V_{IO} – Input Offset Voltage – mV

Precentage of Amplifiers – %

Figure 3

**INPUT OFFSET VOLTAGE†
vs
COMMON-MODE INPUT VOLTAGE**

$V_{DD} = 3$ V
$R_S = 50$ Ω
$T_A = 25°C$

V_{IC} – Common-Mode Input Voltage – V

V_{IO} – Input Offset Voltage – mV

Figure 4

**INPUT OFFSET VOLTAGE†
vs
COMMON-MODE INPUT VOLTAGE**

$V_{DD} = 5$ V
$R_S = 50$ Ω
$T_A = 25°C$

V_{IC} – Common-Mode Input Voltage – V

V_{IO} – Input Offset Voltage – mV

Figure 5

† For all curves where $V_{DD} = 5$ V, all loads are referenced to 2.5 V. For all curves where $V_{DD} = 3$ V, all loads are referenced to 1.5 V.

**TEXAS
INSTRUMENTS**

TYPICAL CHARACTERISTICS

**DISTRIBUTION OF TLV2711 INPUT OFFSET
VOLTAGE TEMPERATURE COEFFICIENT**

32 Amplifiers From 1 Wafer Lot
$V_{DD} = \pm 1.5$ V
P Package
$T_A = 25°C$

Percentage of Amplifiers – %

α_{VIO} – Temperature Coefficient – μV/°C

Figure 6

**DISTRIBUTION OF TLV2711 INPUT OFFSET
VOLTAGE TEMPERATURE COEFFICIENT**

32 Amplifiers From 1 Wafer Lot
$V_{DD} = \pm 2.5$ V
P Package
$T_A = 25°C$

Percentage of Amplifiers – %

α_{VIO} – Temperature Coefficient – μV/°C

Figure 7

**INPUT BIAS AND INPUT OFFSET CURRENTS†
vs
FREE-AIR TEMPERATURE**

$V_{DD\pm} = \pm 2.5$ V
$V_{IC} = 0$
$V_O = 0$
$R_S = 50$ Ω

I_{IB} and I_{IO} – Input Bias and Input Offset Currents – pA

I_{IB}

I_{IO}

T_A – Free-Air Temperature – °C

Figure 8

**INPUT VOLTAGE
vs
SUPPLY VOLTAGE**

$R_S = 50$ Ω
$T_A = 25°C$

V_I – Input Voltage – V

$| V_{IO} | \leq 5$ mV

$| V_{DD\pm} |$ – Supply Voltage – V

Figure 9

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

INPUT VOLTAGE†‡
vs
FREE-AIR TEMPERATURE

Figure 10

HIGH-LEVEL OUTPUT VOLTAGE†‡
vs
HIGH-LEVEL OUTPUT CURRENT

Figure 11

LOW-LEVEL OUTPUT VOLTAGE‡
vs
LOW-LEVEL OUTPUT CURRENT

Figure 12

LOW-LEVEL OUTPUT VOLTAGE†‡
vs
LOW-LEVEL OUTPUT CURRENT

Figure 13

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS

TYPICAL CHARACTERISTICS

HIGH-LEVEL OUTPUT VOLTAGE†‡
vs
HIGH-LEVEL OUTPUT CURRENT

Figure 14

LOW-LEVEL OUTPUT VOLTAGE†‡
vs
LOW-LEVEL OUTPUT CURRENT

Figure 15

MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE‡
vs
FREQUENCY

Figure 16

SHORT-CIRCUIT OUTPUT CURRENT
vs
SUPPLY VOLTAGE

Figure 17

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

TYPICAL CHARACTERISTICS

SHORT-CIRCUIT OUTPUT CURRENT†‡
vs
FREE-AIR TEMPERATURE

$V_{DD} = 5$ V
$V_{IC} = 2.5$ V
$V_O = 2.5$ V

$V_{ID} = -100$ mV

$V_{ID} = 100$ mV

Figure 18

OUTPUT VOLTAGE‡
vs
DIFFERENTIAL INPUT VOLTAGE

$V_{DD} = 3$ V
$R_I = 10$ kΩ
$V_{IC} = 1.5$ V
$T_A = 25°C$

Figure 19

OUTPUT VOLTAGE‡
vs
DIFFERENTIAL INPUT VOLTAGE

$V_{DD} = 5$ V
$V_{IC} = 2.5$ V
$R_L = 10$ kΩ
$T_A = 25°C$

Figure 20

DIFFERENTIAL VOLTAGE AMPLIFICATION‡
vs
LOAD RESISTANCE

$V_{O(PP)} = 2$ V
$T_A = 25°C$

$V_{DD} = 5$ V

$V_{DD} = 3$ V

Figure 21

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where $V_{DD} = 5$ V, all loads are referenced to 2.5 V. For all curves where $V_{DD} = 3$ V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS
POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

15

TYPICAL CHARACTERISTICS

**LARGE-SIGNAL DIFFERENTIAL VOLTAGE
AMPLIFICATION AND PHASE MARGIN†
vs
FREQUENCY**

Figure 22

**LARGE-SIGNAL DIFFERENTIAL VOLTAGE
AMPLIFICATION AND PHASE MARGIN†
vs
FREQUENCY**

Figure 23

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

![Texas Instruments logo]
TEXAS
INSTRUMENTS
POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL
VOLTAGE AMPLIFICATION†‡
vs
FREE-AIR TEMPERATURE

Figure 24

LARGE-SIGNAL DIFFERENTIAL
VOLTAGE AMPLIFICATION†‡
vs
FREE-AIR TEMPERATURE

Figure 25

OUTPUT IMPEDANCE‡
vs
FREQUENCY

Figure 26

OUTPUT IMPEDANCE‡
vs
FREQUENCY

Figure 27

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS

TYPICAL CHARACTERISTICS

COMMON-MODE REJECTION RATIO†
vs
FREQUENCY

Figure 28

COMMON-MODE REJECTION RATIO†‡
vs
FREE-AIR TEMPERATURE

Figure 29

SUPPLY-VOLTAGE REJECTION RATIO†
vs
FREQUENCY


Figure 30

SUPPLY-VOLTAGE REJECTION RATIO†
vs
FREQUENCY

Figure 31

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.
‡ Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TEXAS
INSTRUMENTS

TYPICAL CHARACTERISTICS

SUPPLY-VOLTAGE REJECTION RATIO†
vs
FREE-AIR TEMPERATURE

V_{DD} = 2.7 V to 8 V
V_{IC} = V_O = V_{DD}/2

Figure 32

SUPPLY CURRENT†
vs
SUPPLY VOLTAGE

V_O = V_{DD}/2
V_{IC} = V_{DD}/2
No Load

T_A = −40°C
T_A = 25°C
T_A = 85°C

Figure 33

SLEW RATE‡
vs
LOAD CAPACITANCE

V_{DD} = 5 V
A_V = −1
T_A = 25°C

SR−
SR+

Figure 34

SLEW RATE†‡
vs
FREE-AIR TEMPERATURE

V_{DD} = 5 V
R_L = 10 kΩ
C_L = 100 pF
A_V = 1

SR−
SR+

Figure 35

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

19

TYPICAL CHARACTERISTICS

INVERTING LARGE-SIGNAL PULSE
RESPONSE†

V_{DD} = 3 V
R_L = 10 kΩ
C_L = 100 pF
A_V = −1
T_A = 25°C

Figure 36

INVERTING LARGE-SIGNAL PULSE
RESPONSE†

V_{DD} = 5 V
R_L = 10 kΩ
C_L = 100 pF
A_V = −1
T_A = 25°C

Figure 37

VOLTAGE-FOLLOWER LARGE-SIGNAL
PULSE RESPONSE†

V_{DD} = 5 V
R_L = 10 kΩ
C_L = 100 pF
A_V = 1
T_A = 25°C

Figure 38

VOLTAGE-FOLLOWER LARGE-SIGNAL
PULSE RESPONSE†

V_{DD} = 5 V
C_L = 100 pF
A_V = 1
T_A = 25°C

R_L = 100 kΩ
Tied to 2.5 V

R_L = 10 kΩ
Tied to 2.5 V

R_L = 10 kΩ
Tied to 0 V

Figure 39

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

TYPICAL CHARACTERISTICS

INVERTING SMALL-SIGNAL
PULSE RESPONSE†

V_{DD} = 3 V
R_L = 10 kΩ
C_L = 100 pF
A_V = −1
T_A = 25°C

Figure 40

INVERTING SMALL-SIGNAL
PULSE RESPONSE†

V_{DD} = 5 V
R_L = 10 kΩ
C_L = 100 pF
A_V = −1
T_A = 25°C

Figure 41

VOLTAGE-FOLLOWER SMALL-SIGNAL
PULSE RESPONSE†

V_{DD} = 3 V
R_L = 10 kΩ
C_L = 100 pF
A_V = 1
T_A = 25°C

Figure 42

VOLTAGE-FOLLOWER SMALL-SIGNAL
PULSE RESPONSE†

V_{DD} = 5 V
R_L = 10 kΩ
C_L = 100 pF
A_V = 1
T_A = 25°C

Figure 43

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS

TYPICAL CHARACTERISTICS

EQUIVALENT INPUT NOISE VOLTAGE†
vs
FREQUENCY

Figure 44

EQUIVALENT INPUT NOISE VOLTAGE†
vs
FREQUENCY

Figure 45

INPUT NOISE VOLTAGE OVER
A 10-SECOND PERIOD†

Figure 46

TOTAL HARMONIC DISTORTION PLUS NOISE†
vs
FREQUENCY

Figure 47

† For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TEXAS
INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

TYPICAL CHARACTERISTICS

GAIN-BANDWIDTH PRODUCT†‡
vs
FREE-AIR TEMPERATURE

Figure 48

GAIN-BANDWIDTH PRODUCT
vs
SUPPLY VOLTAGE

Figure 49

PHASE MARGIN
vs
LOAD CAPACITANCE

Figure 50

GAIN MARGIN
vs
LOAD CAPACITANCE

Figure 51

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.
‡ For all curves where V_{DD} = 5 V, all loads are referenced to 2.5 V. For all curves where V_{DD} = 3 V, all loads are referenced to 1.5 V.

TYPICAL CHARACTERISTICS

UNITY-GAIN BANDWIDTH
vs
LOAD CAPACITANCE

Figure 52

APPLICATION INFORMATION

driving large capacitive loads

The TLV2711 is designed to drive larger capacitive loads than most CMOS operational amplifiers. Figure 50 and Figure 51 illustrate its ability to drive loads up to 600 pF while maintaining good gain and phase margins (R_{null} = 0).

A smaller series resistor (R_{null}) at the output of the device (see Figure 53) improves the gain and phase margins when driving large capacitive loads. Figure 50 and Figure 51 show the effects of adding series resistances of 500 Ω and 1000 Ω. The addition of this series resistor has two effects: the first is that it adds a zero to the transfer function and the second is that it reduces the frequency of the pole associated with the output load in the transfer function.

The zero introduced to the transfer function is equal to the series resistance times the load capacitance. To calculate the improvement in phase margin, equation 1 can be used.

$$\Delta\phi_{m1} = \tan^{-1}\left(2 \times \pi \times UGBW \times R_{null} \times C_L\right) \tag{1}$$

Where :

$\Delta\phi_{m1}$ = Improvement in phase margin

UGBW = Unity-gain bandwidth frequency

R_{null} = Output series resistance

C_L = : Load capacitance

![Texas Instruments logo]
TEXAS
INSTRUMENTS

APPLICATION INFORMATION

driving large capacitive loads (continued)

The unity-gain bandwidth (UGBW) frequency decreases as the capacitive load increases (see Figure 52). To use equation 1, UGBW must be approximated from Figure 52.


Figure 53. Series-Resistance Circuit

driving heavy dc loads

The TLV2711 is designed to provide better sinking and sourcing output currents than earlier CMOS rail-to-rail output devices. This device is specified to sink 500 µA and source 250 µA at V_{DD} = 3 V and V_{DD} = 5 V at a maximum quiescent I_{DD} of 25 µA. This provides a greater than 90% power efficiency.

When driving heavy dc loads, such as 10 kΩ, the positive edge under slewing conditions can experience some distortion. This condition can be seen in Figure 38. This condition is affected by three factors.

● Where the load is referenced. When the load is referenced to either rail, this condition does not occur. The distortion occurs only when the output signal swings through the point where the load is referenced. Figure 39 illustrates two 10-kΩ load conditions. The first load condition shows the distortion seen for a 10-kΩ load tied to 2.5 V. The third load condition shows no distortion for a 10-kΩ load tied to 0 V.

● Load resistance. As the load resistance increases, the distortion seen on the output decreases. Figure 39 illustrates the difference seen on the output for a 10-kΩ load and a 100-kΩ load with both tied to 2.5 V.

● Input signal edge rate. Faster input edge rates for a step input result in more distortion than with slower input edge rates.

APPLICATION INFORMATION

macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 6) and subcircuit in Figure 54 are generated using the TLV2711 typical electrical and operating characteristics at T_A = 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification

- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 6: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, "Macromodeling of Integrated Circuit Operational Amplifiers", *IEEE Journal of Solid-State Circuits,* SC-9, 353 (1974).


```
.SUBCKT TLV2711 1 2 3 4 5
        C1      11      12      8.86E–12
        C2      6       7       50.00E–12
        DC      5       53      DX
        DE      54      5       DX
        DLP     90      91      DX
        DLN     92      90      DX
        DP      4       3       DX
        EGND    99      0       POLY (2) (3,0) (4,0) 0 .5 .5
        FB      7       99      POLY (5) VB VC VE VLP
+ VLN 0 4.29E6 –6E6 6E6 6E6 –6E6
        GA      6       0       11      12 9.425E–6
        GCM     0       6       10      99 1320.2E–12
        ISS     3       10      DC 1.250E–6
        HLIM    90      0       VLIM 1K
        J1      11      2       10 JX
        J2      12      1       10 JX
        R2      6       9       100.0E3
```

```
        RD1     60      11      106.1E3
        RD2     60      12      106.1E3
        R01     8       5       50
        R02     7       99      150
        RP      3       4       419.2E3
        RSS     10      99      160.0E6
        VAD     60      4       –.5
        VB      9       0       DC 0
        VC      3       53      DC .55
        VE      54      4       DC .55
        VLIM    7       8       DC 0
        VLP     91      0       DC 0.1
        VLN     0       92      DC 2.6
.MODEL DX D (IS=800.0E–18)
.MODEL JX PJF (IS=500.0E–15 BETA=166E–6
+ VTO=–.004)
.ENDS
```

Figure 54. Boyle Macromodel and Subcircuit

PSpice and *Parts* are trademark of MicroSim Corporation.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish	MSL Peak Temp (3)	Op Temp (°C)	Top-Side Markings (4)	Samples
TLV2711CDBV	OBSOLETE	SOT-23	DBV	5		TBD	Call TI	Call TI			
TLV2711CDBVR	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	0 to 70	VAJC	Samples
TLV2711CDBVRG4	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	0 to 70	VAJC	Samples
TLV2711CDBVT	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		VAJC	Samples
TLV2711CDBVTG4	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		VAJC	Samples
TLV2711IDBV	OBSOLETE	SOT-23	DBV	5		TBD	Call TI	Call TI			
TLV2711IDBVR	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 85	VAJI	Samples
TLV2711IDBVRG4	ACTIVE	SOT-23	DBV	5	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-40 to 85	VAJI	Samples
TLV2711IDBVT	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		VAJI	Samples
TLV2711IDBVTG4	ACTIVE	SOT-23	DBV	5	250	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM		VAJI	Samples

[1] The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

[2] Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) Multiple Top-Side Markings will be inside parentheses. Only one Top-Side Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Top-Side Marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS

TAPE DIMENSIONS

A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLV2711CDBVR	SOT-23	DBV	5	3000	178.0	9.0	3.3	3.2	1.4	4.0	8.0	Q3
TLV2711CDBVT	SOT-23	DBV	5	250	178.0	9.0	3.3	3.2	1.4	4.0	8.0	Q3
TLV2711IDBVR	SOT-23	DBV	5	3000	178.0	9.0	3.3	3.2	1.4	4.0	8.0	Q3
TLV2711IDBVT	SOT-23	DBV	5	250	178.0	9.0	3.3	3.2	1.4	4.0	8.0	Q3

TAPE AND REEL BOX DIMENSIONS

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLV2711CDBVR	SOT-23	DBV	5	3000	180.0	180.0	18.0
TLV2711CDBVT	SOT-23	DBV	5	250	180.0	180.0	18.0
TLV2711IDBVR	SOT-23	DBV	5	3000	180.0	180.0	18.0
TLV2711IDBVT	SOT-23	DBV	5	250	180.0	180.0	18.0

DBV (R−PDSO−G5)   PLASTIC SMALL−OUTLINE PACKAGE

0,95

5X $\frac{0,50}{0,30}$ ⊕ 0,20 Ⓜ

5   4

$\frac{1,75}{1,45}$ $\frac{3,00}{2,60}$

Pin 1
Index Area
(Optional)

1   3

$\frac{3,05}{2,75}$

$\frac{0,22}{0,08}$

Gage Plane

0°−8°

0,25

$\frac{0,55}{0,30}$

1,45 MAX

$\frac{0,15}{0,00}$

Seating Plane

⌒ 0,10

4073253−4/L 08/2013

NOTES: A.   All linear dimensions are in millimeters.
         B.   This drawing is subject to change without notice.
         C.   Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
         D.   Falls within JEDEC MO−178 Variation AA.

DBV (R−PDSO−G5)   PLASTIC SMALL OUTLINE

Example Board Layout

Stencil Openings
Based on a stencil thickness
of .127mm (.005inch).

1,90

2,7

0,95

1,90

1,00

0,55

2,7

0,95

0,6

Solder Mask Opening

1,05

Pad Geometry

0,07
All Around

4209593−3/C 08/11

NOTES: A.   All linear dimensions are in millimeters.
         B.   This drawing is subject to change without notice.
         C.   Customers should place a note on the circuit board fabrication drawing not to alter the center solder mask defined pad.
         D.   Publication IPC−7351 is recommended for alternate designs.
         E.   Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should
              contact their board assembly site for stencil design recommendations. Example stencil design based on a 50% volumetric
              metal load solder paste. Refer to IPC−7525 for other stencil recommendations.

TEXAS
INSTRUMENTS
www.ti.com

IMPORTANT NOTICE

Products		Applications	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	**TI E2E Community**	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		