CREATE TABLE Items1 (Itemid INT PRIMARY KEY,Itemname VARCHAR(50),Category VARCHAR(50),Price DECIMAL(10,2),Instock INT CHECK (Instock >= 0));
INSERT INTO Items1 VALUES (1, 'Dell Inspiron Laptop', 'Electronics', 6000, 10);
INSERT INTO Items1 VALUES (2, 'Samsung GalaxyS4', 'Mobile', 9000, 6);
INSERT INTO Items1 VALUES (3, 'Sony Bluetooth Speaker', 'Electronics', 6500, 7);
INSERT INTO Items1 VALUES (4,'JBL Headphones', 'Headset',1000,12);
INSERT INTO Items1 VALUES (5,'Iphone 17','Mobile',7000,5);
INSERT INTO Items1 VALUES (6, 'Lenovo Tablet', 'Electronics', 5200, 6);

	ITEMID	ITEMNAME	CATEGORY	PRICE	INSTOCK
1	1	Dell Inspiron Laptop	Electronics	6000	10
2	2	Samsung GalaxyS4	Mobile	9000	6
3	3	Sony Bluetooth Speaker	Electronics	6500	7
4	4	JBL Headphones	Headset	1000	12
5	5	Iphone 17	Mobile	7000	5
6	6	Lenovo Tablet	Electronics	5200	6

CREATE TABLE Customers1 (Custid INT PRIMARY KEY,Custname VARCHAR(50),Address VARCHAR(100),State VARCHAR(20));
INSERT INTO Customers1 VALUES (101, 'John', '33 Ocean Drive', 'New York');
INSERT INTO Customers1 VALUES (102, 'Alice', '21 Forest Way', 'Colorado');
INSERT INTO Customers1 VALUES (103, ''Mickey', '56 Sunrise Street', 'Oregon');
INSERT INTO Customers1 VALUES (104, 'Jennifer', '89 Pine Lane', 'Arizona');
INSERT INTO Customers1 VALUES (105, 'Robert', '67 River Road', 'Illinois');
INSERT INTO Customers1 VALUES (106, 'Julia', '22 Green Ave', 'Texas');

	CUSTID	CUSTNAME	ADDRESS	STATE
1	101	John	33 Ocean Drive	New York
2	102	Alice	21 Forest Way	Colorado
3	103	Mickey	56 Sunrise Street	Oregon
4	104	Jennifer	89 Pine Lane	Arizona
5	105	Robert	67 River Road	Illinois
6	106	Julia	22 Green Ave	Texas

```
CREATE TABLE Orderss1 (
orderid INT PRIMARY KEY,Itemid INT,Custid INT,Quantity INT,Orderdate DATE,  FOREIGN
KEY (Itemid) REFERENCES Items1(itemid),    FOREIGN KEY (Custid) REFERENCES
Customers1(custid)
);
INSERT INTO Orderss1 VALUES (1001, 2, 104, 2,
TO_DATE('03-AUG-2013','DD-MON-YYYY'));
INSERT INTO Orderss1 VALUES (1002, 4, 102, 1, TO_DATE('18-JAN-2020','DD-MON-YYYY'));
INSERT INTO Orderss1 VALUES (1003, 6, 103, 3, TO_DATE('22-MAY-2021','DD-MON-YYYY'));
INSERT INTO Orderss1 VALUES (1004, 1, 105, 1,
TO_DATE('09-OCT-2014','DD-MON-YYYY'));
INSERT INTO Orderss1 VALUES (1005, 5, 106, 2, TO_DATE('14-FEB-2022','DD-MON-YYYY'));
INSERT INTO Orderss1 VALUES (1006, 3, 104, 1, TO_DATE('30-JUN-2016','DD-MON-YYYY'));
```

	ORDERID	ITEMID	CUSTID	QUANTITY	ORDERDATE
1	1001	2	104	2	03-08-13
2	1002	4	102	1	18-01-20
3	1003	6	103	3	22-05-21
4	1004	1	105	1	09-10-14
5	1005	5	106	2	14-02-22
6	1006	3	104	1	30-06-16

```
CREATE TABLE Delivery1 (
 deliveryid INT PRIMARY KEY, Custid INT, orderid INT, FOREIGN KEY (Custid) REFERENCES
Customers1(custid),  FOREIGN KEY (orderid) REFERENCES Orderss1(orderid)
);
INSERT INTO Delivery1 VALUES (5001, 101, 1001);
INSERT INTO Delivery1 VALUES (5002, 102, 1002);
INSERT INTO Delivery1 VALUES (5003, 103, 1003);
INSERT INTO Delivery1 VALUES (5004, 104, 1005);
INSERT INTO Delivery1 VALUES (5005, 106, 1006);
```

	DELIVERYID	CUSTID	ORDERID
1	5001	101	1001
2	5002	102	1002
3	5003	103	1003
4	5004	104	1005
5	5005	106	1006

1.SELECT DISTINCT c.*FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid;

	CUSTID	CUSTNAME	ADDRESS	STATE
1	106	Julia	22 Green Ave	Texas
2	105	Robert	67 River Road	Illinois
3	104	Jennifer	89 Pine Lane	Arizona
4	103	Mickey	56 Sunrise Street	Oregon
5	102	Alice	21 Forest Way	Colorado

2.SELECT DISTINCT c.*FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid INNER JOIN Delivery1 d ON o.orderid = d.orderid;

	CUSTID	CUSTNAME	ADDRESS	STATE
1	106	Julia	22 Green Ave	Texas
2	103	Mickey	56 Sunrise Street	Oregon
3	104	Jennifer	89 Pine Lane	Arizona
4	102	Alice	21 Forest Way	Colorado

3.SELECT c.custname, o.orderdate FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid WHERE c.custname LIKE 'J%';

	CUSTNAME	ORDERDATE
1	Jennifer	03-08-13
2	Julia	14-02-22
3	Jennifer	30-06-16

4.SELECT i.itemname, i.price FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid INNER JOIN Items1 i ON o.itemid = i.itemid WHERE c.custname = 'Mickey';

	ITEMNAME	PRICE
1	Lenovo Tablet	5200

5.SELECT DISTINCT c.* FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid WHERE o.Orderdate > TO_DATE('31-JAN-2013','DD-MON-YYYY') AND NOT EXISTS (SELECT 1 FROM Delivery1 d WHERE d.Orderid = o.Orderid);

	CUSTID	CUSTNAME	ADDRESS	STATE
1	105	Robert	67 River Road	Illinois

6.SELECT DISTINCT i.itemid, i.itemname FROM Items1 i JOIN Orderss1 o ON i.itemid = o.itemid LEFT JOIN Delivery1 d ON o.orderid = d.orderid WHERE d.deliveryid IS NULL;

	ITEMID	ITEMNAME
1	1	Dell Inspiron Laptop

7.SELECT DISTINCT c.Custname FROM Customers1 c INNER JOIN Orderss1 o ON c.custid = o.custid INNER JOIN Delivery1 d ON o.orderid = d.orderid;

	CUSTNAME
1	Alice
2	Julia
3	Mickey
4	Jennifer

8.SELECT c.custnameFROM Customers1 c WHERE c.custid IN (SELECT o.custid FROM Orderss1)
MINUS
SELECT c.custname FROM Customers1 WHERE c.custid IN (SELECT o.custid FROM Orderss1 o JOIN Delivery1 ON o.orderid = d.orderid);

	CUSTNAME
1	Robert

SELECT c.custnameFROM Customers1 cWHERE c.custid IN (SELECT o.custid FROM Orderss1 o)INTERSECT SELECT c.custname FROM Customers1 c WHERE c.custid IN (SELECT o.custid FROM Orderss1 o JOIN Delivery1 d ON o.orderid = d.orderid);

	CUSTNAME
1	Alice
2	Jennifer
3	Julia
4	Mickey

9.SELECT c.custnameFROM Customers1 c JOIN Orderss1 o ON c.custid = o.custid GROUP BY c.custname HAVING COUNT(o.orderid) = (SELECT MAX(COUNT(orderid)) FROM Orderss1 GROUP BY custid);

	CUSTNAME
1	Jennifer

10.SELECT DISTINCT c.* FROM Customers1 c JOIN Orderss1 o ON c.custid = o.custid JOIN Items1 i ON o.itemid = i.itemid WHERE i.price > 5000;

	CUSTID	CUSTNAME	ADDRESS	STATE
1	106	Julia	22 Green Ave	Texas
2	105	Robert	67 River Road	Illinois
3	103	Mickey	56 Sunrise Street	Oregon
4	104	Jennifer	89 Pine Lane	Arizona

11.
SELECT c.custname, c.address FROM Customers1 WHERE c.custid NOT IN (SELECT o.custid FROM Orderss1 o JOIN Items1 i ON o.itemid = i.itemid WHERE i.itemname = 'Samsung GalaxyS4');

	CUSTNAME	ADDRESS
1	John	33 Ocean Drive
2	Alice	21 Forest Way
3	Mickey	56 Sunrise Street
4	Robert	67 River Road
5	Julia	22 Green Ave

12.SELECT c.custid, c.custname, o.orderid FROM Customers1 c LEFT JOIN Orderss1 o ON c.custid = o.custid;

	CUSTID	CUSTNAME	ORDERID
1	104	Jennifer	1001
2	102	Alice	1002
3	103	Mickey	1003
4	105	Robert	1004
5	106	Julia	1005
6	104	Jennifer	1006
7	101	John	(null)

13.SELECT c.custid, c.custname, o.orderid FROM Customers1 c RIGHT JOIN Orderss1 o ON c.custid = o.custid;

	CUSTID	CUSTNAME	ORDERID
1	102	Alice	1002
2	103	Mickey	1003
3	104	Jennifer	1006
4	104	Jennifer	1001
5	105	Robert	1004
6	106	Julia	1005

14.SELECT category, itemid, itemname, priceFROM Items1 WHERE price > (SELECT AVG(price)FROM Items1)ORDER BY category;

	CATEGORY	ITEMID	ITEMNAME	PRICE
1	Electronics	3	Sony Bluetooth Speaker	6500
2	Electronics	1	Dell Inspiron Laptop	6000
3	Mobile	5	Iphone 17	7000
4	Mobile	2	Samsung GalaxyS4	9000