

pfadmin 1.x

Installation guide

1. Requirements

- Perl 5.x
- Postfix 2.x or higher (*tested on 3.1*)
- Dovecot 2.2.x (*tested on 2.2.22*)

2. Install and setup pfadmin

- Download the latest version and unpack it into: /opt/pfadmin (copy the content to this directory)
- Go to directory: /opt/pfadmin/configs
- Edit 'wstkd.conf', replace 'address=127.0.0.1' to your IP address
- Edit 'pfadmin.conf'
 - specify the correct pathes for Postfix and Dovecot options
 - specify the correct values for: mailbox_base, mailbox_uid, mailbox_gid (it should be like in: postfix/main.cf)(see example configs here: [example configs here: example configs.tar.gz](http://example.configs.tar.gz))
- adjust logger in: log4perl.conf
- try to start (debug mode): **/opt/pfadmin/bin/wstkd.sh start** (ctrl+c to stop)
if everything is ok you will see (on console or in a log file): *pfadmin is ready (version x.x)*
now you can try to open it in the browser

3. Install Postfix and Dovecot

- **Postfix**
apt-get install postfix postfix-pcre
- **Dovecot**
apt-get install dovecot-core dovecot-imapd dovecot-pop3d
- **Configure**
see example configs

4. Register it in systemd

Copy (or make a symlink) '/pfadmin/bin/pfadmin' to /etc/init.d
(*** on ubuntu won't forget to do: update-rc.d pfadmin defaults)

5. Web console

By default web interface available on: <http://127.0.0.1:8080/>
with login/password: admin / secret.