

Sofya Aksenyuk

03 II 2022

150284

AI

ex. 1.

Random sequential algorithm (for vertex coloring) has no graph hard to color, since graph is considered to be hard to color if any algorithm implementation for ~~this~~ this graph colors it not optimally. But since random sequential algorithm's worst case is $S_{RS}(G) \geq O(n)$, it colors a graph optimally, ~~and~~ regardless of what implementation is used.

ex. 2.

The consequences of ~~described~~ algorithms for the $P=NP$, $P \neq NP$ open question is that, ~~as~~ as for $P=NP$, such problem can be solved using DTM which gives us polynomial time. But as for $P \neq NP$, ~~we~~ we cannot be sure in that. Such algorithms don't prove $P=NP$ initially. If A exists then $P=NP$.

Sofya Aksenyuk
03 II 2022

1502 84.
AI.

ex. 3.

a) $\Delta + 1$ always (greedy way of solving)
~~can be checked in polynomial time~~
b) Δ if graph got no clique
of size $w(G) = \Delta + 1$ as well as if
is not a odd length cycle.

c) 2 colors, where Δ is graph
degree is true for bipartite
graphs.

a) can be checked in polynomial
time.

b) can't be checked in polynomial
time since clique is NP-Hard.

c) ~~graph~~ bipartite graphs can be
checked in polynomial time.

Sofya Aksenyuk
03 II 2022

150284
AI

ex. 4.

1.

	0	1	2	3	4	5
0	0	1		5		
1		0			4	3
2	2	3	0	7		1
3		9	2	0		
4	3	4			8	0
5			3	8		0

2.

	0	1	2	3	4	5
0	0	1		5	5	4
1		0			4	3
2	2	3	0	7	7	1
3		9	2	0	13	12
4	3	4			8	0
5			3	8		0

3.

	0	1	2	3	4	5
0	0	1		5	5	4
1		0			4	3
2	2	3	0	7	7	1
3	4	5	2	0	9	3
4	3	4			8	0
5	5	6	3	8	10	0

4.

	0	1	2	3	4	5
0	0	1	7	5	5	4
1		0			4	3
2	2	3	0	7	7	1
3	4	5	2	0	9	3
4	3	4	10	8	0	7
5	5	6	3	8	10	0

5.

	0	1	2	3	4	5
0	0	1	7	5	5	4
1	7	0	14	12	4	3
2	2	3	0	7	7	1
3	4	5	2	0	9	3
4	3	4	10	8	0	7
5	5	6	3	8	10	0

6.

	0	1	2	3	4	5
0	0	1	7	5	5	4
1	7	0	6	11	4	3
2	2	3	0	7	7	1
3	4	5	2	0	9	3
4	3	4	10	8	0	7
5	5	6	3	8	10	0