

Applications of SVD/PCA

Rafikul Alam
Department of Mathematics
Indian Institute of Technology Guwahati
Guwahati - 781039, INDIA

Outline

- SVD/PCA based algorithm for face recognition
- SVD and Polar decomposition

Face recognition



Figure: Library of twelve Presidents of the United States.

We store these images as vectors or matrices and apply PCA ([Principal Component Analysis](#)) to process the images.

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \longrightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns.

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \longrightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns. Consider the **average image**

$$\mathbf{p} := \frac{1}{N}(Pe_1 + \cdots + Pe_N) = \frac{1}{N}P\mathbf{e}, \quad \text{where } \mathbf{e} := [1, 1, \dots, 1]^T \in \mathbb{R}^N.$$

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \longrightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns. Consider the **average image**

$$\mathbf{p} := \frac{1}{N}(Pe_1 + \cdots + Pe_N) = \frac{1}{N}P\mathbf{e}, \quad \text{where } \mathbf{e} := [1, 1, \dots, 1]^T \in \mathbb{R}^N.$$

Subtracting \mathbf{p} from each columns of P , we have **mean-subtracted images** $A := P - \mathbf{p}\mathbf{e}^T$.

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \longrightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns. Consider the **average image**

$$\mathbf{p} := \frac{1}{N}(Pe_1 + \cdots + Pe_N) = \frac{1}{N}P\mathbf{e}, \quad \text{where } \mathbf{e} := [1, 1, \dots, 1]^T \in \mathbb{R}^N.$$

Subtracting \mathbf{p} from each columns of P , we have **mean-subtracted images** $A := P - \mathbf{p}\mathbf{e}^T$. Note that each row of A has zero mean. Hence $S := \frac{1}{N-1}AA^T$ is the **covariance** matrix.

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \rightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns. Consider the **average image**

$$\mathbf{p} := \frac{1}{N}(Pe_1 + \cdots + Pe_N) = \frac{1}{N}P\mathbf{e}, \quad \text{where } \mathbf{e} := [1, 1, \dots, 1]^T \in \mathbb{R}^N.$$

Subtracting \mathbf{p} from each columns of P , we have **mean-subtracted images** $A := P - \mathbf{p}\mathbf{e}^T$. Note that each row of A has zero mean. Hence $S := \frac{1}{N-1}AA^T$ is the **covariance** matrix.

Eigenvectors of S are called **eigenfaces**. Note that eigenfaces are left singular vectors of A and span the columns space of A . PCA uses **eigenfaces** to recapture an approximation to the original faces.

Face recognition

Assume that each image has the same **pixel resolution** with m rows and n columns. Let P_1, \dots, P_N be $m \times n$ matrices representing N images. Define

$$P := [\text{Vec}(P_1) \quad \cdots \quad \text{Vec}(P_N)] \in \mathbb{R}^{mn \times N},$$

where $\text{Vec} : \mathbb{R}^{m \times n} \rightarrow \mathbb{R}^{mn}$ converts a matrix to a column vector by stacking the columns. Consider the **average image**

$$\mathbf{p} := \frac{1}{N}(Pe_1 + \cdots + Pe_N) = \frac{1}{N}P\mathbf{e}, \quad \text{where } \mathbf{e} := [1, 1, \dots, 1]^T \in \mathbb{R}^N.$$

Subtracting \mathbf{p} from each columns of P , we have **mean-subtracted images** $A := P - \mathbf{p}\mathbf{e}^T$. Note that each row of A has zero mean. Hence $S := \frac{1}{N-1}AA^T$ is the **covariance** matrix.

Eigenvectors of S are called **eigenfaces**. Note that eigenfaces are left singular vectors of A and span the columns space of A . PCA uses **eigenfaces** to recapture an approximation to the original faces.

Usually 50 or 100 eigenfaces are required to create strong approximations to a set of 10,000 faces.

Face recognition



(a) label 1



(b) label 2

Figure: (a) The average image of twelve U.S. Presidents and (b) the average image subtracted from the image of President Kennedy .

Face recognition

For the presidential library images, S is a 50000×50000 matrix. Finding **eigenvectors** would be prohibitively time-consuming even for a supercomputer.

Face recognition

For the presidential library images, S is a 50000×50000 matrix. Finding **eigenvectors** would be **prohibitively time-consuming even for a supercomputer**.

However, when there are N images in the library, there will be at most N **linearly independent eigenvectors** of S .

Face recognition

For the presidential library images, S is a 50000×50000 matrix. Finding eigenvectors would be prohibitively time-consuming even for a supercomputer.

However, when there are N images in the library, there will be at most N linearly independent eigenvectors of S .

Since $A^T A$ and AA^T have the same nonzero eigenvalues, we solve $A^T A v = \lambda v$. If $\lambda \neq 0$ then $AA^T(Av) = \lambda(Av)$ and $Av \neq 0$. Hence $u := Av$ is an eigenvector of S corresponding to the eigenvalue $\lambda/(N-1)$.

Face recognition

For the presidential library images, S is a 50000×50000 matrix. Finding eigenvectors would be prohibitively time-consuming even for a supercomputer.

However, when there are N images in the library, there will be at most N linearly independent eigenvectors of S .

Since $A^T A$ and AA^T have the same nonzero eigenvalues, we solve $A^T A v = \lambda v$. If $\lambda \neq 0$ then $AA^T(Av) = \lambda(Av)$ and $Av \neq 0$. Hence $u := Av$ is an eigenvector of S corresponding to the eigenvalue $\lambda/(N-1)$.

For the presidential library images, the eigenfaces are obtained from eigenvectors of the 12×12 matrix $A^T A$.



Figure: A half dozen eigenfaces of the library of twelve U.S. Presidents.

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly.

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Eigenfaces can be used to recognize a new face as follows. Subtract the average image \mathbf{p} from the new image \mathbf{x} .

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Eigenfaces can be used to recognize a new face as follows. Subtract the average image \mathbf{p} from the new image \mathbf{x} . Project the mean-subtracted image $\mathbf{v} := \mathbf{x} - \mathbf{p}$ on the space spanned by the eigenfaces $\mathbf{u}_1, \dots, \mathbf{u}_r$:

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Eigenfaces can be used to recognize a new face as follows. Subtract the average image \mathbf{p} from the new image \mathbf{x} . Project the mean-subtracted image $\mathbf{v} := \mathbf{x} - \mathbf{p}$ on the space spanned by the eigenfaces $\mathbf{u}_1, \dots, \mathbf{u}_r$:

$$\mathbf{v}_{proj} := \sum_{j=1}^r (\mathbf{u}_j^T \mathbf{v}) \mathbf{u}_j = [\mathbf{u}_1 \cdots \mathbf{u}_r] [\mathbf{u}_1 \cdots \mathbf{u}_r]^T \mathbf{v}.$$

Then adding the average presidential image we obtain a recognizable face (or an approximation) $\hat{\mathbf{v}} := \mathbf{v}_{proj} + \mathbf{p}$.

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Eigenfaces can be used to recognize a new face as follows. Subtract the average image \mathbf{p} from the new image \mathbf{x} . Project the mean-subtracted image $\mathbf{v} := \mathbf{x} - \mathbf{p}$ on the space spanned by the eigenfaces $\mathbf{u}_1, \dots, \mathbf{u}_r$:

$$\mathbf{v}_{proj} := \sum_{j=1}^r (\mathbf{u}_j^T \mathbf{v}) \mathbf{u}_j = [\mathbf{u}_1 \cdots \mathbf{u}_r] [\mathbf{u}_1 \cdots \mathbf{u}_r]^T \mathbf{v}.$$

Then adding the average presidential image we obtain a recognizable face (or an approximation) $\hat{\mathbf{v}} := \mathbf{v}_{proj} + \mathbf{p}$. If $\|\text{Vec}(P_j) - \hat{\mathbf{v}}\|_2$ is smallest then $\hat{\mathbf{v}} \approx \text{Vec}(P_j)$.

Face recognition

Nonzero singular values of A are square roots of the nonzero eigenvalues of $A^T A$. The singular values have tendency to drop off in value quickly. This allows us to approximate a large collection of images, like $N = 5,000$, with only a small subset of eigenfaces.

Eigenfaces can be used to recognize a new face as follows. Subtract the average image \mathbf{p} from the new image \mathbf{x} . Project the mean-subtracted image $\mathbf{v} := \mathbf{x} - \mathbf{p}$ on the space spanned by the eigenfaces $\mathbf{u}_1, \dots, \mathbf{u}_r$:

$$\mathbf{v}_{proj} := \sum_{j=1}^r (\mathbf{u}_j^T \mathbf{v}) \mathbf{u}_j = [\mathbf{u}_1 \cdots \mathbf{u}_r] [\mathbf{u}_1 \cdots \mathbf{u}_r]^T \mathbf{v}.$$

Then adding the average presidential image we obtain a recognizable face (or an approximation) $\hat{\mathbf{v}} := \mathbf{v}_{proj} + \mathbf{p}$. If $\|\text{Vec}(P_j) - \hat{\mathbf{v}}\|_2$ is smallest then $\hat{\mathbf{v}} \approx \text{Vec}(P_j)$.

This is part of the power of PCA in facial recognition. One can use a large library of images, reduce it to a much smaller set of eigenfaces, and then use it to recognize a face or create an approximation, even with some disguising.

Face recognition



(a) label 1



(b) label 2

Figure: (a) An altered image of President Kennedy and (b) the image recreated using the six eigenfaces.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Note that if polar decomposition $A = WR$ exists then $R^2 = A^*A \implies R$ is the **positive square root** of A^*A . Often R is also denoted by $|A|$, that is, $|A| = \sqrt{A^*A} \succeq \mathbf{0}$.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Note that if polar decomposition $A = WR$ exists then $R^2 = A^*A \implies R$ is the **positive square root** of A^*A . Often R is also denoted by $|A|$, that is, $|A| = \sqrt{A^*A} \succeq \mathbf{0}$.

If A is nonsingular then $R = \sqrt{A^*A} \succ \mathbf{0}$ (positive definite). Define $W := AR^{-1}$.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Note that if polar decomposition $A = WR$ exists then $R^2 = A^*A \implies R$ is the **positive square root** of A^*A . Often R is also denoted by $|A|$, that is, $|A| = \sqrt{A^*A} \succeq \mathbf{0}$.

If A is nonsingular then $R = \sqrt{A^*A} \succ \mathbf{0}$ (positive definite). Define $W := AR^{-1}$. Then we have $A = WR$ and $W^*W = R^{-1}A^*AR^{-1} = I_n$. This shows that $A = WR$ is a polar decomposition.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Note that if polar decomposition $A = WR$ exists then $R^2 = A^*A \implies R$ is the **positive square root** of A^*A . Often R is also denoted by $|A|$, that is, $|A| = \sqrt{A^*A} \succeq \mathbf{0}$.

If A is nonsingular then $R = \sqrt{A^*A} \succ \mathbf{0}$ (positive definite). Define $W := AR^{-1}$. Then we have $A = WR$ and $W^*W = R^{-1}A^*AR^{-1} = I_n$. This shows that $A = WR$ is a polar decomposition.

Remark: Note that polar decomposition is unique when A is nonsingular.

Polar decomposition of a matrix

If $z \in \mathbb{C}$ then z has a polar representation $z = rw$, where $r = |z| = \sqrt{\bar{z}z}$ and $\bar{w}w = 1$. A similar decomposition holds for a matrix.

Definition: Let $A \in \mathbb{C}^{n \times n}$. Then a decomposition of the form $A = WR$, where $W \in \mathbb{C}^{n \times n}$ is unitary and $R \succeq \mathbf{0}$ (positive semidefinite), is called a **polar decomposition** of A . The matrices W and R are called polar factors.

Note that if polar decomposition $A = WR$ exists then $R^2 = A^*A \implies R$ is the **positive square root** of A^*A . Often R is also denoted by $|A|$, that is, $|A| = \sqrt{A^*A} \succeq \mathbf{0}$.

If A is nonsingular then $R = \sqrt{A^*A} \succ \mathbf{0}$ (positive definite). Define $W := AR^{-1}$. Then we have $A = WR$ and $W^*W = R^{-1}A^*AR^{-1} = I_n$. This shows that $A = WR$ is a polar decomposition.

Remark: Note that polar decomposition is unique when A is nonsingular.

Theorem: Let $A \in \mathbb{C}^{m \times n}$ with $m \geq n$. Then there exists an isometry $W \in \mathbb{C}^{m \times n}$ and a positive semidefinite matrix $R \in \mathbb{C}^{n \times n}$ such that $A = WR$.

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$.

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$. Then

$$A = U_n \Sigma_n V_n^* = U_n V_n^* (V_n \Sigma_n V_n^*) = WR,$$

where $W := U_n V_n^* \in \mathbb{C}^{m \times n}$ is an isometry and $R := V_n \Sigma_n V_n^* \succeq \mathbf{0}$. ■

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$. Then

$$A = U_n \Sigma_n V_n^* = U_n V_n^* (V_n \Sigma_n V_n^*) = WR,$$

where $W := U_n V_n^* \in \mathbb{C}^{m \times n}$ is an isometry and $R := V_n \Sigma_n V_n^* \succeq \mathbf{0}$. ■

SVD from polar decomposition: Let $A \in \mathbb{C}^{m \times n}$ and $A = WR$ be a polar decomposition.

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$. Then

$$A = U_n \Sigma_n V_n^* = U_n V_n^* (V_n \Sigma_n V_n^*) = WR,$$

where $W := U_n V_n^* \in \mathbb{C}^{m \times n}$ is an isometry and $R := V_n \Sigma_n V_n^* \succeq \mathbf{0}$. ■

SVD from polar decomposition: Let $A \in \mathbb{C}^{m \times n}$ and $A = WR$ be a polar decomposition. Since $R \succeq 0$, by spectral theorem, we have $R = V \Sigma V^*$, where V is unitary, $\Sigma := \text{diag}(\sigma_1, \dots, \sigma_n)$ and $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_n \geq 0$ are eigenvalues of R .

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$. Then

$$A = U_n \Sigma_n V_n^* = U_n V_n^* (V_n \Sigma_n V_n^*) = WR,$$

where $W := U_n V_n^* \in \mathbb{C}^{m \times n}$ is an isometry and $R := V_n \Sigma_n V_n^* \succeq \mathbf{0}$. ■

SVD from polar decomposition: Let $A \in \mathbb{C}^{m \times n}$ and $A = WR$ be a polar decomposition. Since $R \succeq 0$, by spectral theorem, we have $R = V \Sigma V^*$, where V is unitary, $\Sigma := \text{diag}(\sigma_1, \dots, \sigma_n)$ and $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_n \geq 0$ are eigenvalues of R .

This shows that $A = WR = WV \Sigma V^* = U \Sigma V^*$ is a trimmed SVD of A , where $U := WV$ is an isometry.

Polar decomposition

Proof: Consider the trimmed SVD $A = U_n \Sigma_n V_n^*$, where $U_n \in \mathbb{C}^{m \times n}$ is an isometry, $V_n \in \mathbb{C}^{n \times n}$ is unitary, and $\Sigma_n = \text{diag}(\sigma_1, \dots, \sigma_n) \in \mathbb{R}^{n \times n}$. Then

$$A = U_n \Sigma_n V_n^* = U_n V_n^* (V_n \Sigma_n V_n^*) = WR,$$

where $W := U_n V_n^* \in \mathbb{C}^{m \times n}$ is an isometry and $R := V_n \Sigma_n V_n^* \succeq \mathbf{0}$. ■

SVD from polar decomposition: Let $A \in \mathbb{C}^{m \times n}$ and $A = WR$ be a polar decomposition. Since $R \succeq 0$, by spectral theorem, we have $R = V \Sigma V^*$, where V is unitary, $\Sigma := \text{diag}(\sigma_1, \dots, \sigma_n)$ and $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_n \geq 0$ are eigenvalues of R .

This shows that $A = WR = WV \Sigma V^* = U \Sigma V^*$ is a trimmed SVD of A , where $U := WV$ is an isometry.

Example: Consider $A := \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \\ 10 & 11 & 12 \end{bmatrix}$. We now compute polar decomposition $A = WR$ from

SVD of A .

Example

The trimmed SVD of A is given by

```
>> [U, S, V] = svd(A, 0)
```

$$U = \begin{bmatrix} -0.1409 & 0.8247 & 0.5477 \\ -0.3439 & 0.4263 & -0.7276 \\ -0.5470 & 0.0278 & -0.1880 \\ -0.7501 & -0.3706 & 0.3679 \end{bmatrix}, \quad S = \begin{bmatrix} 25.4624 & 0 & 0 \\ 0 & 1.2907 & 0 \\ 0 & 0 & 0.0000 \end{bmatrix},$$
$$V = \begin{bmatrix} -0.5045 & -0.7608 & -0.4082 \\ -0.5745 & -0.0571 & 0.8165 \\ -0.6445 & 0.6465 & -0.4082 \end{bmatrix}$$

Example

The desired polar factors are given by

`>> W = U*V', R = V*S*V'`

$$W = \begin{bmatrix} -0.7799 & 0.4810 & 0.4004 \\ 0.1463 & -0.4208 & 0.7943 \\ 0.3316 & 0.1592 & 0.4473 \\ 0.5102 & 0.7525 & 0.0936 \end{bmatrix}, \quad R = \begin{bmatrix} 7.2286 & 7.4367 & 7.6448 \\ 7.4367 & 8.4085 & 9.3804 \\ 7.6448 & 9.3804 & 11.1160 \end{bmatrix}.$$
