HelloTravel Leads API – Sandbox Documentation

Overview

The HelloTravel Sandbox API is a static testing endpoint designed for CRM and API integration validation before moving to production.

The sandbox:

- Returns a fixed response
- Has no database side effects
- Does not maintain cursors
- Does not apply rate limits
- Can be called repeatedly with the same response

This environment should be used to validate:

- Authentication flow
- Request handling
- JSON parsing
- CRM lead ingestion

Base Endpoint

URL
`https://ihook.hellotravel.com/modal/hookleadapi_test.php`

Method
`POST`

Content-Type
`application/x-www-form-urlencoded`

Sandbox API Key
`HT-SANDBOX-2026-LEADS-API`

Response Format
`application/json`

Sample Request

cURL Example

```
curl -X POST "https://ihook.hellotravel.com/modal/hookleadapi_test.php" \
    -d "API_KEY=HT-SANDBOX-2026-LEADS-API"
```

PHP Example

```
$ch = curl_init();
curl_setopt($ch, CURLOPT_URL, "https://ihook.hellotravel.com/modal/hookleadapi_test.php");
curl_setopt($ch, CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS, "API_KEY=HT-SANDBOX-2026-LEADS-API");
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
```

Success Response


```
{
  "status": true,
  "code": 200,
  "msg": "Success",
  "data": [
    {
      "LEAD_ID": "74559",
      "NAME": "krish",
      "EMAIL": "sample@hooklms.com",
      "PHONE": "+254-770850909",
```

```
    "ADULT": "1",
    "FROM_CITY": "",
    "TO_CITY": "Singapore",
    "DESCRIPTION": "Interested in Singapore holiday package",
    "TRAVEL_DATE": "2026-08-15",
    "DAYS": "7",
    "FROM_COUNTRY_ISO": "KE",
    "TO_COUNTRY_ISO": "SG",
    "BUDGET": "Economy",
    "VISIT_VALUE": "Casual Vacation"
   }
 ]
}
```

Error Responses

Invalid Request Method


```
{
  "status": false,
  "code": 201,
  "msg": "Invalid Request Mothod"
}
```

Missing API Key


```
{
  "status": false,
  "code": 202,
  "msg": "API_KEY not found"
}
```

Invalid API Key


```
{
  "status": false,
```

```
  "code": 202,
  "msg": "Invalid api key"
}
```

Lead Fields

Field	Description
LEAD_ID	Unique lead identifier
NAME	Traveler name
EMAIL	Proxy email address
PHONE	Contact number
ADULT	Number of adult travelers
FROM_CITY	Departure city
TO_CITY	Destination city
DESCRIPTION	Travel enquiry details
TRAVEL_DATE	Planned travel date
DAYS	Trip duration
FROM_COUNTRY_ISO	Departure country ISO code
TO_COUNTRY_ISO	Destination country ISO code
BUDGET	Travel budget category
VISIT_VALUE	Travel type

Important Notes

- All response values are returned as strings.
- Sandbox responses are static and do not change between requests.
- HTTP status is always returned as `200`, even for application-level errors.

- Error handling should be implemented using:
  - `status`
  - `code`
  - `msg`

Production vs Sandbox

Feature	Sandbox	Production
Static response	Yes	No
Database writes	No	Yes
Cursor handling	No	Yes
Pagination	No	Yes
Real-time leads	No	Yes
Rate limits	No	Yes
Intended use	Testing	Live CRM integration

Production Migration Notes

Once sandbox validation is completed:

1. Replace the sandbox endpoint with the production endpoint.
2. Replace the sandbox API key with the issued production API key.
3. Implement polling logic for incremental lead fetching.
4. Handle empty responses (`data: []`) as successful requests.

Recommended Validation Checklist

- Validate POST request handling
- Validate authentication flow
- Validate JSON parsing
- Validate CRM lead creation
- Validate duplicate lead handling
- Validate retry/error handling
- Validate special characters in descriptions