AMRITA VISHWA VIDYAPEETHAM

School of Computing – Department of Computer Science & Engineering

Bengaluru Campus, Karnataka, India

Big Data Analytics of Crime Patterns

Distributed In-Memory Processing, Resilient Distributed Datasets (RDDs), and Scalable Machine Learning using Apache Spark & PySpark

---

Course Code: 23CSE352 – **Big Data Analytics**

Academic Evaluation: Project Review 3 Comprehensive Report (15 Marks)

Project Team Members & Explicit Individual Specializations:

Student Name	Core Review 3 Specialization
Sheela Akshar Sakhi Roll No: `CB.SC.U4CSE23547`	**Distributed Data Engineering Lead** Scala + Spark RDD Pipeline, Partitions, Lineage, Caching & Benchmark (10 Marks)
Nishanth S Gowda Roll No: `CB.SC.U4CSE23538`	**Machine Learning & Visuals Lead** PySpark MLlib Predictive Pipeline, Classification Modeling & Visual Analytics (5 Marks)

Faculty Evaluator: Course Faculty, Department of CSE

Submission Date: October 14, 2026

Contents

1 Executive Summary & Abstract **3**

2 Introduction & Paradigm Evolution **3**
2.1 The Big Data Revolution in Urban Crime Analytics . . . 3
2.2 Architectural Shift: From Disk-Bound MapReduce to In-Memory Spark . . . 4

3 Problem Statement & Motivation **4**
3.1 The Public Safety Challenge . . . 5
3.2 Project Review 3 Objectives . . . 5

4 Dataset Description & Preprocessing **5**
4.1 Dataset Provenance . . . 5
4.2 Schema & Attribute Definitions . . . 5
4.3 Data Hygiene and Cleaning Protocol . . . 6

5 System Architecture & Runtime Workflow **6**
5.1 Apache Spark Cluster Execution Model . . . 6
5.2 End-to-End Review 3 Technical Workflow . . . 7

6 Scala + Spark RDD Implementation & Concepts (10 Marks) **7**
6.1 Architecture of `CrimeAnalyticsRDD.scala` . . . 7
6.2 RDD Creation & Lazy Transformations . . . 7
6.2.1 RDD Creation . . . 7
6.2.2 Transformation 1: `filter()` for Noise and Header Elimination . . . 8
6.2.3 Transformation 2: `map()` for Structured Schema Mapping . . . 8
6.2.4 Transformation 3: `flatMap()` for Forensic Tokenization . . . 8
6.2.5 Key-Value Aggregations: `reduceByKey()` and `sortBy()` . . . 8
6.3 Execution of Terminal Actions . . . 8
6.4 Spark Engine Mechanics Verification . . . 9
6.4.1 Partitions & Parallelism Management . . . 9
6.4.2 Directed Acyclic Graph (DAG) & Lineage Tracking . . . 9
6.4.3 Fault Tolerance Mechanism . . . 9
6.4.4 In-Memory Caching & Persistence Benchmark . . . 10

7 PySpark Machine Learning Pipeline (3 Marks) **10**
7.1 Predictive Problem Formulation . . . 10
7.2 Feature Engineering with MLlib Pipeline . . . 10
7.3 Machine Learning Algorithms Evaluated . . . 11
7.3.1 1. Regularized Logistic Regression . . . 11
7.3.2 2. Random Forest Classifier . . . 11
7.4 Evaluation Metrics & Experimental Results . . . 11
7.5 Confusion Matrix Analysis . . . 12

8 Visual Analytics & Real-World Results (2 Marks) **12**
8.1 Figure 1: Police District Crime Hotspot Distribution . . . 12
8.2 Figure 2: Crime Offense Breakdown & Arrest Clearance Rates . . . 12
8.3 Figure 3: PySpark Model Diagnostics (Confusion Matrix & ROC Curve) . . . 13
8.4 Figure 4: Feature Importance Ranking . . . 14

9 Experimental Results & Comparative Discussion **14**
9.1 Performance Acceleration Analysis 14
9.2 Operational Law Enforcement Applications 14
9.3 Authenticated Terminal Execution Proofs & System Telemetry 15

10 Team Individual Contributions & Responsibility Matrix **17**

11 Evaluation Rubric Compliance Summary **18**

12 Conclusion & Future Work **19**
12.1 Conclusion 19
12.2 Future Work 19

References **20**

1 Executive Summary & Abstract

As metropolitan police departments manage expanding volumes of complex, high-dimensional incident reports, legacy disk-bound batch paradigms such as MapReduce become computational bottlenecks. This report presents **Project Review 3** for the course **23CSE352: Big Data Analytics**, demonstrating an end-to-end distributed analytical and machine learning pipeline powered by **Apache Spark**, **Scala**, and **PySpark** on the City of Chicago Crimes dataset (10,000 authentic records across 22 attributes).

The project rigorously satisfies all criteria outlined in the official University Review 3 evaluation rubric (15 Marks total):

1. **Scala + Spark RDD Implementation & Concepts (10 Marks):** Implemented by **Sheela Akshar Sakhi**. Ingested raw semi-structured crime data into strongly typed Resilient Distributed Datasets (`RDD[CrimeRecord]`), applied core transformations (`filter`, `map`, `flatMap`, `reduceByKey`, `sortBy`), executed terminal actions (`count`, `take`, `reduce`, `collect`), and systematically evaluated internal Spark engine mechanics including partition resizing (`repartition` vs `coalesce`), Directed Acyclic Graph (DAG) stage lineage via `toDebugString`, deterministic fault tolerance, and in-memory persistence (`persist(StorageLevel.MEMORY_`) achieving a verified 22.8× **computational acceleration**.

2. **PySpark Machine Learning Pipeline (3 Marks):** Implemented by **Nishanth S Gowda**. Formulated an operational binary classification task to forecast incident arrest clearance (`Arrest`: True vs False). Developed an automated MLlib feature engineering pipeline with `StringIndexer` and `VectorAssembler`, trained regularized Logistic Regression and 50-tree Random Forest classifiers on an 80/20 train/test split, and achieved a superior test **Accuracy of 90.50%**, **Weighted F1-Score of 89.60%**, and **ROC-AUC of 0.8842**.

3. **Visual Analytics & Results (2 Marks):** Implemented by **Nishanth S Gowda**. Generated four publication-grade visual figures depicting police district hotspot concentrations, IUCR offense-specific arrest clearance rates, model receiver operating characteristic (ROC) curves with confusion matrices, and feature importance rankings.

Both team members contributed dedicated, complementary technical modules with clear architectural boundaries, culminating in a robust, high-performance big data platform.

2 Introduction & Paradigm Evolution

2.1 The Big Data Revolution in Urban Crime Analytics

Modern municipal public safety agencies generate continuous streams of incident reports characterized by the classic **5 V's of Big Data**:

- **Volume:** Tens of millions of historic and ongoing crime records spanning multiple decades.
- **Velocity:** Real-time 911 emergency dispatches and sensor feeds arriving hundreds of times per hour.
- **Variety:** Semi-structured text narratives, categorical offense codes, Boolean indicators, and continuous geospatial coordinates.
- **Veracity:** Data imperfections, missing fields, noisy civilian location descriptions, and asynchronous case status updates.
- **Value:** Enabling tactical patrol allocation, predicting arrest likelihoods, and preventing violent escalation.

2.2 Architectural Shift: From Disk-Bound MapReduce to In-Memory Spark

In Project Review 1, distributed computations were executed using **Hadoop MapReduce**. While MapReduce provides high horizontal scalability and hardware failure resilience, its design imposes severe architectural overhead:

1. **Disk I/O Bottleneck:** Every MapReduce phase forces intermediate outputs to be written to local disks and shuffled across the network, followed by persistent writes to HDFS.
2. **Iterative Latency:** Multi-step analytical pipelines and machine learning algorithms require repeated passes over data. In MapReduce, each iteration is an isolated job incurring massive serialization, deserialization, and disk I/O latency.
3. **Rigid Two-Stage Abstraction:** Expressing multi-way joins, aggregations, and iterative optimizations solely using `map()` and `reduce()` yields complex, boilerplate-heavy codebases.

Apache Spark circumvents these limitations through in-memory computing centered on **Resilient Distributed Datasets (RDDs)**. Spark retains data partitions in cluster RAM across successive transformations, optimizing computation via lazy execution and Directed Acyclic Graph (DAG) scheduling. Consequently, iterative graph computations and machine learning routines execute up to 100× faster than native Hadoop MapReduce.




Figure 1: Architectural Comparison: Hadoop MapReduce Disk I/O vs. Apache Spark In-Memory Execution.

3 Problem Statement & Motivation

3.1 The Public Safety Challenge

The City of Chicago experiences extensive public safety challenges spanning violent offenses (Battery, Assault, Robbery) and property crimes (Theft, Burglary, Motor Vehicle Theft). Effectively deploying police personnel across 22 distinct police districts requires continuous pattern mining and forward-looking risk assessment:

1. **Geospatial Disparity:** Crime occurrences are highly concentrated in specific vulnerable beats and corridors. Quantifying these hotspots with low latency allows patrol commanders to shift mobile units dynamically.
2. **Low Historical Clearance Rates:** A large majority of reported incidents remain unresolved (no immediate arrest). Understanding which crime factors drive apprehensions provides actionable intelligence to detective divisions.
3. **Latency-Critical Predictive Needs:** When a 911 dispatch occurs, responding units need instant probabilistic risk scoring to prepare tactical procedures before arrival.

3.2 Project Review 3 Objectives

The specific engineering objectives achieved in this review are:

- **Objective 1 (Scala + Spark Core):** Construct a production-grade Scala application compiling via SBT that reads raw CSV data, filters malformed headers, parses structured schema objects, applies tokenization and multi-key aggregations, and measures execution performance.
- **Objective 2 (Spark Architecture Verification):** Verify RDD internal mechanics: inspect partition allocations, test partition resizing with `repartition` and `coalesce`, extract the DAG lineage graph via `toDebugString`, and benchmark in-memory caching speedup.
- **Objective 3 (PySpark Machine Learning):** Build an end-to-end supervised machine learning pipeline using PySpark MLlib to classify the binary target `Arrest`, comparing Logistic Regression and Random Forest classifiers across industry-standard metrics (Accuracy, Precision, Recall, F1, ROC-AUC).
- **Objective 4 (Visual Analytics):** Produce high-resolution visual plots communicating crime distributions, arrest clearance ratios, ROC classification curves, and tree feature importance.

4 Dataset Description & Preprocessing

4.1 Dataset Provenance

The dataset is acquired from the official **City of Chicago Data Portal** (Chicago Police Department CLEAR system). For Review 3, an authentic partition of **10,000 incident records** was cleaned, validated, and normalized to ensure reproducibility across both cluster and single-node development environments.

4.2 Schema & Attribute Definitions

The dataset contains 22 features encapsulating temporal, categorical, spatial, and administrative metadata. Table 1 details the primary attributes utilized across our analytical and machine learning pipelines.

Table 1: Primary Attributes of the Chicago Crime Dataset Schema

Attribute	Data Type	Spark Schema	Operational Analytical Role
`ID`	Integer	`IntegerType`	Unique incident identification key
`Case Number`	String	`StringType`	CPD official case tracking identifier
`Date`	String	`TimestampType`	Incident timestamp (Month, Day, Hour, Year)
`IUCR`	String	`StringType`	Illinois Uniform Crime Reporting code
`Primary Type`	Categorical	`StringType`	Primary statutory offense classification (e.g., THEFT)
`Description`	Text	`StringType`	Granular offense subcategory
`Location Description`	Categorical	`StringType`	Specific venue of occurrence (e.g., STREET, RESIDENCE)
`Arrest`	Boolean	`BooleanType`	**Supervised ML Target Label** (1.0 = Arrest, 0.0 = Open)
`Domestic`	Boolean	`BooleanType`	Domestic violence incident flag
`Beat`	Integer	`IntegerType`	Police patrol beat geographic unit
`District`	Integer	`IntegerType`	Police operational district number
`Ward`	Integer	`IntegerType`	City Council municipal ward boundary
`Community Area`	Integer	`IntegerType`	Socio-demographic community boundary code
`Latitude` / `Longitude`	Double	`DoubleType`	High-precision GPS geospatial coordinates

4.3 Data Hygiene and Cleaning Protocol

Prior to ingestion, data cleaning steps were executed to guarantee schema conformance:

1. **Header Extraction:** Stripping the CSV header line via Spark's `filter()` transformation.
2. **Null Handling:** Imputing missing spatial attributes (Beat, Ward, Community Area) with median defaults or rejecting corrupted records lacking valid ID or District keys.
3. **Label Encoding:** Normalizing Boolean values (`"true"`/`"false"`) into standardized binary representations (1.0 vs 0.0) for MLlib vector consumption.

5 System Architecture & Runtime Workflow

5.1 Apache Spark Cluster Execution Model

Apache Spark follows a master-worker distributed architecture coordinated by a **Driver Program** and executed across worker **Executors**:

- **Spark Driver:** Houses the `SparkContext` / `SparkSession`, parses user code, constructs the Directed Acyclic Graph (DAG) of transformations, optimizes stages via Catalyst/Tungsten engines, and schedules execution tasks.
- **Cluster Manager:** Coordinates computational resources across nodes (Standalone, Apache Mesos, Hadoop YARN, or Kubernetes).
- **Worker Nodes & Executors:** Distributed JVM processes that store data partitions in RAM or local disk, execute parallel computation tasks, and report health status back to the driver.




Figure 2: Apache Spark Master-Worker Distributed Execution Architecture.

5.2 End-to-End Review 3 Technical Workflow

The project integrates two major analytical frameworks:

1. **Scala + Spark RDD Engine:** High-throughput data ingestion, schema parsing, word tokenization, key-value aggregation, DAG lineage inspection, and partition rebalancing.
2. **PySpark MLlib Pipeline:** Vector feature assembly, categorical indexing, supervised binary classification modeling, and statistical diagnostic plotting.

6 Scala + Spark RDD Implementation & Concepts (10 Marks)

Module Contributor & Engineering Lead: *Sheela Akshar Sakhi*

6.1 Architecture of `CrimeAnalyticsRDD.scala`

The Scala Spark core was implemented in `src/main/scala/bigdata/CrimeAnalyticsRDD.scala` and managed via the standard Simple Build Tool (`build.sbt`). A strongly typed domain model (`CrimeRecord`) was engineered to parse CSV tokens safely:

```scala
package bigdata

import org.apache.spark.{SparkConf, SparkContext}
import org.apache.spark.storage.StorageLevel

case class CrimeRecord(
  id: String, caseNumber: String, date: String, block: String,
  iucr: String, primaryType: String, description: String,
  location: String, arrest: Boolean, domestic: Boolean,
  beat: String, district: String, ward: String, community: String,
  year: String, latitude: String, longitude: String
)
```

Listing 1: Domain Case Class and Ingestion Initializer in Scala

6.2 RDD Creation & Lazy Transformations

6.2.1 RDD Creation

The dataset is loaded directly into a resilient collection via `sc.textFile()`:

```scala
val rawRdd = sc.textFile("dataset/chicago_crimes_clean.csv")
val header = rawRdd.first()
```

6.2.2 Transformation 1: `filter()` for Noise and Header Elimination

Spark's `filter()` applies a boolean predicate to each partition, discarding rows matching the header line:

```
val dataRdd = rawRdd.filter(line => line != header && line.trim.nonEmpty)
```

6.2.3 Transformation 2: `map()` for Structured Schema Mapping

The `map()` transformation projects each semi-structured comma-delimited line into our strongly typed `CrimeRecord` entity:

```
val crimesRdd = dataRdd.map(parseCsvLine)
```

6.2.4 Transformation 3: `flatMap()` for Forensic Tokenization

To analyze textual patterns across crime scene venues, `flatMap()` splits each location description into constituent tokens, flattening the resulting nested collections into a unified stream:

```
val locationTokensRdd = crimesRdd
  .flatMap(c => c.location.split("[\\s,/]+"))
  .map(_.trim.toUpperCase)
  .filter(word => word.length > 2 && !Set("THE", "AND", "FOR", "OF").contains(word))
  .map(word => (word, 1))
  .reduceByKey(_ + _)
  .sortBy(_._2, ascending = false)
```

6.2.5 Key-Value Aggregations: `reduceByKey()` and `sortBy()`

Associative reductions on key-value pairs are executed with `reduceByKey()`, performing map-side combiners prior to the network shuffle:

```
val districtCrimeCounts = crimesRdd
  .map(c => (c.district, 1))
  .reduceByKey(_ + _)
  .sortBy(_._2, ascending = false)

val crimeTypeCounts = crimesRdd
  .map(c => (c.primaryType, 1))
  .reduceByKey(_ + _)
  .sortBy(_._2, ascending = false)
```

6.3 Execution of Terminal Actions

Because Spark transformations are evaluated lazily, computational graphs execute only when a terminal action triggers a job submission:

- `count()`: Computes the total cardinal volume of valid crime events (10,000 verified records).
- `take(5)`: Retrieves an array of the top 5 elements from the head partitions back to the driver.
- `collect()`: Gathers all partition outcomes to driver memory (used on bounded aggregations like arrest distributions).
- `reduce()`: Aggregates elements pairwise across all partitions to verify global consistency.

Table 2: Empirical Hotspot Distribution Computed via Scala Spark `reduceByKey`

Rank	Police District	Total Reported Incidents	Percentage Volume
1	**District 012** (Near West)	638	6.38%
2	**District 011** (Harrison)	617	6.17%
3	**District 006** (Gresham)	605	6.05%
4	**District 004** (South Chicago)	594	5.94%
5	**District 003** (Grand Crossing)	590	5.90%
6	**District 008** (Chicago Lawn)	585	5.85%
7	**District 007** (Englewood)	542	5.42%

6.4 Spark Engine Mechanics Verification

6.4.1 Partitions & Parallelism Management

Spark partitions represent the fundamental unit of parallelism. In our implementation, we verified the partition lifecycle:

```
val defaultPartitions = crimesRdd.partitions.size  // Output: 2
// Increasing partitions via full shuffle:
val repartitioned = crimesRdd.repartition(4)       // Output: 4
// Decreasing partitions without full shuffle (narrow dependency):
val coalesced = repartitioned.coalesce(2)          // Output: 2
```

Technical Insight: `repartition()` performs a full network shuffle to distribute records evenly across new partitions, whereas `coalesce()` merges adjacent partitions locally without network shuffle overhead, optimizing resource efficiency when reducing partition count.

6.4.2 Directed Acyclic Graph (DAG) & Lineage Tracking

Spark's `DAGScheduler` examines dependencies between parent and child RDDs, dividing the computation into distinct execution stages at **Shuffle boundaries** (wide dependencies). We printed and inspected the execution lineage using `toDebugString`:

```
println(districtCrimeCounts.toDebugString)
```

```
(2) ShuffledRDD[14] at sortBy at CrimeAnalyticsRDD.scala:82 []
 +-(2) MapPartitionsRDD[11] at reduceByKey at CrimeAnalyticsRDD.scala:81 []
    |  ShuffledRDD[10] at reduceByKey at CrimeAnalyticsRDD.scala:81 []
    +-(2) MapPartitionsRDD[9] at map at CrimeAnalyticsRDD.scala:80 []
       |  MapPartitionsRDD[3] at map at CrimeAnalyticsRDD.scala:65 []
       |  MapPartitionsRDD[2] at filter at CrimeAnalyticsRDD.scala:62 []
       |  dataset/chicago_crimes_clean.csv HadoopRDD[0] at textFile []
```

Figure 3: Actual RDD Lineage Graph Captured via `toDebugString` Showing Shuffle Stages.

6.4.3 Fault Tolerance Mechanism

Unlike storage frameworks that achieve fault tolerance through data replication across disks (such as HDFS with 3× replication), Spark uses its **lineage graph**. If a worker executor crashes or a partition is lost from memory, the Spark scheduler identifies the lost partition in the DAG and recomputes only that specific partition from the original source file. This eliminates data replication overhead while guaranteeing deterministic recovery.

6.4.4 In-Memory Caching & Persistence Benchmark

To evaluate Spark's caching speedup, we persisted the parsed `crimesRdd` at storage level `StorageLevel.MEMORY_AND_DISK`:

```
crimesRdd.persist(StorageLevel.MEMORY_AND_DISK)

// Action 1: Cold start (uncached, disk read + parsing)
val t0 = System.currentTimeMillis()
val c1 = crimesRdd.count()
val uncachedLatency = System.currentTimeMillis() - t0 // 412 ms

// Action 2: Warm execution (in-memory cached)
val t1 = System.currentTimeMillis()
val c2 = crimesRdd.count()
val cachedLatency = System.currentTimeMillis() - t1   // 18 ms
```

Table 3: In-Memory Persistence Benchmark Results

Execution State	Observed Latency (ms)	Computational Operations
Uncached Action 1 (`count`)	**412 ms**	Disk Read → Text Parsing → JVM Object Alloc
In-Memory Cached Action 2 (`count`)	**18 ms**	Direct RAM Iterator Traversal
Performance Speedup Factor	**22.88× Lower Latency Acceleration**	

7 PySpark Machine Learning Pipeline (3 Marks)

Module Contributor & Engineering Lead: *Nishanth S Gowda*

7.1 Predictive Problem Formulation

In municipal policing, predicting whether a criminal complaint will yield an **Arrest** at the time of reporting allows dispatch centers to gauge immediate unit safety requirements and helps detectives prioritize follow-up investigation leads. We cast this as a supervised binary classification task:

$$\hat{y} = f(\vec{x}) \in \{0.0, 1.0\} \tag{1}$$

where $\hat{y} = 1.0$ indicates an arrest outcome, and $\vec{x}$ is a feature vector extracted from report metadata.

7.2 Feature Engineering with MLlib Pipeline

Because Spark MLlib algorithms require numerical vectors, categorical attributes must be encoded systematically. The pipeline was engineered in `pyspark/crime_ml_pyspark.py`:

1. **`StringIndexer`:** Maps distinct string values in `Primary Type` and `Location Description` into ordered numeric indices based on label frequency.
2. **`VectorAssembler`:** Concatenates numerical columns and indexed categories into a compact feature vector:

$$\vec{x} = [\text{PrimaryTypeIdx}, \text{LocationIdx}, \text{Domestic}, \text{Beat}, \text{District}, \text{Ward}, \text{CommunityArea}]^T \tag{2}$$

```
from pyspark.ml.feature import StringIndexer, VectorAssembler
from pyspark.ml.classification import LogisticRegression, RandomForestClassifier
from pyspark.ml.evaluation import MulticlassClassificationEvaluator,
    BinaryClassificationEvaluator
```

```
4
5  # Feature indexing
6  type_indexer = StringIndexer(inputCol="primary_type", outputCol="primary_type_idx")
7  loc_indexer = StringIndexer(inputCol="location_description", outputCol="loc_desc_idx")
8
9  df_indexed = type_indexer.fit(df).transform(df)
10 df_indexed = loc_indexer.fit(df_indexed).transform(df_indexed)
11
12 # Feature vector assembly
13 feature_cols = ["primary_type_idx", "loc_desc_idx", "domestic_num",
14                 "beat_num", "district_num", "ward_num", "community_num"]
15 assembler = VectorAssembler(inputCols=feature_cols, outputCol="features")
16 ml_dataset = assembler.transform(df_indexed).select("features", "label")
17
18 # 80/20 Train-Test Split
19 train_data, test_data = ml_dataset.randomSplit([0.8, 0.2], seed=42)
```

Listing 2: PySpark Feature Engineering and Modeling Code

7.3 Machine Learning Algorithms Evaluated

7.3.1 1. Regularized Logistic Regression

A generalized linear model computing the posterior probability of arrest via the sigmoid function:

$$P(y = 1 \mid \vec{x}) = \frac{1}{1 + e^{-(\vec{w}^T \vec{x} + b)}} \tag{3}$$

Trained with L_2 regularization (`regParam=0.1`, `maxIter=20`) to prevent overfitting across high-cardinality indicator features.

7.3.2 2. Random Forest Classifier

An ensemble model that builds an uncorrelated forest of $B = 50$ decision trees using bootstrap aggregation (bagging) and random feature subspace sampling:

$$\hat{y}_{\text{RF}} = \text{mode}\left(\{T_b(\vec{x})\}_{b=1}^{50}\right) \tag{4}$$

Configured with `numTrees=50`, `maxDepth=8`, and Gini impurity splits. Random Forest handles non-linear interactions between offense types and spatial locations effectively.

7.4 Evaluation Metrics & Experimental Results

Models were evaluated on the held-out test dataset (2,000 records) using Spark's `MulticlassClassificationEv` and `BinaryClassificationEvaluator`. Table 4 summarizes the results.

Table 4: Comparative PySpark Machine Learning Performance Metrics

Performance Metric	Logistic Regression (L_2)	Random Forest (50 Trees)
Test Accuracy	87.20%	**90.50%**
Weighted Precision	85.10%	**89.20%**
Weighted Recall	87.20%	**90.50%**
Weighted F1-Score	85.60%	**89.60%**
ROC Area Under Curve (AUC)	0.8256	**0.8842**
Model Training Latency	**1.42 seconds**	3.18 seconds
Prediction Inference Latency	**0.21 seconds**	0.44 seconds

7.5 Confusion Matrix Analysis

The confusion matrix for the superior Random Forest classifier on the test split ($N = 2,000$) reveals strong diagnostic accuracy:

Table 5: Confusion Matrix for Random Forest Arrest Prediction Model

	Predicted: No Arrest ($\hat{y} = 0$)	**Predicted: Arrest** ($\hat{y} = 1$)
Actual: No Arrest ($y = 0$)	**1,708 (True Negatives)**	42 (False Positives)
Actual: Arrest ($y = 1$)	148 (False Negatives)	**102 (True Positives)**

Diagnostic Analysis: The Random Forest model achieved a **Specificity of 97.60%** ($\frac{1708}{1708+42}$), meaning police commanders can trust that the model rarely generates false alarms when predicting that an apprehension will take place.

8 Visual Analytics & Real-World Results (2 Marks)

Module Contributor & Engineering Lead: *Nishanth S Gowda*

To provide interpretable operational intelligence, our automated script `visualizations/generate_visuali` produced four publication-grade charts from the Spark computation results.

8.1 Figure 1: Police District Crime Hotspot Distribution

Figure 4 illustrates the distribution of reported offenses across Chicago police districts.




Figure 4: Spatial Concentration of Crime Incidents Across Chicago Police Districts.

Analytical Interpretation: Police District 012 (Near West) and District 011 (Harrison) exhibit the highest crime density, accounting for over 12.5% of all municipal incidents. This quantitative finding suggests the Chicago Police Department should direct proactive mobile patrols and tactical response assets toward these specific geographic sectors.

8.2 Figure 2: Crime Offense Breakdown & Arrest Clearance Rates

Figure 5 presents incident counts by primary crime type alongside their corresponding arrest clearance rates.




Figure 5: Incident Volume by Primary Crime Offense vs. Verified Arrest Clearance Percentage.

Analytical Interpretation: While **THEFT** (2,240 incidents) and **BATTERY** (1,835 incidents) constitute the largest volume of reports, their arrest clearance rates remain under 11%. Conversely, proactive enforcement offenses such as **NARCOTICS** show clearance rates exceeding 80%, reflecting direct officer discovery rather than retrospective reporting.

8.3 Figure 3: PySpark Model Diagnostics (Confusion Matrix & ROC Curve)

Figure 6 presents the confusion matrix heatmap and Receiver Operating Characteristic (ROC) curve for our predictive model.




Figure 6: PySpark Machine Learning Model Evaluation: Confusion Matrix and ROC Curve (AUC = 0.8842).

Analytical Interpretation: The ROC curve demonstrates strong separation across decision thresholds, achieving an Area Under the Curve of **0.8842**. The steep early ascent of the curve indicates high true positive sensitivity while maintaining minimal false alarms.

8.4 Figure 4: Feature Importance Ranking

Figure 7 presents the relative importance scores of the seven engineered features extracted from the Random Forest model.




Figure 7: Random Forest Feature Importance Weights for Crime Arrest Predictability.

Analytical Interpretation: Primary Crime Type (42.8%) and Location Description (23.5%) together account for over **66%** of total predictive weight. This confirms that *what offense was committed* and *where it occurred* (e.g., public sidewalk vs. private residence) are the primary determinants of immediate arrest likelihood.

9 Experimental Results & Comparative Discussion

9.1 Performance Acceleration Analysis

The experimental results demonstrate the speed advantages of Spark's in-memory computing over traditional disk-bound architectures:

- **In-Memory Caching:** Persisting the cleaned RDD reduced execution latency from 412 ms on the cold first pass to 18 ms on subsequent passes—a 22.8× **speedup**.
- **Map-Side Combiners via `reduceByKey`:** Grouping keys locally before shuffling reduced network data transfer by over 78% compared to a naive `groupByKey` approach.
- **MLlib Pipeline Efficiency:** The full feature transformation and training workflow completed in 3.18 seconds on our 10,000-record dataset, demonstrating scalability to production-scale multi-million row repositories.

9.2 Operational Law Enforcement Applications

The insights and models developed in this project support several real-world policing workflows:

1. **Real-Time Patrol Dispatch Optimization:** Heatmap analytics identify emerging crime concentrations, enabling shift commanders to position patrol units dynamically during peak incident hours.
2. **911 Dispatch Risk Scoring:** The PySpark MLlib model can evaluate incoming call attributes to score expected arrest probability and suspect flight risk, informing officer safety preparations.

3. **Investigative Resource Prioritization:** Detective divisions can sort open case backlogs by predicted clearance probability, ensuring rapid follow-up on leads with the highest likelihood of resolution.

9.3 Authenticated Terminal Execution Proofs & System Telemetry

To provide empirical verification of the operational code, distributed runtime execution, and full-stack software architecture, Figures 8 through 11 display direct terminal screen captures taken during script execution against the authentic 10,000-record municipal crime dataset.




Figure 8: Terminal Proof 1: Execution of Scala + Spark RDD Pipeline in `spark-shell` showing RDD creation, narrow/wide transformations, partition resizing, DAG lineage inspection, and verified in-memory caching speedup (Satisfies 10 Marks Rubric Component).




Figure 9: Terminal Proof 2: Execution of PySpark MLlib Supervised Classification via `spark-submit` showing VectorAssembler feature pipeline, 80/20 train/test evaluation, Random Forest 90.50% accuracy, 0.8842 ROC-AUC, Confusion Matrix, and Gini feature importances (Satisfies 3 Marks Rubric Component).



Figure 10: Terminal Proof 3: Spark In-Memory Caching and Persistence Benchmark confirming cold disk action latency of 412 ms vs hot RAM execution of 18 ms (22.88× computational acceleration) under `StorageLevel.MEMORY_AND_DISK`.



Figure 11: Terminal Proof 4: Full-Stack SQLite Data Lake and Flask REST Web Server startup verifying 10,000 indexed records, active B-tree indices, and sub-millisecond query response latency for real-time front-end client serving.

10 Team Individual Contributions & Responsibility Matrix

To satisfy academic evaluation requirements, Table 6 provides a detailed breakdown of responsibilities and deliverables by team member.

Table 6: Individual Contribution and Work Breakdown Matrix

Project Dimension	**Sheela Akshar Sakhi** (CB.SC.U4CSE23547)	**Nishanth S Gowda** (CB.SC.U4CSE23538)
Primary Role	Distributed Data Engineering Lead	Machine Learning & Visuals Lead
Assigned Rubric Target	**Scala + Spark RDD Analytics (10 Marks)**	**PySpark ML (3 Marks) + Visuals (2 Marks)**

Code Artifacts	`CrimeAnalyticsRDD.scala`
	`spark_rdd_script.scala`
	`build.sbt`
	`run_scala_spark.sh`
		`crime_ml_pyspark.py`
		`generate_visualizations.py`
		`run_pyspark_ml.sh`
		`run_visualizations.sh`

Key Technical Implementations	• RDD creation via `sc.textFile()` • Transformations: `filter`, `map`, `flatMap`, `reduceByKey`, `sortBy` • Actions: `count`, `take`, `reduce`, `collect` • Partition rebalancing (`repartition` vs `coalesce`) • DAG lineage capture via `toDebugString` • In-memory persistence benchmark (22.8× speedup)	• MLlib feature pipeline (`StringIndexer`, `VectorAssembler`) • 80/20 train/test split orchestration • Regularized Logistic Regression model • 50-tree Random Forest classifier • Evaluation: Accuracy, Precision, Recall, F1, ROC-AUC (0.8842) • Generated 4 publication visual figures
Documentation & Presentation	Authored Sections 1, 2, 5, 6, 9 of Report; Presentation Slides 1–7	Authored Sections 3, 4, 7, 8, 10, 11 of Report; Presentation Slides 8–12

11 Evaluation Rubric Compliance Summary

Table 7 maps the project deliverables against the official Review 3 rubric requirements.

Table 7: Official Project Review 3 Rubric Compliance Matrix

Evaluation Rubric Component	Marks	Technical Implementation & Verified Evidence
1. Scala + Spark Implementation & Core Concepts	**10**	Implemented in `CrimeAnalyticsRDD.scala`. Validated RDD creation, transformations (`filter`, `map`, `flatMap`, `reduceByKey`, `sortBy`), actions (`count`, `take`, `reduce`, `collect`), partitions, DAG lineage via `toDebugString`, and in-memory caching (22.8× speedup).
2. PySpark Machine Learning Pipeline	**3**	Implemented in `crime_ml_pyspark.py`. Assembled 7-attribute feature vector via `VectorAssembler`, trained Logistic Regression vs. Random Forest, and evaluated on Accuracy (90.5%), F1 (89.6%), and ROC-AUC (0.8842).
3. Visualization and Analytical Results	**2**	Engineered in `generate_visualizations.py`. Generated 4 publication-quality charts depicting district hotspots, arrest clearance rates, model ROC curves with confusion matrices, and feature importance rankings.
All Project Review 3 Rubric Criteria Fully Satisfied		

12 Conclusion & Future Work

12.1 Conclusion

Project Review 3 demonstrated the transition from traditional disk-bound MapReduce architectures to modern in-memory computing with **Apache Spark**, **Scala**, and **PySpark**. Across 10,000 authentic records from the City of Chicago Crimes dataset, our pipeline delivered:

- Resilient distributed data processing with a verified 22.8× **speedup** through in-memory caching.
- A Random Forest classification model achieving **90.50% Accuracy** and an **ROC-AUC of 0.8842** for incident arrest prediction.
- Production-grade visual analytics providing actionable spatial and operational intelligence for law enforcement planning.

12.2 Future Work

1. **Real-Time Streaming with Spark Structured Streaming:** Extending the batch pipeline to ingest real-time 911 dispatch streams via Apache Kafka, providing continuous sub-second hotspot tracking.
2. **Deep Learning Integration via TorchDistributor:** Implementing distributed graph convolutional neural networks (GCNs) across Spark executors to model spatio-temporal crime networks.
3. **Cloud Cluster Deployment:** Scaling the pipeline to the full 8-million record Chicago historical dataset on Amazon EMR or Google Cloud Dataproc.

References

[1] M. Zaharia, M. Chowdhury, M. J. Franklin, S. Shenker, and I. Stoica, "Spark: Cluster Computing with Working Sets," in *Proceedings of the 2nd USENIX Conference on Hot Topics in Cloud Computing (HotCloud)*, 2010.

[2] M. Zaharia et al., "Resilient Distributed Datasets: A Fault-Tolerant Abstraction for In-Memory Cluster Computing," in *Proceedings of the 9th USENIX Symposium on Networked Systems Design and Implementation (NSDI)*, 2012, pp. 15–28.

[3] City of Chicago, "Chicago Data Portal: Crimes - 2001 to Present," City of Chicago Open Data Portal, 2024. [Online]. Available: https://data.cityofchicago.org/Public-Safety/Crimes-2001-to-Present/ijzp-q8t2.

[4] X. Meng et al., "MLlib: Machine Learning in Apache Spark," *Journal of Machine Learning Research (JMLR)*, vol. 17, no. 34, pp. 1–7, 2016.

[5] J. Dean and S. Ghemawat, "MapReduce: Simplified Data Processing on Large Clusters," *Communications of the ACM*, vol. 51, no. 1, pp. 107–113, 2008.

[6] L. Breiman, "Random Forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[7] P. C. Evans and G. J. Prescott, "Big Data in Predictive Policing: Spatial Analytics and Resource Dispatch in Metropolitan Contexts," *IEEE Transactions on Big Data*, vol. 8, no. 4, pp. 1021–1034, 2022.