

Big Data Analytics of Crime Patterns

using Hadoop MapReduce and Apache Hive

Sheela Akshar Sakhi Nishanth S Gowda

Amrita Vishwa Vidyapeetham

Agenda

- ▶ Introduction & Motivation
- ▶ Problem Statement
- ▶ Dataset Description
- ▶ Architecture Pipeline
- ▶ Hadoop MapReduce Implementation
- ▶ Apache Hive Analytics
- ▶ Execution Results
- ▶ Conclusion

Introduction

- ▶ The rise of Big Data provides an unprecedented opportunity to analyze public safety records.
- ▶ City crime records encompass millions of rows of incidents, locations, dates, and types.
- ▶ Processing this data efficiently requires distributed frameworks.
- ▶ We leverage **Hadoop MapReduce** for raw parallel processing and **Apache Hive** for SQL-based analytical querying.

Motivation

Why analyze crime data?

- ▶ **Public Safety:** Identifying high-crime zones helps improve community security.
- ▶ **Resource Allocation:** Enables police departments to deploy patrols dynamically based on historical hotspots.
- ▶ **Trend Forecasting:** Predicting the frequency and nature of crimes across different districts and timeframes.
- ▶ **Big Data Challenge:** Traditional RDBMS fail to scale efficiently with millions of such rows.

Problem Statement

"To design and implement a scalable Big Data pipeline that can ingest, process, and extract actionable intelligence from massive real-world crime datasets."

Objectives:

- ▶ Demonstrate a complete data pipeline from HDFS storage to advanced analytics.
- ▶ Perform category-wise statistics using MapReduce.
- ▶ Execute 10 meaningful complex queries utilizing aggregations, filtering, and joins in Hive.

Dataset Overview

Dataset: Chicago Crimes (2001 to Present)

- ▶ **Scope:** Extracts real-world incident reports from the Chicago Data Portal.
- ▶ **Size:** 10,000 recent records processed for this demonstration.

Attribute Type	Fields
Identifiers	id, case_number, date
Categories	primary_type, description
Location	district, ward, community_area
Flags	arrest, domestic

Data Preprocessing & HDFS Storage


Preprocessing Phase:

- ▶ Raw CSV files often contain embedded newlines within quotes.
- ▶ We implemented a Python script to clean these records, ensuring perfect compatibility with Hadoop's `TextInputFormat`.

HDFS Storage:

- ▶ Dataset uploaded to HDFS distributed storage.
- ▶ Command: `hdfs dfs -put chicago_crimes.csv /user/crimes/`

System Architecture



- ▶ Centralized data lake on HDFS.
- ▶ MapReduce for low-level transformations.
- ▶ Hive for structured intelligence gathering.

Hadoop MapReduce Implementation

Problem: Calculate the total occurrences of each Crime Type.

Mapper Logic:

- ▶ Input: (ByteOffset, Line of text)
- ▶ Ignores CSV headers.
- ▶ Splits line correctly handling commas within double quotes.
- ▶ Extracts the 6th column (primary_type).
- ▶ Output: (CrimeType, 1)

MapReduce: Reducer Logic

Reducer Logic:

- ▶ Input: (CrimeType, [1, 1, 1, ...])
- ▶ Sums up all the '1's for a given crime type.
- ▶ Output: (CrimeType, Total_Count)

```
public void reduce(Text key, Iterable<IntWritable> values, Context
    context) {
    int sum = 0;
    for (IntWritable val : values) {
        sum += val.get();
    }
    result.set(sum);
    context.write(key, result);
}
```


MapReduce Execution & Results

- ▶ Successfully packaged as a JAR and executed on YARN.
- ▶ Processed 10,000 rows across mappers and reducers.

Sample Output (part-r-00000):

Crime Type	Frequency
THEFT	2,150
BATTERY	1,857
CRIMINAL DAMAGE	1,207
ASSAULT	905

MapReduce Execution Screenshots



The screenshot shows a terminal window titled "hadoop@aksharsakhi-QEMU-Virtual-Machine: ~/Big-Data-Analytics-of-Crime-Patterns". The terminal output displays the results of a MapReduce job. It starts with "WRONG_REDUCE=0", followed by input/output statistics. A warning message indicates that the native Hadoop library could not be loaded, so the built-in Java classes are used. The final output is a list of crime categories and their counts, formatted as a table.

```
WRONG_REDUCE=0
File Input Format Counters
  Bytes Read=2484524
File Output Format Counters
  Bytes Written=521
MapReduce job completed successfully.
Displaying output:
2026-08-13 15:53:00,899 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-ja
va classes where applicable
ARSON      20
ASSAULT    905
BATTERY    1857
BURGLARY   628
CONCEALED CARRY LICENSE VIOLATION      20
CRIMINAL DAMAGE 1207
CRIMINAL SEXUAL ASSAULT 59
CRIMINAL TRESPASS 250
DECEPTIVE PRACTICE 418
GAMBLING    2
HOMICIDE    17
HUMAN TRAFFICKING 1
INTERFERENCE WITH PUBLIC OFFICER      48
INTIMIDATION 7
KIDNAPPING  4
LIQUOR LAW VIOLATION 9
MOTOR VEHICLE THEFT 895
NARCOTICS   298
OFFENSE INVOLVING CHILDREN 68
OTHER OFFENSE 667
hadoop@aksharsakhi-QEMU-Virtual-Machine:~/Big-Data-Analytics-of-Crime-Patterns$
```

Apache Hive Analytics: Setup

- ▶ Created an external table `crimes` mapping directly to HDFS data.
- ▶ **Serialization/Deserialization:** Used `OpenCSVSerde` to properly parse fields enclosed in quotes containing commas.
- ▶ Created a secondary table `community_areas` holding area codes and names to demonstrate table joins.


Hive Analytics: Basic Queries

- ▶ **SELECT & LIMIT:** Retrieved incident IDs and descriptions.
- ▶ **WHERE clause:** Filtered incidents resulting specifically in a narcotics arrest.
- ▶ **ORDER BY:** Sorted severe cases like homicides by recency.
- ▶ **GROUP BY & COUNT:** Identified which locations (e.g., STREET, APARTMENT) experience the highest crime volumes.

Hive Analytics: Advanced Aggregations

- ▶ **HAVING clause:** Extracted major crime categories by filtering for counts > 500.
- ▶ **SUM:** Calculated the absolute total number of arrests made within each police district.
- ▶ **AVG:** Analyzed the average rate of domestic-related crimes across different beats.
- ▶ **MAX & MIN:** Automatically pinpointed the highest and lowest crime districts.
- ▶ **JOIN:** Combined the raw crimes data with `community_areas` to print human-readable neighborhood names.

Hive Analytics Execution Screenshot



The screenshot shows a terminal window titled "hadoop@aksharsakhi-QEMU-Virtual-Machine: ~/Big-Data-Analytics-of-Crime-Patterns". The terminal output indicates that the initialization script is completed and the Hive script execution is successful. The results are saved to "hive_output.txt". The top 20 lines of the Hive output are displayed, showing a list of crime incidents with their IDs, descriptions, and timestamps.

```
Initialization script completed
schemaTool completed
hadoop@aksharsakhi-QEMU-Virtual-Machine:~/Big-Data-Analytics-of-Crime-Patterns$ ./run_hive.sh
Starting Hive script execution...
This may take a few minutes.
Hive execution completed successfully.
Results saved to hive_output.txt.

=== Top 20 lines of Hive Output ===
14285893      BURGLARY      BURGLARY FROM MOTOR VEHICLE      2026-08-04T00:00:00.000
14283703      CRIMINAL DAMAGE TO PROPERTY      2026-08-04T00:00:00.000
14283908      OTHER OFFENSE VIOLATE ORDER OF PROTECTION      2026-08-04T00:00:00.000
14283293      THEFT $500 AND UNDER      2026-08-04T00:00:00.000
14284321      CRIMINAL DAMAGE TO VEHICLE      2026-08-04T00:00:00.000
14283777      BATTERY AGGRAVATED DOMESTIC BATTERY - OTHER DANGEROUS WEAPON      2026-08-04T00:00:00.000
14284479      CRIMINAL DAMAGE TO VEHICLE      2026-08-04T00:00:00.000
14283403      DECEPTIVE PRACTICE STATE BENEFITS FRAUD      2026-08-04T00:00:00.000
14283429      MOTOR VEHICLE THEFT THEFT / RECOVERY - AUTOMOBILE      2026-08-04T00:00:00.000
14283519      CRIMINAL DAMAGE TO VEHICLE      2026-08-04T00:00:00.000
14283075      NARCOTICS POSSESS - COCAINE true
14283074      NARCOTICS POSSESS - CANNABIS 30 GRAMS OR LESS true
14283062      NARCOTICS MANUFACTURE / DELIVER - CANNABIS OVER 10 GRAMS true
14282837      NARCOTICS POSSESS - CRACK true
14283009      NARCOTICS POSSESS - CANNABIS MORE THAN 30 GRAMS true
14282739      NARCOTICS MANUFACTURE / DELIVER - CANNABIS OVER 10 GRAMS true
14282717      NARCOTICS MANUFACTURE / DELIVER - CANNABIS OVER 10 GRAMS true
14282623      NARCOTICS POSSESS - HEROIN (TAN / BROWN TAR) true
14282521      NARCOTICS POSSESS - HEROIN (WHITE) true
14282606      NARCOTICS POSSESS - HEROIN (WHITE) true
hadoop@aksharsakhi-QEMU-Virtual-Machine:~/Big-Data-Analytics-of-Crime-Patterns$
```


Results & Quantitative Interpretation

Empirical Data Insights:

- ▶ **Top Crime Categories:** BATTERY (1,857 cases), CRIMINAL DAMAGE (1,207 cases), ASSAULT (905 cases), and MOTOR VEHICLE THEFT (895 cases).
- ▶ **Enforcement Efficacy:** Narcotics cases show a 100% arrest rate flag, whereas theft offenses show lower arrest ratios.
- ▶ **Spatial Hotspots:** Streets and Sidewalks represent the primary spatial vulnerability zones for property crimes.
- ▶ **Geographical Variations:** High crime density concentrated in District 11.

Conclusion

- ▶ Successfully ingested and analyzed a large-scale real-world dataset.
- ▶ **MapReduce** proved highly efficient for unstructured low-level data processing and aggregations.
- ▶ **Apache Hive** demonstrated immense power for executing complex, relational-style queries on distributed files.
- ▶ This pipeline can scale to millions of records, providing an essential backbone for civic analytics.

Q & A

Thank you for your time.

Any Questions?