Quiz 1

Subject: Intro to python Programming in Python 16 Jul 26 Total Marks: 50.00 Questions: 17 With Answers

QUESTIONS

Q1 MCQ *[0.00 marks]*

NAT → integer For all NAT questions in this exam, the answer will always be an integer and not a float value.

OPTIONS

A. Instructions has been mentioned above. ✓ **Correct**

B. This Instructions is just for a reference & not for an evaluation.

Q2 MCQ *[3.00 marks]*

What is the output of the following code?

```
x = "07"
y = int(x) + len(x)
print(f"{y:04d}")
```

OPTIONS

A. `0009` ✓ **Correct**

B. `009`

C. `9`

D. `0007`

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q3 MCQ *[3.00 marks]*

What is the output of the following code?

```
L = [2, 4, 6]
M = L
N = L[:]

M[1] = M[0] + N[-1]
N.append(M[1] - L[0])

print(L, N)
```

OPTIONS

A. `[2, 8, 6] [2, 4, 6, 6]` ✓ **Correct**

B. `[2, 8, 6] [2, 4, 6, 8]`

C. `[2, 4, 6] [2, 4, 6, 6]`

D. `[2, 8, 6, 6] [2, 4, 6]`

Q4 MCQ *[3.00 marks]*

Which of the following statements is TRUE regarding the code below?

```
A = [5, 1, 4]
B = sorted(A)
A.sort(reverse=True)
```

OPTIONS

A. `A` and `B` both become `[5, 4, 1]`

B. `sorted(A)` changes the original list

C. `B` becomes `[1, 4, 5]` while `A` becomes `[5, 4, 1]` ✓ **Correct**

D. `sort()` returns a new sorted list

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q5 MCQ *[4.00 marks]*

Consider the following code.

What will be printed?

```
word = "education"
result = ""

for ch in word:
    if ch in "aeiou":
        continue
    if ch == 't':
        break
    result += ch.upper()

print(result)
```

OPTIONS

A. `DC` ✓ Correct

B. `DCT`

C. `DCN`

D. `EDC`

Q6 MSQ *[4.00 marks]*

Consider the following code. `s = "PyThOn2026"` Select all expressions that evaluate to `True` .

OPTIONS

A. `"Th" in s` ✓ Correct

B. `s.lower() == "python2026"` ✓ Correct

C. `s[2:6] == "Thon"`

D. `s[::-1][0] == "P"`

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q7 MSQ *[4.00 marks]*

Consider the following Python code.

Which of the following statements will run without giving an error?

```
data = ({1, 2}, [3, 4], (5, 6))
```

OPTIONS

A. `data[0].add(7)` ✓ Correct

B. `data[1][0] = 10` ✓ Correct

C. `data[2][1] = 9`

D. `data[1].append(data[2][0])` ✓ Correct

Q8 SA *[4.00 marks]*

What is the output of the following code?

```
values = [3, 5, 2, 8]

new = [x + 1 if x % 2 == 0 else x * 2 for x in values]

print(sum(new))
```

ANSWER

28 (Equal • Numeric)

Q9 SA *[4.00 marks]*

What is the output of the following code?

```
text = "python programming"

A = text.count("m")
B = len(text.split())
C = len('text')

print(A + B - C)
```

ANSWER

0 (Equal • Numeric)

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q10 SA *[4.00 marks]*

What is the output of the following code?

```
num = 531
total = 0

while num > 0:
    digit = num % 10
    if digit % 2 == 1:
        total += digit
    num //= 10

print(total)
```

ANSWER

9 (Equal • Numeric)

Q11 SA *[3.00 marks]*

What is the output of the following code?

```
count = 0

for i in range(1, 5):
    for j in range(i):
        if j == 2:
            break
        count += 1

print(count)
```

ANSWER

7 (Equal • Numeric)

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q12 MCQ *[4.00 marks]*

CONTEXT / PARAGRAPH

Note: isinstance(val, datatype) returns True if val is of object of type 'datatype' and False, otherwise.

Based on the above data, answer the given subquestions.

```
def transform(items):
    out = []

    for i, val in enumerate(items):

        if isinstance(val, str):
            out.append(val.upper()[::-1])

        elif isinstance(val, int):
            if i % 2 == 0:
                out.append(val * 2)
            else:
                out.append(val + 5)

    return out

data = ["go", 4, "cat", 3, 2]

result = transform(data)
```

What is the value of `result` ?

OPTIONS

A. `['OG', 9, 'TAC', 8, 4]` ✓ Correct

B. `['GO', 8, 'CAT', 3, 4]`

C. `['OG', 4, 'TAC', 6, 2]`

D. `['GO', 9, 'TAC', 8, 2]`

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q13 MSQ *[3.00 marks]*

CONTEXT / PARAGRAPH

Note: isinstance(val, datatype) returns True if val is of object of type 'datatype' and False, otherwise.

Based on the above data, answer the given subquestions.

```
def transform(items):
    out = []

    for i, val in enumerate(items):

        if isinstance(val, str):
            out.append(val.upper()[::-1])

        elif isinstance(val, int):
            if i % 2 == 0:
                out.append(val * 2)
            else:
                out.append(val + 5)

    return out

data = ["go", 4, "cat", 3, 2]

result = transform(data)
```

Suppose the following condition inside the transform() function: `if i % 2 == 0:` is replaced with `if val % 2 == 0:` For the given input `data = ["go", 4, "cat", 3, 2]` which of the following statements will become TRUE?

OPTIONS

A. The final output becomes: `['OG', 8, 'TAC', 8, 4]` ✓ **Correct**

B. `"go"` becomes `"GO"`

C. integer `3` becomes `8` ✓ **Correct**

D. integer `4` becomes `9`

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q14 MCQ *[4.00 marks]*

CONTEXT / PARAGRAPH

Based on the above data, answer the given subquestions.

```
def analyze(L):
    total = 0

    for word in L:

        if len(word) < 5:
            total += len(word)

        elif 'a' in word:
            total += 2

        else:
            total += 1

    return total

items = ["pen", "scale", "book", "eraser", "ink"]
ans = analyze(items)
```

What is the value of `ans` ?

OPTIONS

A. `13`

B. `12`

C. `11`

D. `14` ✓ **Correct**

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space

Q15 SA *[3.00 marks]*

CONTEXT / PARAGRAPH

Based on the above data, answer the given subquestions.

```
def analyze(L):
    total = 0

    for word in L:

        if len(word) < 5:
            total += len(word)

        elif 'a' in word:
            total += 2

        else:
            total += 1

    return total

items = ["pen", "scale", "book", "eraser", "ink"]
ans = analyze(items)
```

How many times is the condition `len(word) < 5` evaluated?

ANSWER

5 (Equal • Numeric)

This PDF was generated from **quizpractice.space**

Downloaded by **AKSHAT JAIN** <25f3005317@ds.study.iitm.ac.in> quizpractice.space