Vulnexa PRO

ASSESSMENT TARGET
gujjufurniture.in

SCAN COMPLETION DATE
24/3/2026, 10:35:49 am

Executive Summary

Proprietary Security Exposure Assessment for gujjufurniture.in

100/100

POSTURE: HIGH

RISK POSTURE ANALYSIS



Risk Impact vs. Probability

Based on our automated analysis, the target application demonstrates a **HIGH** operational risk profile. This score integrates vulnerability counts, exploitability, and potential business impact of confirmed threats.

CRITICAL	HIGH	MEDIUM	LOW
1	2	2	4

INFO	IDENTIFIED ENDPOINTS
0	1

INFRASTRUCTURE & RECONNAISSANCE CONTEXT

🔒 SSL/TLS Configuration

Status: Valid & Secure
Protocol: TLSv1.3
Issuer: Let's Encrypt
Expires In: 58 days

🛡️ Edge Defense / WAF

Detected WAF: None
Confidence: N/A
Evasion Status: Active

🌐 Cloud / ASN Intelligence

Organization: Hostinger International Ltd.
Network Route: N/A
ASN: AS47583 Hostinger International Limited

📝 HTTP Security Headers

Strict-Transport-Security: Missing
Content-Security-Policy: Missing
X-Frame-Options: Missing

SECURITY POSTURE & CONFIGURATION CHECKS

Security Control	Status	Details
Transport Security (SSL/TLS)	✅ Secure	Valid certificate installed and served over HTTPS.
Directory Listing Exposure	❌ Vulnerable	Sensitive directories or files are publicly accessible.
HTTP Security Headers	✅ Hardened	Modern security headers (CSP, HSTS) are actively enforced.
Admin / Default Panel Protection	✅ Secure	No easily guessable admin panels or login portals found.

TECHNICAL FINDINGS & FORENSICS

A06:2021-Vulnerable and Outdated Components

MEDIUM

CVE-2007-3205

Observation: The parse_str function in (1) PHP, (2) Hardened-PHP, and (3) Suhosin, when called without a second parameter, might allow remote attackers to overwrite arbitrary variables by specifying variable names and values in the string to be parsed. NOTE: it is not clear whether this is a design limitation of the function or a bug in PHP, although it is likely to be regarded as a bug in Hardened-PHP and Suhosin.

Technical Context: `Vulnerability Scanner (PHP)`

HIGH

CVE-2013-2220

Observation: Buffer overflow in the radius_get_vendor_attr function in the Radius extension before 1.2.7 for PHP allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a large Vendor Specific Attributes (VSA) length value.

Technical Context: `Vulnerability Scanner (PHP)`

CRITICAL

CVE-2024-3566

Observation: A command inject vulnerability allows an attacker to perform command injection on Windows applications that indirectly depend on the CreateProcess function when the specific conditions are satisfied.

Technical Context: `Vulnerability Scanner (PHP)`

MEDIUM

CVE-2025-6491

Observation: In PHP versions:8.1.* before 8.1.33, 8.2.* before 8.2.29, 8.3.* before 8.3.23, 8.4.* before 8.4.10 when parsing XML data in SOAP extensions, overly large (>2Gb) XML namespace prefix may lead to null pointer dereference. This may lead to crashes and affect the availability of the target server.

Technical Context: `Vulnerability Scanner (PHP)`

LOW

CVE-2025-1220

Observation: In PHP versions:8.1.* before 8.1.33, 8.2.* before 8.2.29, 8.3.* before 8.3.23, 8.4.* before 8.4.10 some functions like fsockopen() lack validation that the hostname supplied does not contain null characters. This may lead to other functions like parse_url() treat the hostname in different way, thus opening way to security problems if the user code implements access checks before access using such functions.

Technical Context: `Vulnerability Scanner (PHP)`

A00:2021-General Security

LOW

Unsafe HTML Assignment (innerHTML)

Observation: The script assigns content to innerHTML. If this content is not properly sanitized, it can execute scripts embedded in the HTML.

Technical Context: `Script: inline-script`

Remediation: Use element.textContent for plain text or use a trusted sanitization library (like DOMPurify) before using innerHTML.

A10:2021-Server-Side Request Forgery

HIGH

SSRF Vulnerability

Observation: A Server-Side Request Forgery vulnerability was observed, potentially allowing servers to be coerced into making arbitrary internal/external requests.

Technical Context: `https://gujjufurniture.in/ (and 7 related endpoints)`

FORENSIC EVIDENCE & EXPLOIT PROOF

Affected URL: `https://gujjufurniture.in/ (and 7 related endpoints)`

```
Vulnerable Endpoints:\nhttps://gujjufurniture.in/?url=http://169.254.169.254/latest/meta-data/\nh
```

A05:2021-Security Misconfiguration

LOW

Open Directory / File Exposure

Observation: A sensitive directory or file backup was discovered on the server.

Technical Context: `https://gujjufurniture.in/config`

FORENSIC EVIDENCE & EXPLOIT PROOF

Affected URL: `https://gujjufurniture.in/config`

```
https://gujjufurniture.in/config
```

LOW

Open Directory / File Exposure

Observation: A sensitive directory or file backup was discovered on the server.

Technical Context: `https://gujjufurniture.in/.git/config`

FORENSIC EVIDENCE & EXPLOIT PROOF

Affected URL: `https://gujjufurniture.in/.git/config`

```
https://gujjufurniture.in/.git/config
```

Suspicious Scripts & Code execution Risks

Source: `inline-script`

> **Unsafe HTML Assignment (innerHTML)**: The script assigns content to innerHTML. If this content is not properly sanitized, it can execute scripts embedded in the HTML.

🕵️ Hacker OSINT & Intelligence Mining

JAVASCRIPT ANALYSIS

Endpoints Found: 0 **Secrets Leaked:** 0

GITHUB EXPOSURE

Found **0** related repositories and **0** potential code leaks.

BEHAVIORAL ENGINE PROFILER

Sent **12** blind payloads and confirmed **0** behavioral anomalies via timing and length variance mapping.

CONFIDENTIAL DOCUMENT
This report contains sensitive security findings. Access should be restricted to authorized technical management.
© 2026 Vulnexa Security Systems. All rights reserved. Made by Akshat Jain.