Status	Finished
Started	Sunday, 11 October 2026, 10:57 PM
Completed	Sunday, 11 October 2026, 11:08 PM
Duration	11 mins 8 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Choose the correct statement

a. We can create function with argument(s) and no return value.
b. We can create function with no argument and with return value(s)
c. All of the mentioned ✓
d. We can create function with no argument and no return value.

Question **2**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def maximum(x, y):
    if x > y:
        return x
    elif x == y:
        return 'The numbers are equal'
    else:
        return y
print(maximum(2, 3))
```

a. 3 ✓
b. The numbers are equal
c. None of the mentioned
d. 2

Question **3**

Correct

Mark 1.00 out of 1.00

Write the output of : print(abs(-45))

- a. 45 ✓
- b. 45.0
- c. -45
- d. None of the mentioned

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is not the type of function argument?

- a. Keyword argument
- b. default argument
- c. initial argument ✓
- d. Required argument

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following statement is a function call?

- a. function sum
- b. call sum
- c. def sum
- d. sum ✓

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following display() function call?

```
def display(**kwargs):
   for i in kwargs:
      print(i)
display(emp="Kelly", salary=9000)
```

a. Kelly
9000

b. emp ✓
salary

c. ('emp', 'Kelly')
('salary', 9000)

d. TypeError

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following statement is not true regarding functions?

a. Function header always ends with a colon (.

b. A function may or may not return value.

c. A function may or may not have parameters.

d. A function definition begins with "define" ✓

Question **8**

Correct

Mark 1.00 out of 1.00

Python function always returns a value

Select one:

True ✓

False

Question **9**

Correct

Mark 1.00 out of 1.00

6. Which of the following is not the built-in function?

- a. tuple( )
- b. print( )
- c. input( )
- d. dictionary( ) ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following items are present in the function header?

- a. B. parameter list
- b. Both A and B ✓
- c. A. function name
- d. return value

Question **11**

Correct

Mark 1.00 out of 1.00

Which keyword is used to begin the definition of a function?

- a. DEF
- b. def ✓
- c. Define
- d. Def

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following number can never be generated by the following code: random.randrange(0, 100)

- a. 100 ✓
- b. 99
- c. 0
- d. 1

Question **13**

Correct

Mark 1.00 out of 1.00

A variable that is defined inside any function or a block is known as a ____.

- a. Local variable ✓
- b. Function Variable
- c. inside variable
- d. Global variable

Question **14**

Correct

Mark 1.00 out of 1.00

____ can be defined as a named group of instructions that accomplish a specific task when it is invoked/called.

- a. Operator
- b. Function ✓
- c. Token
- d. Datatype

Question **15**

Correct

Mark 1.00 out of 1.00

A function may return multiple values using ____.

- a. String
- b. Tuple ✓
- c. List
- d. Dictionary