

CS245: Databases

SQL

Vijaya saradhi

Department of Computer Science and Engineering
Indian Institute of Technology Guwahati

Active Databases

Constructs

- Triggers: a series of actions associated with INSERT, UPDATE or DELETE queries and performed whenever these queries are involved
- Assertions: a boolean valued SQL expression that must be true at all times
- Events: Time based actions as opposed to query based

Active Databases - Triggers

Triggers

- Triggers also known as **event-condition-action** rules or ECA rules
- Triggers are involved only when certain conditions specified by the database programmer occur
- Trigger tests a specified condition. If the condition does not hold then nothing else associated with the trigger happens
- If the condition is satisfied then associated **action** is performed

Active Databases - Triggers

Triggers

- Has all the power of assertions
- Easier to implement
- Programmer specifies when they should be invoked
- Every trigger must be associated with a table
- Triggers are invoked automatically
- Triggers cannot be called directly
- Are part of transactions and can ROLLBACK transactions

Active Databases - Triggers

Triggers

- Cascade changes through related tables in database
- Enforce complex data integrity than a CHECK constraint
- Define custom error messages
- Compare before and after states of data under modification
- Triggers can be
 - Created
 - Altered
 - Dropped

Active Databases - Triggers

Triggers

- The action may be executed either **before** or **after** the triggering event
- Action can refer to old and new values of tuples that were inserted, deleted or updated
- Condition may be specified using **WHEN** clause
- Programmer has an option of specifying that the action is performed either:
 - Once for each modified tuple OR
 - Once for all the tuples that are changed in the database operation

Active Databases - Triggers

Triggers

- Invoke certain operations upon **specified action** on a table
- Action could be: **insert a tuple into a table**
- Action could be: **delete a row from a table**
- Action could be: **update a row from in a table**
- Performed operation can be on the table itself
- Performed Operation can be on other tables and/or databases

Trigger - Example - 01

Totaling amount

account (acct_num INT, amount FLOAT)

Sum Keep track of how much amount is deposited (irrespective of account number)

Insert The above operation should be performed for deposits only (not withdraw)

Before Sum operation should be performed even before the tuple (acct_num, amount) is inserted into the **account** table

Trigger - Example - 01

```
CREATE TABLE account(acct_num INT, amount FLOAT);
```

```
-- Create a global variable @sum
```

```
SET @sum = 0;
```

```
CREATE TRIGGER insert_sum
```

```
BEFORE INSERT
```

```
ON account
```

```
FOR EACH ROW
```

```
    SET @sum = @sum + NEW.amount;
```

Trigger - Example - 01

Trigger Action

```
CREATE TRIGGER insert_sum
BEFORE INSERT
ON account
FOR EACH ROW
SET @sum = @sum + NEW.amount;
```

Trigger Events

```
INSERT INTO account VALUES (137, 14.98);
INSERT INTO account VALUES (141, 1937.50);
INSERT INTO account VALUES (97, -100.00);
SELECT @sum AS "Total amount inserted ";
-----
```

Example

Explanation

- `CREATE TRIGGER` will create a trigger with the name `insert_sum`
- The trigger will not get executed immediately
- Condition for invoking trigger is: When a `INSERT` operation is performed on table `account`
- Statements in trigger gets executed even before the row is written into the `account` table

Names and meanings

```
INSERT INTO Sailor (sid, sname, rating, age)
VALUES (99, 'Sailor 99', 9, 37);
```

NEW.sid	NEW.sname	NEW.rating	NEW.age
99	Sailor 99	9	37

Sailors			
OLD.sid	OLD.sname	OLD.rating	OLD.age
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5
99	Sailor 99	9	37

Names and meanings

- Before the statement `INSERT INTO account VALUES (137, 14.98);` there are no rows in the table
- Attributes/columns in a new row **to be inserted** are referred with **NEW**
- **NEW.acct_num** refers to 137
- **NEW.amount** refers to 14.98
- Rows that are already present in the `account` table are referred with **OLD**
- The statement `SET @sum = @sum + NEW.amount;` gets executed before row is inserted into `account` table

Trigger - Example - 02

Assumption

- Assume existence of table: `account(acc_num, amount)`
- updated amount must always be between 0 and 100
- If the updated amount is more than 100, clamp to 100
- If the updated amount is less than 0, clamp to 0

```
DELIMITER //
CREATE TRIGGER update-check
BEFORE UPDATE ON account
FOR EACH ROW
BEGIN
    IF NEW.amount < 0 THEN
        SET NEW.amount = 0;
    ELSEIF NEW.amount > 100 THEN
        SET NEW.amount = 100;
    END IF
END; //
DELIMITER ;
```

Trigger - Example - 03

```
CREATE TABLE test1(a1 INT);  
CREATE TABLE test2(a2 INT);  
CREATE TABLE test3(a3 INT NOT NULL PRIMARY KEY(a3));  
CREATE TABLE test4(a4 INT NOT NULL PRIMARY KEY(a4), b4 INT DEFAULT 0);
```

Trigger - Example - 03

```
DELIMITER |

CREATE TRIGGER testref BEFORE INSERT ON test1
FOR EACH ROW
BEGIN
    INSERT INTO test2 SET a2 = NEW.a1;
    DELETE FROM test3 WHERE a3 = NEW.a1;
    UPDATE test4 SET b4 = b4 + 1 WHERE a4 = NEW.a1;
END;
|

DELIMITER ;
```


Trigger - Example - 03

```
INSERT INTO test3 values (1), (2), (3), (4), (5), (6), (7), (8), (9), (10);
INSERT INTO test4 values (1, 0), (2, 0), (3, 0), (4, 0), (5, 0), (6, 0), (7,
0), (8, 0), (9, 0), (10, 0);
```

Database state

test1	test2	test3	test4	
a1	a2	a3	a4	b4
		1	1	0
		2	2	0
		3	3	0
		4	4	0
		5	5	0
		6	6	0
		7	7	0
		8	8	0
		9	9	0
		10	10	0

Trigger - Example - 03

```
INSERT INTO test1 VALUES (4);
```

```
DELIMITER |
```

```
CREATE TRIGGER testref BEFORE INSERT ON test1
FOR EACH ROW
BEGIN
  INSERT INTO test2 SET a2 = NEW.a1;
  DELETE FROM test3 WHERE a3 = NEW.a1;
  UPDATE test4 SET b4 = b4 + 1 WHERE a4 = NEW.a1;
END;
```

```
DELIMITER ;
```

Database state

test1	test2	test3	test4	
a1	a2	a3	a4	b4
1	1	1	1	3
3	3	2	2	0
1	1	3	3	1
7	7	4	4	2
1	1	5	5	0
8	8	6	6	0
4	4	7	7	1
4	4	8	8	1
		9	9	0
		10	10	0

Multiple Triggers On Same Table

Multiple Triggers

- Multiple triggers can be placed on a single table
- Source of multiple triggers are due to the way a trigger is created

```
CREATE TRIGGER trigger_name  
{BEFORE | AFTER} {INSERT | DELETE | UPDATE }  
ON table_name  
{FOLLOWS | PRECEDES}
```

- When multiple triggers exists on same table, they must be ordered
- The ordering is specified at the time of creation
- $Trigger_1 \rightarrow Trigger_2 \rightarrow Trigger_3 \dots$
- $Trigger_2$ follows $Trigger_1$
- $Trigger_3$ follows $Trigger_2$ and so on

Multiple Triggers On Same Table

Example

```
CREATE TABLE T2 (  
  id INT,  
  productCode VARCHAR(15) NOT NULL,  
  price DECIMAL(10,2) NOT NULL,  
  updated_at TIMESTAMP NOT NULL  
    DEFAULT CURRENT_TIMESTAMP  
    ON UPDATE CURRENT_TIMESTAMP,  
  PRIMARY KEY (id),  
  FOREIGN KEY (productCode)  
    REFERENCES T1 (productCode)  
    ON DELETE CASCADE  
    ON UPDATE CASCADE  
);
```

Multiple Triggers On Same Table

Example

```
DELIMITER |

CREATE TRIGGER before_products_update
BEFORE UPDATE ON T1
FOR EACH ROW
BEGIN
    IF OLD.msrp <> NEW.msrp THEN
        INSERT INTO T2(product_code , price)
        VALUES( old .productCode , old .msrp);
    END IF ;
END|

DELIMITER ;
```

Multiple Triggers On Same Table

Example

```
SELECT
    productCode ,
    msrp
FROM
    T1
WHERE
    productCode = 'S12_1099 ';
```

productCode	msrp
S12_1099	194.57

Multiple Triggers On Same Table

Example

```
UPDATE T1  
SET msrp = 200  
WHERE productCode = 'S12-1099 ';
```

T2			
id	productCode	price	updated_at
1	S12-1099	194.57	2019-09-08 09:07:02

Multiple Triggers On Same Table

Example

```
CREATE TABLE T3 (  
  id INT,  
  productCode VARCHAR(15) DEFAULT NULL,  
  updatedAt TIMESTAMP NOT NULL  
    DEFAULT CURRENT_TIMESTAMP  
    ON UPDATE CURRENT_TIMESTAMP,  
  updatedBy VARCHAR(30) NOT NULL,  
  PRIMARY KEY (id),  
  FOREIGN KEY (productCode)  
    REFERENCES T1 (productCode)  
    ON DELETE CASCADE  
    ON UPDATE CASCADE  
);
```


Multiple Triggers On Same Table

Example

- Table T1 has one trigger on **BEFORE UPDATE** to insert some content into T2
- We now set another trigger on **BEFORE UPDATE** on T1 to insert some content into T3

Multiple Triggers On Same Table

Example

```
DELIMITER |

CREATE TRIGGER before_products_update_log_user
  BEFORE UPDATE ON T1
  FOR EACH ROW
  FOLLOWS before_products_update
BEGIN
  IF OLD.msrp <> NEW.msrp THEN
    INSERT INTO
      T3(productCode , updatedBy )
    VALUES
      (OLD.productCode , USER ());
  END IF ;
END|

DELIMITER ;
```

Multiple Triggers On Same Table

Example

```
UPDATE  
  T1  
SET  
  msrp = 220  
WHERE  
  productCode = 'S12_1099';
```

T2			
id	productCode	price	updated_at
1	S12_1099	194.57	2019-09-08 09:07:02
2	S12_1099	200.00	2019-09-08 09:10:32

Multiple Triggers On Same Table

Example

```
UPDATE
  T1
SET
  msrp = 220
WHERE
  productCode = 'S12_1099 ';
```

T3		
productCode	UpdatedAt	UpdatedBy
S12_1099	2019-09-08 09:10:32	root@localhost

System Information

Obtaining All Triggers

```
SHOW TRIGGERS
FROM classicmodels
WHERE 'table' = 'T1';
```

TRIGGERS				
Trigger	Event	Table	Statement	Timing
before_products.update	UPDATE	T1	BEGIN IF old.msrp ...	BEFORE
before_products.update_log_user	UPDATE	T1	BEGIN IF OLD.msrp ...	BEFORE

System Information

Action Order

```
SELECT
    trigger_name ,
    action_order
FROM
    information_schema.triggers
WHERE
    trigger_schema = 'classicmodels'
ORDER BY
    event_object_table ,
    action_timing ,
    event_manipulation;
```

information_schema	
TRIGGER_NAME	ACTION_ORDER
before_products_update	1
before_products_update_log_user	2

Nested Triggers

Example

- 1 Place a trigger on table T1 with some action (say when a row gets inserted)
- 2 Place a trigger on table T2 with action that on insert, invoke a trigger to update table T3
- 3 When a row gets inserted into T1, it invokes first trigger
- 4 Invocation of first triggers causes invocation of second trigger

Recursive Triggers

Types

Direct recursion Occurs when a trigger fires and performs an action that causes the same trigger to fire again

Indirect recursion Occurs when a trigger fires and performs an action that causes a trigger on another table to fire... that causes original trigger to fire again

Considerations for Using Triggers

Considerations

- Constraints are proactive
- Triggers are reactive
- Constraints are checked before triggers
- Multiple triggers can be placed for an action
- Each trigger must be sequenced