

The Anatomy of a Website — Quick Reference

Terminal Commands

- `mkdir <dir>` — create a new folder
- `cd <dir>` — change into a folder
- `touch <file>` — create an empty file
- `vim <file>` — open the file in vim (:wq to save & quit)
- `open <file>` — open the file in the default app

HTML Element Anatomy

- **Opening Tag** — element name in `< >`, e.g. `<p>`
- **Attribute** — optional property inside the opening tag
- **Content** — the text/media shown on screen
- **Closing Tag** — same name with `/`, e.g. `</p>`

Void Elements (no closing tag)

- `<img>` `<br>` `<hr>`
- `<meta>` `<link>` `<input>`

Popular Browsers & Makers

- **Chrome** — Google
- **Firefox** — Mozilla
- **Safari** — Apple
- **Edge** — Microsoft
- **Brave** — Brave Software

Page Source vs. Elements (Inspect)

- **View Page Source** — original static HTML sent by the server
- **Elements tab** — live view of the **DOM**, updates as the page changes
- **DOM** — tree-like structure the browser builds from the HTML

VS Code Emmet

- In a blank `.html` file, type `!` then press **Enter** — generates the HTML5 boilerplate

Git: First Push

1. `git init`
2. `git add .`
3. `git commit -m "message"`
4. `git push`

Enable GitHub Pages

1. Repo → **Settings** → **Pages**
 2. Build and deployment → **GitHub Actions**
 3. "GitHub Pages Jekyll" card → **Configure** → **Commit changes**
 4. **Actions** tab — wait for the run to turn green (~50s)
 5. **Settings** → **Pages** — open the published link
- `<link>/<folder>/<file>` — full page path = link + folder + filename
 - `git pull` — sync down changes made on GitHub (e.g. the new `.github` folder)

Lecture Notes